



Microtest
微 测 检 测

Test Report

Report No.: MTi210817007-10E1
Date of issue: September 17, 2021
Applicant: Anker Innovations Limited
Product name: Wireless Headphone
Model(s): A3510, A3511
FCC ID: 2AOKB-A3510

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Contents

1	General Information.....	5
1.1	Description of EUT	5
1.2	Operation channel list	5
1.3	Test channel list	6
1.4	Ancillary equipment list	6
1.5	Description of Support Units	7
2	Summary of Test Results	8
3	Test Facilities and Accreditations	9
3.1	Test laboratory.....	9
3.2	Environmental conditions.....	9
3.3	Measurement uncertainty	9
3.4	Test software	9
4	Equipment List.....	10
5	Test Result.....	11
5.1	Antenna requirement	11
5.2	Peak output power	12
5.3	Conducted emission	19
5.4	Radiated spurious emission.....	23
5.5	20dB occupied channel bandwidth	31
5.6	Carrier frequency separation	38
5.7	Hopping Channel	44
5.8	Dwell time.....	47
5.9	Conducted band edge.....	54
5.10	Spurious RF Conducted Emissions	61
	Photographs of the Test Setup.....	64
	Photographs of the EUT	65

TEST RESULT CERTIFICATION

Applicant's name..... :	Anker Innovations Limited
Address..... :	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong
Manufacturer's Name..... :	Anker Innovations Limited
Address..... :	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hongkong
Factory's Name..... :	Senmai Electron Limited
Address..... :	No. 5 Shuiling Road, Zhouwu Industrial Zone, Dongcheng District, Dongguan City

Product description

Product name..... :	Wireless Headphone
Trademark..... :	ANKER
Model Name..... :	A3510
Serial Model..... :	A3511
Standards..... :	FCC Part 15.247
Test procedure..... :	ANSI C63.10-2013

Date of Test

Date (s) of performance of tests..... :	August 26, 2021 ~ September 17, 2021
Test Result..... :	Pass

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Testing Engineer

: _____  _____
 (Danny Xu)

Technical Manager

: _____  _____
 (Leon Chen)

Authorized Signatory

: _____  _____
 (Tom Xue)

1 General Information

1.1 Description of EUT

Product name:	Wireless Headphone
Model name:	A3510
Serial model:	A3511
Difference in series models:	Type A3511 has the same Circuit diagram, PCB layout and all electrical construction with type A3510. For A3511: The ANC function has been cancelled, and the two ANC MICs are cancelled, and the surface paint color is different form A3510.
Operation frequency:	2402-2480MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK,8DPSK
Bit Rate of transmitter:	1 Mbps, 2Mbps, 3Mbps
Antenna type:	PCB Antenna
Antenna gain:	1.5dBi
Max. output power:	9.319dBm
Hardware version:	D
Software version:	V1.5
Power source:	DC 3.7V from battery
Serial number:	MTi210817007-10-S0001

1.2 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465

10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454	--	--
26	2428	53	2455	--	--

1.3 Test channel list

Channel	Channel	Frequency (MHz)
Low	00	2402
Middle	39	2441
High	78	2480

1.4 Ancillary equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
/	/	/	/	/

1.5 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model	S/N	Manufacturer	Certificate type
Laptop	E485	/	Lenovo	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2 Summary of Test Results

Test procedures according to the technical standards:

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna requirement	Pass	
2	15.247(b)(1)	Peak output power	Pass	
3	15.207	Conducted emission	Pass	
4	15.247(d)	Band edge	Pass	
5	15.205/15.209	Spurious emission	Pass	
6	15.247(a)(1)	20dB occupied bandwidth	Pass	
7	15.247(a)(1)	Carrier Frequencies Separation	Pass	
8	15.247(a)(1)	Hopping channel number	Pass	
9	15.247(a)(1)	Dwell time	Pass	
10	15.247(d)	Spurious RF Conducted Emissions	Pass	

3 Test Facilities and Accreditations

3.1 Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd.
Location	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.
FCC Registration No.:	448573

3.2 Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3 Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

3.4 Test software

Software Name	Manufacturer	Model	Version
Bluetooth and WiFi Test System	Shenzhen JS tonskend co., ltd	JS1120-3	2.5.77.0418

4 Equipment List

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E043	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2021/06/02	2022/06/01
MTI-E044	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2021/05/30	2023/05/29
MTI-E047	Amplifier	Hewlett-Packard	8447F	3113A06150	2021/06/02	2022/06/01
MTI-E089	ESG Vector Signal Generator	Agilent	N5182A	MY49060455	2021/06/02	2022/06/01
MTI-E058	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2021/06/02	2022/06/01
MTI-E062	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2021/06/02	2022/06/01
MTI-E066	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2021/06/02	2022/06/01
MTI-E078	Synthesized Sweeper	Agilent	83752A	3610A01957	2021/06/02	2022/06/01
MTI-E079	DC Power Supply	Agilent	E3632A	MY40027695	2021/06/02	2022/06/01
MTI-E045	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	9120D-2278	2021/05/30	2023/05/29
MTI-E021	EMI Test Receiver	Rohde&schwarz	ESCS30	100210	2021/06/02	2022/06/01
MTI-E022	Pulse Limiter	Schwarzbeck	VSTD 9561-F	00679	2021/06/02	2022/06/01
MTI-E023	Artificial mains network	Schwarzbeck	NSLK 8127	NSLK 8127 #841	2021/06/02	2022/06/01
MTI-E046	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00044	2021/05/30	2023/05/29
MTI-E048	Amplifier	Agilent	8449B	3008A02400	2021/06/02	2022/06/01
MTI-E072	Thermometer Clock Humidity Monitor	-	HTC-1	/	2021/06/02	2022/06/01

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

5 Test Result

5.1 Antenna requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT antenna


The EUT antenna is PCB antenna (1.5dBi). It complies with the standard requirement.

5.2 Peak output power

5.2.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(1)	Peak output power	Power<0.125W (20.97dBm)	2400-2483.5

5.2.2 Test setup



5.2.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
 RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.2.4 Test results

Test data

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery

GFSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	8.662	20.97
CH39	2441	9.241	20.97
CH78	2480	8.917	20.97

 $\pi/4$ -DQPSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	8.741	20.97
CH39	2441	9.319	20.97
CH78	2480	8.964	20.97

8DPSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	8.745	20.97
CH39	2441	9.294	20.97
CH78	2480	8.979	20.97

Test plots
GFSK mode-CH00

GFSK mode-CH39


GFSK mode-CH78

 $\pi/4$ -DQPSK mode-CH00


$\pi/4$ -DQPSK mode-CH39

 $\pi/4$ -DQPSK mode-CH78


8DPSK mode-CH00

8DPSK mode-CH39


8DPSK mode-CH78




5.3 Conducted emission

5.3.1 Limits

FREQUENCY (MHz)	Class B (dB μ V)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note: *Decreases with the logarithm of the frequency.

5.3.2 Test setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.3.3 Test procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.


For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.3.4 Test results

Note:


1. The three modulated high, medium, and low channels have been tested. The report only shows the worst mode. The worst mode is GFSK CH39.
2. Emission Level = Reading Level + Factor, Margin = Emission Level - Limit, Factor = LISN modulus + Cable Loss

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from notebook AC 120V/60Hz	Test Mode:	TX



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.4580	29.08	11.04	40.12	56.73	-16.61	QP
2		0.4580	21.09	11.04	32.13	46.73	-14.60	AVG
3		0.7940	23.81	11.17	34.98	56.00	-21.02	QP
4		0.7940	15.62	11.17	26.79	46.00	-19.21	AVG
5		1.1220	21.11	13.54	34.65	56.00	-21.35	QP
6		1.1220	11.54	13.54	25.08	46.00	-20.92	AVG
7		3.5100	29.40	11.41	40.81	56.00	-15.19	QP
8		3.5100	20.02	11.41	31.43	46.00	-14.57	AVG
9	*	4.9660	30.14	11.48	41.62	56.00	-14.38	QP
10		4.9660	19.76	11.48	31.24	46.00	-14.76	AVG
11		13.7660	22.58	11.68	34.26	60.00	-25.74	QP
12		13.7660	11.10	11.68	22.78	50.00	-27.22	AVG

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from notebook AC 120V/60Hz	Test Mode:	TX



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1		0.1780	41.23	10.92	52.15	64.58	-12.43	QP
2		0.1780	25.49	10.92	36.41	54.58	-18.17	AVG
3		0.4540	31.43	10.90	42.33	56.80	-14.47	QP
4	*	0.4540	24.40	10.90	35.30	46.80	-11.50	AVG
5		1.1260	21.37	13.49	34.86	56.00	-21.14	QP
6		1.1260	13.41	13.49	26.90	46.00	-19.10	AVG
7		3.6420	31.06	11.39	42.45	56.00	-13.55	QP
8		3.6420	20.09	11.39	31.48	46.00	-14.52	AVG
9		6.1860	31.25	11.41	42.66	60.00	-17.34	QP
10		6.1860	21.04	11.41	32.45	50.00	-17.55	AVG
11		13.9580	16.11	11.63	27.74	60.00	-32.26	QP
12		13.9580	6.74	11.63	18.37	50.00	-31.63	AVG

5.4 Radiated spurious emission

5.4.1 Limits

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.


Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.4.2 Test setup


Radiated emission test-up frequency below 30MHz



Radiated emission test-up frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.4.3 Test procedure

- a. EUT operating conditions. The EUT tested system was configured as the statements of 3.2 Unless otherwise a special operating condition is specified in the follows during the testing.
- b. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- c. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3-meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the floor on a support that is RF transparent for the frequencies of interest. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m.
- f. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits, and then no additional QP Mode measurement performed.
- h. For the actual test configuration, please refer to the related Item –EUT Test photos.

Note: Both horizontal and vertical antenna polarities were tested. The worst-case emissions were reported.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

5.4.4 Test results
Below 30MHz

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1010 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	TX	Polarization:	--


Freq.	Reading	Limit	Margin	State
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB).
3. Limit line = specific limits (dB μ V) + distance extrapolation factor.


Between 30MHz – 1GHz

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1010 hPa	Phase:	H
Test Mode:	TX	Test Voltage:	DC 3.7V from battery



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	72.0843	37.16	-10.04	27.12	40.00	-12.88	QP
2		96.0986	36.76	-8.66	28.10	43.50	-15.40	QP
3		143.8295	40.69	-10.69	30.00	43.50	-13.50	QP
4		155.9101	34.18	-10.05	24.13	43.50	-19.37	QP
5		167.8243	35.21	-9.66	25.55	43.50	-17.95	QP
6		191.7450	30.69	-8.40	22.29	43.50	-21.21	QP

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1010 hPa	Phase:	V
Test Mode:	TX	Test Voltage:	DC 3.7V from battery



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		71.8320	34.37	-10.03	24.34	40.00	-15.66	QP
2		96.0986	29.38	-8.66	20.72	43.50	-22.78	QP
3		143.8295	31.66	-10.69	20.97	43.50	-22.53	QP
4		211.5265	28.54	-7.35	21.19	43.50	-22.31	QP
5		480.5276	31.35	-3.22	28.13	46.00	-17.87	QP
6		492.4685	31.16	-2.59	28.57	46.00	-17.43	QP
7		798.9797	34.81	1.18	35.99	46.00	-10.01	QP
8	*	900.1474	32.45	3.60	36.05	46.00	-9.95	QP

Note:

- Emission Level = Meter Reading + Factor, Margin= Emission Level- Limit, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is GFSK CH39

1GHz-25GHz

Frequency	Read Level	Correct Factor	Emission Level	Limits	Margin	Detector	Polarization
(MHz)	(dB μ V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)	Peak/AVG	H/V
Low Channel (2402 MHz) (GFSK)--Above 1G							
4804	53.08	1.52	54.60	74	-19.40	Peak	V
4804	49.44	1.52	50.96	54	-3.04	AVG	V
7206	47.37	5.46	52.83	74	-21.17	Peak	V
9608	41.92	6.33	48.25	74	-25.75	Peak	V
4804	46.34	1.52	47.86	74.00	-26.14	Peak	H
7206	42.26	5.46	47.72	74.00	-26.28	Peak	H
9608	41.76	6.33	48.09	74.00	-25.91	peak	H
Mid Channel (2441 MHz) (GFSK) --Above 1G							
4882	50.16	1.68	51.84	74.00	-22.16	Peak	V
7323	46.19	5.45	51.64	74.00	-22.36	Peak	V
9764	40.77	6.37	47.14	74.00	-26.86	peak	V
4882	43.63	1.68	45.31	74.00	-28.69	peak	H
7323	42.73	5.45	48.18	74.00	-25.82	peak	H
9764	42.53	6.37	48.90	74.00	-25.10	peak	H
High Channel (2480 MHz) (GFSK)-- Above 1G							
4960	52.56	1.83	54.39	74	-19.61	Peak	V
4960	48.50	1.83	50.33	54	-3.67	AVG	V
7440	46.18	5.43	51.61	74.00	-22.39	Peak	V
9920	41.71	6.41	48.12	74.00	-25.88	Peak	V
4960	44.72	1.83	46.55	74.00	-27.45	Peak	H
7440	41.53	5.43	46.96	74.00	-27.04	Peak	H
9920	41.83	6.41	48.24	74.00	-25.76	Peak	H

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier Gain
3. Emission Level= Read Level + Correct Factor.
4. All the modulation modes have been tested, and only the worst results are reflected in the report.

5.4.5 Band edge – radiated

Frequency	Meter Reading	Correct Factor	Emission Level	Limits	Margin	Detector	Polarization
(MHz)	(dB μ V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)	Peak/AVG	H/V
GFSK mode							
2310	26.26	26.94	53.20	74.00	-20.80	Peak	H
2310	16.35	26.94	43.29	54.00	-10.71	AVG	H
2390	26.87	27.29	54.16	74.00	-19.84	Peak	H
2390	16.99	27.29	44.28	54.00	-9.72	AVG	H
2310	26.37	26.94	53.31	74.00	-20.69	Peak	V
2310	16.72	26.94	43.66	54.00	-10.34	AVG	V
2390	25.92	27.29	53.21	74.00	-20.79	Peak	V
2390	17.39	27.29	44.68	54.00	-9.32	AVG	V
2483.500	26.96	27.71	54.67	74.00	-19.33	Peak	H
2483.500	17.58	27.71	45.29	54.00	-8.71	AVG	H
2500.000	26.28	27.78	54.06	74.00	-19.94	Peak	H
2500.000	17.27	27.78	45.05	54.00	-8.95	AVG	H
2483.500	26.79	27.71	54.50	74.00	-19.50	Peak	V
2483.500	18.67	27.71	46.38	54.00	-7.62	AVG	V
2500.000	26.76	27.78	54.54	74.00	-19.46	Peak	V
2500.000	17.57	27.78	45.35	54.00	-8.65	AVG	V

Note:


1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier Gain
3. Emission Level= Read Level + Correct Factor.
4. All the modulation modes have been tested, and only the worst results are reflected in the report.

5.5 20dB occupied channel bandwidth

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247a(1)	20dB bandwidth	N/A	2400-2483.5

5.5.2 Test setup



5.5.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 Bandwidth: RBW=30 kHz, VBW=100 kHz, detector= Peak


5.5.4 Test results

Test data


EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery

Mode	Frequency (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Result
GFSK	2402	1.035	N/A	Pass
	2441	1.049	N/A	Pass
	2480	1.022	N/A	Pass
$\pi/4$ -DQPSK	2402	1.265	N/A	Pass
	2441	1.228	N/A	Pass
	2480	1.272	N/A	Pass
8DPSK	2402	1.264	N/A	Pass
	2441	1.261	N/A	Pass
	2480	1.250	N/A	Pass

Test plots
GFSK mode






$\pi/4$ -DQPSK



TX CH39

TX CH78


8DPSK mode
TX CH00

TX CH39

5.6 Carrier frequency separation

5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(1)	Channel Separation	>25kHz or >two-thirds of the 20 dB bandwidth (Which is greater)	2400-2483.5

5.6.2 Test setup



5.6.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=30 kHz, VBW=100 kHz, detector= Peak, Sweep Time =auto.
- (3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

5.6.4 Test results

Test data

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	GFSK, $\pi/4$ -DQPSK, 8DPSK /CH00, CH39, CH78		

Mode	Channel	Frequency (MHz)	Test Result (kHz)	Limit		Result
					(kHz)	
GFSK	Low	2402	994	690.00	2/3 of 20dB BW	Pass
	Middle	2441	998	699.33	2/3 of 20dB BW	Pass
	High	2480	998	681.33	2/3 of 20dB BW	Pass
$\pi/4$ -DQPSK	Low	2402	1002	843.33	2/3 of 20dB BW	Pass
	Middle	2441	998	818.67	2/3 of 20dB BW	Pass
	High	2480	998	848.00	2/3 of 20dB BW	Pass
8DPSK	Low	2402	1000	842.67	2/3 of 20dB BW	Pass
	Middle	2441	1000	840.67	2/3 of 20dB BW	Pass
	High	2480	998	833.33	2/3 of 20dB BW	Pass

Test plots


GFSK mode-CH39



GFSK mode-CH78



$\pi/4$ -DQPSK mode-CH00

 $\pi/4$ -DQPSK mode-CH39


$\pi/4$ -DQPSK mode-CH78



8DPSK mode-CH00



8DPSK mode-CH39


8DPSK mode-CH78


5.7 Hopping Channel

5.7.1 Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

5.7.2 Test setup



5.7.3 Test procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW RBW



Sweep = auto

Detector function = peak


Trace = max hold

5.7.4 Test results

Mode	Quantity of Hopping Channel	Limit	Results
GFSK, $\pi/4$ -DQPSK, 8DPSK	79	>15	Pass

Test plots
GFSK mode

 $\pi/4$ -DQPSK mode


8DPSK mode



5.8 Dwell time

5.8.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(1)	Dwell time	0.4 sec	2400-2483.5

5.8.2 Test setup



5.8.3 Test procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.
- (9) The EUT was set to the Hopping Mode for Dwell Time Test.

5.8.4 Test results

Test data

EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	GFSK, $\pi/4$ -DQPSK, 8DPSK /CH39		

Mode	Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (ms)	Limit(s)	Conclusion
GFSK	DH1	2441	0.3939	126.05	<0.4	Pass
	DH3	2441	1.650	264.00	<0.4	Pass
	DH5	2441	2.898	309.12	<0.4	Pass
$\pi/4$ DQPSK	2DH1	2441	0.4028	128.90	<0.4	Pass
	2DH3	2441	1.656	264.96	<0.4	Pass
	2DH5	2441	2.904	309.76	<0.4	Pass
8DPSK	3DH1	2441	0.4041	129.31	<0.4	Pass
	3DH3	2441	1.654	264.64	<0.4	Pass
	3DH5	2441	2.904	309.76	<0.4	Pass

Note:

1. A period time = 0.4 (s) * 79 = 31.6(s)





2. DH1 time slot = Pulse Duration * (1600/(2*79)) * A period time



DH3 time slot = Pulse Duration * (1600/(4*79)) * A period time



DH5 time slot = Pulse Duration * (1600/(6*79)) * A period time



3. For GFSK, $\pi/4$ -DQPSK and 8DPSK: The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test plots


	Modulation mode	GFSK mode
DH1		
DH3		



<p>2-DH3</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.441000000 GHz</p> <p>Start Freq 2.441000000 GHz</p> <p>Stop Freq 2.441000000 GHz</p> <p>CF Step 1.000000 MHz Auto Man</p> <p>Freq Offset 0 Hz</p>
<p>2-DH5</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.441000000 GHz</p> <p>Start Freq 2.441000000 GHz</p> <p>Stop Freq 2.441000000 GHz</p> <p>CF Step 1.000000 MHz Auto Man</p> <p>Freq Offset 0 Hz</p>

Modulation mode	8DPSK mode
3-DH1	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.441000000 GHz Ref 30.00 dBm $\Delta Mkr2$ 404.1 μs 7.86 dB Center 2.441000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 10.13 ms (8000 pts)</p>
3-DH3	 <p>Agilent Spectrum Analyzer - Swept SA Center Freq 2.441000000 GHz Ref 30.00 dBm $\Delta Mkr2$ 1.654 ms 9.30 dB Center 2.441000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 10.13 ms (8000 pts)</p>

3-DH5



5.9 Conducted band edge

5.9.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.9.2 Test setup





5.9.3 Test procedure

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.


5.9.4 Test results

Test data


EUT:	Wireless Headphone	Model Name:	A3510
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery



Test plots
GFSK: Band Edge, Left Side

GFSK: Band Edge, Right Side


π/4-DQPSK: Band Edge, Left Side




π/4-DQPSK: Band Edge, Right Side




8DPSK: Band Edge, Left Side

8DPSK: Band Edge, Right Side


Hopping Mode
 Test plots


GFSK: Band Edge, Left Side



GFSK: Band Edge, Right Side





π/4-DQPSK: Band Edge, Left Side



π/4-DQPSK Band Edge, Right Side



8DPSK: Band Edge, Left Side

8DPSK Band Edge, Right Side


5.10 Spurious RF Conducted Emissions


5.10.1 Limit

Below -20dB of the highest emission level in operating band.

5.10.2 Measuring instruments

The Measuring equipment is listed in the section 4 of this test report.

5.10.3 Test setup



5.10.4 Test procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW=300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.


5.10.5 Test results

Note:


1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

2: The worst mode is $\pi/4$ -DQPSK mode, and the report only show the worst mode data.


$\pi/4$ -DQPSK on Channel 00

 $\pi/4$ -DQPSK on Channel 00

 $\pi/4$ -DQPSK on Channel 00

 $\pi/4$ -DQPSK on Channel 39

 $\pi/4$ -DQPSK on Channel 39

 $\pi/4$ -DQPSK on Channel 39


$\pi/4$ -DQPSK on Channel 78

 $\pi/4$ -DQPSK on Channel 78

 $\pi/4$ -DQPSK on Channel 78


Photographs of the Test Setup

See the APPENDIX – Test Setup Photos.

Photographs of the EUT

See the APPENDIX - EUT Photos.

----END OF REPORT----