



## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	Soundcore Liberty 2 Pro, Soundcore Liberty 2
Model Name	A3909L, A3913L
FCC ID	2AOKB-A3909L

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

BR/EDR

$P_t=8.605\text{dBm}=7.25\text{mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR}=(7.25\text{mW}/5\text{mm}) \cdot [\sqrt{2.402(\text{GHz})}]= 2.25<3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

BLE

$P_t=7.967\text{dBm}=6.26\text{mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR}=(6.26\text{mW}/5\text{mm}) \cdot [\sqrt{2.402(\text{GHz})}]= 1.94<3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118