


Model: D2341
Input: 100V-240V~50/60Hz 2.5A
Anker Innovations Limited
Room 1318-19, Hollywood Plaza, 610 Nathan Road,
Mongkok, Kowloon, Hong Kong

R-R-AII-D2341

FCC ID: 2AOKB-D2341 IC: 23451-D2341
CAN ICES-003(B)/NMB-003(B)



RG1 IEC 62471-5:2015
Complies with 21 CFR 1040.10 and 1040.11
except for deviations pursuant to Laser Notice No. 50,
dated June 24, 2007.
Conforme aux normes 21 CFR 1040.10 et 1040.11,
à l'exception des écarts conformément à l'avis
laser n° 50 du 24 juin 2007
Made in China / Fabriqué en Chine USB 2.0 port

This device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.


Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan
Apparatet må tilkoples jordat stikkontakt
Apparaten skall anslutas till jordat uttag
Apparatets stikprop skal tilsluttes en stikkontakt
med jord, som giver forbindelse til stikproppens jord.

248.4mm

Model: D2350
Input: 100V-240V~50/60Hz 2.5A
Anker Innovations Limited
Room 1318-19, Hollywood Plaza, 610 Nathan Road,
Mongkok, Kowloon, Hong Kong

R-R-All-D2341

FCC ID: 2AOKB-D2341 IC: 23451-D2341
CAN ICES-003(B)/NMB-003(B)



RG1 IEC 62471-5:2015
Complies with 21 CFR 1040.10, 10 and 1040.11
except for deviations pursuant to Laser Notice No. 50,
dated June 24, 2007.
Conforme aux normes 21 CFR 1040.10 et 1040.11,
à l'exception des écarts conformément à l'avis
laser n° 50 du 24 juin 2007
Made in China / Fabriqué en Chine USB 2.0 port

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan
 Apparaten må tilkoples jorden stikkontakt
 Apparaten skall anslutas till jordat uttag
 Apparaten stikprop skal tilsluttes en stikkontakt
 med jord, som giver forbindelse til stikproppens jord.

248.4mm