



TEST REPORT

APPLICANT : Anker Innovations Limited
PRODUCT NAME : Nebula Astro
MODEL NAME : D2400
BRAND NAME : NEBULA
FCC ID : 2AOKB-D2400
STANDARD(S) : 47 CFR Part 15 Subpart C
RECEIPT DATE : 2020-04-10
TEST DATE : 2020-05-27 to 2020-06-16
ISSUE DATE : 2020-06-28

Edited by: Chen Bilian
Chen Bilian (Rapporteur)
Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information 3**
- 1.1. Applicant and Manufacturer Information 3**
- 1.2. Equipment Under Test (EUT) Description 3**
- 1.3. Modulation Type and Data Rate of EUT 4**
- 1.4. The Channel Number and Frequency 5**
- 1.5. Test Standards and Results 6**
- 1.6. Environmental Conditions 7**
- 2. 47 CFR Part 15C Requirements 8**
- 2.1. Antenna Requirement 8**
- 2.2. Duty Cycle of Test Signal 9**
- 2.3. Maximum Peak and Average Conducted Output Power 12**
- 2.4. Bandwidth 15**
- 2.5. Conducted Spurious Emissions and Band Edge 22**
- 2.6. Power Spectral Density (PSD) 32**
- 2.7. Conducted Emission 39**
- 2.8. Restricted Frequency Bands 43**
- 2.9. Radiated Emission 53**
- Annex A Test Uncertainty 66**
- Annex B Testing Laboratory Information 67**

Change History		
Version	Date	Reason for change
1.0	2020-06-28	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Anker Innovations Limited
Applicant Address:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Room 1318-19 ,Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong

1.2. Equipment Under Test (EUT) Description

Product Name:	Nebula Astro	
Serial No:	(N/A, marked #1 by test site)	
Hardware Version:	V0.3	
Software Version:	msm8909.Astro_V6.0.8-master	
Equipment Type:	WLAN2.4G	
Modulation Type:	DSSS, OFDM	
Operating Frequency Range:	802.11b/g/ n(HT20): 2.412GHz - 2.462GHz	
Antenna Type:	FPC antenna	
Antenna Gain:	0dBi	
Accessory Information:	Battery	
	Brand Name:	N/A
	Model No.:	INR18650F1L(1INR1966)
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	3150mAh
	Rated Voltage:	3.63V



Accessory Information:	AC Adapter	
	Brand Name:	N/A
	Model No.:	TEKA012-0502000UK
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5.0V=2.0A
	Rated Input:	100-240V ~ 0.35A

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Modulation Type and Data Rate of EUT

Modulation technology	Modulation Type	Data Rate (Mbps) ^{Note1}
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n-20MHz)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.



1.4. The Channel Number and Frequency

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/ n(HT20)	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		

Note1: The Lowest Channel (1), Middle Channel (6) and Highest Channel (11) was selected test for 802.11b/g/n(HT20) mode;



1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle Of Test Signal	Jun 9, 2020	Ouyang Feng	PASS	No deviation
3	15.247(b)	Maximum Peak and Average Conducted Output Power	Jun 9, 2020	Ouyang Feng	PASS	No deviation
4	15.247(a)	Bandwidth	Jun 9, 2020	Ouyang Feng	PASS	No deviation
5	15.247(d)	Conducted Spurious Emission and Band Edge	Jun 9, 2020	Ouyang Feng	PASS	No deviation
6	15.247(e)	Power spectral density (PSD)	Jun 9, 2020	Ouyang Feng	PASS	No deviation
7	15.207	Conducted Emission	May 27, 2020	Ouyang Feng	PASS	No deviation
8	15.247(d)	Restricted Frequency Bands	Jun 16, 2020	Huang Zhiye	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Jun 16, 2020	Li ZiHao	PASS	No deviation

Note1: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013, KDB558074 D01 v05r02.

Note2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12dB contains two parts that cable loss 2dB and Attenuator 10dB.



Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.




2.2.3. Test Result


A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*Ig[1/D])
802.11b	97.51	0.11
802.11g	87.82	0.56
802.11n(HT20)	86.49	0.63


B. Test Plots



(Channel 1, 2412MHz, 802.11b)



(Channel 1, 2412MHz, 802.11g)



(Channel 1, 2412MHz, 802.11 n (HT20))

2.3. Maximum Peak and Average Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



2.3.3. Test Result

Maximum Peak Conducted Output Power

802.11b Test Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	24.53	0.284	30	1	PASS
6	2437	24.45	0.279			PASS
11	2462	24.27	0.267			PASS

802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	24.42	0.277	30	1	PASS
6	2437	25.24	0.334			PASS
11	2462	25.02	0.318			PASS

802.11n (HT20) Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	25.17	0.329	30	1	PASS
6	2437	25.24	0.334			PASS
11	2462	25.10	0.324			PASS



Maximum Average Conducted Output Power

802.11b Test Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated		dBm	W	
		dBm		dBm	W			
1	2412	21.47	0.11	21.58	0.144	30	1	PASS
6	2437	21.43		21.54	0.143			PASS
11	2462	21.29		21.40	0.138			PASS

802.11g Test mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated		dBm	W	
		dBm		dBm	W			
1	2412	21.44	0.56	22.00	0.158	30	1	PASS
6	2437	17.33		17.89	0.062			PASS
11	2462	17.19		17.75	0.060			PASS

802.11n (HT20) Test mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated		dBm	W	
		dBm		dBm	W			
1	2412	17.35	0.63	17.98	0.063	30	1	PASS
6	2437	17.42		18.05	0.064			PASS
11	2462	17.26		17.89	0.062			PASS


2.4. Bandwidth

2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.4.3. Test Procedure

KDB 558074 Section 8.2 was used in order to prove compliance.



2.4.4. Test Result

802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.57	≥500	PASS
6	2437	8.53	≥500	PASS
11	2462	8.08	≥500	PASS

B. Test Plots



(Channel 1, 802.11b)



(Channel 6, 802.11b)



(Channel 11, 802.11b)



802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.39	≥500	PASS
6	2437	16.44	≥500	PASS
11	2462	16.38	≥500	PASS

B. Test Plots:



(Channel 1, 802.11g)



(Channel 6, 802.11g)



(Channel 11, 802.11g)




802.11n (HT20) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.62	≥500	PASS
6	2437	17.61	≥500	PASS
11	2462	17.60	≥500	PASS


B. Test Plots:



(Channel 1, 802.11n(HT20))



(Channel 6, 802.11n(HT20))



(Channel 11, 802.11n(HT20))


2.5. Conducted Spurious Emissions and Band Edge

2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.



2.5.4. Test Result

802.11b Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-37.54	13.54	-6.46	PASS
6	2437	-38.15	13.15	-6.85	PASS
11	2462	-37.37	13.20	-6.8	PASS

B. Test Plots:



(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)



802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-37.23	5.93	-14.07	PASS
6	2437	-38.02	4.71	-15.29	PASS
11	2462	-38.00	4.89	-15.11	PASS

B. Test Plots:



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




802.11n (HT20) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-37.91	4.58	-15.42	PASS
6	2437	-37.82	7.67	-12.33	PASS
11	2462	-38.02	7.24	-12.76	PASS

B. Test Plots:



(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)


2.6. Power Spectral Density (PSD)

2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.6.3. Test Procedure

KDB 558074 Section 8.4 was used in order to prove compliance.



2.6.4. Test Result

802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	1.03	8	PASS
6	2437	1.10	8	PASS
11	2462	1.93	8	PASS

B. Test Plots:



(Channel = 1, 802.11b)



(Channel = 6, 802.11b)



(Channel = 11, 802.11b)



802.11g Test mode


A. Test Verd0.90t:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-5.77	8	PASS
6	2437	-4.70	8	PASS
11	2462	-6.48	8	PASS

B. Test Plots:




(Channel = 1, 802.11g)




(Channel = 6, 802.11g)



(Channel = 11, 802.11g)



(Channel = 6, 802.11n(HT20))



(Channel = 11, 802.11n(HT20))

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode1: EUT+ADAPTER+ WIFI TX


Test Voltage: AC 120V/60Hz

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$


U_R : Receiver Reading

A_{Factor} : Voltage division factor of LISN



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1772	39.96	28.25	64.62	54.62	Line	PASS
2	0.5055	42.10	32.41	56.00	46.00		PASS
3	0.7668	32.01	23.18	56.00	46.00		PASS
4	1.2627	29.53	21.65	56.00	46.00		PASS
5	3.0105	40.46	29.42	56.00	46.00		PASS
6	4.9604	25.30	15.91	56.00	46.00		PASS



(N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.5009	43.63	34.40	56.00	46.00	Neutral	PASS
2	1.9809	39.83	26.99	56.00	46.00		PASS
3	3.4689	35.61	22.50	56.00	46.00		PASS
4	4.4524	33.58	20.82	56.00	46.00		PASS
5	5.1058	30.23	18.81	60.00	50.00		PASS
6	9.8706	29.52	19.29	60.00	50.00		PASS


2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.8.3. Test Procedure

KDB 558074 Section 8.6 and 8.7 was used in order to prove compliance.

2.8.4. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2387.81	PK	57.47	-29.67	32.56	60.36	74	PASS
1	2387.81	AV	34.74	-29.67	32.56	37.63	54	PASS
11	2484.61	PK	58.37	-29.67	32.56	61.26	74	PASS
11	2483.89	AV	35.28	-29.67	32.56	38.17	54	PASS




B. Test Plots:




(PEAK, Channel = 1, 802.11b)



(AVG, Channel = 1, 802.11b)



(PEAK, Channel = 11, 802.11b)



(AVG, Channel = 11, 802.11b)




802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	A _T (dB)	A _{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV	U _R (dBuV)					
1	2389.38	PK	61.77	-29.67	32.56	64.66	74	PASS
1	2390.05	AV	40.97	-29.67	32.56	43.86	54	PASS
11	2483.66	PK	67.54	-29.67	32.56	70.43	74	PASS
11	2483.62	AV	44.13	-29.67	32.56	47.02	54	PASS


B. Test Plots:




(PEAK, Channel = 1, 802.11g)



(AVG, Channel = 1, 802.11g)



(PEAK, Channel = 11, 802.11g)



(AVG, Channel = 11,802.11g)




802.11 n (HT20) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	A_T	A_{Factor}	Max. Emission	Limit	Verdict
		PK/ AV	U_R (dBuV)	(dB)	(dB@3m)	E (dBuV/m)	(dBuV/m)	
1	2389.04	PK	63.94	-29.67	32.56	66.83	74	PASS
1	2389.82	AV	43.43	-29.67	32.56	46.32	54	PASS
11	2483.93	PK	67.81	-29.67	32.56	70.70	74	PASS
11	2483.85	AV	45.92	-29.67	32.56	48.81	54	PASS

B. Test Plots:




(PEAK, Channel = 1, 802.11n(HT20))



(AVG, Channel = 1, 802.11n(HT20))



(PEAK, Channel = 11, 802.11n(HT20))



(AVG, Channel = 11, 802.11n(HT20))



2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.9.2. Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading



For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


802.11b Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
195.106	34.89	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1230.492	45.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2260.100	54.09	N/A	32.08	74.00	N/A	54.00	Horizontal	PASS
4824.100	51.06	N/A	45.43	74.00	N/A	54.00	Horizontal	PASS
8987.961	47.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17865.576	49.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
189.036	30.66	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1000.000	26.87	N/A	N/A	N/A	54.00	N/A	Vertical	PASS
2341.337	50.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4823.604	50.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9648.882	48.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
17946.790	50.59	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
165.970	24.71	N/A	32.37	N/A	43.50	N/A	Horizontal	PASS
2369.500	52.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2523.810	50.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4874.013	49.87	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8805.928	47.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17929.987	50.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
185.394	30.99	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2354.500	56.96	N/A	32.79	74.00	N/A	54.00	Vertical	PASS
4874.000	52.46	N/A	48.06	74.00	N/A	54.00	Vertical	PASS
8450.264	47.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9746.899	50.02	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
17960.793	49.54	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
190.250	29.04	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2356.900	54.36	N/A	32.32	74.00	N/A	54.00	Horizontal	PASS
2514.400	56.01	N/A	33.32	74.00	N/A	54.00	Horizontal	PASS
4924.423	48.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10872.704	47.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17932.788	49.27	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
190.250	32.26	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2342.100	54.76	N/A	32.38	74.00	N/A	54.00	Vertical	PASS
2505.900	55.10	N/A	32.37	74.00	N/A	54.00	Vertical	PASS
4924.423	49.41	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9847.718	49.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12894.672	47.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


802.11g Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
197.534	25.47	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2276.600	53.84	N/A	32.05	74.00	N/A	54.00	Horizontal	PASS
2352.100	55.71	N/A	32.61	74.00	N/A	54.00	Horizontal	PASS
5397.709	48.97	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8450.264	47.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12687.434	47.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
192.678	29.22	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2311.200	52.08	N/A	32.69	74.00	N/A	54.00	Vertical	PASS
2388.000	55.73	N/A	33.73	74.00	N/A	54.00	Vertical	PASS
5632.951	47.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9648.882	48.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
17935.588	49.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
232.741	24.67	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2369.508	50.90	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2506.600	52.83	N/A	32.42	74.00	N/A	54.00	Horizontal	PASS
5610.547	46.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10231.388	46.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12891.871	48.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
243.667	25.34	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2259.800	53.96	N/A	32.14	74.00	N/A	54.00	Vertical	PASS
2377.000	55.13	N/A	32.65	74.00	N/A	54.00	Vertical	PASS
4874.013	47.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9746.899	50.29	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12158.138	49.30	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 11



Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
158.686	22.06	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2380.392	50.62	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4924.423	46.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5672.159	47.38	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10354.610	47.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17943.990	49.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
199.962	32.30	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2355.900	55.17	N/A	32.81	74.00	N/A	54.00	Vertical	PASS
2518.800	56.49	N/A	34.16	74.00	N/A	54.00	Vertical	PASS
2617.400	56.97	N/A	32.30	74.00	N/A	54.00	Vertical	PASS
9847.718	49.63	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
17969.194	49.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




802.11n (HT20) Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
105.269	25.04	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2386.300	59.99	N/A	37.45	74.00	N/A	54.00	Horizontal	PASS
4829.205	50.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8433.461	47.82	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12597.818	47.85	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17960.793	50.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
192.678	26.57	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2245.298	58.58	N/A	33.68	74.00	N/A	54.00	Vertical	PASS
2378.471	65.75	N/A	46.12	74.00	N/A	54.00	Vertical	PASS
4818.003	48.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9648.882	48.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
17932.788	49.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
89.487	25.79	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2340.200	53.55	N/A	32.71	74.00	N/A	54.00	Horizontal	PASS
5624.550	47.49	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7912.566	46.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12665.030	48.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17952.391	49.87	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
185.394	26.78	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2283.900	55.05	N/A	31.66	74.00	N/A	54.00	Vertical	PASS
2366.500	59.07	N/A	32.32	74.00	N/A	54.00	Vertical	PASS
5649.755	47.46	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9746.899	50.01	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
17977.596	50.02	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
201.176	23.99	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2208.163	50.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4451.137	46.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8441.862	47.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12519.404	48.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17929.987	49.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
198.748	30.41	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2386.300	52.23	N/A	31.98	74.00	N/A	54.00	Vertical	PASS
2516.400	53.36	N/A	32.36	74.00	N/A	54.00	Vertical	PASS
3997.454	47.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5761.775	48.67	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9847.718	50.30	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Attenuator 1	(N/A.)	10dB	Resent	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2020.04.01	2021.03.31
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2020.04.01	2021.03.31
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2020.03.26	2021.03.25
LISN	812744	NSLK 8127	Schwarzbeck	2020.03.26	2021.03.25
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2019.05.08	2020.05.09
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A
Adapter	NA	HA-190501 00UU	HONGGUAN GDE	N/A	N/A
Mobile phone	FFMZGMJ9J C6F	iPhone 8	Apple	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Townsend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V1.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2019.07.29	2020.07.28
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2019.02.14	2022.02.13
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2019.05.24	2022.05.23
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2019.12.01	2020.12.01
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

————— END OF REPORT —————