

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AOKB-T8360

### EUT Specification

<b>EUT</b>	eufyCare Baby Monitor 2
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	WIFI 2.4G: 22.15dBm (0.1641W); BLE: 4.213dBm (0.0026W)
<b>Antenna gain (Max)</b>	BLE/WIFI2.4G: 2.53 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	<b>F/300</b>	<b>6</b>
1500-100000	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	<b>F/1500</b>	<b>6</b>
1500-100000	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $Pd=(Pout \cdot G) \cdot (4 \cdot \pi \cdot R^2)$

Where

$Pd$ = Power density in  $mW/cm^2$

$Pout$ =output power to antenna in Mw

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$Pd$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits ( $mW/cm^2$ )
	(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	( $mW/cm^2$ )	
802.11b	2412	22.15	22.15 $\pm 1$	23.15	2.53	0.0736	1
	2437	22.11	22.11 $\pm 1$	23.11	2.53	0.0729	1
	2462	21.83	21.83 $\pm 1$	22.83	2.53	0.0684	1
802.11g	2412	20.96	20.96 $\pm 1$	21.96	2.53	0.0560	1
	2437	21.44	21.44 $\pm 1$	22.44	2.53	0.0625	1
	2462	21.52	21.52 $\pm 1$	22.52	2.53	0.0637	1
802.11n (HT20)	2412	21.50	21.50 $\pm 1$	22.50	2.53	0.0634	1
	2437	21.39	21.39 $\pm 1$	22.39	2.53	0.0618	1
	2462	21.00	21.00 $\pm 1$	22.00	2.53	0.0565	1
BLE	2402	4.213	4.213 $\pm 1$	5.21	2.53	0.0012	1
	2440	3.823	3.823 $\pm 1$	4.82	2.53	0.0011	1
	2480	2.744	2.744 $\pm 1$	3.74	2.53	0.0008	1

**Note: BT&WIFI cannot support simultaneous transmission.**