

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AOKB-T8520

### EUT Specification

|                                   |                                                                                                                                                                                                                                              |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT</b>                        | <b>Smart Lock Touch &amp; Wi-Fi</b>                                                                                                                                                                                                          |
| <b>Frequency band (Operating)</b> | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz<br><input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz<br><input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz BLE |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others ____                                                                                |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> )<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )                                                |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity               |
| <b>Max. output power</b>          | BLE: 7.492dBm (0.0056W)<br>2.4G : 21.03dBm (0.1268W)                                                                                                                                                                                         |
| <b>Antenna gain (Max)</b>         | 0 dBi                                                                                                                                                                                                                                        |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/> MPE Evaluation<br><input type="checkbox"/> SAR Evaluation                                                                                                                                                |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz)                                         | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--------------------------------------------------------------|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| <b>300-1500</b>                                              | --                           | --                           | <b>F/300</b>                       | <b>6</b>     |
| <b>1500-100000</b>                                           | --                           | --                           | <b>5</b>                           | <b>6</b>     |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| <b>300-1500</b>                                              | --                           | --                           | <b>F/1500</b>                      | <b>6</b>     |
| <b>1500-100000</b>                                           | --                           | --                           | <b>1</b>                           | <b>30</b>    |

## Friis transmission formula: $P_d = \frac{P_{out} * G}{(4 * \pi * R^2)}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### 2.4GHz WiFi ANT A:

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm  | Power density Limits (mW/cm <sup>2</sup> ) |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|--------------------------------------------|
|                | (MHz)             | (dBm)          | (dBm)             | (dBm)              | (dBi)        | (mW/ cm <sup>2</sup> ) |                                            |
| 802.11b        | 2412              | 21.03          | 21.03±1           | 22.03              | 0            | 0.0317                 | 1                                          |
|                | 2437              | 20.60          | 20.60±1           | 21.60              | 0            | 0.0288                 | 1                                          |
|                | 2462              | 20.42          | 20.42±1           | 21.42              | 0            | 0.0276                 | 1                                          |
| 802.11g        | 2412              | 20.47          | 20.47±1           | 21.47              | 0            | 0.0279                 | 1                                          |
|                | 2437              | 20.48          | 20.48±1           | 21.48              | 0            | 0.0280                 | 1                                          |
|                | 2462              | 19.77          | 19.77±1           | 20.77              | 0            | 0.0238                 | 1                                          |
| 802.11n (HT20) | 2412              | 20.49          | 20.49±1           | 21.49              | 0            | 0.0280                 | 1                                          |
|                | 2437              | 20.44          | 20.44±1           | 21.44              | 0            | 0.0277                 | 1                                          |
|                | 2462              | 19.91          | 19.91±1           | 20.91              | 0            | 0.0245                 | 1                                          |
| BLE            | 2402              | 7.492          | 7.492±1           | 8.492              | 0            | 0.0014                 | 1                                          |
|                | 2440              | 7.075          | 7.075±1           | 8.075              | 0            | 0.0013                 | 1                                          |
|                | 2480              | 6.488          | 6.488±1           | 7.488              | 0            | 0.0011                 | 1                                          |

**Note: BT and 2.4G WIFI cannot support simultaneous transmission.**