



REPORT No.: SZ25030153W02

TEST REPORT

APPLICANT : Anker Innovations Limited

PRODUCT NAME : HomeBase Professional S1

MODEL NAME : T9000

BRAND NAME : eufy

FCC ID : 2AOKB-T9000

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2025-04-01


TEST DATE : 2025-05-12 to 2025-05-22

ISSUE DATE : 2025-06-17

Edited by:


Zeng Xiaoying (Rapporteur)

Approved by:


Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	11
2.4. Test Configuration of EUT	12
2.5. Test Conditions	12
2.6. Test Setup Layout Diagram	12
3. Test Results	15
3.1. Antenna Requirement	15
3.2. Duty Cycle of Test Signal	16
3.3. Maximum Peak Conducted Output Power	17
3.4. Maximum Average Conducted Output Power	18
3.5. 6 dB Bandwidth	19
3.6. Conducted Spurious Emissions and Band Edge	20
3.7. Power Spectral Density	21
3.8. Conducted Emission	22
3.9. Restricted Frequency Bands	23
3.10. Radiated Emission	24
Annex A Test Data and Result	26



REPORT No.: SZ25030153W02

Change History		
Version	Date	Reason for change
1.0	2025-06-17	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	May 12, 2025	Su Xiaoxian	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	May 12, 2025	Su Xiaoxian	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	May 12, 2025	Su Xiaoxian	PASS	/
5	15.247(a)	Bandwidth	May 12, 2025	Su Xiaoxian	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	May 12, 2025	Su Xiaoxian	PASS	/
7	15.247(e)	Power Spectral Density	May 12, 2025	Su Xiaoxian	PASS	/
8	15.207	Conducted Emission	May 22, 2025	Fan Shengquan	PASS	/
9	15.247(d)	Restricted Frequency Bands	May 15, 2025	Li Hanbin	PASS	/
10	15.209, 15.247(d)	Radiated Emission	May 17, 2025	Li Hanbin	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2025.01.06	2026.01.05
LISN	8127449	NSLK 8127	Schwarzbeck	2025.01.09	2026.01.08
Pulse Limiter (10dB)	VTSD 9561 F- B #206	VTSD 9561-F	Schwarzbeck	2024.05.30	2025.05.29
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	N/A	N/A
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	N/A	N/A
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	N/A	N/A
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Anker Innovations Limited
Applicant Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

2.2. Information of EUT

Product Name:	HomeBase Professional S1	
Sample No.:	1#, 17#, 18#	
Hardware Version:	V7	
Software Version:	V4.0.1.6	
Equipment Type:	Zigbee	
Modulation Type:	QPSK	
Operating Frequency Range:	2405MHz-2480MHz	
Antenna Type:	PCB Antenna	
Antenna Gain:	2.94dBi	
Accessory Information:	Battery	
	Brand Name:	N/A
	Model No.:	T9000
	Serial No.:	N/A
	Capacity:	9800mAh
	Rated Voltage:	9.6V
	Charge Limit:	10.95V
	Manufacturer:	Fujian SCUD Power Technology Co., Ltd.
	AC Adapter	
	Brand Name:	Huntkey
	Model No.:	HKA12048025-7E
	Serial No.:	N/A
	Rated Output:	48V $\overline{\sim}$ 2.5A
	Rated Input:	100-240V $\sim$ 50/60Hz, 1.8A



REPORT No.: SZ25030153W02

	Manufacturer:	Shenzhen Huntkey Electric Co., Ltd.
--	---------------	-------------------------------------

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	21	2455
12	2410	22	2460
13	2415	23	2465
14	2420	24	2470
15	2425	25	2475
16	2430	26	2480
17	2435		
18	2440		
19	2445		
20	2450		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions


Temperature (°C):	15–35
Relative Humidity (%):	30–60
Atmospheric Pressure (kPa):	86–106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☒ PCB Antenna ☐ PIFA Antenna ☐ On-board Antenna	☒ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

Refer to Annex A.8 in this report.



3.9. Restricted Frequency Bands

3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result

Refer to Annex A.10 in this report.



Annex A Test Data and Result


A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	Zigbee	2405	Ant1	33.95	4.69	0.9
NVNT	Zigbee	2445	Ant1	34.04	4.68	0.9
NVNT	Zigbee	2480	Ant1	34.04	4.68	0.9




Test Graphs

Duty Cycle NVNT Zigbee 2405MHz Ant1




Duty Cycle NVNT Zigbee 2445MHz Ant1





Duty Cycle NVNT Zigbee 2480MHz Ant1




**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	Zigbee	2405	Ant1	19.97	0	19.97	0.09931	30	Pass
NVNT	Zigbee	2445	Ant1	19.55	0	19.55	0.09016	30	Pass
NVNT	Zigbee	2480	Ant1	19.79	0	19.79	0.09528	30	Pass

Test Graphs

Peak Power NVNT Zigbee 2405MHz Ant1




Peak Power NVNT Zigbee 2445MHz Ant1





Peak Power NVNT Zigbee 2480MHz Ant1




**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	Zigbee	2405	Ant1	15.19	4.69	19.88	0.09727	30	Pass
NVNT	Zigbee	2445	Ant1	14.52	4.68	19.2	0.08318	30	Pass
NVNT	Zigbee	2480	Ant1	15	4.68	19.68	0.0929	30	Pass




Test Graphs

Average Power NVNT Zigbee 2405MHz Ant1




Average Power NVNT Zigbee 2445MHz Ant1





Average Power NVNT Zigbee 2480MHz Ant1






REPORT No.: SZ25030153W02

A.4. 6 dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	Zigbee	2405	Ant1	1.543	0.5	Pass
NVNT	Zigbee	2445	Ant1	1.428	0.5	Pass
NVNT	Zigbee	2480	Ant1	1.327	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT Zigbee 2405MHz Ant1




-6dB Bandwidth NVNT Zigbee 2445MHz Ant1





-6dB Bandwidth NVNT Zigbee 2480MHz Ant1



**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	Zigbee	2405	Ant1	-47.88	-20	Pass
NVNT	Zigbee	2445	Ant1	-46.97	-20	Pass
NVNT	Zigbee	2480	Ant1	-48.5	-20	Pass

Test Graphs

Tx. Spurious NVNT Zigbee 2405MHz Ant1 Ref




Tx. Spurious NVNT Zigbee 2405MHz Ant1 Emission







Tx. Spurious NVNT Zigbee 2445MHz Ant1 Ref




Tx. Spurious NVNT Zigbee 2445MHz Ant1 Emission



Tx. Spurious NVNT Zigbee 2480MHz Ant1 Ref



Tx. Spurious NVNT Zigbee 2480MHz Ant1 Emission





REPORT No.: SZ25030153W02

A.6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	Zigbee	2405	Ant1	-57.15	-20	Pass
NVNT	Zigbee	2480	Ant1	-54.03	-20	Pass




Test Graphs

Band Edge NVNT Zigbee 2405MHz Ant1 Ref



Band Edge NVNT Zigbee 2405MHz Ant1 Emission






Band Edge NVNT Zigbee 2480MHz Ant1 Ref



Band Edge NVNT Zigbee 2480MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	Zigbee	2405	Ant1	6.34	0	6.34	8	Pass
NVNT	Zigbee	2445	Ant1	5.89	0	5.89	8	Pass
NVNT	Zigbee	2480	Ant1	5.98	0	5.98	8	Pass




Test Graphs

PSD NVNT Zigbee 2405MHz Ant1




PSD NVNT Zigbee 2445MHz Ant1





PSD NVNT Zigbee 2480MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+Router+RJ45+Camera1+Camera2+Camera3+Camera4+Mobile phone+Zigbee TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1500	56.57	38.69	66.00	56.00	Line	PASS
2	0.2940	33.81	23.21	60.41	50.41		PASS
3	0.6676	24.02	19.69	56.00	46.00		PASS
4	2.1480	26.17	20.32	56.00	46.00		PASS
5	10.2888	40.68	30.16	60.00	50.00		PASS
6	20.2563	43.18	35.22	60.00	50.00		PASS




(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1500	56.65	38.77	66.00	56.00	Neutral	PASS
2	0.4605	30.39	25.95	56.68	46.68		PASS
3	1.1761	25.18	20.02	56.00	46.00		PASS
4	4.0020	30.39	24.46	56.00	46.00		PASS
5	10.3562	40.94	29.82	60.00	50.00		PASS
6	18.3041	43.17	35.96	60.00	50.00		PASS

A.9. Restricted Frequency Bands

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Vertical) was recorded in this test report.


Plot for Channel 11



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2351.92	9.7	42.08	32.400	54.00	11.92	150	106	AV	PASS
2354.08	22.7	55.10	32.420	74.00	18.90	150	233	PK	PASS
2365.74	22.3	54.78	32.460	74.00	19.22	150	106	PK	PASS
2365.98	11.0	43.50	32.460	54.00	10.50	150	106	AV	PASS
2378.23	22.4	54.86	32.510	74.00	19.14	150	263	PK	PASS
2382.67	10.0	42.49	32.520	54.00	11.51	150	97	AV	PASS



Plot for Channel 26



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.52	17.7	50.73	33.030	54.00	3.27	150	266	AV	PASS
2483.74	29.1	62.10	33.030	74.00	11.90	150	273	PK	PASS
2485.24	25.9	58.91	33.030	74.00	15.09	150	273	PK	PASS
2485.69	13.3	46.34	33.030	54.00	7.66	150	273	AV	PASS
2486.64	12.8	45.87	33.030	54.00	8.13	150	273	AV	PASS
2486.87	23.4	56.47	33.030	74.00	17.53	150	273	PK	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.




Plot for Channel 11




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
48.04	61.0	32.68	-28.290	40.00	7.32	150	335	PK	PASS
65.79	62.5	29.60	-32.930	40.00	10.40	150	66	PK	PASS
95.09	62.4	31.71	-30.700	43.50	11.79	150	349	PK	PASS
145.10	66.2	32.66	-33.540	43.50	10.84	150	160	PK	PASS
206.65	60.4	30.30	-30.060	43.50	13.20	150	281	PK	PASS
840.96	54.9	39.11	-15.770	46.00	6.89	150	254	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2404.31	59.2	59.93	0.760	74.00	14.07	150	130	PK	PASS
2404.76	52.4	53.13	0.770	54.00	0.87	150	130	AV	PASS
2568.35	50.4	51.03	0.600	74.00	22.97	150	120	PK	PASS
4809.56	45.1	34.39	-10.670	54.00	19.61	150	172	AV	PASS
7212.64	53.1	49.39	-3.720	74.00	24.61	150	55	PK	PASS
7216.14	44.5	40.77	-3.750	54.00	13.23	150	34	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
47.99	64.9	36.65	-28.290	40.00	3.35	150	146	PK	PASS
71.71	70.4	35.58	-34.800	40.00	4.42	150	11	PK	PASS
95.67	62.6	32.06	-30.580	43.50	11.44	150	267	PK	PASS
262.13	63.0	35.12	-27.920	46.00	10.88	150	252	PK	PASS
533.21	56.4	35.05	-21.380	46.00	10.95	150	360	PK	PASS
838.87	57.8	41.95	-15.830	46.00	4.05	150	225	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2404.31	63.6	64.34	0.760	74.00	9.66	150	110	PK	NA
2404.76	57.1	57.85	0.770	54.00	-3.85	150	87	AV	NA
4493.05	52.2	40.47	-11.740	54.00	13.53	150	173	AV	PASS
5998.60	56.3	49.07	-7.260	74.00	24.93	150	173	PK	PASS
7213.14	48.2	44.48	-3.720	54.00	9.52	150	80	AV	PASS
7215.14	54.4	50.65	-3.740	74.00	23.35	150	80	PK	PASS




Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
47.99	60.9	32.63	-28.290	40.00	7.37	150	353	PK	PASS
67.40	62.7	29.12	-33.540	40.00	10.88	150	106	PK	PASS
95.58	61.7	31.09	-30.590	43.50	12.41	150	11	PK	PASS
146.26	73.4	39.87	-33.500	43.50	3.63	150	11	PK	PASS
207.96	60.0	30.04	-29.960	43.50	13.46	150	227	PK	PASS
833.01	55.6	39.62	-15.940	46.00	6.38	150	268	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2445.21	48.0	49.04	1.040	54.00	4.96	150	215	AV	PASS
2445.65	54.1	55.15	1.050	74.00	18.85	150	215	PK	PASS
4889.56	51.8	41.93	-9.910	54.00	12.07	150	47	AV	PASS
4889.56	57.3	47.42	-9.910	74.00	26.58	150	47	PK	PASS
7336.14	52.5	48.76	-3.780	74.00	25.24	150	139	PK	PASS
7336.14	45.8	41.99	-3.780	54.00	12.01	150	139	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
47.99	65.3	36.97	-28.290	40.00	3.03	150	134	PK	PASS
66.62	69.9	36.62	-33.240	40.00	3.38	150	350	PK	PASS
72.49	71.4	36.48	-34.910	40.00	3.52	150	350	PK	PASS
95.53	63.2	32.60	-30.600	43.50	10.90	150	282	PK	PASS
252.92	63.4	35.39	-28.050	46.00	10.61	150	0	PK	PASS
843.48	56.2	40.52	-15.680	46.00	5.48	150	215	PK	PASS




(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2445.21	51.8	52.86	1.040	54.00	1.14	150	109	AV	PASS
2445.65	58.2	59.22	1.050	74.00	14.78	150	109	PK	PASS
4890.56	58.7	48.81	-9.890	74.00	25.19	150	34	PK	PASS
4890.56	52.6	42.74	-9.890	54.00	11.26	150	219	AV	PASS
7333.14	48.0	44.22	-3.760	54.00	9.78	150	195	AV	PASS
7333.14	55.1	51.36	-3.760	74.00	22.64	150	195	PK	PASS




Plot for Channel 26




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
38.29	62.8	33.18	-29.630	40.00	6.82	150	310	PK	PASS
47.99	60.9	32.64	-28.290	40.00	7.36	150	323	PK	PASS
66.72	63.4	30.10	-33.280	40.00	9.90	150	80	PK	PASS
77.14	71.3	36.00	-35.310	40.00	4.00	150	310	PK	PASS
144.81	65.9	32.35	-33.540	43.50	11.15	150	175	PK	PASS
834.85	58.1	42.16	-15.900	46.00	3.84	150	242	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.44	62.6	63.51	0.920	74.00	10.49	150	136	PK	NA
2479.88	56.2	57.07	0.920	54.00	-3.07	150	136	AV	NA
4960.57	54.3	44.12	-10.130	54.00	9.88	150	0	AV	PASS
4960.57	60.3	50.16	-10.130	74.00	23.84	150	2	PK	PASS
7441.15	44.5	39.98	-4.470	54.00	14.02	150	234	AV	PASS
7441.65	51.9	47.41	-4.480	74.00	26.59	150	0	PK	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
48.09	64.6	36.29	-28.300	40.00	3.71	150	186	PK	PASS
66.72	69.8	36.55	-33.280	40.00	3.45	150	345	PK	PASS
72.49	70.8	35.91	-34.910	40.00	4.09	150	25	PK	PASS
95.09	63.2	32.51	-30.700	43.50	10.99	150	200	PK	PASS
262.13	62.9	34.97	-27.920	46.00	11.03	150	11	PK	PASS
835.82	58.6	42.73	-15.890	46.00	3.27	150	226	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.44	63.6	64.52	0.920	74.00	9.48	150	191	PK	NA
2479.88	57.3	58.26	0.920	54.00	-4.26	150	191	AV	NA
4958.57	61.6	51.44	-10.130	74.00	22.56	150	166	PK	PASS
4958.57	56.5	46.34	-10.130	54.00	7.66	150	188	AV	PASS
7438.15	52.3	47.91	-4.430	54.00	6.09	150	166	AV	PASS
7441.15	58.6	54.15	-4.470	74.00	19.85	150	142	PK	PASS

————— END OF REPORT —————