

TEST REPORT

| | | |
|--|---|---|
| FCC ID : | 2AOKB-T9149 | |
| Test Report No : | TCT211220E041 | |
| Date of issue : | Jan. 12, 2022 | |
| Testing laboratory | SHENZHEN TONGCE TESTING LAB | |
| Testing location/ address: | TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China | |
| Applicant's name : | Anker Innovations Limited | |
| Address : | Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong | |
| Manufacturer's name ... : | Shenzhen Unique Scales Co., Ltd | |
| Address : | Room# 301, 601, No. 22, Huanping Road, Gaoqiao Community, Pingdi Street, Longgang District, Shenzhen, Guangdong, 518100, China | |
| Standard(s) | FCC CFR Title 47 Part 1.1307 | |
| Test item description | Smart Scale | |
| Trade Mark | N/A | |
| Model/Type reference : | T9149, T9148 | |
| Rating(s) : | DC 6V(4*AAA Battery) | |
| Date of receipt of test item | Dec. 20, 2021 | |
| Date (s) of performance of test : | Dec. 20, 2021 ~ Jan. 12, 2022 | |
| Tested by (+signature) ... : | Aaron MO |  |
| Check by (+signature) : | Beryl ZHAO |  |
| Approved by (+signature): | Tomsin |  |



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

| | |
|---|----------|
| 1. General Product Information | 3 |
| 1.1. EUT description | 3 |
| 1.2. Model(s) list..... | 3 |
| 2. General Information..... | 4 |
| 2.1. Test environment and mode..... | 4 |
| 2.2. Description of Support Units..... | 4 |
| 3. Facilities and Accreditations | 5 |
| 3.1. Facilities | 5 |
| 3.2. Location | 5 |
| 4. Test Results and Measurement Data | 6 |

1. General Product Information

1.1. EUT description

| | |
|-----------------------------|--|
| Test item description | Smart Scale |
| Model/Type reference..... | T9149 |
| Sample Number..... | TCT211220E032-0101 |
| Operation Frequency | For BLE: 2402MHz~2480MHz For WIFI: 2412MHz~2472MHz (802.11b/802.11g/802.11n(HT20)) |
| Modulation Type | For BLE: GFSK For WIFI: DSSS(802.11b), OFDM (802.11g/802.11n) |
| Antenna Type..... | For BLE: PCB Antenna For WIFI: Internal Antenna |
| Antenna Gain..... | BLE: 1.24dBi WIFI: 2.46dBi |
| Rating(s)..... | DC 6V(4*AAA Battery) |

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

| No. | Model No. | Tested with |
|--------------|-----------|-------------------------------------|
| 1 | T9149 | <input checked="" type="checkbox"/> |
| Other models | T9148 | <input type="checkbox"/> |

Note: T9149 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of T9149 can represent the remaining models.

2. General Information

2.1. Test environment and mode

| Item | Normal condition |
|-----------------------|---|
| Temperature | +25°C |
| Voltage | DC 6V |
| Humidity | 56% |
| Atmospheric Pressure: | 1008 mbar |
| Test Mode: | |
| Engineering mode: | Keep the EUT in continuous transmitting by select channel |

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| / | / | / | / | / |

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
SHENZHEN TONGCE TESTING LAB
Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1
SHENZHEN TONGCE TESTING LAB
CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4. Test Results and Measurement Data

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

For BLE:

| Channel | Frequency (GHz) | Max. Power (dBm) | Tune up Power (dBm) | Max. Tune up Power (dBm) | Max. Tune up Power (mW) | Test distance (mm) | Result | exclusion thresholds for 1-g SAR |
|---------|-----------------|------------------|---------------------|--------------------------|-------------------------|--------------------|--------|----------------------------------|
| CH 0 | 2.402 | 1.47 | 1±1 | 2 | 1.58 | 5 | 0.49 | 3.0 |

For WIFI:

| Channel | Frequency (GHz) | Max. Power (dBm) | Tune up Power (dBm) | Max. Tune up Power (dBm) | Max. Tune up Power (mW) | Test distance (mm) | Result | exclusion thresholds for 1-g SAR |
|---------|-----------------|------------------|---------------------|--------------------------|-------------------------|--------------------|--------|----------------------------------|
| CH 11 | 2.462 | 5.91 | 5±1 | 6 | 3.98 | 5 | 1.25 | 3.0 |

Result:

Base on the calculation value, No SAR measurement is required.

*******END OF REPORT*******