

FCC TEST REPORT

For

Anker Innovations Limited

PowerPort Wireless 5 Pad

Model No.: A2518

Prepared For : Anker Innovations Limited
Address : Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon,
Hong Kong

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei
community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong,
China.518102
Tel: (86) 755-26066440 Fax: (86) 755-26014772

Report Number : SZAWW181030004-01

Date of Receipt : Oct. 30, 2018

Date of Test : Oct. 30~Nov. 05, 2018

Date of Report : Nov. 05, 2018

Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	4
1.4. Description of Test Modes.....	5
1.5. Description Of Test Setup.....	6
1.6. Test Equipment List.....	7
1.7. Description of Test Facility.....	8
2. Summary of Test Results.....	9
3. Conducted Emission Test.....	10
3.1. Test Standard and Limit.....	10
3.2. Test Setup.....	10
3.3. Test Procedure.....	10
3.4. Test Data.....	10
4. Radiation Spurious Emission and Band Edge.....	15
4.1. Test Standard and Limit.....	15
4.2. Test Setup.....	15
4.3. Test Procedure.....	16
4.4. Test Data.....	17
5. Antenna Requirement.....	23
5.1. Test Standard and Requirement.....	23
5.2. Antenna Connected Construction.....	23
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	24
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	26
APPENDIX III -- INTERNAL PHOTOGRAPH.....	29

TEST REPORT

Applicant : Anker Innovations Limited
Manufacturer : Anker Innovations Limited
Product Name : PowerPort Wireless 5 Pad
Model No. : A2518
Trade Mark : ANKER
Rating(s) : Input: 5V=== 2A
Output: 5V=== 1A

Test Standard(s) : FCC Part15 Subpart C 2018, Paragraph 15.209

Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test

Oct. 30~Nov. 05, 2018

Prepared By



Oliay Yang

(Engineer / Oliay Yang)

Reviewer

Snowy Meng

(Supervisor / Snowy Meng)

Approved & Authorized Signer

Sally Zhang

(Manager / Sally Zhang)

1. General Information

1.1. Client Information

Applicant	:	Anker Innovations Limited
Address	:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong
Manufacturer	:	Anker Innovations Limited
Address	:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong
Factory	:	SHENZHEN RUIJING INDUSTRIAL CO., LTD
Address	:	Building C1, Hengli Industrial Park, Xiakeng 1st Road No.168, Longgang Street, Longgang District, Shenzhen, Guangdong, China

1.2. Description of Device (EUT)

Product Name	:	PowerPort Wireless 5 Pad	
Model No.	:	A2518	
Trade Mark	:	ANKER	
Test Power Supply	:	AC 240V, 60Hz for adapter/ AC 120V, 60Hz for adapter	
Test Sample No.	:	S1(Normal Sample), S2(Engineering Sample)	
Product Description	:	Operation Frequency:	111~205KHz
		Modulation Type:	MSK
		Antenna Type:	Inductive loop coil Antenna
		Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	Model: A2013 Input: 100-240V~ 50-60Hz 0.7A Output: 3.6-6.5V=== 3A/ 6.5-9V=== 2A/ 9-12V=== 1.5A
Mobile Phone	:	iPhone

1.4. Description of Test Modes



To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode

1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 17, 2017	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 17, 2017	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 17, 2017	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 18, 2017	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 17, 2017	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 20, 2017	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 20, 2017	1 Year
9.	Loop Antenna	Schwarzbeck	HFH2-Z2	100047	Nov. 17, 2017	1 Year
10.	Horn Antenna	Schwarzbeck	BBHA9170	9170-375	Nov. 17, 2017	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Nov. 17, 2017	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 18, 2017	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 17, 2017	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 17, 2017	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 18, 2017	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 18, 2017	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 18, 2017	1 Year
19.	DC Power Supply	LW	TPR-6410D	349315	Nov. 18, 2017	1 Year
20.	Constant Temperature Humidity Chamber	Sertep	ZJ-HWHS80B	ZJ-17042804	Nov. 18, 2017	1 Year

1.7. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS
Part 15.203	Antenna Requirement	PASS


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
5MHz~30MHz	60	50	

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 240V, 60Hz for adapter
 Comment: Live Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.4620	19.72	19.96	39.68	56.66	-16.98	QP	
2	0.5820	14.53	20.00	34.53	56.00	-21.47	QP	
3	1.3340	16.56	20.13	36.69	56.00	-19.31	QP	
4	2.0980	15.94	20.14	36.08	56.00	-19.92	QP	
5	4.2700	16.64	20.19	36.83	56.00	-19.17	QP	
6	11.9180	11.48	20.31	31.79	50.00	-18.21	AVG	
7	12.1380	17.15	20.31	37.46	60.00	-22.54	QP	
8	12.1380	11.83	20.31	32.14	50.00	-17.86	AVG	
9	12.3580	11.46	20.30	31.76	50.00	-18.24	AVG	
10	17.6540	11.47	20.30	31.77	50.00	-18.23	AVG	
11	18.3180	12.99	20.31	33.30	50.00	-16.70	AVG	
12	19.8620	12.98	20.34	33.32	50.00	-16.68	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 240V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2100	22.10	19.90	42.00	63.20	-21.20	QP	
2	0.2740	20.12	19.89	40.01	60.99	-20.98	QP	
3	0.3420	18.25	19.91	38.16	59.15	-20.99	QP	
4	0.4100	18.65	19.94	38.59	57.65	-19.06	QP	
5	0.5860	13.16	20.01	33.17	56.00	-22.83	QP	
6	1.1780	14.09	20.12	34.21	56.00	-21.79	QP	
7	12.1380	10.89	20.31	31.20	50.00	-18.80	AVG	
8	17.4340	12.00	20.30	32.30	50.00	-17.70	AVG	
9	18.0980	12.39	20.31	32.70	50.00	-17.30	AVG	
10	18.7580	12.86	20.32	33.18	50.00	-16.82	AVG	
11	26.2620	10.95	20.28	31.23	50.00	-18.77	AVG	
12	26.4820	11.55	20.28	31.83	50.00	-18.17	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Live Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1499	29.72	19.90	49.62	66.00	-16.38	QP	
2	0.1539	14.75	19.90	34.65	55.78	-21.13	AVG	
3	0.2260	10.30	19.89	30.19	52.59	-22.40	AVG	
4	0.3780	20.82	19.93	40.75	58.32	-17.57	QP	
5	4.7259	4.42	20.20	24.62	46.00	-21.38	AVG	
6	10.3899	15.13	20.33	35.46	60.00	-24.54	QP	
7	10.8339	10.10	20.33	30.43	50.00	-19.57	AVG	
8	11.9379	16.09	20.31	36.40	60.00	-23.60	QP	
9	12.8219	11.68	20.29	31.97	50.00	-18.03	AVG	
10	13.0419	15.37	20.29	35.66	60.00	-24.34	QP	
11	18.5699	16.75	20.32	37.07	60.00	-22.93	QP	
12	19.6739	12.46	20.33	32.79	50.00	-17.21	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: TX Mode
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 23.1°C Hum.: 30%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2100	33.20	19.90	53.10	63.20	-10.10	QP	
2	0.5060	13.96	19.98	33.94	56.00	-22.06	QP	
3	0.5180	26.67	19.99	46.66	56.00	-9.34	QP	
4	0.6060	26.58	20.01	46.59	56.00	-9.41	QP	
5	0.6340	26.02	20.02	46.04	56.00	-9.96	QP	
6	0.6660	26.89	20.03	46.92	56.00	-9.08	QP	
7	11.6980	11.25	20.31	31.56	50.00	-18.44	AVG	
8	12.5980	10.61	20.30	30.91	50.00	-19.09	AVG	
9	12.8220	10.95	20.29	31.24	50.00	-18.76	AVG	
10	18.2220	11.19	20.31	31.50	50.00	-18.50	AVG	
11	18.4460	12.05	20.32	32.37	50.00	-17.63	AVG	
12	20.4700	10.65	20.33	30.98	50.00	-19.02	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.


4.4. Test Data

PASS

Test Results

(Between 9KHz – 30MHz)

Job No.:	SZAWW181030004-01		
Standard:	FCC PART15 C _3m	Power Source:	AC 120V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.7°C/51%RH
Test Mode:	Mode 1	Distance:	3m




Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	degree (dgc)
0.0371	57.49	19.30	2.53	0	79.32	136.09	-56.77	Peak	52
0.0371	43.87	19.30	2.53	0	65.70	116.09	-50.39	AV	52
0.0792	47.48	19.32	2.55	0	69.35	129.54	-60.19	Peak	41
0.0792	36.98	19.32	2.55	0	58.85	109.54	-50.69	AV	41
0.0859	48.78	19.32	2.55	0	70.65	128.84	-58.19	Peak	59
0.0859	41.46	19.32	2.55	0	63.33	108.84	-45.51	AV	59
0.1107	41.96	19.36	2.62	0	63.94	126.65	-62.71	Peak	147
0.1107	31.84	19.36	2.62	0	53.82	106.65	-52.83	AV	147
0.1779	67.65	19.37	2.63	0	89.65	122.55	-32.90	Peak	252
0.1779	52.14	19.37	2.63	0	74.14	102.55	-28.41	AV	252
0.2740	51.93	19.38	2.64	0	73.95	118.82	-44.87	Peak	84
0.2740	41.25	19.38	2.64	0	63.27	98.82	-35.55	AV	84

Remark: According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.


(Between 30MHz -1000 MHz)

Job No.:	SZAWW181030004-01	Polarization:	Horizontal
Standard:	FCC PART15 C _3m	Power Source:	AC 120V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.7°C/54%RH
Test Mode:	Mode 1	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	37.8121	36.75	-15.56	21.19	40.00	-18.81	QP	300	0	
2	42.7496	35.27	-15.17	20.10	40.00	-19.90	QP	300	63	
3	56.1974	36.59	-17.80	18.79	40.00	-21.21	QP	300	102	
4	96.0986	47.96	-22.12	25.84	43.50	-17.66	QP	300	231	
5	248.5519	45.77	-18.96	26.81	46.00	-19.19	QP	300	312	
6	416.1791	34.44	-12.47	21.97	46.00	-24.03	QP	300	360	

Job No.: SZAWW181030004-01 **Polarization:** Vertical
Standard: FCC PART15 C_3m **Power Source:** AC 120V, 60Hz for adapter
Test item: Radiation Test **Temp.(C)/Hum.(%RH):** 24.7°C/54%RH
Test Mode: Mode 1 **Distance:** 3m




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.7662	47.70	-15.14	32.56	40.00	-7.44	QP	300	0	
2	39.5757	45.81	-13.60	32.21	40.00	-7.79	QP	300	36	
3	58.2030	41.87	-16.90	24.97	40.00	-15.03	QP	300	122	
4	68.1514	43.82	-20.10	23.72	40.00	-16.28	QP	300	220	
5	103.8055	38.29	-15.71	22.58	43.50	-20.92	QP	300	263	
6	219.0753	40.34	-15.33	25.01	46.00	-20.99	QP	300	360	

Job No.:	SZAWW181030004-01	Polarization:	Horizontal
Standard:	FCC PART15 C _3m	Power Source:	AC 240V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.7°C/54%RH
Test Mode:	Mode 1	Distance:	3m



No.	Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	33.2112	40.44	-17.61	22.83	40.00	-17.17	QP	300	0	
2	39.8542	36.24	-14.45	21.79	40.00	-18.21	QP	300	54	
3	66.4989	42.58	-20.46	22.12	40.00	-17.88	QP	300	132	
4	103.8055	46.71	-21.71	25.00	43.50	-18.50	QP	300	222	
5	256.5211	45.71	-19.40	26.31	46.00	-19.69	QP	300	293	
6	411.8240	35.61	-12.58	23.03	46.00	-22.97	QP	300	360	

Job No.: SZAWW181030004-01 **Polarization:** Vertical
Standard: FCC PART15 C _3m **Power Source:** AC 240V, 60Hz for adapter
Test item: Radiation Test **Temp.(C)/Hum.(%RH):** 24.7°C/54%RH
Test Mode: Mode 1 **Distance:** 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	34.8823	49.63	-16.12	33.51	40.00	-6.49	QP	300	0	
2	40.1347	43.40	-13.41	29.99	40.00	-10.01	QP	300	57	
3	58.8185	39.61	-16.93	22.68	40.00	-17.32	QP	300	121	
4	84.1099	37.77	-19.27	18.50	40.00	-21.50	QP	300	196	
5	112.1304	33.79	-15.77	18.02	43.50	-25.48	QP	300	252	
6	222.1698	34.83	-15.22	19.61	46.00	-26.39	QP	300	360	


5. Antenna Requirement

5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard

5.2. Antenna Connected Construction

The Wireless Charging antenna is a Inductive loop coil Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.




APPENDIX I-- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement





Photo of Radiation Emission Test






APPENDIX II -- EXTERNAL PHOTOGRAPH










APPENDIX III -- INTERNAL PHOTOGRAPH







----- End of Report -----