

# Sichuan AI-Link Technology Co., Ltd.

# MPE ASSESSMENT REPORT

**Report Type:**

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

**Model:**

WF-M38B-UWG1,WF-M38B-UWG1(FCC/IC)

**REPORT NUMBER:**

220800952SHA-006

**ISSUE DATE:**

September 7, 2022

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



**TEST REPORT**

**Applicant:** Sichuan AI-Link Technology Co., Ltd.  
Anzhou, Industrial park, Mianyang, Sichuan, China

**Manufacturer:** Sichuan AI-Link Technology Co., Ltd.  
Anzhou, Industrial park, Mianyang, Sichuan, China

**Product Name:** WIFI BT Module

**Type/Model:** WF-M38B-UWG1,WF-M38B-UWG1(FCC/IC)

**FCC ID:** 2AOKI-WFM38BUWG1

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06  
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

**PREPARED BY:**

Project Engineer  
Dylan Tang

**REVIEWED BY:**

Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****Revision History**

Report No.	Version	Description	Issued Date
220800952SHA-006	Rev. 01	Initial issue of report	September 7, 2022

**TEST REPORT****1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

Product name:	WIFI BT Module
Type/Model:	WF-M38B-UWG1,WF-M38B-UWG1(FCC/IC)
Description of EUT:	The EUT is a WIFI BT Module which supports WIFI and Bluetooth function. there have two models and they are same except the label type. We choose WF-M38B-UWG1 to test as representative.
Rating:	DC 5V
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	QAtool 0.0.1.88
Hardware Version:	JUI7.820
Serial numbers:	0220908-05-001(for radiation sample), 0220908-05-002(for conduction sample)
Sample received date:	August 10, 2022
Date of test:	August 10, 2022 ~ September 6, 2022

**1.2 Technical Specification**

Frequency Range:	2402-2480MHz
Support Standards:	IEEE 802.15.1
Type of Modulation:	GFSK
Channel Number:	40
Data Rate:	1Mbps, 2Mbps
Channel Separation:	2MHz
Antenna Information:	2.32dBi, PIFA antenna 1.72dBi, PIFA antenna (Optional)

Frequency Range:	2400MHz ~ 2483.5MHz
Support Standards:	Bluetooth 4.2/5.0 (BR+EDR)
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Channel Number:	79 (0 - 78)
Data Rate:	1Mbps
Channel Separation:	1 MHz
Antenna:	2.32dBi, PIFA antenna 1.72dBi, PIFA antenna (Optional)

**TEST REPORT**

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20), IEEE 802.11n(HT40)
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT20): OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT40): OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20) 2422MHz to 2452MHz for IEEE 802.11n(HT40)
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20) 7 Channels for 802.11n(HT40)
Channel Separation:	5 MHz
Antenna Information:	PCB Antenna1: 1.89dBi PCB Antenna2: 1.85dBi

Frequency Range:	5150 ~ 5250MHz 5250 ~ 5350MHz 5470 ~ 5725MHz 5725 ~ 5850MHz
Support Standards:	802.11a, 802.11n(HT20), 802.11n(HT40)
Type of Modulation:	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Channel Number:	For 5150 ~ 5250MHz band: Channel 36 - 48 For 5250 ~ 5350MHz Band: Channel 52 - 64 For 5470 ~ 5725MHz Band: Channel 100 - 140 For 5725 ~ 5850MHz band: Channel 149 - 165
Antenna Information:	PCB Antenna1: 1.84dBi PCB Antenna2: 1.96dBi

**TEST REPORT****1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

**TEST REPORT****2 MPE Assessment****Test result:** Pass**2.1 MPE Assessment Limit**

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (Ut)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4 000/f$	$5 000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$**

## TEST REPORT

### 2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi r^2)$$

Where S = power density in  $\text{mW/cm}^2$

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 220800952SHA-001&220800952SHA-002&220800952SHA-003&220800952SHA-004:

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Working Mode	Frequency band (MHz)	Power		Antenna Gain dBi	R (cm)	S (mW/cm <sup>2</sup> )	Limits (mW/cm <sup>2</sup> )
		dBm	mW				
BLE	2402-2480	-1.45	0.72	2.32	20	0.0003	1
BT	2402-2480	0.89	1.23	2.32	20	0.0005	1
2.4G WIFI	2412 - 2462	16.52	44.87	1.89	20	0.0169	1
5G WIFI	5180 - 5825	14.68	29.38	1.96	20	0.0115	1

Note: 1  $\text{mW/cm}^2$  from 1.310 Table 1.

BT/BLE and 2.4G WIFI can simultaneous transmitting, so the maximum rate of MPE is,  $0.0005/1+0.0169/1=0.0174<=1.0$ .

BT/BLE and 5G WIFI can simultaneous transmitting, so the maximum rate of MPE is,  $0.0005/1+0.0115/1=0.012<=1.0$ .

**TEST REPORT**

**Appendix I**

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

\*\*\*\*\*END\*\*\*\*\*