

TEST REPORT

FCC ID: 2AOKI-WFM68AUWF1

Product: WiFi Module

Model No.: WF-M68A-UWF1

Additional Model No.: N/A

Trade Mark: N/A

Report No.: TCT191030E038

Issued Date: Dec. 10, 2019

Issued for:

**Sichuan AI-Link Technology Co., Ltd.
Anzhou, Industrial park, Mianyang, Sichuan, China**

Issued By:

**Shenzhen Tongce Testing Lab.
1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China
TEL: +86-755-27673339
FAX: +86-755-27673332**

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification.....	3
2. Test Result Summary	4
3. EUT Description	5
4. General Information.....	7
4.1. Test environment and mode	7
4.2. Description of Support Units	8
5. Facilities and Accreditations	9
5.1. Facilities	9
5.2. Location	9
5.3. Measurement Uncertainty	9
6. Test Results and Measurement Data	10
6.1. Antenna requirement	10
6.2. Conducted Emission.....	11
6.3. Maximum Conducted (Average) Output Power	15
6.4. Emission Bandwidth	17
6.5. Power Spectral Density	18
6.6. Conducted Band Edge and Spurious Emission Measurement	20
6.7. Radiated Spurious Emission Measurement	22

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. Test Certification

Product:	WiFi Module
Model No.:	WF-M68A-UWF1
Additional Model No.:	N/A
Trade Mark:	N/A
Applicant:	Sichuan AI-Link Technology Co., Ltd.
Address:	Anzhou, Industrial park, Mianyang, Sichuan, China
Manufacturer:	Sichuan AI-Link Technology Co., Ltd.
Address:	Anzhou, Industrial park, Mianyang, Sichuan, China
Date of Test:	Oct. 31, 2019 – Dec. 09, 2019
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 FCC KDB 662911 D01 Multiple Transmitter Output v02r01 ANSI C63.10:2013

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Rleo

Date:

Dec. 09, 2019

Reviewed By:



Beryl Zhao

Date:

Dec. 10, 2019

Approved By:



Tomsin

Date:

Dec. 10, 2019

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3)	PASS
6dB Emission Bandwidth	§15.247 (a)(2)	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product:	WiFi Module
Model No.:	WF-M68A-UWF1
Additional Model No.:	N/A
Trade Mark:	N/A
Hardware Version:	JUI7.820.0536-2
Software Version:	customer_package_UIv1.88_DLLv3.87_20170918_WinDriverV.0.0.4.31_FWv.69237
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel Separation:	5MHz
Number of Channel:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Modulation Technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation Technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 300Mbps
Antenna Type:	Internal Antenna
Antenna Gain:	2dBi
Power Supply:	DC 3.3V

Operation Frequency each of channel For 802.11b/g/n(HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel For 802.11n (HT40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (HT20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

802.11n (HT40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

4. General Information

4.1. Test environment and mode

Operating Environment:

Condition	Conducted Emission	Radiated Emission
Temperature:	25.0 °C	25.0 °C
Humidity:	55 % RH	55 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar

Test Mode:

Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery
-------------------	--

The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case (Z axis) are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps

Final Test Mode:

Operation mode:	Keep the EUT in continuous transmitting with modulation
-----------------	---

1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.
2. According to ANSI C63.10 standards, the test results are both the "worst case" and "worst setup" 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20), 13.5Mbps for 802.11(H40). Duty cycle setting during the transmission is 98.46% with maximum power setting for all modulations.

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339


5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^{\circ}\text{C}$
7	Humidity	$\pm 1.0\%$


6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The WIFI antennas are internal antennas, and the best case gains of the both antennas are 2dBi.	
	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane  Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Charging + transmitting with modulation														
Test Procedure:	1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														

6.2.2. Test Instruments


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	R&S	ESPI	101402	Jul. 29, 2020
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 11, 2020
Coax cable (9KHz-30MHz)	TCT	CE-05	N/A	Sep. 08, 2020
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **L1** Temperature: 25
Limit: FCC Part 15C Conduction(QP) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	43.56	10.12	53.68	66.00	-12.32	QP	
2		0.1500	27.76	10.12	37.88	56.00	-18.12	AVG	
3		0.5325	32.01	10.13	42.14	56.00	-13.86	QP	
4		0.5325	22.37	10.13	32.50	46.00	-13.50	AVG	
5		2.5935	28.79	10.12	38.91	56.00	-17.09	QP	
6		2.5935	18.05	10.12	28.17	46.00	-17.83	AVG	
7		5.3430	25.87	10.13	36.00	60.00	-24.00	QP	
8		5.3430	16.14	10.13	26.27	50.00	-23.73	AVG	
9		14.1675	26.91	10.17	37.08	60.00	-22.92	QP	
10		14.1675	20.63	10.17	30.80	50.00	-19.20	AVG	
11		15.8595	26.45	10.18	36.63	60.00	-23.37	QP	
12		15.8595	18.71	10.18	28.89	50.00	-21.11	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)


Q.P. =Quasi-Peak

AVG =average

*Any value more than 10dB below limit have not been specifically reported.

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **N** Temperature: 25
Limit: FCC Part 15C Conduction(QP) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1500	42.56	10.12	52.68	66.00	-13.32	QP	
2		0.1500	32.33	10.12	42.45	56.00	-13.55	AVG	
3		0.5190	32.14	10.13	42.27	56.00	-13.73	QP	
4	*	0.5190	22.60	10.13	32.73	46.00	-13.27	AVG	
5		2.4360	28.79	10.12	38.91	56.00	-17.09	QP	
6		2.4360	19.50	10.12	29.62	46.00	-16.38	AVG	
7		5.0055	27.85	10.13	37.98	60.00	-22.02	QP	
8		5.0055	18.60	10.13	28.73	50.00	-21.27	AVG	
9		8.0520	21.33	10.14	31.47	60.00	-28.53	QP	
10		8.0520	13.65	10.14	23.79	50.00	-26.21	AVG	
11		13.6545	22.64	10.17	32.81	60.00	-27.19	QP	
12		13.6545	18.42	10.17	28.59	50.00	-21.41	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

*Any value more than 10dB below limit have not been specifically reported.

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

6.3. Maximum Conducted (Average) Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB 558074 D01 v05r02, KDB662911 D01 v02r01
Limit:	30dBm
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Measure the conducted output power and record the results in the test report.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 12, 2020
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 12, 2020
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2020

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3.3. Test Data

Configuration IEEE 802.11b/ Antenna 0+Antenna 1				
Test channel	Maximum Conducted (Average) Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	22.02	20.40	30	PASS
Middle	22.50	20.47	30	PASS
Highest	22.42	20.44	30	PASS

Configuration IEEE 802.11g/ Antenna 0+Antenna 1				
Test channel	Maximum Conducted (Average) Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	19.82	18.32	30	PASS
Middle	20.20	18.59	30	PASS
Highest	20.38	18.31	30	PASS

Configuration IEEE 802.11n(H20)/ Antenna 0+Antenna 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Antenna 0	Antenna 1	Total		
Lowest	18.76	17.27	21.09	30	PASS
Middle	19.15	17.46	21.40	30	PASS
Highest	19.24	17.33	21.40	30	PASS

Configuration IEEE 802.11n(H40)/ Antenna 0+Antenna 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Antenna 0	Antenna 1	Total		
Lowest	18.40	16.78	20.68	30	PASS
Middle	18.71	16.81	20.87	30	PASS
Highest	18.66	16.78	20.83	30	PASS

Note:

$G_{ANT} = 2\text{dBi}$, Array Gain= $10\log(N_{ANT}) = 3.01\text{dBi}$

Directional Gain= $G_{ANT} + \text{Array Gain} = 5.01\text{dBi} < 6\text{dBi}$, So limit=30dBm

Refer to Appendix A: Test Result of Conducted Test

6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074 D01 v05r02
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set to the maximum power setting and enable the EUT transmit continuously. 2. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 3. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 12, 2020
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 12, 2020
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2020

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB 558074
Limit:	The average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW. 4. Detector = RMS, Sweep time = auto couple. 5. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 12, 2020
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 12, 2020
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2020

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI)

6.5.3. Test data

Configuration IEEE 802.11b/ Antenna 0, Antenna 1				
Test channel	AVG Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-7.10	-3.27	8	PASS
Middle	-3.97	-8.32	8	PASS
Highest	5.93	-7.97	8	PASS

Configuration IEEE 802.11g/ Antenna 0, Antenna 1				
Test channel	AVG Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-9.99	-9.89	8	PASS
Middle	-10.25	-10.91	8	PASS
Highest	-10.13	-10.50	8	PASS

Configuration IEEE 802.11n (HT20)/ Antenna 0, Antenna 1					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1	Total		
Lowest	-9.86	-12.59	-8.00	8	PASS
Middle	-9.95	-12.84	-8.15	8	PASS
Highest	-10.91	-12.61	-8.67	8	PASS

Configuration IEEE 802.11n (HT40)/ Antenna 0, Antenna 1					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1	Total		
Lowest	-15.90	-18.23	-13.90	8	PASS
Middle	-16.36	-18.89	-14.43	8	PASS
Highest	-16.51	-18.13	-14.23	8	PASS

Note:


$G_{ANT} = 2\text{dBi}$, Array Gain= $10\log(N_{ANT}) = 3.01\text{dBi}$

Directional Gain= $G_{ANT} + \text{Array Gain} = 5.01\text{dBi} < 6\text{dBi}$, So limit=8dBm/3kHz

Refer to Appendix A: Test Result of Conducted Test

6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS

6.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Sep. 12, 2020
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 12, 2020
Antenna Connector	TCT	RFC-01	N/A	Sep. 12, 2020


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.7. Radiated Spurious Emission Measurement


6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.10: 2013			
Frequency Range:	9 kHz to 25 GHz			
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal & Vertical			
Operation mode:	Transmitting mode with modulation			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	120KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Limit:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Remark
	0.009-0.490	2400/F(KHz)	300	Quasi-peak Value
	0.490-1.705	24000/F(KHz)	30	Quasi-peak Value
	1.705-30	30	30	Quasi-peak Value
	30-88	100	3	Quasi-peak Value
Test setup:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	88-216	150	3	Average
	216-960	200	3	Peak
	Above 960	500	3	
	Above 1GHz	5000	3	


For radiated emissions below 30MHz



30MHz to 1GHz



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final

	measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 5. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test results:	PASS

6.7.2. Test Instruments


Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	ROHDE&SCHW ARZ	ESIB7	100197	Jul. 29, 2020
Spectrum Analyzer	ROHDE&SCHW ARZ	FSQ40	200061	Sep. 11, 2020
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 08, 2020
Pre-amplifier	HP	8447D	2727A05017	Sep. 08, 2020
Loop antenna	ZHINAN	ZN30900A	12024	Sep. 11, 2020
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 06, 2020
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 06, 2020
Horn Antenna	A-INFO	LB-180400-KF	J211020657	Sep. 06, 2020
Antenna Mast	Keleto	RE-AM	N/A	N/A
Coax cable (9KHz-40GHz)	TCT	RE-high-02	N/A	Sep. 08, 2020
Coax cable (9KHz-40GHz)	TCT	RE-high-04	N/A	Sep. 08, 2020
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.7.3. Test Data

Please refer to following diagram for individual
Below 1GHz


Horizontal:



Site: Polarization: **Horizontal** Temperature: 25
Limit: FCC Part 15C 3M Radiation Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		116.4475	44.97	-10.60	34.37	43.50	-9.13	QP
2	!	133.0809	54.57	-15.62	38.95	43.50	-4.55	QP
3	*	145.8109	56.00	-16.19	39.81	43.50	-3.69	QP
4	!	155.3305	55.27	-16.02	39.25	43.50	-4.25	QP
5	!	280.2936	51.73	-11.57	40.16	46.00	-5.84	QP
6		424.2998	44.60	-8.65	35.95	46.00	-10.05	QP

Vertical:



Site: Polarization: **Vertical** Temperature: 25
Limit: FCC Part 15C 3M Radiation Power: Humidity: 55 %


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		72.7203	38.44	-15.93	22.51	40.00	-17.49	QP
2		133.0809	47.00	-15.62	31.38	43.50	-12.12	QP
3	*	145.8109	47.62	-16.19	31.43	43.50	-12.07	QP
4		280.2936	41.05	-11.57	29.48	46.00	-16.52	QP
5		458.3987	41.73	-8.17	33.56	46.00	-12.44	QP
6		669.9523	35.56	-5.54	30.02	46.00	-15.98	QP

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported
2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (Middle channel and 802.11b) was submitted only.
3. Freq. = Emission frequency in MHz
Measurement (dBμV/m) = Reading level (dBμV) + Corr. Factor (dB)
Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
Limit (dBμV/m) = Limit stated in standard
Margin (dB) = Measurement (dBμV/m) – Limits (dBμV/m)
Any value more than 10dB below limit have not been specifically reported.
* is meaning the worst frequency has been tested in the test frequency range

Test Result of Radiated Spurious at Band edges

Lowest channel 2412:


Horizontal:



Site: Polarization: **Horizontal** Temperature: 25
Limit: FCC part 15.247 bandedge(peak) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		2400.000	69.49	-13.02	56.47	74.00	-17.53	peak
2	*	2400.000	65.18	-13.02	52.16	54.00	-1.84	AVG

Vertical:




Site: Polarization: **Vertical** Temperature: 25
 Limit: FCC part 15.247 bandedge(peak) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		2400.000	71.04	-13.02	58.02	74.00	-15.98	peak
2	*	2400.000	66.04	-13.02	53.02	54.00	-0.98	AVG

Highest channel 2462:


Horizontal:



Site: Polarization: **Horizontal** Temperature: 25
Limit: FCC part 15.247 bandedge(peak) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		2483.500	61.53	-12.84	48.69	74.00	-25.31	peak
2	*	2483.500	57.22	-12.84	44.38	54.00	-9.62	AVG

Vertical:



Site: Polarization: **Vertical** Temperature: 25
 Limit: FCC part 15.247 bandedge(peak) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		2483.500	58.18	-12.84	45.34	74.00	-28.66	peak
2	*	2483.500	56.96	-12.84	44.12	54.00	-9.88	AVG

Note:

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
3. Measurements were conducted in all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (802.11n(HT20)) was submitted only.

Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	47.84	---	0.75	48.59	---	74	54	-5.41
7236	H	36.27	---	9.87	46.14	---	74	54	-7.86
---	H	---	---	---	---	---	---	---	---
4824	V	44.59	---	0.75	45.34	---	74	54	-8.66
7236	V	35.01	---	9.87	44.88	---	74	54	-9.12
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	46.70	---	0.97	47.67	---	74	54	-6.33
7311	H	34.18	---	9.83	44.01	---	74	54	-9.99
---	H	---	---	---	---	---	---	---	---
4874	V	48.36	---	0.97	49.33	---	74	54	-4.67
7311	V	37.92	---	9.83	47.75	---	74	54	-6.25
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	45.65	---	1.18	46.83	---	74	54	-7.17
7386	H	37.43	---	10.07	47.50	---	74	54	-6.50
---	H	---	---	---	---	---	---	---	---
4924	V	47.29	---	1.18	48.47	---	74	54	-5.53
7386	V	38.54	---	10.07	48.61	---	74	54	-5.39
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11b is SISO mode and the worst case Antenna (ANT0) was submitted only.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	45.18	---	0.75	45.93	---	74	54	-8.07
7236	H	34.70	---	9.87	44.57	---	74	54	-9.43
---	H	---	---	---	---	---	---	---	---
4824	V	46.56	---	0.75	47.31	---	74	54	-6.69
7236	V	35.84	---	9.87	45.71	---	74	54	-8.29
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	44.95	---	0.97	45.92	---	74	54	-8.08
7311	H	35.21	---	9.83	45.04	---	74	54	-8.96
---	H	---	---	---	---	---	---	---	---
4874	V	47.63	---	0.97	48.60	---	74	54	-5.40
7311	V	38.49	---	9.83	48.32	---	74	54	-5.68
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	43.37	---	1.18	44.55	---	74	54	-9.45
7386	H	34.02	---	10.07	44.09	---	74	54	-9.91
---	H	---	---	---	---	---	---	---	---
4924	V	42.16	---	1.18	43.34	---	74	54	-10.66
7386	V	36.74	---	10.07	46.81	---	74	54	-7.19
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11g is SISO mode and the worst case Antenna (ANT0) was submitted only.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	44.75	---	0.75	45.50	---	74	54	-8.50
7236	H	35.49	---	9.87	45.36	---	74	54	-8.64
---	H	---	---	---	---	---	---	---	---
4824	V	44.16	---	0.75	44.91	---	74	54	-9.09
7236	V	34.83	---	9.87	44.70	---	74	54	-9.30
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	46.50	---	0.97	47.47	---	74	54	-6.53
7311	H	35.24	---	9.83	45.07	---	74	54	-8.93
---	H	---	---	---	---	---	---	---	---
4874	V	45.61	---	0.97	46.58	---	74	54	-7.42
7311	V	36.08	---	9.83	45.91	---	74	54	-8.09
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	43.92	---	1.18	45.10	---	74	54	-8.90
7386	H	34.37	---	10.07	44.44	---	74	54	-9.56
---	H	---	---	---	---	---	---	---	---
4924	V	45.85	---	1.18	47.03	---	74	54	-6.97
7386	V	36.49	---	10.07	46.56	---	74	54	-7.44
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "---" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11n(HT20) is MIMO mode.

Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4844	H	42.90	---	0.75	43.65	---	74	54	-10.35
7266	H	33.54	---	9.87	43.41	---	74	54	-10.59
---	H	---	---	---	---	---	---	---	---
4824	V	43.38	---	0.75	44.13	---	74	54	-9.87
7236	V	34.71	---	9.87	44.58	---	74	54	-9.42
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	43.29	---	0.97	44.26	---	74	54	-9.74
7311	H	33.83	---	9.83	43.66	---	74	54	-10.34
---	H	---	---	---	---	---	---	---	---
4874	V	44.67	---	0.97	45.64	---	74	54	-8.36
7311	V	35.15	---	9.83	44.98	---	74	54	-9.02
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4904	H	43.02	---	1.18	44.20	---	74	54	-9.80
7356	H	33.46	---	10.07	43.53	---	74	54	-10.47
---	H	---	---	---	---	---	---	---	---
4904	V	45.91	---	1.18	47.09	---	74	54	-6.91
7356	V	36.34	---	10.07	46.41	---	74	54	-7.59
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "----" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11n(HT40) is MIMO mode.

Appendix A: Test Result of Conducted Test


Antenna 0

Appendix A): Duty Cycle


Result Table

Mode	Channel	Meas.Level [%]
11B	LCH	99.58
11B	MCH	99.58
11B	HCH	99.61
11G	LCH	99.16
11G	MCH	99.16
11G	HCH	99.16
11N20SISO	LCH	98.96
11N20SISO	MCH	98.96
11N20SISO	HCH	98.96
11N40SISO	LCH	98.05
11N40SISO	MCH	98.07
11N40SISO	HCH	98.05


Test Graph




11B/MCH




11B/HCH




11G/LCH




11G/MCH




11G/HCH




11N20SISO/LCH




11N20SISO/MCH




11N20SISO/HCH




11N40SISO/LCH



11N40SISO/MCH



11N40SISO/HCH




Conducted Average Output Power


Result Table

Mode	Channel	Meas.Level [dBm]	Verdict
11B	LCH	22.02	PASS
11B	MCH	22.5	PASS
11B	HCH	22.42	PASS
11G	LCH	19.82	PASS
11G	MCH	20.2	PASS
11G	HCH	20.38	PASS
11N20SISO	LCH	18.76	PASS
11N20SISO	MCH	19.15	PASS
11N20SISO	HCH	19.24	PASS
11N40SISO	LCH	18.4	PASS
11N40SISO	MCH	18.71	PASS
11N40SISO	HCH	18.66	PASS


Test Graph




11B/MCH




11B/HCH




11G/LCH




11G/MCH







11G/HCH



11N20SISO/LCH



11N20SISO/MCH	
11N20SISO/HCH	
11N40SISO/LCH	

11N40SISO/MCH	
11N40SISO/HCH	


6dB Occupied Bandwidth

Result Table

Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	LCH	9.106	12.983	PASS
11B	MCH	9.107	13.092	PASS
11B	HCH	9.550	13.087	PASS
11G	LCH	15.08	17.094	PASS
11G	MCH	15.12	17.042	PASS
11G	HCH	15.09	17.087	PASS
11N20SISO	LCH	15.10	17.804	PASS
11N20SISO	MCH	15.12	17.795	PASS
11N20SISO	HCH	15.11	17.809	PASS
11N40SISO	LCH	35.12	35.964	PASS
11N40SISO	MCH	35.13	35.997	PASS
11N40SISO	HCH	35.06	35.928	PASS

Test Graph

6dB Bandwidth




11B/MCH




11B/HCH




11G/LCH




11G/MCH




11G/HCH




11N20SISO/LCH




11N20SISO/MCH





11N20SISO/HCH



11N40SISO/LCH




11N40SISO/MCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Center Freq 2.437000000 GHz Trig: Free Run Avg/Hold: 10/10 Radio Std: None Radio Device: BTS Ref Offset 0.9 dB Ref 23.90 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 8 ms Occupied Bandwidth 36.059 MHz Total Power 24.9 dBm Transmit Freq Error -15.541 kHz OBW Power 99.00 % x dB Bandwidth 35.13 MHz x dB -6.00 dB Frequency Center Freq 2.437000000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz
11N40SISO/HCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.452000000 GHz Center Freq 2.452000000 GHz Trig: Free Run Avg/Hold: 10/10 Radio Std: None Radio Device: BTS Ref Offset 0.9 dB Ref 23.90 dBm Center 2.452 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 8 ms Occupied Bandwidth 36.068 MHz Total Power 24.9 dBm Transmit Freq Error -35.079 kHz OBW Power 99.00 % x dB Bandwidth 35.06 MHz x dB -6.00 dB Frequency Center Freq 2.452000000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz

99% OBW

Graphs	
11B/LCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Center Freq 2.412000000 GHz Trig: Free Run Avg/Hold: 10/10 Radio Std: None Radio Device: BTS Ref Offset 0.2 dB Ref 23.20 dBm Center 2.412 GHz #Res BW 510 kHz #VBW 1.5 MHz Span 40 MHz Sweep 1.067 ms Occupied Bandwidth 12.983 MHz Total Power 13.3 dBm Transmit Freq Error -2.631 kHz OBW Power 99.00 % x dB Bandwidth 10.17 MHz x dB -6.00 dB Frequency Center Freq 2.412000000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz

11B/MCH



11B/HCH



11G/LCH



11G/MCH



11G/HCH



11N20SISO/LCH




11N20SISO/MCH




11N20SISO/HCH



11N40SISO/LCH



11N40SISO/MCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Ref Offset 0.2 dB Ref 23.20 dBm Center 2.437 GHz #Res BW 510 kHz #VBW 1.5 MHz Span 80 MHz Sweep 1.067 ms Occupied Bandwidth 35.997 MHz Total Power 14.0 dBm Transmit Freq Error 41.740 kHz OBW Power 99.00 % x dB Bandwidth 35.87 MHz x dB -6.00 dB
11N40SISO/HCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.452000000 GHz Ref Offset 0.2 dB Ref 23.20 dBm Center 2.452 GHz #Res BW 510 kHz #VBW 1.5 MHz Span 80 MHz Sweep 1.067 ms Occupied Bandwidth 35.928 MHz Total Power 11.4 dBm Transmit Freq Error 17.314 kHz OBW Power 99.00 % x dB Bandwidth 35.73 MHz x dB -6.00 dB

Band-edge for RF Conducted Emissions

Result Table

Mode	Channel	Carrier Power [dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	12.481	-47.697	-17.52	PASS
11B	HCH	12.889	-43.366	-17.11	PASS
11G	LCH	-7.451	-48.417	-37.45	PASS
11G	HCH	-7.078	-47.422	-37.08	PASS
11N20SISO	LCH	-7.181	-47.356	-37.18	PASS
11N20SISO	HCH	-5.710	-47.941	-36.71	PASS
11N40SISO	LCH	-11.137	-44.633	-41.14	PASS
11N40SISO	HCH	-11.811	-48.338	-41.81	PASS

Test Graph

