

Single Modular approval Declaration letter

We , apply Single modular approval for

Product Name: WiFi Module

Model: WIFI-2-Q379UWP1

FCC ID: 2AOKI-WIFI2Q379UWP1

According to 996369 D01 Module Equip Auth Guide v01r04 and 15.212 requirement:

1) The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;

Answer : Yes, The modular have RF own shielding

2)The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;

Answer : Yes, The modular transmitter have buffered modulation/data inputs.

3)The modular transmitter must have its own power supply regulation.

Answer : Yes, The modular transmitter must have its own power supply regulation

4)The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);

Answer : Yes ; The modular have antenna that comply with the antenna and transmission system requirements of Sections 15.203, 15.204(b) and 15.204(c).

(5)The module must demonstrate compliance in a stand-alone configuration;

Answer : Yes, The EUT module can't be operated by its own due to its power-less characteristic and hence needs external power supply to make it function. Under testing condition, no matter in pure verification or manufacturing stage, the specified

(6) The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements);


Answer : Yes, The FCC identification number can put on the modular with either a permanently affixed label .

(7)The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee;

Answer : Yes, The instructions will be provided and apply to a complete transmitter and comply with specific rule

(8)The module must comply with RF exposure requirements

Answer : Yes, The total power density of modular transmitter final configuration comply with FCC RF Exposure

Signature: 

Name: Caixia Hu

Title: Engineer

Company: Sichuan AI-Link Technology Co., Ltd.