

FCC/IC REPORT

Applicant: Remote Tech LLC

Address of Applicant: 310 ALDER RD, DOVER DE 19904 USA

Equipment Under Test (EUT)

Product Name: smart key

Model No.: RT-MZ3

FCC ID: 2AOKM-TY11

Canada IC: 24223-TY11

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.231
RSS-Gen Issue 5 March 2019
RSS-210 Issue 10 December 2019 Annex A Section A.1.1

Date of sample receipt: 19 Jun., 2020

Date of Test: 19 Jun., to 21 Aug., 2020

Date of report issue: 24 Aug., 2020

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	24 Aug., 2020	Original

Prepared By:

Yao Wu

Test Engineer

Date:

24 Aug., 2020

Check By:

Winnier Zhang

Project Engineer

Date:

24 Aug., 2020

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE	5
5.4 DESCRIPTION OF SUPPORT UNITS.....	5
5.5 MEASUREMENT UNCERTAINTY.....	5
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	5
5.7 LABORATORY FACILITY.....	6
5.8 LABORATORY LOCATION	6
5.9 TEST INSTRUMENTS LIST.....	6
6 TEST RESULTS AND MEASUREMENT DATA	7
6.1 ANTENNA REQUIREMENT	7
6.2 RADIATED EMISSION	8
6.2.1 Field Strength Of The Fundamental Signal.....	10
6.2.2 Spurious Emissions	16
6.3 20dB BANDWIDTH.....	26
6.4 DURATION TIME.....	28
6.5 FREQUENCY STABILITY	30
7 TEST SETUP PHOTOS	33
8 EUT CONSTRUCTIONAL PHOTOS	34

4 Test Summary

Test Item	Test Standard Section		Result
	FCC	IC	
Antenna requirement	15.203	RSS-GEN 6.8	Pass
Field strength of the fundamental signal	15.231 (b)	RSS-210 Annex A Section A.1.2 (a)	Pass
Spurious emissions	15.231 (b)/15.209	RSS-210 Annex A Section A.1.2 (b)	Pass
20dB Bandwidth	15.231 (c)	RSS-210 Annex A Section A.1.3	Pass
Duration time	15.231 (a)(1)	RSS-210 Annex A Section A.1.1 (a)	Pass
Frequency stability	/	RSS-GEN Section 8.11	Pass
Conducted Emission	15.207	RSS-GEN Section 8.8	N/A
Remarks: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: The EUT not applicable of the test item. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.4-2014 ANSI C63.10-2013		

5 General Information

5.1 Client Information

Applicant:	Remote Tech LLC
Address:	310 ALDER RD, DOVER DE 19904 USA
Manufacturer:	Remote Tech LLC
Address:	310 ALDER RD, DOVER DE 19904 USA

5.2 General Description of E.U.T.

Product Name:	smart key
Model No.:	RT-MZ3
Operation Frequency:	312.10MHz / 314.35MHz
Channel numbers:	2
Modulation type:	FSK
Antenna Type:	PCB antenna
Antenna gain:	0 dBi
Power supply:	DC 3V (CR2032 battery)
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with modulation（new battery used）			
Pre-Test Mode:				
CCIS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:				
Axis	Frequency	X	Y	Z
Field Strength(dBuV/m)	312.10MHz	72.40	68.35	69.02
	314.35MHz	73.98	68.92	69.94
Final Test Mode:				
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”: X axis (see the test setup photo)				

5.4 Description of Support Units

N/A

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location


Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5.9 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
				07-22-2020	07-21-2023
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2020	03-17-2021
Broadband Antenna	SCHWARZBECK	VUBA9117	359	06-22-2017	06-21-2020
				06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2020	03-17-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
				06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA9170	582	11-18-2019	11-17-2020
Loop Antenna	SCHWARZBECK	FMZB1519 B	00044	03-18-2020	03-17-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-18-2020	03-17-2021
Pre-amplifier	CD	PAP-1G18	11804	03-18-2020	03-17-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2020	03-17-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2020	03-17-2021
Simulated Station	Anritsu	MT8820C	6201026545	03-18-2020	03-17-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2020	03-17-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2020	03-17-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2020	03-17-2021
DC Power Supply	XinNuoEr	WYK-10020K	1409050110020	09-25-2019	09-24-2020
Temperature Humidity Chamber	HengPu	HPGDS-500	20140828008	11-01-2019	10-31-2020



6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT make use of a PCB antenna, The typical gain of the antenna is 0 dBi.	
	

6.2 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.231(a) and 15.209 RSS-210 Annex A Section A.1.2				
Test Frequency Range:	30MHz to 3500MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	312.10 MHz		75.45		Average Value
			95.45		Peak Value
	314.35 MHz		75.58		Average Value
			95.58		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
	Or The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level whichever limit permits higher field strength.				
Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				

Test setup:	Below 1GHz  Above 1GHz 
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


6.2.1 Field Strength Of The Fundamental Signal

312.10MHz:

Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
312.10	42.43	18.73	2.98	0.00	64.14	95.45	-31.31	Vertical
312.10	42.49	18.73	2.98	0.00	64.20	95.45	-31.25	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
312.10	40.15	18.73	2.98	0.00	61.86	75.45	-13.59	Vertical
312.10	40.13	18.73	2.98	0.00	61.84	75.45	-13.61	Horizontal

314.35MHz:


Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
314.35	42.24	18.73	2.98	0.00	63.95	95.58	-31.63	Vertical
314.35	38.74	18.73	2.98	0.00	60.45	95.58	-35.13	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
314.35	40.02	18.73	2.98	0.00	61.73	75.58	-13.85	Vertical
314.35	36.33	18.73	2.98	0.00	58.04	75.58	-17.54	Horizontal



Test Plots:

312.10MHz:

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	312.10 MHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24°C Humi: 57%




	ReadAntenna	Cable	Aux	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Factor	Level	Line	Limit
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	312.123	42.43	18.73	2.98	0.00	0.00	64.14	-----
2	312.123	40.15	18.73	2.98	0.00	0.00	61.86	-----
								Peak
								Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	312.10 MHz	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Huni: 57%




	Freq	ReadAntenna		Cable	Aux	Preamp	Level	Limit	Over	Remark
		Level	Factor	Loss	Factor	Factor		Line	Limit	
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	312.093	42.49	18.73	2.98	0.00	0.00	64.20	-----	-----	Peak
2	312.093	40.13	18.73	2.98	0.00	0.00	61.84	-----	-----	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

314.35MHz:

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	314.35 MHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24°C Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	314.345	42.24	18.73	2.98	0.00	0.00	63.95	-----	-----	Peak
2	314.345	40.02	18.73	2.98	0.00	0.00	61.73	-----	-----	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	314.35 MHz	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	314.345	38.74	18.73	2.98	0.00	0.00	60.45	-----	-----	Peak
2	314.345	36.33	18.73	2.98	0.00	0.00	58.04	-----	-----	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

6.2.2 Spurious Emissions

312.10MHz:

Below 1GHz (30MHz-1000MHz)								
Peak value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
624.20	16.86	20.00	3.90	0.00	40.76	75.45	-34.69	Vertical
936.30	17.59	22.76	4.10	0.00	44.45	75.45	-31.00	Vertical
624.20	17.38	20.00	3.90	0.00	41.28	75.45	-34.17	Horizontal
936.30	16.73	22.76	4.10	0.00	43.59	75.45	-31.86	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
624.20	15.93	20.00	3.90	0.00	39.83	55.45	-15.62	Vertical
936.30	15.49	22.76	4.10	0.00	42.35	55.45	-13.10	Vertical
624.20	15.70	20.00	3.90	0.00	39.60	55.45	-15.85	Horizontal
936.30	14.32	22.76	4.10	0.00	41.18	55.45	-14.27	Horizontal
Remark: Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.								

Above 1GHz									
Peak value									
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1248.40	55.97	24.55	3.00	1.22	41.05	43.69	75.45	-31.76	Vertical
1560.50	57.06	24.98	3.38	1.38	41.03	45.77	74.00	-28.23	Vertical
1872.60	54.85	25.50	3.78	1.54	41.37	44.30	74.00	-29.70	Vertical
2184.70	54.47	26.51	4.07	1.64	41.68	45.01	75.45	-30.44	Vertical
2496.80	55.20	27.30	4.39	1.70	41.90	46.69	74.00	-27.31	Vertical
2808.90	54.94	28.00	4.66	1.83	41.65	47.78	74.00	-26.22	Vertical
3121.00	54.90	28.48	5.00	1.97	41.45	48.90	75.45	-26.55	Vertical
1248.40	55.53	24.55	3.00	1.22	41.05	43.25	75.45	-32.20	Horizontal
1560.50	56.55	24.98	3.38	1.38	41.03	45.26	74.00	-28.74	Horizontal
1872.60	55.49	25.50	3.78	1.54	41.37	44.94	74.00	-29.06	Horizontal
2184.70	54.64	26.51	4.07	1.64	41.68	45.18	75.45	-30.27	Horizontal
2496.80	55.67	27.30	4.39	1.70	41.90	47.16	74.00	-26.84	Horizontal
2808.90	55.09	28.00	4.66	1.83	41.65	47.93	74.00	-26.07	Horizontal
3121.00	55.21	28.48	5.00	1.97	41.45	49.21	75.45	-26.24	Horizontal

314.35MHz:


Below 1GHz (30MHz-1000MHz)								
Peak value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
628.70	17.80	20.01	3.90	0.00	41.71	75.58	-33.87	Vertical
943.05	17.66	22.77	4.13	0.00	44.56	75.58	-31.02	Vertical
628.70	17.97	20.01	3.90	0.00	41.88	75.58	-33.70	Horizontal
943.05	16.93	22.77	4.13	0.00	43.83	75.58	-31.75	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
628.70	16.00	20.01	3.90	0.00	39.91	55.58	-15.67	Vertical
943.05	15.53	22.77	4.13	0.00	42.43	55.58	-13.15	Vertical
628.70	15.22	20.01	3.90	0.00	39.13	55.58	-16.45	Horizontal
943.05	13.31	22.77	4.13	0.00	40.21	55.58	-15.37	Horizontal
Remark: Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.								

Above 1GHz									
Peak value									
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1257.40	52.80	24.60	3.02	1.23	41.05	40.60	75.58	-34.98	Vertical
1571.75	53.98	24.95	3.39	1.39	41.03	42.68	74.00	-31.32	Vertical
1886.10	53.12	25.55	3.79	1.55	41.40	42.61	75.58	-32.97	Vertical
2200.45	54.15	26.56	4.09	1.64	41.68	44.76	74.00	-29.24	Vertical
2514.80	55.32	27.33	4.40	1.70	41.90	46.85	75.58	-28.73	Vertical
2829.15	53.55	28.05	4.69	1.83	41.63	46.49	74.00	-27.51	Vertical
3143.50	53.20	28.49	5.01	1.98	41.44	47.24	75.58	-28.34	Vertical
1257.40	53.91	24.60	3.02	1.23	41.05	41.71	75.58	-33.87	Horizontal
1571.75	54.01	24.95	3.39	1.39	41.03	42.71	74.00	-31.29	Horizontal
1886.10	53.43	25.55	3.79	1.55	41.40	42.92	75.58	-32.66	Horizontal
2200.45	53.67	26.56	4.09	1.64	41.68	44.28	74.00	-29.72	Horizontal
2514.80	55.09	27.33	4.40	1.70	41.90	46.62	75.58	-28.96	Horizontal
2829.15	54.44	28.05	4.69	1.83	41.63	47.38	74.00	-26.62	Horizontal
3143.50	53.26	28.49	5.01	1.98	41.44	47.30	75.58	-28.28	Horizontal

Test Plots:

312.1MHz:

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24°C Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	625.078	16.86	20.00	3.90	0.00	0.00	40.76	46.00	-5.24 Peak
2	625.078	15.93	20.00	3.90	0.00	0.00	39.83	46.00	-6.17 Average
3	938.833	17.59	22.76	4.10	0.00	0.00	44.45	46.00	-1.55 Peak
4	938.833	15.49	22.76	4.10	0.00	0.00	42.35	46.00	-3.65 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	625.078	17.38	20.00	3.90	0.00	0.00	41.28	46.00	-4.72 Peak
2	625.078	15.70	20.00	3.90	0.00	0.00	39.60	46.00	-6.40 Average
3	938.833	16.73	22.76	4.10	0.00	0.00	43.59	46.00	-2.41 Peak
4	938.833	14.32	22.76	4.10	0.00	0.00	41.18	46.00	-4.82 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	1246.691	55.97	24.55	3.00	1.22	41.05	43.69	74.00	-30.31	
2	1559.250	57.06	24.98	3.38	1.38	41.03	45.77	74.00	-28.23	
3	1873.261	54.85	25.50	3.78	1.54	41.37	44.30	74.00	-29.70	
4	2182.732	54.47	26.51	4.07	1.64	41.68	45.01	74.00	-28.99	
5	2498.699	55.20	27.30	4.39	1.70	41.90	46.69	74.00	-27.31	
6	2810.210	54.94	28.00	4.66	1.83	41.65	47.78	74.00	-26.22	
7	3120.124	54.90	28.48	5.00	1.97	41.45	48.90	74.00	-25.10	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	1246.691	55.53	24.55	3.00	1.22	41.05	43.25	74.00	-30.75	
2	1559.250	56.55	24.98	3.38	1.38	41.03	45.26	74.00	-28.74	
3	1873.261	55.49	25.50	3.78	1.54	41.37	44.94	74.00	-29.06	
4	2182.732	54.64	26.51	4.07	1.64	41.68	45.18	74.00	-28.82	
5	2498.699	55.67	27.30	4.39	1.70	41.90	47.16	74.00	-26.84	
6	2810.210	55.09	28.00	4.66	1.83	41.65	47.93	74.00	-26.07	
7	3120.124	55.21	28.48	5.00	1.97	41.45	49.21	74.00	-24.79	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

314.3MHz:

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24°C Humi: 57%




	Freq	Read	Antenna	Cable	Aux	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	627.274	17.80	20.01	3.90	0.00	0.00	41.71	46.00	-4.29	Peak
2	627.274	16.00	20.01	3.90	0.00	0.00	39.91	46.00	-6.09	Average
3	942.131	17.66	22.77	4.13	0.00	0.00	44.56	46.00	-1.44	Peak
4	942.131	15.53	22.77	4.13	0.00	0.00	42.43	46.00	-3.57	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	627.274	17.97	20.01	3.90	0.00	0.00	41.88	46.00	-4.12 Peak
2	627.274	15.22	20.01	3.90	0.00	0.00	39.13	46.00	-6.87 Average
3	942.131	16.93	22.77	4.13	0.00	0.00	43.83	46.00	-2.17 Peak
4	942.131	13.31	22.77	4.13	0.00	0.00	40.21	46.00	-5.79 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	1256.764	52.80	24.60	3.02	1.23	41.05	40.60	74.00	-33.40	
2	1574.380	53.98	24.95	3.39	1.39	41.03	42.68	74.00	-31.32	
3	1885.359	53.12	25.55	3.79	1.55	41.40	42.61	74.00	-31.39	
4	2200.368	54.15	26.56	4.09	1.64	41.68	44.76	74.00	-29.24	
5	2514.837	55.32	27.33	4.40	1.70	41.90	46.85	74.00	-27.15	
6	2828.360	53.55	28.05	4.69	1.83	41.63	46.49	74.00	-27.51	
7	3145.333	53.19	28.49	5.01	1.98	41.44	47.23	74.00	-26.77	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart key	Product Model:	RT-MZ3
Test By:	Yaro	Test mode:	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	1256.764	53.91	24.60	3.02	1.23	41.05	41.71	74.00	-32.29	
2	1574.380	54.01	24.95	3.39	1.39	41.03	42.71	74.00	-31.29	
3	1885.359	53.43	25.55	3.79	1.55	41.40	42.92	74.00	-31.08	
4	2200.368	53.67	26.56	4.09	1.64	41.68	44.28	74.00	-29.72	
5	2514.837	55.09	27.33	4.40	1.70	41.90	46.62	74.00	-27.38	
6	2828.360	54.44	28.05	4.69	1.83	41.63	47.38	74.00	-26.62	
7	3145.333	53.26	28.49	5.01	1.98	41.44	47.30	74.00	-26.70	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.3 20dB Bandwidth

Test Requirement:	FCC Part15 C Section 15.231 (c) RSS-210 Annex A Section A.1.3
Receiver setup:	RBW=1kHz, VBW=3kHz, detector: Peak
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

312.10MHz:

20dB bandwidth (MHz)	Limit (MHz)	99% Occupy Bandwidth (MHz)	Results
0.042	0.78075	0.041	Passed


Note: 20dB bandwidth Limit= Fundamental frequency $\times$ 0.25%=312.10 $\times$ 0.25%=0.78075MHz

314.35MHz:


20dB bandwidth (MHz)	Limit (MHz)	99% Occupy Bandwidth (MHz)	Results
0.043	0.78588	0.040	Passed

Note: 20dB bandwidth Limit= Fundamental frequency $\times$ 0.25%=314.35 $\times$ 0.25%=0.78588MHz

Test plot as follows:



6.4 Duration Time

Test Requirement:	FCC Part15 C Section 15.231 (a) (1) RSS-210 Annex A Section A.1.1 (a)
Receiver setup:	RBW=100kHz, VBW=300kHz, span=0Hz, detector: Peak
Limit:	Not more than 5 seconds
Test mode:	Transmitting mode
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Single scan the transmission, and read the transmission time.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data


312.1MHz:

Duration time (second)	Limit (second)	Result
1.22	<5.0	Pass


314.3MHz:

Duration time (second)	Limit (second)	Result
1.30	<5.0	Pass

Test plot as follows:




Date: 11.AUG.2020 14:42:29



Date: 11.AUG.2020 15:13:02

6.5 Frequency Stability

Test Requirement:	RSS-GEN Section 8.11
Limit:	kept within at least the central 80% of its permitted operating frequency band.
Test setup:	Temperature Chamber  Variable Power Supply Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The EUT is installed in an environment test chamber with external power source. 2. Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT. 3. A sufficient stabilization period at each temperature is used prior to each frequency measurement. 4. When temperature is stabled, measure the frequency stability. 5. The test shall be performed under -30 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:**312.1MHz:**

Voltage vs. Frequency Stability

Test conditions		Measurement Frequency (MHz)	Limit (MHz)
Temp(℃)	Voltage(ac)		
20	3.2V	312.1219	281 ~ 449
	3.0V	312.1220	
	2.5V	312.1217	
Note: EUT stops working when the supply voltage is lower than DC 2.5V.			

Temperature vs. Frequency Stability

Test conditions		Frequency(MHz)	Limit (MHz)
Voltage(dc)	Temp(°C)		
3 V	-20	312.1215	281 ~ 449
	-10	312.1214	
	0	312.1216	
	10	312.1217	
	20	312.1220	
	30	312.1219	
	40	312.1217	
	50	312.1210	

314.3MHz:


Voltage vs. Frequency Stability

Test conditions		Measurement Frequency (MHz)	Limit (MHz)
Temp(℃)	Voltage(ac)		
20	3.2V	314.3408	281 ~ 449
	3.0V	314.3410	
	2.5V	314.3400	
Note: EUT stops working when the supply voltage is lower than DC 2.5V,			


Temperature vs. Frequency Stability

Test conditions		Frequency(MHz)	Limit (MHz)
Voltage(dc)	Temp(°C)		
3 V	-20	314.3401	281 ~ 449
	-10	314.3406	
	0	314.3405	
	10	314.3408	
	20	314.3410	
	30	314.3409	
	40	314.3407	
	50	314.3403	

Test plot as follows (worst case):



Date: 11.AUG.2020 15:11:05



Date: 11.AUG.2020 14:47:23