

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-185-RWD-019
AGR No. : A184A-182
Applicant : AIRSOUND INC.
Address : 208, 75, Techno 1-ro, Yuseong-gu, Daejeon, 34014, Korea
Manufacturer : AIRSOUND INC.
Address : 208, 75, Techno 1-ro, Yuseong-gu, Daejeon, 34014, Korea
Type of Equipment : NEW-MYPIN
FCC ID. : 2AOL5-AMP-N180
Model Name : AMP-N180
Serial number : N/A
Total page of Report : 79 pages (including this page)
Date of Incoming : May 01, 2018
Date of issue : May 10, 2018


SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**


This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:


 Ki-Hong, Nam / Chief Engineer
 ONETECH Corp.

Approved by:


 Keun-Young, Choi / Vice President
 ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	6
2. TEST SUMMARY	7
2.1 TEST ITEMS AND RESULTS	7
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	7
2.3 RELATED SUBMITTAL(S) / GRANT(S)	7
2.4 PURPOSE OF THE TEST	7
2.5 TEST METHODOLOGY.....	7
2.6 TEST FACILITY.....	8
3. GENERAL INFORMATION.....	9
3.1 PRODUCT DESCRIPTION.....	9
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	9
4. EUT MODIFICATIONS.....	9
5. SYSTEM TEST CONFIGURATION	10
5.1 JUSTIFICATION.....	10
5.2 PERIPHERAL EQUIPMENT	10
5.3 MODE OF OPERATION DURING THE TEST	10
5.4 CONFIGURATION OF TEST SYSTEM.....	10
5.5 ANTENNA REQUIREMENT	10
6. PRELIMINARY TEST	11
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	11
6.2 GENERAL RADIATED EMISSIONS TESTS	11
7. MINIMUM 20 DB BANDWIDTH.....	12
7.1 OPERATING ENVIRONMENT	12
7.2 TEST SET-UP	12
7.3 TEST EQUIPMENT USED.....	12
7.4 TEST DATA FOR 1 MBPS	13
7.5 TEST DATA FOR 2 MBPS	15
7.6 TEST DATA FOR 3 MBPS	17
8. HOPPING FREQUENCY SEPARATION.....	19
8.1 OPERATING ENVIRONMENT	19
8.2 TEST SET-UP	19

8.3 TEST EQUIPMENT USED	19
8.4 TEST DATA FOR 1 MBPS	20
8.5 TEST DATA FOR 2 MBPS	21
8.6 TEST DATA FOR 3 MBPS	22
9. NUMBER OF HOPPING CHANNELS	23
9.1 OPERATING ENVIRONMENT	23
9.2 TEST SET-UP	23
9.3 TEST EQUIPMENT USED	23
9.4 TEST DATA FOR 1 MBPS	24
9.5 TEST DATA FOR 2 MBPS	27
9.6 TEST DATA FOR 3 MBPS	30
10. TIME OF OCCUPANCY	33
10.1 OPERATING ENVIRONMENT	33
10.2 TEST SET-UP	33
10.3 TEST EQUIPMENT USED	33
10.4 TEST DATA FOR 1 MBPS	34
10.5 TEST DATA FOR 2 MBPS	37
10.6 TEST DATA FOR 3 MBPS	40
11. MAXIMUM PEAK OUTPUT POWER	43
11.1 OPERATING ENVIRONMENT	43
11.2 TEST SET-UP	43
11.3 TEST EQUIPMENT USED	43
11.4 TEST DATA FOR 1 MBPS	44
11.5 TEST DATA FOR 2 MBPS	46
11.6 TEST DATA FOR 3 MBPS	48
12. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND	50
12.1 OPERATING ENVIRONMENT	50
12.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	50
12.3 TEST SET-UP FOR RADIATED MEASUREMENT	50
12.4 TEST EQUIPMENT USED	50
12.5 TEST DATA FOR CONDUCTED EMISSION	51
12.5.1 Test data for 1 Mbps	51
12.5.2 Test data for 2 Mbps	56
12.5.3 Test data for 3 Mbps	61
12.6 TEST DATA FOR TRANSMITTING MODE RADIATED EMISSION	66
12.6.1 Radiated Emission which fall in the Restricted Band	66

12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz.....	69
13. RADIATED EMISSION TEST	72
13.1 OPERATING ENVIRONMENT	72
13.2 TEST SET-UP	72
13.3 TEST EQUIPMENT USED	72
13.4 TEST DATA FOR 30 MHz ~ 1 000 MHz	73
13.5 TEST DATA FOR BELOW 30 MHz	76
13.6 TEST DATA FOR ABOVE 1 GHz	76
14. CONDUCTED EMISSION TEST	77
14.1 OPERATING ENVIRONMENT	77
14.2 TEST SET-UP	77
14.3 TEST EQUIPMENT USED	77
14.4 TEST DATA	78

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-185-RWD-019	2018.05.10	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : AIRSOUND INC.
Address : 208, 75, Techno 1-ro, Yuseong-gu, Daejeon, 34014, Korea
Contact Person : Yukyeom, Kim / Principal Research Engineer
Telephone No. : +82-42-826-8400
FCC ID : 2AOL5-AMP-N180
Model Name : AMP-N180
Serial Number : N/A
Date : May 10, 2018

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	NEW-MYPIN
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (1)	Carrier Frequency Separation	Met the Limit / PASS
15.247 (a) (1) (iii)	Minimum Number of Hopping Channels	Met the Limit / PASS
15.247 (a) (1) (iii)	Average Time of Occupancy	Met the Limit / PASS
15.247 (b) (1)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-14617/ G-10666 / T-1842

IC (Industry Canada) – Registration No. Site# 3736A-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The AIRSOUND INC., Model AMP-N180 (referred to as the EUT in this report) is a NEW-MYPIN. Product specification information described herein was obtained from product data sheet or user's manual.

Device Type	NEW-MYPIN	
Operating Frequency	2 402 MHz ~ 2 480 MHz	
RF Output Power	1 Mbps	3.30 dBm
	2 Mbps	2.94 dBm
	3 Mbps	3.02 dBm
Number of Channel	79 Channel	
Modulation Type	1 Mbps	GFSK
	2 Mbps	$\pi/4$ -QPSK
	3 Mbps	8-DPSK
Antenna Type	Chip Antenna	
Antenna Gain	0.5 dBi	
List of each Osc. or crystal Freq.(Freq. $\geq$ 1 MHz)	26 MHz	

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
MAIN BOARD	AIRSOUND INC.	AMP-N180_V.D.B	N/A
BATTERY	N/A	GJ301025	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
AMP-N180	AIRSOUND INC.	NEW-MYPIN (EUT)	Notebook PC
PP11L	DELL	Notebook PC	EUT

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at 2 402 MHz, 2 441MHz, and 2 480 MHz to get a maximum emission levels from the EUT. The EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XZ” axis, but the worst data was recorded in this report.

5.4 Configuration of Test System

Line Conducted Test: The EUT was connected to Notebook PC and the power of USB was connected to Notebook PC. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is a Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-003 (Rev.2)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Charging Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X


7. MINIMUM 20 dB BANDWIDTH

7.1 Operating environment

Temperature : 22.4°C
Relative humidity : 43.8 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 10 kHz, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.



7.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.


7.4 Test data for 1 Mbps

-. Test Date : May 01, 2018 ~ May 04, 2018


CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	929.10
Middle	2 441.00	924.10
High	2 480.00	929.10




Tested by: Tae-Ho, Kim / Senior Manager



Low Channel



Middle Channel



High Channel


7.5 Test data for 2 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 318.70
Middle	2 441.00	1 328.70
High	2 480.00	1 333.70




Tested by: Tae-Ho, Kim / Senior Manager





Middle Channel




High Channel

-. Test Date : May 01, 2018 ~ May 04, 2018


CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402.00	1 293.70
Middle	2 441.00	1 298.70
High	2 480.00	1 308.70

Tested by: Tae-Ho, Kim / Senior Manager





Middle Channel



High Channel

8. HOPPING FREQUENCY SEPARATION

8.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 43.8 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 10 MHz. The analyzer is set to peak hold then a pseudo-random hopping sequence of the transmitter is captured. The mark delta function was used to measure the frequency separation between two adjacent hopping channels.



8.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

8.4 Test data for 1 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
1 009.00	616.07	Separated by a minimum of 25 kHz



Tested by: Tae-Ho, Kim / Senior Manager



8.5 Test data for 2 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
1 009.00	885.80	Separated by a minimum of 25 kHz



Tested by: Tae-Ho, Kim / Senior Manager



8.6 Test data for 3 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
1 009.00	865.80	Separated by a minimum of 25 kHz



Tested by: Tae-Ho, Kim / Senior Manager




9. NUMBER OF HOPPING CHANNELS

9.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 43.8 % R.H.

9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 100 MHz and the resolution bandwidth is set to 1 MHz. The analyzer is set to peak hold and then complete pseudo-random hopping sequence of the transmitter is captured.



9.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Apr. 05, 2017 (1Y)


All test equipment used is calibrated on a regular basis.

9.4 Test data for 1 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
1 Mbps	79	Minimum of 15	64




Tested by: Tae-Ho, Kim / Senior Manager






Number of hopping channel: 28



Number of hopping channel: 30




Number of hopping channel: 21

9.5 Test data for 2 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
2 Mbps	79	Minimum of 15	64




Tested by: Tae-Ho, Kim / Senior Manager






Number of hopping channel: 28



Number of hopping channel: 30




Number of hopping channel: 21

9.6 Test data for 3 Mbps


-. Test Date : May 01, 2018 ~ May 04, 2018


-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
3 Mbps	79	Minimum of 15	64




Tested by: Tae-Ho, Kim / Senior Manager






Number of hopping channel: 28



Number of hopping channel: 30



Number of hopping channel: 21


10. TIME OF OCCUPANCY

10.1 Operating environment

Temperature : 22.4 °C
Relative humidity : 43.8 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The transmitter is set to operate in its normal frequency hopping mode. The center frequency of the spectrum analyzer is set to one of hopping channels near the center of the operating band and span is set to zero Hz. The sweep time is set to display one complete pulse. The mark delta function is used to measure the duration of the pulses.



10.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ - FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

10.4 Test data for 1 Mbps

-. Test Date : May 01, 2018 ~ May 04, 2018

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.390	10.13	31.6	124.84	400	PASS
DH3	1.650	5.06	31.6	263.83	400	
DH5	2.900	3.38	31.6	309.74	400	


Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time


Remark: See next page for an overview sweep performed with peak detector.




Tested by: Tae-Ho, Kim / Senior Manager



DH1



DH3



DH5

10.5 Test data for 2 Mbps

-. Test Date : May 01, 2018 ~ May 04, 2018

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1 600/2/79) for DH1, and 5.06 times (= 1 600/4/79) for DH3, and 3.38 times (= 1 600/6/79) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.400	10.13	31.6	128.04	400	PASS
DH3	1.660	5.06	31.6	265.43	400	
DH5	2.900	3.38	31.6	309.74	400	


Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time


Remark: See next page for an overview sweep performed with peak detector.




Tested by: Tae-Ho, Kim / Senior Manager



DH1



DH3



DH5

10.6 Test data for 3 Mbps

-. Test Date : May 01, 2018 ~ May 04, 2018

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second ($= 1\,600/2/79$) for DH1, and 5.06 times ($= 1\,600/4/79$) for DH3, and 3.38 times ($= 1\,600/6/79$) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (ms)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.410	10.13	31.6	131.24	400	PASS
DH3	1.650	5.06	31.6	263.83	400	
DH5	2.910	3.38	31.6	310.81	400	


Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time


Remark: See next page for an overview sweep performed with peak detector.




Tested by: Tae-Ho, Kim / Senior Manager



DH1



DH3



DH5