


MEASUREMENT REPORT

FCC PART 15.247 / RSS-247 Bluetooth-LE

FCC ID: 2AOLGVS332I
IC: 23294-VS332I
APPLICANT: Honeywell, spol, s.r.o.-HTS CZ o.z.


Application Type: Certification
Product: Hearing protection headset
Model No.: VS332i
Brand Name: Honeywell
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part15 Subpart C (Section 15.247)
IC Rule(s): RSS-247 Issue 2, RSS-GEN Issue 5
Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v05r02
Test Date: July 08 ~ July 22, 2019

Reviewed By:



(Jame Yuan)

Approved By:



(Robin Wu)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1906RSU033-U2	Rev. 01	Initial Report	07-26-2019	Valid

CONTENTS

Description	Page
1. INTRODUCTION	7
1.1. Scope	7
1.2. MRT Test Location	7
2. PRODUCT INFORMATION	8
2.1. Feature of Equipment under Test	8
2.2. Product Specification Subjective to this Report.....	8
2.3. Working Frequencies for this Report.....	9
2.4. Test Mode	9
2.5. Device Capabilities	10
2.6. Test Configuration	10
2.7. EMI Suppression Device(s)/Modifications.....	10
2.8. Description of Test Software.....	10
2.9. Labeling Requirements.....	11
3. DESCRIPTION OF TEST	12
3.1. Evaluation Procedure	12
3.2. AC Line Conducted Emissions	12
3.3. Radiated Emissions	13
4. ANTENNA REQUIREMENTS.....	14
5. TEST EQUIPMENT CALIBRATION DATE.....	15
6. MEASUREMENT UNCERTAINTY.....	17
7. TEST RESULT	18
7.1. Summary	18
7.2. 99% Occupied Bandwidth Measurement	19
7.2.1. Test Limit	19
7.2.2. Test Procedure used.....	19
7.2.3. Test Setting.....	19
7.2.4. Test Setup.....	19
7.2.5. Test Result.....	20
7.3. 6dB Occupied Bandwidth Measurement.....	22
7.3.1. Test Limit	22
7.3.2. Test Procedure used.....	22
7.3.3. Test Setting.....	22
7.3.4. Test Setup.....	22

7.3.5.	Test Result	23
7.4.	Output Power Measurement	25
7.4.1.	Test Limit	25
7.4.2.	Test Procedure Used	25
7.4.3.	Test Setting	25
7.4.4.	Test Setup.....	26
7.4.5.	Test Result of Output Power	27
7.5.	Power Spectral Density Measurement	28
7.5.1.	Test Limit	28
7.5.2.	Test Procedure Used	28
7.5.3.	Test Setting	28
7.5.4.	Test Setup.....	28
7.5.5.	Test Result	29
7.6.	Conducted Band Edge and Out-of-Band Emissions.....	31
7.6.1.	Test Limit	31
7.6.2.	Test Procedure Used	31
7.6.3.	Test Setting	31
7.6.4.	Test Setup.....	32
7.6.5.	Test Result	33
7.7.	Radiated Spurious Emission Measurement	38
7.7.1.	Test Limit	38
7.7.2.	Test Procedure Used	38
7.7.3.	Test Setting	38
7.7.4.	Test Setup.....	40
7.7.5.	Test Result	41
7.8.	Radiated Restricted Band Edge Measurement	49
7.8.1.	Test Limit	49
7.8.2.	Test Procedure Used	52
7.8.3.	Test Setting	52
7.8.4.	Test Setup.....	53
7.8.5.	Test Result	54
7.9.	AC Conducted Emissions Measurement.....	70
7.9.1.	Test Limit	70
7.9.2.	Test Setup.....	70
7.9.3.	Test Result	71
8.	CONCLUSION.....	73
	Appendix A - Test Setup Photograph	74



Appendix B - EUT Photograph.....	75
---	-----------

§2.1033 General Information

Applicant:	Honeywell, spol, s.r.o.-HTS CZ o.z.
Applicant Address:	Turanka 100 Brno 627 00, Czech Republic
Manufacturer:	Honeywell, spol, s.r.o.-HTS CZ o.z.
Manufacturer Address:	Turanka 100 Brno 627 00, Czech Republic
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D 8 B u i l d i n g , N o . 2 T i a n ö e d a n g R d Development Zone, Suzhou, China
Test Device Serial No.:	N/A ☐ Production ☒ Pre-Production ☐ Engineering

Test Facility / Accreditations

Measurements were performed at MRT Laboratory loc a t e d i n T i a n ö e d a n g R d , S u z h o u , C h i n a .

¹ MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in ANSI C63.4-2014.

¹ MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.

¹ MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.

¹ MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications, Radio and SAR testing.



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake.

These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility

located at D8 Building, No. 2 Tianöedang Rd., Wuzh

China. The measurement facility compliant with the test site requirements specified in ANSI C63.4-2014.



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name:	Hearing protection headset
Model No.:	VS332i
Brand Name:	Honeywell
Bluetooth Version:	v5.0 single mode (BLE Only)
Bluetooth Version:	v5.0 single mode (Basic and EDR Only)
RFID Specification:	902MHz ~ 928MHz (Passive)
Accessories	
Battery:	Model No.: 30001-10 Capacitance: 2.7Wh, 750mAh Rated Voltage: 3.6V

Note 1: This device has two Bluetooth modules located on the right and left side of the headset.

Note 2: There is no DC adapter to ship with the product, during AC conducted emission testing, one adapter (Model No.: TEKA012-0502000UK) was supplied by MRT lab for testing.

2.2. Product Specification Subjective to this Report

Frequency Range:	2402 ~ 2480MHz
Channel Number:	40
Type of modulation:	GFSK
Data Rate:	Up to 2Mbps
Antenna Type:	Chip Antenna
Antenna Gain:	1.5dBi

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this Report

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	--	--	--	--

2.4. Test Mode

Test Mode	Mode 1: Transmit by Bluetooth-LE (1Mbps)
	Mode 2: Transmit by Bluetooth-LE (2Mbps)


2.5. Device Capabilities

This device contains the following capabilities:

Bluetooth v3.0 (DSS), Bluetooth v5.0 (DTS) and UHF RFID passive only

Note: The maximum achievable duty cycles was determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 8MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
Bluetooth-LE - 1Mbps	100%
Bluetooth-LE - 2Mbps	100%



2.6. Test Configuration

The device was tested per the guidance of ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.8. Description of Test Software

The test utility software used during testing was SmartRF Studio and the version was 2.13.1.

2.9. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

RSP-100 Issue 11 Section 3

The manufacturer, importer or distributor shall meet the labeling requirements set out in this section for every unit:

- (i) prior to marketing in Canada, for products manufactured in Canada
- (ii) prior to importation into Canada, for imported products

For information regarding the e-labeling option, see Notice 2014-DRS1003. The label for the certified product represents the manufacturer's compliance with the regulatory requirements of the Canadian Radio-television and Telecommunications Commission (CRTC) and the Department of Economic Development Canada (ISED).

Please see attachment for IC label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance was used in the measurement.

Deviation from measurement procedure

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50_/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the Antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive Antenna height using a broadband Antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn Antennas were used. For frequencies below 30MHz, a calibrated loop Antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband Antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive Antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn Antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive Antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive Antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn Antenna, the horn Antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

ó A n i n t e n t i o n a l shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provision s o f t h i s s e c t i o n . ô

- ° The antenna of the unit is **permanently attached**.
- ° There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2020/04/15
Two-Line V-Network	R&S	ENV 216	MRTSUE06002	1 year	2020/06/13
Two-Line V-Network	R&S	ENV 216	MRTSUE06003	1 year	2020/06/13
Thermohygrometer	Testo	608-H1	MRTSUE06404	1 year	2019/08/14
Shielding Anechoic Chamber	MIX-BEP	Chamber-SR2	MRTSUE06214	N/A	N/A

Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2020/08/01
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2019/09/25
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2019/11/09
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2020/03/31
Broad Band Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2019/10/19
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2019/12/17
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2019/11/16
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2020/06/11
Thermohygrometer	Testo	608-H1	MRTSUE06403	1 year	2019/08/14
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06213	1 year	2020/04/30

Radiated Emission - AC2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Keysight	N9038A	MRTSUE06125	1 year	2019/08/13
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2019/11/09
Bilog Period Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2019/10/19
Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06171	1 year	2019/11/09
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2019/12/17
Broadband Coaxial Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2019/11/16
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2020/06/11
Temperature/Humidity Meter	Minggao	ETH529	MRTSUE06170	1 year	2019/12/13
Anechoic Chamber	RIKEN	Chamber-AC2	MRTSUE06213	1 year	2020/04/30

Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2020/04/15
EXA Signal Analyzer	Keysight	N9010B	MRTSUE06452	1 year	2020/07/11
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2020/04/15
Power Meter	Agilent	U2021XA	MRTSUE06030	1 year	2019/11/16
USB wideband power sensor	Keysight	U2021XA	MRTSUE06446	1 year	2020/06/30
USB wideband power sensor	Keysight	U2021XA	MRTSUE06447	1 year	2020/06/30
Bluetooth Test Set	Anritsu	MT8852B-042	MRTSUE06389	1 year	2020/06/13
Audio Analyzer	Agilent	U8903B	MRTSUE06143	1 year	2019/08/14
Modulation Analyzer	HP	8901A	MRTSUE06098	1 year	2019/10/18
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2019/11/16
DC Power Supply	GWINSTEK	DPS-3303C	MRTSUE06064	N/A	N/A
Temperature & Humidity Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2019/11/16
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2019/08/14

Software	Version	Function
EMI Software	V3	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement - SR2

Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$):

9kHz~150kHz: 3.84dB

150kHz~30MHz: 3.46dB

Radiated Emission Measurement - AC1

Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$):

Horizontal: 30MHz~300MHz: 4.07dB

300MHz~1GHz: 3.63dB

1GHz~18GHz: 4.16dB

Vertical: 30MHz~300MHz: 4.18dB

300MHz~1GHz: 3.60dB

1GHz~18GHz: 4.76dB

Radiated Emission Measurement - AC2

Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$):

Horizontal: 30MHz~300MHz: 3.75dB

300MHz~1GHz: 3.53dB

1GHz~18GHz: 4.28dB

Vertical: 30MHz~300MHz: 3.86dB

300MHz~1GHz: 3.53dB

1GHz~18GHz: 4.33dB

7. TEST RESULT

7.1. Summary

FCC Part Section(s)	IC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
N/A	RSS-Gen [6.7]	99% Bandwidth	N/A	Conducted	Pass	Section 7.2
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	500 kHz		Pass	Section 7.3
15.247(b)(3)	RSS-247 [5.4(d)]	Output Power	1 Watt EIRP 4Watt		Pass	Section 7.4
15.247(e)	RSS-247 [5.2]	Power Spectral Density	8 dBm / 3 kHz		Pass	Section 7.5
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	20dBc (Peak)		Pass	Section 7.6
15.205 15.209	RSS-247 [5.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.7 Section 7.8
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz - 30MHz	Refer to section 7.8	Line Conducted	Pass	Section 7.9

Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.

7.2. 99% Occupied Bandwidth Measurement

7.2.1. Test Limit

N/A


7.2.2. Test Procedure used

ANSI C63.10-2013 - Section 6.9.3

7.2.3. Test Setting

1. Span = 1.5 times to 5 times the OBW
2. Set RBW = 1% to 5% the OBW
3. $VBW \approx 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace was allowed to stabilize


7.2.4. Test Setup



7.2.5. Test Result

Product	Hearing protection headset	Temperature	25 ℃
Test Engineer	Snake Ni	Relative Humidity	52%
Test Site	TR3	Test Date	2019/07/20

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	99% Bandwidth (MHz)
Bluetooth-LE	1	00	2402	1.075
Bluetooth-LE	1	19	2440	1.052
Bluetooth-LE	1	39	2480	1.074
Bluetooth-LE	2	00	2402	2.106
Bluetooth-LE	2	19	2440	2.111
Bluetooth-LE	2	39	2480	2.097



Bluetooth-LE (2Mbps) 99% Bandwidth

Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



7.3. 6dB Occupied Bandwidth Measurement

7.3.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.3.2. Test Procedure used

ANSI C63.10-2013 - Section 11.8

7.3.3. Test Setting

1. The Spectrum's automatic bandwidth measurement bandwidth measurement. The 6dB parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW = 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace was allowed to stabilize


7.3.4. Test Setup



7.3.5. Test Result

Product	Hearing protection headset	Temperature	25 ℃
Test Engineer	Snake Ni	Relative Humidity	52%
Test Site	TR3	Test Date	2019/07/16

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Bluetooth-LE	1	00	2402	0.692	0.5	Pass
Bluetooth-LE	1	19	2440	0.728	0.5	Pass
Bluetooth-LE	1	39	2480	0.722	0.5	Pass
Bluetooth-LE	2	00	2402	1.358	0.5	Pass
Bluetooth-LE	2	19	2440	1.490	0.5	Pass
Bluetooth-LE	2	39	2480	1.411	0.5	Pass




Bluetooth-LE (2Mbps) 6dB Bandwidth

Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



7.4. Output Power Measurement

7.4.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm) and the E.I.R.P shall not exceed 4 Watt (36.02dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.4.2. Test Procedure Used

ANSI C63.10 - Section 11.9.1.3

ANSI C63.10 - Section 11.9.2.3

7.4.3. Test Setting


Method PKPM1 (Peak Power Measurement)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

Method AVGPM-G (Measurement using a gated RF average-reading power meter)

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

7.4.4. Test Setup



7.4.5. Test Result of Output Power

Product	Hearing protection headset	Temperature	25 Ć
Test Engineer	Snake Ni	Relative Humidity	52%
Test Site	TR3	Test Date	2019/07/16

Test Result of Peak Output Power

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)	Result
Bluetooth-LE	1	00	2402	2.72	Ė30.00	4.22	Ė36.02	Pass
Bluetooth-LE	1	19	2440	2.43	Ė30.00	3.93	Ė36.02	Pass
Bluetooth-LE	1	39	2480	1.69	Ė30.00	3.19	Ė36.02	Pass
Bluetooth-LE	2	00	2402	3.14	Ė30.00	4.64	Ė36.02	Pass
Bluetooth-LE	2	19	2440	2.52	Ė30.00	4.02	Ė36.02	Pass
Bluetooth-LE	2	39	2480	1.67	Ė30.00	3.17	Ė36.02	Pass

Note: E.I.R.P (dBm) = Peak Power (dBm) + Antenna Gain (dBi), Antenna Gain = 1.5 dBi.

Test Result of Average Output Power (Reporting Only)

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Average Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)	Result
Bluetooth-LE	1	00	2402	2.57	Ė30.00	4.07	Ė36.02	Pass
Bluetooth-LE	1	19	2440	2.25	Ė30.00	3.75	Ė36.02	Pass
Bluetooth-LE	1	39	2480	1.53	Ė30.00	3.03	Ė36.02	Pass
Bluetooth-LE	2	00	2402	2.89	Ė30.00	4.39	Ė36.02	Pass
Bluetooth-LE	2	19	2440	2.23	Ė30.00	3.73	Ė36.02	Pass
Bluetooth-LE	2	39	2480	1.49	Ė30.00	2.99	Ė36.02	Pass

Note: E.I.R.P (dBm) = Average Power (dBm) + Antenna Gain (dBi), Antenna Gain = 1.5 dBi.

7.5. Power Spectral Density Measurement

7.5.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


7.5.2. Test Procedure Used

ANSI C63.10 - Section 11.10.2

7.5.3. Test Setting

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 10kHz
5. Detector = Peak
6. Sweep time = Auto couple
7. Trace mode = Max hold
8. Trace was allowed to stabilize


7.5.4. Test Setup



7.5.5. Test Result


Product	Hearing protection headset	Temperature	25 ºC
Test Engineer	Snake Ni	Relative Humidity	52%
Test Site	TR3	Test Date	2019/07/16

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
Bluetooth-LE	1	00	2402	-4.63	Ø8.00	Pass
Bluetooth-LE	1	19	2440	-5.41	Ø8.00	Pass
Bluetooth-LE	1	39	2480	-5.38	Ø8.00	Pass
Bluetooth-LE	2	00	2402	-9.99	Ø8.00	Pass
Bluetooth-LE	2	19	2440	-11.40	Ø8.00	Pass
Bluetooth-LE	2	39	2480	-10.24	Ø8.00	Pass




Bluetooth-LE (2Mbps) PSD


Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



7.6. Conducted Band Edge and Out-of-Band Emissions

7.6.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20 dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

7.6.2. Test Procedure Used

ANSI C63.10 - Section 11.11

7.6.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≈ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\approx 3 \times$ RBW
5. Detector = Peak
6. Sweep time = Auto couple
7. Trace mode = Max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep time = Auto couple
7. The trace was allowed to stabilize

7.6.4. Test Setup



7.6.5. Test Result


Product	Hearing protection headset	Temperature	25 Ć
Test Engineer	Snake Ni	Relative Humidity	52%
Test Site	TR3	Test Date	2019/07/16

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit	Result
Bluetooth-LE	1	00	2402	20dBc	Pass
Bluetooth-LE	1	19	2440	20dBc	Pass
Bluetooth-LE	1	39	2480	20dBc	Pass
Bluetooth-LE	2	00	2402	20dBc	Pass
Bluetooth-LE	2	19	2440	20dBc	Pass
Bluetooth-LE	2	39	2480	20dBc	Pass


Bluetooth-LE (1Mbps) Out-of-Band Emissions

Channel 00 (2402MHz)


100kHz PSD reference Level



Low Band Edge




Spurious Emission 30MHz ~ 25GHz




Channel 19 (2440MHz)

100kHz PSD reference Level



Spurious Emission 30MHz ~ 25GHz




Channel 39 (2480MHz)


100kHz PSD reference Level



High Band Edge




Spurious Emission 30MHz ~ 25GHz




Bluetooth-LE (2Mbps) Out-of-Band Emissions

Channel 00 (2402MHz)


100kHz PSD reference Level



Low Band Edge




Spurious Emission 30MHz ~ 25GHz




Channel 19 (2440MHz)

100kHz PSD reference Level




Spurious Emission 30MHz ~ 25GHz



Channel 39 (2480MHz)



100kHz PSD reference Level



High Band Edge



Spurious Emission 30MHz ~ 25GHz



7.7. Radiated Spurious Emission Measurement

7.7.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Field Strength ($\mu V/m$)	Measured Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.7.2. Test Procedure Used

ANSI C63.10 - Section 6.3 (General Requirements)

ANSI C63.10 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - Section 6.6 (Standard test method above 1GHz)

7.7.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\leq 98\%$, then the minimum transmission duration is 10ms. If the EUT duty cycle is $< 98\%$, then the minimum transmission duration is determined by the duty cycle.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

7.7.4.Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



7.7.5. Test Result

Product	Hearing protection headset	Temperature	25 °C
Test Engineer	Snake Ni	Relative Humidity	54%
Test Site	AC1	Test Date	2019/07/17
Test Mode	Bluetooth-LE (1Mbps)	Test Channel:	00
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB _{μV})	Factor (dB)	Measure Level (dB _{μV})	Limit (dB _{μV})	Margin (dB)	Detector	Polarization
	4808.0	41.6	4.7	46.3	74.0	-27.7	Peak	Horizontal
	7451.5	35.5	10.7	46.2	74.0	-27.8	Peak	Horizontal
*	7800.0	36.3	10.8	47.1	80.0	-32.9	Peak	Horizontal
*	10579.5	35.3	15.7	51.0	80.0	-29.0	Peak	Horizontal
	4808.0	37.5	4.7	42.2	74.0	-31.8	Peak	Vertical
	7290.0	35.5	10.6	46.1	74.0	-27.9	Peak	Vertical
*	8709.5	35.6	11.8	47.4	80.0	-32.6	Peak	Vertical
*	10120.5	34.8	14.9	49.7	80.0	-30.3	Peak	Vertical

Note 1: * in restricted band, its limit is 20dBc of the fundamental emission level (100.0dB_{μV} or 15.209 which is higher.

Note 2: Measure Level (dB_{μV}) = Reading Level (dB_{μV}) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Hearing protection headset	Temperature	25 °C
Test Engineer	Snake Ni	Relative Humidity	54%
Test Site	AC1	Test Date	2019/07/17
Test Mode	Bluetooth-LE (1Mbps)	Test Channel:	19
Remark	1. Average measurement was not performed if peak level lower than average limit. So the margin was calculated using the average limit for emissions fall within the restricted bands. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Polarization
	4876.0	39.8	4.8	44.6	74.0	-29.4	Peak	Horizontal
	7681.0	35.9	10.6	46.5	74.0	-27.5	Peak	Horizontal
*	7987.0	35.6	11.3	46.9	74.6	-27.7	Peak	Horizontal
*	8879.5	35.7	12.1	47.8	74.6	-26.8	Peak	Horizontal
	5037.5	35.0	5.2	40.2	74.0	-33.8	Peak	Vertical
	7672.5	35.7	10.6	46.3	74.0	-27.7	Peak	Vertical
*	9253.5	36.2	13.5	49.7	74.6	-24.9	Peak	Vertical
*	10528.5	35.6	15.8	51.4	74.6	-23.2	Peak	Vertical

Note 1: * is not in range of the fundamental emission levels (94.6 dBμV or 15.209 which is higher.

Note 2: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Hearing protection headset	Temperature	25 °C
Test Engineer	Snake Ni	Relative Humidity	54%
Test Site	AC1	Test Date	2019/07/17
Test Mode	Bluetooth-LE (1Mbps)	Test Channel:	39
Remark	1. Average measurement was not performed if peak level lower than average limit. So the margin was calculated using the average limit for emissions fall within the restricted bands. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Polarization
	4961.0	39.7	4.9	44.6	74.0	-29.4	Peak	Horizontal
	7383.5	35.6	10.5	46.1	74.0	-27.9	Peak	Horizontal
*	7902.0	36.4	11.1	47.5	74.0	-26.5	Peak	Horizontal
*	9916.5	35.0	14.6	49.6	74.0	-24.4	Peak	Horizontal
	4961.0	39.4	4.9	44.3	74.0	-29.7	Peak	Vertical
	7375.0	35.4	10.6	46.0	74.0	-28.0	Peak	Vertical
*	7961.5	35.8	11.3	47.1	74.0	-26.9	Peak	Vertical
*	9891.0	34.1	14.7	48.8	74.0	-25.2	Peak	Vertical

Note 1: * is not in range of the fundamental emission levels (88.9dBμV or 15.209 which is higher.

Note 2: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Hearing protection headset	Temperature	25 °C
Test Engineer	Snake Ni	Relative Humidity	54%
Test Site	AC1	Test Date	2019/07/17
Test Mode	Bluetooth-LE (2Mbps)	Test Channel:	00
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB _{μV})	Factor (dB)	Measure Level (dB _{μV})	Limit (dB _{μV})	Margin (dB)	Detector	Polarization
	4799.5	41.6	4.6	46.2	74.0	-27.8	Peak	Horizontal
	9075.0	36.1	12.5	48.6	74.0	-25.4	Peak	Horizontal
*	9636.0	34.5	14.2	48.7	74.0	-25.3	Peak	Horizontal
*	10018.5	34.7	14.7	49.4	74.0	-24.6	Peak	Horizontal
	4808.0	38.9	4.7	43.6	74.0	-30.4	Peak	Vertical
	7366.5	36.0	10.6	46.6	74.0	-27.4	Peak	Vertical
*	8888.0	35.3	12.0	47.3	74.0	-26.7	Peak	Vertical
*	10562.5	34.3	15.8	50.1	74.0	-23.9	Peak	Vertical

Note 1: * is not in range of the fundamental emission levels (93.8dB_{μV} / or 15.209 which is higher.

Note 2: Measure Level (dB_{μV}) = Reading Level (dB_{μV}) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Hearing protection headset	Temperature	25 °C
Test Engineer	Snake Ni	Relative Humidity	54%
Test Site	AC1	Test Date	2019/07/17
Test Mode	Bluetooth-LE (2Mbps)	Test Channel:	19
Remark	1. Average measurement was not performed if peak level lower than average limit. So the margin was calculated using the average limit for emissions fall within the restricted bands. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Polarization
	4876.0	39.7	4.8	44.5	74.0	-29.5	Peak	Horizontal
	7409.0	36.5	10.6	47.1	74.0	-26.9	Peak	Horizontal
*	8548.0	35.2	11.5	46.7	74.0	-27.3	Peak	Horizontal
*	10452.0	35.1	15.3	50.4	74.0	-23.6	Peak	Horizontal
	4876.0	39.4	4.8	44.2	74.0	-29.8	Peak	Vertical
	7562.0	35.6	10.7	46.3	74.0	-27.7	Peak	Vertical
*	7944.5	36.1	11.3	47.4	74.0	-26.6	Peak	Vertical
*	10171.5	34.5	15.0	49.5	74.0	-24.5	Peak	Vertical

Note 1: * is not in range of the fundamental emission levels (92.4dBμV or 15.209 which is higher.

Note 2: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Hearing protection headset	Temperature	25 °C
Test Engineer	Snake Ni	Relative Humidity	54%
Test Site	AC1	Test Date	2019/07/17
Test Mode	Bluetooth-LE (2Mbps)	Test Channel:	39
Remark	1. Average measurement was not performed if peak level lower than average limit. So the margin was calculated using the average limit for emissions fall within the restricted bands. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector	Polarization
	4961.0	40.8	4.9	45.7	74.0	-28.3	Peak	Horizontal
	7740.5	36.2	10.6	46.8	74.0	-27.2	Peak	Horizontal
*	8743.5	35.3	12.0	47.3	74.0	-26.7	Peak	Horizontal
*	9721.0	34.6	14.1	48.7	74.0	-25.3	Peak	Horizontal
	4961.0	40.8	4.9	45.7	74.0	-28.3	Peak	Vertical
	7375.0	36.3	10.6	46.9	74.0	-27.1	Peak	Vertical
*	8021.0	36.1	11.4	47.5	74.0	-26.5	Peak	Vertical
*	10528.5	34.7	15.8	50.5	74.0	-23.5	Peak	Vertical


Note 1: * is not in range of the fundamental emission levels (88.6dBμV or 15.209 which is higher.

Note 2: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The Worst Case of Radiated Emission below 1GHz:

Site: AC1	Time: 2019/07/19 - 11:57
Limit: FCC_Part15.209_RSE(3m)	Engineer: Cloud Guo
Probe: VULB 9168 _20-2000MHz	Polarity: Horizontal
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by Bluetooth-LE (1Mbps) at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			61.040	31.716	18.389	-8.284	40.000	13.327	QP
2			120.210	40.290	26.961	-3.210	43.500	13.329	QP
3			147.370	38.250	23.039	-5.250	43.500	15.211	QP
4		*	226.910	34.549	22.006	-11.451	46.000	12.543	QP
5			300.145	42.047	27.500	-3.953	46.000	14.547	QP
6			499.965	42.481	23.747	-3.519	46.000	18.734	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

Site: AC1	Time: 2019/07/19 - 11:57
Limit: FCC_Part15.209_RSE(3m)	Engineer: Cloud Guo
Probe: VULB 9168 _20-2000MHz	Polarity: Vertical
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by Bluetooth-LE (1Mbps) at Channel 2402MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			61.020	37.854	24.524	-2.146	40.000	13.330	QP
2		*	120.210	31.393	18.064	-12.107	43.500	13.329	QP
3			231.760	31.695	18.917	-14.305	46.000	12.778	QP
4			300.145	40.756	26.209	-5.244	46.000	14.547	QP
5			499.965	39.678	20.944	-6.322	46.000	18.734	QP
6			900.090	33.737	8.979	-12.263	46.000	24.758	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

7.8. Radiated Restricted Band Edge Measurement

7.8.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 ñ 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measured Distance (m)
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

For RSS-Gen Section 8.10 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 8.10 of RSS-Gen, must also comply with the radiated emission limits specified in Section 8.9.

Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for license exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	

All out of band emissions appearing in a restricted band as specified in Section 8.10 of the RSS-Gen must not exceed the limits shown in Table per Section 8.9.

RSS-Gen Section 8.9			
Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Magnetic Field Strength (H-Field) ($\mu\text{A/m}$)	Measured Distance (m)
0.009 - 0.490	--	6.37/F (F in kHz)	300
0.490 - 1.705	--	6.37/F (F in kHz)	30
1.705 - 30	--	0.08	30
30 - 88	100	--	3
88 - 216	150	--	3
216 - 960	200	--	3
Above 960	500	--	3

7.8.2.Test Procedure Used

ANSI C63.10 - Section 6.3 (General Requirements)

ANSI C63.10 - Section 6.6 (Standard test method above 1GHz)

7.8.3.Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with a 10% duty cycle
4. If the EUT duty cycle is the minimum transmission duration $\tau = 1/T$
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

7.8.4. Test Setup



7.8.5.Test Result


Site: AC1	Time: 2019/07/16 - 08:01
Limit: FCC_Part15.209_RE(3m)	Engineer: Cloud Guo
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by BLE 1M at 2402MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2382.333	48.899	16.472	-25.101	74.000	32.427	PK
2			2390.000	45.180	12.767	-28.820	74.000	32.413	PK
3		*	2402.214	92.757	60.361	N/A	N/A	32.396	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)


Site: AC1	Time: 2019/07/16 - 08:05
Limit: FCC_Part15.209_RE(3m)	Engineer: Cloud Guo
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by BLE 1M at 2402MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	27.480	-4.933	-26.520	54.000	32.413	AV
2		*	2402.214	90.346	57.950	N/A	N/A	32.396	AV

Note: Measure Level (dBuV/m) + Factor (dB) = Reading Level (dBuV)
Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)


Site: AC1	Time: 2019/07/16 - 08:03
Limit: FCC_Part15.209_RE(3m)	Engineer: Cloud Guo
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by BLE 1M at 2402MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2371.194	48.890	16.440	-25.110	74.000	32.450	PK
2			2390.000	48.320	15.907	-25.680	74.000	32.413	PK
3		*	2401.697	99.975	67.579	N/A	N/A	32.396	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/07/16 - 08:12
Limit: FCC_Part15.209_RE(3m)	Engineer: Cloud Guo
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by BLE 1M at 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2388.161	29.490	-2.926	-24.510	54.000	32.417	AV
2			2390.000	29.402	-3.011	-24.598	54.000	32.413	AV
3		*	2402.073	99.279	66.883	N/A	N/A	32.395	AV

Note: $\text{Measurement Level (dBuV/m)} = \text{Reading Level (dBuV)} + \text{Factor (dB)}$

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2019/07/16 - 08:17
Limit: FCC_Part15.209_RE(3m)	Engineer: Cloud Guo
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Hearing protection headset	Power: By Battery
Test Mode: Transmit by BLE 1M at 2480MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.000	88.457	56.049	N/A	N/A	32.408	PK
2			2483.500	46.397	13.982	-27.603	74.000	32.416	PK
3			2490.320	48.385	15.956	-25.615	74.000	32.429	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)