



Shenzhen Chenxing Electronic Technology Co., LTD

Product Specification

PRODUCT SPECIFICATION FOR APPROVAL

customer
name : Lianxin Micro
CUSTOMER

product
name : MPP transmitter coil

PRODUCT NAME

material code : Sensing specification: 8. 1uH±10%

PART No.

Magnet size: 42.4*0.4 single slot ferrite soft magnet +20*1 small round plate

size of
product : Wire specification: 0. 08*65*11Ts (21.7mm inner diameter/40mm outer diameter)

PRODUCT SPEC

Length of the tape: 28mm 3mm high temperature tape /41*25*0. 5mmEVA double-sided tape

sun designated
time : March 21,2025

DATE

Version and mod-
el: REV 1.2

VERSION

edition Revision	Changes Modified Content	person liable Principle	date Date	remarks Note
REV 1.0	First release	Xue Lei	2024-11-11	
REV 1.1	Add 0.5mmEVA double-sided tape later	Zhou Xiaoju	2025-03-21	
REV 1.2	The exit length is changed from 40mm to 38mm	Zhou Xiaoju	2025-05-26	

Formulate / Prepared by	Reviewed/checked by	Approved/APPROVED BY

Customer's authorized signature and seal		
---	--	--

Attached is the product specification, if you have any questions, please feel free to contact us, thank you!

Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: 5th Floor, Building 1, Xinkecheng Technology Industrial Park, 51 Dabao Road, Xian Street, Baoan District, Shenzhen



Shenzhen Chenxing Electronic Technology Co., LTD

Size of Product SPECIFICATION

I. Product Size

	Disk diameter A	42.4±0.3mm
	Wire coil outer diameter B	40±1mm
	Inner diameter of coil C	21.7±0.5mm
	Product thickness D	<2.1mm
	Outgoing line length E	38mm±2mm
	Welding tin length F	3-5mm
	Hole diameter of magnetic disk G	sclausura
	Thickness of magnetic sheet	0.4±0.05mm
	Disk shape	Round open slot
	gum	0.5mmEVA double-sided tape
	Specifications of small magnetic separator	20* 1 disc

	Hot tape	3mm
--	-----------------	-----


Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: 5th Floor, Building 1, Xinkecheng Technology Industrial Park, 51 Dabao Road, Xinan Street, Baoan District, Shenzhen



Shenzhen Chenxing Electronic Technology Co., LTD

II. Schematic Diagram



3. Winding Parameters

terminal TERMINAL	Wire diameter WIRE	number of turns Turns	direction of winding Winding Direction
S F	Enamel wire 0.08*65	11Ts	CCW

IV. Electrical Characteristics

Temperature: $25\pm10^{\circ}\text{C}$, humidity: $65\pm20\%$

project ITEM	terminal TERMINAL	standard SPECIFICATION	test condition TEST FREQUENCY	measuring and test in- struments TEST EQUIPMENTS
IND.	S-F	L: $8.1\mu\text{H}\pm10\%$ Q: Greater than 60	100KHz/1.0V	LCZ METER 1062B

V. List of Materials

order nu- mber	material	specifications
1	wire stock	0.08*65p 2 UEW-hot air copper wire
2	magnetic sheet	42.4*0.4 single slot (ferrite soft magnetic sheet) +20*1 hard magnetic sheet
3	glue	Water-based white latex
4	tin bar	Environmentally friendly and lead-free
5	adhesive tape	3mm high temperature tape

Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: 5th Floor, Building 1, Xinkecheng Technology Industrial Park, 51 Dabao Road, Xinan Street, Baoan District, Shenzhen



Shenzhen Chenxing Electronic Technology Co., LTD

VI. Physical Map



Company name: Shenzhen Chenxing Electronic Technology Co., LTD

Factory address: 5th Floor, Building 1, Xinkecheng Technology Industrial Park, 51 Dabao Road, Xinan Street, Baoan District, Shenzhen