

RF Exposure evaluation report

Applicant:	Vaultek Safe, Inc.
Address of Applicant:	37 N Orange Ave. Suite 800B Orlando, FL 32801 United States
Manufacturer:	Jeritech Electronics, Ltd.
Address of Manufacturer:	Guannanyong Industrial Estate, Shiqi Town, Panyu, GuangZhou, China
Product name:	RS500i/RS500/RS200i/RS200 safe
Model:	RS500i-BK, RS500i-TG, RS500i-WT, RS200i-BK, RS200i-TG, RS200i-WT, RS500-BK, RS500-TG, RS500-WT, RS200-BK, RS200-TG, RS200-WT
Rating(s):	DC 3.7V
Trademark:	Vaultek
Standards:	47 CFR Part 1.1310 (2013) 47 CFR Part 2.1091 (2013) KDB447498D01 General RF Exposure Guidance v06
FCC ID:	2AONI-PRO-RS20I01
Date of Receipt:	2019-08-22
Date of Test:	2019-08-22~2019-09-09
Date of Issue:	2019-09-09
Test Result	Pass*

* In the configuration tested, the test item complied with the standards specified above.

Authorized for issue by:

Test by:

Sep 09, 2019 Shaeffer Yang

Project Engineer

Reviewed by:

Sep 09, 2019 Pauler Li

Project Manager



Date

Name/Position

Signature

Date

Name/Position

Signature

Possible test case verdicts:

test case does not apply to the test object ..: N/A

test object does meet the requirement: P (Pass)

test object does not meet the requirement ..: F (Fail)

Testing Laboratory information:

Testing Laboratory Name: ITL Co., Ltd

Address.....: No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan, Guangdong, 523757 P.R.C.

Testing location : Same as above

Tel : 0086-769-39001678

Fax : 0086-20-62824387

E-mail : itl@i-testlab.com

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report would be invalid test report without all the signatures of testing technician and approver.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

General product information:

There's an AC Adapter that charges the battery.

AC Adapter:

Model: GEO101U-050200U

Input: 100-240Vac, 50/60Hz, 0.3A. Output: 5Vdc, 2A.

The models RS500i-BK, RS500i-TG, RS500i-WT, RS200i-BK, RS200i-TG, RS500-BK, RS500-TG, RS500-WT, RS200-BK, RS200-TG, RS200-WT and RS200i-WT are identical to each other except for model names and colour.

All tests were performed on the model RS200i-BK as representative.

1 Contents

	Page
1 CONTENTS.....	3
2 GENERAL INFORMATION	4
2.1 CLIENT INFORMATION	4
2.2 GENERAL DESCRIPTION OF E.U.T.....	4
2.3 DETAILS OF E.U.T.....	4
2.4 DESCRIPTION OF SUPPORT UNITS	4
2.5 TEST LOCATION.....	5
2.6 DEVIATION FROM STANDARDS	5
2.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
2.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
2.9 TEST FACILITY	5
3 RF EXPOSURE EVALUATION.....	6
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
3.1.1 STANDARD REQUIREMENT	6
3.1.2 EUT RF EXPOSURE.....	6

2 General Information

2.1 Client Information

Applicant: Vaultek Safe, Inc.
Address of Applicant: 37 N Orange Ave. Suite 800B Orlando, FL 32801 United States

2.2 General Description of E.U.T.

Name: RS500i/RS500/RS200i/RS200 safe
Model No.: RS200i-BK
Trade Mark: Vaultek
Operating Frequency: 802.11 b/g/n(HT20): 2412MHz-2462MHz
Channels: 802.11b, 802.11g, 802.11n(20MHz): 11
802.11n(40MHz): 7
Type of Modulation: CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Antenna Reference: PCB antenna with 1.7 dBi peak Gain
Function: Safe

2.3 Details of E.U.T.

EUT Power Supply: DC 3.7V
Test mode for WIFI: The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz,
TM2	802.11g	2412MHz, 2437MHz, 2462MHz,
TM3	802.11n(HT20)	2412MHz, 2437MHz, 2462MHz,
TM4	802.11n(40MHz)	2422MHz, 2437MHz, 2452MHz,

2.4 Description of Support Units

The EUT has been tested as an independent unit for fixed frequency by testing lab.

2.5 Test Location

All tests were performed at:

ITL Co., Ltd

No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan, Guangdong, 523757 P.R.C.

0086-769-39001678

itl@i-testlab.com

No tests were sub-contracted.

2.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

2.7 Abnormalities from Standard Conditions

None.

2.8 Other Information Requested by the Customer

None.

2.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS(Lab code:L9342)**
- **FCC (Registration No.: 239076)**
- **IC (Registration NO.:CN0025)**

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06 and FCC 1.1310
Radiofrequency radiation exposure limits for General Population/Uncontrolled Exposure

3.1.2 EUT RF Exposure

The Max Output Power is 17.27dBm in 802.11b Lowest channel (2. 437GHz);

Antenna gain: 1.7dBi

R=20cm

$$S = PG / (4 \pi R^2) = 0.18 < 1 \text{ (limits)}$$