



FCC RF Test Report

APPLICANT : Onyx Healthcare USA
EQUIPMENT : Medical Tablet
BRAND NAME : Onyx Healthcare USA
MODEL NAME : xxxxxMPAD-800 xxxxxxxxxx (X represents
"0-9", "A-Z", "a-z", "-", "blank")
FCC ID : 2A0OUMPAD800WBL
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 05, 2017 and testing was completed on Jan. 30, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID: 2A0OUMPAD800WBL

Page Number : 1 of 33

Report Issued Date : Feb. 07, 2018

Report Version : Rev. 01

Report Template No.: BU5-FR15CWLAC MA Version 2.0



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	5
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	8
2.5 EUT Operation Test Setup	8
2.6 Measurement Results Explanation Example.....	9
3 TEST RESULT	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	25
3.6 AC Conducted Emission Measurement.....	29
3.7 Antenna Requirements.....	31
4 LIST OF MEASURING EQUIPMENT	32
5 UNCERTAINTY OF EVALUATION	33
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7O0519C	Rev. 01	Initial issue of report	Feb. 07, 2018



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.12 dB at 2389.800 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 2.50 dB at 0.374 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Onyx Healthcare USA

324 West Blueridge Avenue Orange, CA 92865

1.2 Manufacturer

AAEON Technology Inc.

5F, No. 135, Lane 235, Pao Chiao Rd., Taipei, Taiwan

1.3 Product Feature of Equipment Under Test

LTE, Bluetooth, and Wi-Fi 2.4GHz 802.11b/g/n

Product Specification subjective to this standard	
Antenna Type	WWAN: PIFA Antenna WLAN: FPC Antenna Bluetooth: FPC Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH05-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.



1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		


2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1: LTE Band 4 Idle + Bluetooth Link + WLAN Link + MPEG4 + TC + Type-C USB Cable (Data Link with Notebook) (Read file from SD Card)
Remark: 1. TC stands for test configuration, and consist of Micro SD Card, Earphone, Adapter, and Type-A USB Device. 2. Data Linking with Notebook means data application transferred mode between EUT and Notebook	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
4.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
6.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	Shielded, 1.0 m	N/A
8.	USB Flash Disk	ADATA	UC350	N/A	N/A	N/A
9.	USB Type C to A Cable	Moshi	99MO084101	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	White Lin and Lena Lo	Temperature :	21~25°C
		Relative Humidity :	51~54%

Number of TX = 1, Ant. 1 (Measured)


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----





Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----


100kHz PSD reference Level



Date: 25.JAN.2018 09:47:38


Channel Plot

Spurious Emission 30MHz~3GHz




Date: 25.JAN.2018 09:47:54

Spurious Emission 2GHz~25GHz




Date: 25.JAN.2018 09:48:02






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----





Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----


100kHz PSD reference Level



Date: 25.JAN.2018 10:14:22


Channel Plot

Spurious Emission 30MHz~3GHz



Date: 25.JAN.2018 10:14:36

Spurious Emission 2GHz~25GHz




Date: 25.JAN.2018 10:14:45




Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 25.JAN.2018 10:17:49

Channel Plot




Date: 25.JAN.2018 10:18:05

Spurious Emission 30MHz~3GHz



Date: 25.JAN.2018 10:18:17

Spurious Emission 2GHz~25GHz




Date: 25.JAN.2018 10:18:25



Test Mode : 802.11n HT20


Test Channel : 01

100kHz PSD reference Level




Date: 25.JAN.2018 10:22:26

Channel Plot




Date: 25.JAN.2018 10:22:37

Spurious Emission 30MHz~3GHz



Date: 25.JAN.2018 10:22:49


Spurious Emission 2GHz~25GHz



Date: 25.JAN.2018 10:22:58

Test Mode :	802.11n HT20	Test Channel :	06
--------------------	--------------	-----------------------	----


100kHz PSD reference Level



Date: 25.JAN.2018 10:25:16


Channel Plot

Spurious Emission 30MHz~3GHz



Date: 25.JAN.2018 10:25:29


Spurious Emission 2GHz~25GHz



Date: 25.JAN.2018 10:25:38



Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1240001	N/A	Sep. 07, 2017	Jan. 11, 2018~ Jan. 25, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz z	Sep. 07, 2017	Jan. 11, 2018~ Jan. 25, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 20, 2017	Jan. 11, 2018~ Jan. 25, 2018	Jun. 19, 2018	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 12, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 20, 2017	Jan. 12, 2018	Sep. 19, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Jan. 12, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2017	Jan. 12, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Dec. 18, 2017	Jan. 26, 2018~ Jan. 30, 2018	Dec. 17, 2018	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 23, 2017	Jan. 26, 2018~ Jan. 30, 2018	Aug. 22, 2018	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 10, 2017	Jan. 26, 2018~ Jan. 30, 2018	Nov. 09, 2019	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 25, 2017	Jan. 26, 2018~ Jan. 30, 2018	Apr. 24, 2018	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 14, 2017	Jan. 26, 2018~ Jan. 30, 2018	Mar. 13, 2018	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 30, 2017	Jan. 26, 2018~ Jan. 30, 2018	Oct. 29, 2018	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2017	Jan. 26, 2018~ Jan. 30, 2018	Apr. 16, 2018	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Jan. 26, 2018~ Jan. 30, 2018	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jan. 26, 2018~ Jan. 30, 2018	N/A	Radiation (03CH07-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Jan. 26, 2018~ Jan. 30, 2018	Jul. 17, 2018	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 16, 2018	Jan. 26, 2018~ Jan. 30, 2018	Jan. 15, 2019	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 27, 2017	Jan. 26, 2018~ Jan. 30, 2018	Nov. 26, 2018	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.7
--	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7
--	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
--	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
--	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	White Lin/Lena Lo	Temperature:	21~25	°C
Test Date:	2018/01/11 ~ 2018/01/25	Relative Humidity:	51~54	%

Maximum Power Density				
Max. Power	Gain	EIRP	20 cm PSD	Limit
12.81	3.03	15.84	0.0076	1.0
dBm	dBi	dBm	mW/cm ²	mW/cm ²

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	11.85	9.04	0.50	Pass
11b	1Mbps	1	6	2437	11.80	8.56	0.50	Pass
11b	1Mbps	1	11	2462	11.85	9.04	0.50	Pass
11g	6Mbps	1	1	2412	18.15	16.32	0.50	Pass
11g	6Mbps	1	6	2437	18.30	16.32	0.50	Pass
11g	6Mbps	1	11	2462	18.20	16.32	0.50	Pass
HT20	MCS0	1	1	2412	19.10	17.60	0.50	Pass
HT20	MCS0	1	6	2437	19.00	17.60	0.50	Pass
HT20	MCS0	1	11	2462	18.95	17.60	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	15.84	30.00	3.03	18.87	36.00	Pass
11b	1Mbps	1	6	2437	15.32	30.00	3.03	18.35	36.00	Pass
11b	1Mbps	1	11	2462	15.23	30.00	3.03	18.26	36.00	Pass
11g	6Mbps	1	1	2412	21.97	30.00	3.03	25.00	36.00	Pass
11g	6Mbps	1	6	2437	21.82	30.00	3.03	24.85	36.00	Pass
11g	6Mbps	1	11	2462	21.64	30.00	3.03	24.67	36.00	Pass
HT20	MCS0	1	1	2412	21.91	30.00	3.03	24.94	36.00	Pass
HT20	MCS0	1	6	2437	21.36	30.00	3.03	24.39	36.00	Pass
HT20	MCS0	1	11	2462	21.28	30.00	3.03	24.31	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	12.81
11b	1Mbps	1	6	2437	0.00	12.35
11b	1Mbps	1	11	2462	0.00	12.21
11g	6Mbps	1	1	2412	0.15	12.01
11g	6Mbps	1	6	2437	0.15	11.42
11g	6Mbps	1	11	2462	0.15	11.31
HT20	MCS0	1	1	2412	0.16	11.91
HT20	MCS0	1	6	2437	0.16	11.51
HT20	MCS0	1	11	2462	0.16	11.30

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-10.30	3.03	8.00	Pass
11b	1Mbps	1	6	2437	-10.81	3.03	8.00	Pass
11b	1Mbps	1	11	2462	-10.71	3.03	8.00	Pass
11g	6Mbps	1	1	2412	-14.03	3.03	8.00	Pass
11g	6Mbps	1	6	2437	-13.48	3.03	8.00	Pass
11g	6Mbps	1	11	2462	-14.18	3.03	8.00	Pass
HT20	MCS0	1	1	2412	-14.54	3.03	8.00	Pass
HT20	MCS0	1	6	2437	-14.65	3.03	8.00	Pass
HT20	MCS0	1	11	2462	-13.93	3.03	8.00	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Shareef Yu	Temperature :	24~25°C
		Relative Humidity :	43~45%

EUT Information

Report NO : 7O0519
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

ENV216 Auto Test FCC Power Bar - L



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.182000	48.5	Off	L1	19.5	15.9	64.4
0.230000	48.3	Off	L1	19.5	14.1	62.4
0.286000	45.7	Off	L1	19.5	14.9	60.6
0.318000	46.1	Off	L1	19.5	13.7	59.8
0.358000	52.8	Off	L1	19.5	6.0	58.8
0.374000	52.3	Off	L1	19.5	6.1	58.4
0.390000	51.6	Off	L1	19.5	6.5	58.1
0.454000	49.9	Off	L1	19.5	6.9	56.8
0.534000	41.0	Off	L1	19.5	15.0	56.0
0.566000	38.5	Off	L1	19.5	17.5	56.0
0.630000	39.9	Off	L1	19.5	16.1	56.0
0.694000	38.7	Off	L1	19.5	17.3	56.0


Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.182000	36.0	Off	L1	19.5	18.4	54.4
0.230000	36.1	Off	L1	19.5	16.3	52.4
0.286000	34.9	Off	L1	19.5	15.7	50.6
0.318000	35.3	Off	L1	19.5	14.5	49.8
0.358000	43.1	Off	L1	19.5	5.7	48.8
0.374000	41.3	Off	L1	19.5	7.1	48.4
0.390000	37.3	Off	L1	19.5	10.8	48.1
0.454000	36.5	Off	L1	19.5	10.3	46.8
0.534000	29.7	Off	L1	19.5	16.3	46.0
0.566000	28.8	Off	L1	19.5	17.2	46.0
0.630000	28.8	Off	L1	19.5	17.2	46.0
0.694000	25.5	Off	L1	19.5	20.5	46.0

EUT Information

Report NO : 700519
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	55.8	Off	N	19.5	10.2	66.0
0.166000	52.6	Off	N	19.5	12.6	65.2
0.190000	50.6	Off	N	19.5	13.4	64.0
0.214000	51.8	Off	N	19.5	11.2	63.0
0.246000	43.3	Off	N	19.5	18.6	61.9
0.302000	54.7	Off	N	19.5	5.5	60.2
0.350000	52.7	Off	N	19.5	6.3	59.0
0.374000	55.9	Off	N	19.5	2.5	58.4
0.446000	43.5	Off	N	19.5	13.4	56.9

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	45.4	Off	N	19.5	10.6	56.0
0.166000	43.0	Off	N	19.5	12.2	55.2
0.190000	41.4	Off	N	19.5	12.6	54.0
0.214000	44.7	Off	N	19.5	8.3	53.0
0.246000	35.3	Off	N	19.5	16.6	51.9
0.302000	47.0	Off	N	19.5	3.2	50.2
0.350000	43.0	Off	N	19.5	6.0	49.0
0.374000	45.8	Off	N	19.5	2.6	48.4
0.446000	35.3	Off	N	19.5	11.6	46.9



Appendix C. Radiated Spurious Emission

Test Engineer :	Jesse Wang, Stan Hsieh, and Lance Chiang	Temperature :	22~24°C
		Relative Humidity :	50~52%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2316.615	55.85	-18.15	74	40.86	31.74	8.28	35.02	400	333	P	H
		2389.8	44.73	-9.27	54	29.6	31.95	8.24	35.05	400	333	A	H
	*	2412	100.4	-	-	85.23	31.99	8.24	35.05	400	333	P	H
	*	2412	97.4	-	-	82.23	31.99	8.24	35.05	400	333	A	H
													H
													H
		2387.07	55.86	-18.14	74	40.72	31.95	8.24	35.04	356	12	P	V
		2390	44.93	-9.07	54	29.8	31.95	8.24	35.05	356	12	A	V
	*	2412	100.07	-	-	84.9	31.99	8.24	35.05	356	12	P	V
	*	2412	97.1	-	-	81.93	31.99	8.24	35.05	356	12	A	V
													V
													V
802.11b CH 06 2437MHz		2314.48	55.61	-18.39	74	40.62	31.74	8.28	35.02	357	316	P	H
		2389.52	44.59	-9.41	54	29.45	31.95	8.24	35.04	357	316	A	H
	*	2437	101.48	-	-	86.2	32.08	8.27	35.06	357	316	P	H
	*	2437	98.32	-	-	83.04	32.08	8.27	35.06	357	316	A	H
		2492.16	55.99	-18.01	74	40.58	32.2	8.3	35.08	357	316	P	H
		2489.57	45.02	-8.98	54	29.6	32.2	8.3	35.07	357	316	A	H
		2324.56	55.14	-18.86	74	40.1	31.79	8.28	35.02	357	360	P	V
		2388.68	44.64	-9.36	54	29.5	31.95	8.24	35.04	357	360	A	V
	*	2437	102.48	-	-	87.2	32.08	8.27	35.06	357	360	P	V
	*	2437	99.39	-	-	84.11	32.08	8.27	35.06	357	360	A	V
		2491.32	56.85	-17.15	74	41.43	32.2	8.3	35.07	357	360	P	V
		2490.55	45.04	-8.96	54	29.62	32.2	8.3	35.07	357	360	A	V



802.11b CH 11 2462MHz	*	2462	101.62	-	-	86.27	32.12	8.3	35.06	200	0	P	H
	*	2462	98.45	-	-	83.1	32.12	8.3	35.06	200	0	A	H
		2499.32	55.52	-18.48	74	40.11	32.2	8.3	35.08	200	0	P	H
		2483.52	45.15	-8.85	54	29.77	32.16	8.3	35.07	200	0	A	H
													H
													H
	*	2462	100.96	-	-	85.61	32.12	8.3	35.06	350	359	P	V
	*	2462	97.89	-	-	82.54	32.12	8.3	35.06	350	359	A	V
		2496	55.92	-18.08	74	40.51	32.2	8.3	35.08	350	359	P	V
		2483.52	45.01	-8.99	54	29.63	32.16	8.3	35.07	350	359	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	41.22	-32.78	74	53.87	34.23	11.93	59.38	100	0	P	H
													H
													H
													H
		4824	41.53	-32.47	74	54.18	34.23	11.93	59.38	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	42.43	-31.57	74	55.04	34.22	11.9	59.29	100	0	P	H
		7311	45.71	-28.29	74	52.69	35.71	14.94	58.05	100	0	P	H
													H
													H
		4874	41.83	-32.17	74	54.44	34.22	11.9	59.29	100	0	P	V
		7311	44.68	-29.32	74	51.66	35.71	14.94	58.05	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	42.53	-31.47	74	55.1	34.21	11.87	59.21	100	0	P	H
		7386	46.35	-27.65	74	53.33	35.66	15.08	58.12	100	0	P	H
													H
													H
		4924	44.01	-29.99	74	56.58	34.21	11.87	59.21	100	0	P	V
		7386	45.06	-28.94	74	52.04	35.66	15.08	58.12	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2387.175	60.37	-13.63	74	45.23	31.95	8.24	35.04	207	0	P	H
		2390	49.47	-4.53	54	34.34	31.95	8.24	35.05	207	0	A	H
	*	2412	101.5	-	-	86.33	31.99	8.24	35.05	207	0	P	H
	*	2412	93.75	-	-	78.58	31.99	8.24	35.05	207	0	A	H
													H
													H
		2390	62.38	-11.62	74	47.25	31.95	8.24	35.05	328	354	P	V
		2389.8	49.63	-4.37	54	34.5	31.95	8.24	35.05	328	354	A	V
	*	2412	102.85	-	-	87.68	31.99	8.24	35.05	328	354	P	V
	*	2412	93.62	-	-	78.45	31.99	8.24	35.05	328	354	A	V
													V
													V
802.11g CH 06 2437MHz		2322.6	55.51	-18.49	74	40.47	31.79	8.28	35.02	203	0	P	H
		2379.72	45.55	-8.45	54	30.43	31.91	8.26	35.04	203	0	A	H
	*	2437	103.12	-	-	87.84	32.08	8.27	35.06	203	0	P	H
	*	2437	95.34	-	-	80.06	32.08	8.27	35.06	203	0	A	H
		2496.64	55.6	-18.4	74	40.19	32.2	8.3	35.08	203	0	P	H
		2500	45.87	-8.13	54	30.46	32.2	8.3	35.08	203	0	A	H
		2329.32	55.28	-18.72	74	40.24	31.79	8.28	35.02	357	341	P	V
		2374.12	45.63	-8.37	54	30.51	31.91	8.26	35.04	357	341	A	V
	*	2437	102.82	-	-	87.54	32.08	8.27	35.06	357	341	P	V
	*	2437	95.08	-	-	79.8	32.08	8.27	35.06	357	341	A	V
		2489.85	55.69	-18.31	74	40.27	32.2	8.3	35.07	357	341	P	V
		2491.11	45.85	-8.15	54	30.43	32.2	8.3	35.07	357	341	A	V



802.11g CH 11 2462MHz	*	2462	104.8	-	-	89.45	32.12	8.3	35.06	201	0	P	H
	*	2462	95.71	-	-	80.36	32.12	8.3	35.06	201	0	A	H
		2483.88	60.77	-13.23	74	45.39	32.16	8.3	35.07	201	0	P	H
		2483.6	47.59	-6.41	54	32.21	32.16	8.3	35.07	201	0	A	H
													H
													H
	*	2462	102.64	-	-	87.29	32.12	8.3	35.06	355	357	P	V
	*	2462	94.72	-	-	79.37	32.12	8.3	35.06	355	357	A	V
		2483.6	58.14	-15.86	74	42.76	32.16	8.3	35.07	355	357	P	V
		2483.56	46.55	-7.45	54	31.17	32.16	8.3	35.07	355	357	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	40.68	-33.32	74	53.33	34.23	11.93	59.38	100	0	P	H
													H
													H
													H
		4824	40.77	-33.23	74	53.42	34.23	11.93	59.38	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	41.35	-32.65	74	53.96	34.22	11.9	59.29	100	0	P	H
		7311	44.82	-29.18	74	51.8	35.71	14.94	58.05	100	0	P	H
													H
													H
		4874	40.74	-33.26	74	53.35	34.22	11.9	59.29	100	0	P	V
		7311	43.6	-30.4	74	50.58	35.71	14.94	58.05	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	40.94	-33.06	74	53.51	34.21	11.87	59.21	100	0	P	H
		7386	45.39	-28.61	74	52.37	35.66	15.08	58.12	100	0	P	H
													H
													H
		4924	41.87	-32.13	74	54.44	34.21	11.87	59.21	100	0	P	V
		7386	44.3	-29.7	74	51.28	35.66	15.08	58.12	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.905	63.13	-10.87	74	48	31.95	8.24	35.05	184	0	P	H
		2389.8	50.88	-3.12	54	35.75	31.95	8.24	35.05	184	0	A	H
	*	2412	101.87	-	-	86.7	31.99	8.24	35.05	184	0	P	H
	*	2412	93.85	-	-	78.68	31.99	8.24	35.05	184	0	A	H
													H
													H
		2390	62.42	-11.58	74	47.29	31.95	8.24	35.05	357	360	P	V
		2390	49.76	-4.24	54	34.63	31.95	8.24	35.05	357	360	A	V
	*	2412	103.03	-	-	87.86	31.99	8.24	35.05	357	360	P	V
	*	2412	93.87	-	-	78.7	31.99	8.24	35.05	357	360	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2371.46	55.31	-18.69	74	40.19	31.91	8.26	35.04	202	360	P	H
		2387.56	45.53	-8.47	54	30.39	31.95	8.24	35.04	202	360	A	H
	*	2437	102.9	-	-	87.62	32.08	8.27	35.06	202	360	P	H
	*	2437	95.21	-	-	79.93	32.08	8.27	35.06	202	360	A	H
		2489.36	55.77	-18.23	74	40.35	32.2	8.3	35.07	202	360	P	H
		2490.13	45.88	-8.12	54	30.46	32.2	8.3	35.07	202	360	A	H
		2326.94	55.85	-18.15	74	40.81	31.79	8.28	35.02	356	350	P	V
		2374.12	45.44	-8.56	54	30.32	31.91	8.26	35.04	356	350	A	V
	*	2437	103.2	-	-	87.92	32.08	8.27	35.06	356	350	P	V
	*	2437	94.76	-	-	79.48	32.08	8.27	35.06	356	350	A	V
		2492.37	56.13	-17.87	74	40.72	32.2	8.3	35.08	356	350	P	V
		2484.46	45.87	-8.13	54	30.49	32.16	8.3	35.07	356	350	A	V



802.11n HT20 CH 11 2462MHz	*	2462	102.97	-	-	87.62	32.12	8.3	35.06	180	0	P	H
	*	2462	92.86	-	-	77.51	32.12	8.3	35.06	180	0	A	H
		2485.4	66.13	-7.87	74	50.75	32.16	8.3	35.07	180	0	P	H
		2483.64	49.93	-4.07	54	34.55	32.16	8.3	35.07	180	0	A	H
													H
													H
	*	2462	101.29	-	-	85.94	32.12	8.3	35.06	348	341	P	V
	*	2462	94.56	-	-	79.21	32.12	8.3	35.06	348	341	A	V
		2483.96	62.34	-11.66	74	46.96	32.16	8.3	35.07	348	341	P	V
		2483.8	49.16	-4.84	54	33.78	32.16	8.3	35.07	348	341	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	41.15	-32.85	74	53.8	34.23	11.93	59.38	100	0	P	H
													H
													H
													H
		4824	41.33	-32.67	74	53.98	34.23	11.93	59.38	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	40.57	-33.43	74	53.18	34.22	11.9	59.29	100	0	P	H
		7311	46.4	-27.6	74	53.38	35.71	14.94	58.05	100	0	P	H
													H
													H
		4874	40.7	-33.3	74	53.31	34.22	11.9	59.29	100	0	P	V
		7311	44.79	-29.21	74	51.77	35.71	14.94	58.05	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	41.73	-32.27	74	54.3	34.21	11.87	59.21	100	0	P	H
		7386	46.36	-27.64	74	53.34	35.66	15.08	58.12	100	0	P	H
													H
													H
		4924	42.23	-31.77	74	54.8	34.21	11.87	59.21	100	0	P	V
		7386	46.75	-27.25	74	53.73	35.66	15.08	58.12	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		161.22	23.79	-19.71	43.5	36	16.47	2.62	31.49	-	-	P	H
		191.46	23.17	-20.33	43.5	37.03	14.77	2.72	31.46	-	-	P	H
		288.12	27.02	-18.98	46	36.06	18.91	3.28	31.32	-	-	P	H
		600.3	33.04	-12.96	46	33.87	25.46	4.39	30.83	-	-	P	H
		659.8	36.38	-9.62	46	36.19	26.17	4.59	30.74	100	0	P	H
		969.2	35.34	-18.66	54	29.26	30.86	5.4	30.51	-	-	P	H
													H
													H
													H
													H
													H
													H
		83.73	27.61	-12.39	40	43.33	13.63	2.11	31.58	-	-	P	V
		117.48	28.64	-14.86	43.5	40.41	17.33	2.34	31.54	-	-	P	V
		294.33	29.22	-16.78	46	38.09	19.06	3.28	31.31	-	-	P	V
		600.3	30.45	-15.55	46	31.28	25.46	4.39	30.83	-	-	P	V
		859.3	33.92	-12.08	46	30.02	29.01	5.2	30.55	100	0	P	V
		991.6	35.2	-18.8	54	29.33	30.51	5.54	30.51	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Jesse Wang, Stan Hsieh, and Lance Chiang	Temperature :	22~24°C
		Relative Humidity :	50~52%

Note symbol





-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz



WIFI 802.11b (Band Edge @ 3m)





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 9	Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 9
Avg.	Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 9	Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 9

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 700519 Mode : 9	 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 700519 Mode : 9
Avg.	 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 700519 Mode : 9	 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 700519 Mode : 9





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 10	 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 10
Avg.	 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 10	 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 10





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-4V Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 10	Left blank
Avg.	 Site : 03CH07-4V Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 10	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 10	 Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 10
Avg.	 Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 10	 Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 10







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4V Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 10	Left blank
Avg.	 Site : 03CH07-4V Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 10	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11	 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11
Avg.	 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11	 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11	 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11
Avg.	 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11	 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 11



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 12	 Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 12
	 Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 12	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 12









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Level (dBuV/m) Frequency (MHz) Date: 2018-01-27 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 12	 Level (dBuV/m) Frequency (MHz) Date: 2018-01-27 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 12
Avg.	 Level (dBuV/m) Frequency (MHz) Date: 2018-01-27 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 12	 Level (dBuV/m) Frequency (MHz) Date: 2018-01-27 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 12

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13	 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13
Avg.	 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13	 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-4V Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 13	Left blank
Avg.	 Site : 03CH07-4V Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 13	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4Y Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13	 Site : 03CH07-4Y Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13
Avg.	 Site : 03CH07-4Y Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13	 Site : 03CH07-4Y Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 13

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 13	Left Blank
Avg.	 Site : 03CH07-4HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 13	Left Blank











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7O0519 : 14	 Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7O0519 : 14
Avg.	 Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:1000KHz SWT:Auto Project : Peak Mode : 7O0519 : 14	 Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : RBW:1000.000KHz VBW:1000KHz SWT:Auto Project : Peak Mode : 7O0519 : 14









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 700519 Mode : 14	 Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 700519 Mode : 14
Avg.	 Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 700519 Mode : 14	 Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 700519 Mode : 14





2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 15	 Site : 03CH07-HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 15
	 Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 15	 Site : 03CH07-HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 15

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4V Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 15	 Site : 03CH07-4V Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 15
	 Site : 03CH07-4V Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 15	 Site : 03CH07-4V Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 15
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 16	 Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 16
Avg.	 Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 16	 Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 7O0519 Mode : 16

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 16	Left blank
Avg.	 Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 700519 Mode : 16	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 16	 Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 16
Avg.	 Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 16	 Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 16

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 16	Left Blank
Avg.	 Site : 03CH07-HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 16	Left Blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak	Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 17	Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 17
Avg.	Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 17	Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 17





WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1HY Condition : PEAK_BE_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 17	 Site : 03CH07-1HY Condition : PEAK_74 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 17
Avg.	 Site : 03CH07-1HY Condition : AVG_BE_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 17	 Site : 03CH07-1HY Condition : AVG_54 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 7O0519 Mode : 17



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 9	 Site : 03CH07-1FY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 7O0519 Mode : 9



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 700519 Mode : 10	 Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 700519 Mode : 10

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-4HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 11	 Site : 03CH07-4HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 7O0519 Mode : 11

2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 12	 Site : 03CH07-1FY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 7O0519 Mode : 12







WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 700519 Mode : 13	 Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 700519 Mode : 13



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH07-4HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 700519 Mode : 14	Site : 03CH07-4HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 700519 Mode : 14



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 7O0519 Mode : 15	 Site : 03CH07-1FY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 7O0519 Mode : 15

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 700519 Mode : 10	 Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 700519 Mode : 10

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH07-4HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 700519 Mode : 17	Site : 03CH07-4HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 700519 Mode : 17


Emission below 1GHz
2.4GHz WIFI 802.11n HT20 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT20 LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH07-4FY Condition : QP 3m LF-ANT-35419(6) HORIZONTAL Detector : Peak Project : 7O0519 Mode : 1B	 Site : 03CH07-4FY Condition : QP 3m LF-ANT-35419(6) VERTICAL Detector : Peak Project : 7O0519 Mode : 1B


Appendix E. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11b	100.00	-	-	10Hz	0.00
802.11g	96.56	1405.00	0.71	1kHz	0.15
2.4GHz 802.11n HT20	96.32	1310.00	0.76	1kHz	0.16


802.11b



Date: 12.JAN.2018 09:13:21

802.11g


Date: 12.JAN.2018 09:18:51

802.11n HT20


Date: 12.JAN.2018 09:25:05