

FCC/ISED

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Smart Phone

ISSUED TO
Shenzhen UniStrong Science & Technology Co., Ltd.

B, 4-4Factory, Zhengcheng Road, FuyongBaoan District, Shenzhen, China.



Tested by: Hu Chao
Hu Chao
(Engineer)

Date: Mar. 20, 2018

Approved by: Wei Yanquan
Wei Yanquan
(Chief Engineer)

Date: Mar. 20, 2018

Report No.: BL-EC17C0360-603
EUT Name: Smart Phone
Model Name: UT10
Brand Name: UniStrong
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen (Issue 4, November 2014)
RSS-247 (Issue 2, February 2017)
FCC ID: 2AOPD-UT10
ISED Number: 11546A-UT10
Test conclusion: Pass
Test Date: Jan. 12, 2018 ~ Mar. 05, 2018
Date of Issue: Mar. 20, 2018

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Mar. 07, 2018</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Mar. 20, 2018</u>	<u>Updated ancillary equipment information.</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION	6
2.1	Applicant Information	6
2.2	Manufacturer Information	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Ancillary Equipment	7
2.6	Technical Information	8
2.7	Additional Instructions	10
3	SUMMARY OF TEST RESULTS	11
3.1	Test Standards	11
3.2	Verdict	11
4	GENERAL TEST CONFIGURATIONS	12
4.1	Test Environments	12
4.2	Test Equipment List	12
4.3	Measurement Uncertainty	14
4.4	Description of Test Setup	14
4.4.1	For Antenna Port Test	14
4.4.2	For AC Power Supply Port Test	15
4.4.3	For Radiated Test (Below 30 MHz)	15
4.4.4	For Radiated Test (30 MHz-1 GHz)	16

4.4.5	For Radiated Test (Above 1 GHz).....	16
4.5	Measurement Results Explanation Example.....	17
4.5.1	For conducted test items:	17
4.5.2	For radiated band edges and spurious emission test:.....	17
5	TEST ITEMS.....	18
5.1	Antenna Requirements.....	18
5.1.1	Relevant Standards.....	18
5.1.2	Antenna Anti-Replacement Construction	19
5.1.3	Antenna Gain	19
5.2	Output Power	20
5.2.1	Test Limit.....	20
5.2.2	Test Setup	20
5.2.3	Test Procedure.....	20
5.2.4	Test Result	21
5.3	6dB Bandwidth	22
5.3.1	Limit.....	22
5.3.2	Test Setup	22
5.3.3	Test Procedure.....	22
5.3.4	Test Result	22
5.4	Conducted Spurious Emission	23
5.4.1	Limit.....	23
5.4.2	Test Setup	23
5.4.3	Test Procedure.....	23
5.4.4	Test Result	24
5.5	Band Edge (Authorized-band band-edge).....	25
5.5.1	Limit.....	25
5.5.2	Test Setup	25
5.5.3	Test Procedure.....	25
5.5.4	Test Result	26
5.6	Conducted Emission	27
5.6.1	Limit.....	27
5.6.2	Test Setup	27

5.6.3	Test Procedure	27
5.6.4	Test Result	27
5.7	Radiated Spurious Emission	28
5.7.1	Limit.....	28
5.7.2	Test Setup	28
5.7.3	Test Procedure	28
5.7.4	Test Result	31
5.8	Band Edge (Restricted-band band-edge).....	32
5.8.1	Limit.....	32
5.8.2	Test Setup	32
5.8.3	Test Procedure	32
5.8.4	Test Result	32
5.9	Power Spectral density (PSD).....	33
5.9.1	Limit.....	33
5.9.2	Test Setup	33
5.9.3	Test Procedure	33
5.9.4	Test Result	33
ANNEX A	TEST RESULT	34
A.1	Output Power	34
A.2	Bandwidth.....	36
A.3	Conducted Spurious Emissions	41
A.4	Band Edge (Authorized-band band-edge).....	48
A.5	Conducted Emissions.....	51
A.6	Radiated Emission	53
A.7	Band Edge (Restricted-band band-edge).....	91
A.8	Power Spectral Density (PSD)	104
ANNEX B	TEST SETUP PHOTOS	107
ANNEX C	EUT EXTERNAL PHOTOS	107
ANNEX D	EUT INTERNAL PHOTOS	107

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v6.0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen UniStrong Science & Technology Co., Ltd.
Address	B, 4-4Factory, Zhengcheng Road, FuyongBaoan District, Shenzhen, China

2.2 Manufacturer Information

Manufacturer	Shenzhen UniStrong Science & Technology Co., Ltd.
Address	B, 4-4Factory, Zhengcheng Road, FuyongBaoan District, Shenzhen, China

2.3 Factory Information

Factory	Shenzhen UniStrong Science & Technology Co., Ltd.
Address	B, 4-4Factory, Zhengcheng Road, FuyongBaoan District, Shenzhen, China

2.4 General Description for Equipment under Test (EUT)

EUT Type	Smart Phone
Model Name Under Test	UT10
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	UT10_V104
Software Version	UT10_V1.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/900/1800/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 1/2/5/8, 4G Network FDD LTE Band 1/2/3/4/5/7/8/17/20/28 TDD LTE Band 38/40/41 CDMA2000 800 MHz Bluetooth 4.0 (BR+EDR+BLE) WIFI 802.11b, 802.11g, 802.11n(HT20) and 802.11ac, 5.8G SRD, GPS, GLONASS, BDS, NFC

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	SJYEnergy
	Model No.	BA7800
	Serial No.	N/A
	Capacity	8000 mAh
	Rated Voltage	3.8 V
	Limit Charge Voltage	4.35 V
Ancillary Equipment 2 ^{Note}	Adapter	
	Brand Name	N/A
	Model No.	ASUC71w-050912300
	Serial No.	ASUC71z-050912300 (z= a, e, i, w)
	Rated Input	100-240 V~, 0.7 A, 50/60 Hz
	Rated Output	5 V= 3 A or 9 V= 2 A or 12 V= 1.5 A
Ancillary Equipment 3	USB Cable	
	Length (Approx.)	1.0 m
Note: All adapter are same with electrical parameters and internal circuit structure, but only differ in model name and plug type. Adapter ASUC71w-050912300 was tested in this report.		

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11.
Modulation Type	DSSS, OFDM
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	PIFA Antenna
Antenna Gain	1.5 dBi
About the Product	Only the WIFI 802.11b, 802.11g and 802.11n (HT20) was tested in this report.

Modulation technology	Modulation Type	Transfer Rate (Mbps)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n-20MHz)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Output Power	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
6dB Bandwidth	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Conducted Spurious Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Conducted Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Radiated Spurious Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Band Edge	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11
Power spectral density (PSD)	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.7 Additional Instructions

EUT Software Settings:


Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

EUT Software Settings:

Power level setup in software			
Test Software Version	QRCT		
Support Units (Software installation media)	Description	Manufacturer	Model
	Laptop	Lenovo	X220
Mode	Channel	Soft Set	
802.11 b	All	12	
802.11 g	All	11	
802.11 n20	All	13	

Run software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-16 Edition)	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
3	KDB Publication 662911 D01v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
4	RSS-Gen (Issue 4, Nov. 2014)	General Requirements for Compliance of Radio Apparatus
5	RSS-247 (Issue 2, February 2017)	Digital Transmission Systems (DTSS), Frequency Hopping Systems(FHSS) and Licence-Exempt Local Area Network (LE-LAN) Devices
6	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC PART No.	ISED Part No.	Test Result	Verdict
1	Antenna Requirement	15.203; 15.247(b)	RSS-247, 5.4 (6)	N/A	Pass ^{Note 1}
2	Output Power	15.247(b)	RSS-247, 5.4 (4)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	RSS-GEN, 6.6; RSS-247, 5.2 (1)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.209; 15.247(d)	RSS-GEN, 8.9; RSS-247, 5.5	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247(d)	RSS-247, 5.5	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247(d)	RSS-247, 5.5	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (2)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	RSS-Gen, 7.1.2	N/A	N/A ^{Note 2}

Note 1: Please refer to section 5.1.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.8 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2017.06.12	2018.06.11
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2017.06.12	2018.06.11
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2017.09.07	2018.09.06
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2017.06.22	2018.06.21
LISN	SCHWARZBECK	NSLK 8127	8127-687	2017.06.22	2018.06.21
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2017.06.12	2018.06.11
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2017.06.12	2018.06.11
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2017.06.22	2018.06.21
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2017.06.27	2018.06.26
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.11.07	2019.11.08
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2017.07.22	2019.07.21
Test Antenna- Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2016.07.12	2018.07.11
Test Antenna- Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2017.06.22	2018.06.21
Test Antenna- Horn (18-40 GHz)	A-INFO	LB- 180400KF	J211060273	N/A	2019.01.06
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.24	2019.02.23
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60 *7.35m	N/A	2017.02.21	2019.02.20
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2017.06.12	2018.06.11
Power Amplifier	OPHIR RF	5225F	1037	2018.02.17	2019.02.16
Power Amplifier	OPHIR RF	5273F	1016	2018.02.17	2019.02.16
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Feld Strength Meter	Narda	EP601	511WX51129	2017.05.22	2018.05.21
Mouth Simulator	B&K	4227	2423931	2017.11.16	2018.11.15
Sound Calibrator	B&K	4231	2430337	2017.11.16	2018.11.15
Sound Level Meter	B&K	NL-20	00844023	2017.11.16	2018.11.15
Ear Simulator	B&K	4185	2409449	2017.11.16	2018.11.15
Ear Simulator	B&K	4195	2418189	2017.11.16	2018.11.15
Audio analyzer	B&K	UPL 16	100129	2017.11.16	2018.11.15

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (4)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.36dB Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz

> 1000 MHz	1 MHz
------------	-------

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(d); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	Duty Cycle	T (ms)	1/T(kHz)
802.11b	0.97	0.008182	0.119289037
802.11g	0.87	0.001356	0.724637681
802.11n-20 MHz	0.86	0.001275	0.777000777

Average Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.15	16.41	30	1000	Pass
Middle	12.73	18.75			Pass
High	12.48	17.70			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.61	18.24	30	1000	Pass
Middle	13.12	20.51			Pass
High	12.75	18.84			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	11.74	14.93	30	1000	Pass
Middle	12.29	16.94			Pass
High	11.91	15.52			Pass

E.I.R.P Test Data (For ISED)

802.11b Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	13.65	23.17	36	4	Pass
Middle	14.23	26.49			Pass
High	13.98	25.00			Pass

802.11g Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	14.11	25.76	36	4	Pass
Middle	14.62	28.97			Pass
High	14.25	26.61			Pass

802.11n-20 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	13.24	21.09	36	4	Pass
Middle	13.79	23.93			Pass
High	13.41	21.93			Pass

A.2 Bandwidth

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	7.659668	12.387844	≥ 500
Middle	8.110107	12.561505	≥ 500
High	7.209229	12.503618	≥ 500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	15.86987	18.465991	≥ 500
Middle	16.42065	18.350217	≥ 500
High	16.42065	18.118669	≥ 500


802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.82080	18.871201	≥ 500
Middle	17.72192	19.102750	≥ 500
High	17.67188	18.929088	≥ 500

Test plots


6 dB Bandwidth

802.11b LOW CHANNEL



Date: 8 JAN 2018 08:13:43

802.11b MIDDLE CHANNEL




Date: 8 JAN 2018 08:20:21

802.11b HIGH CHANNEL




Date: 8 JAN 2018 08:22:19

802.11g LOW CHANNEL




Date: 8 JAN 2018 08:27:18

802.11g MIDDLE CHANNEL




Date: 8 JAN 2018 08:29:44

802.11g HIGH CHANNEL




Date: 8 JAN 2018 08:33:01


802.11n-20 MHz LOW CHANNEL



802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



99% Bandwidth


802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL



802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL




Date: 8 JAN 2018 08:39:40

802.11 n-20 MHz MIDDLE CHANNEL



Date: 8 JAN 2018 08:42:29

802.11n-20 MHz HIGH CHANNEL



Date: 8 JAN 2018 08:45:09

A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low	-38.19	3.88	-26.12	Pass
Middle	-39.32	4.63	-25.37	Pass
High	-39.84	4.14	-25.86	Pass

802.11g Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low	-39.39	2.07	-27.93	Pass
Middle	-39.92	2.14	-27.86	Pass
High	-39.37	2.36	-27.64	Pass

802.11n-20MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low	-39.06	1.40	-28.60	Pass
Middle	-39.39	1.07	-28.93	Pass
High	-38.47	1.36	-28.64	Pass

Test Plots


802.11b LOW CHANNEL CARRIER LEVEL



802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11b MIDDLE CHANNEL CARRIER LEVEL




802.11b MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 9 JAN 2018 11:38:44

802.11b MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 9 JAN 2018 11:38:53

802.11b HIGH CHANNEL CARRIER LEVEL




Date: 9 JAN 2018 11:39:25

802.11b HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 9 JAN 2018 11:39:45

802.11b HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 9 JAN 2018 11:39:52

802.11g LOW CHANNEL CARRIER LEVEL




Date: 9 JAN 2018 11:40:34

802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 9 JAN 2018 11:41:02

802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 9 JAN 2018 11:41:10

802.11g MIDDLE CHANNEL CARRIER LEVEL




Date: 9 JAN 2018 11:41:43

802.11g MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 9 JAN 2018 11:42:07

802.11g MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 9 JAN 2018 11:42:15

802.11g HIGH CHANNEL CARRIER LEVEL




Date: 9 JAN 2018 11:42:42

802.11g HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 9 JAN 2018 11:43:06

802.11g HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




Date: 9 JAN 2018 11:43:13


802.11n-20 MHz LOW CHANNEL CARRIER LEVEL




802.11n-20 MHz LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS
30 MHz ~ 3 GHz


Date: 9 JAN 2018 11:45:49


802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


Date: 9 JAN 2018 11:45:55


802.11n-20 MHz HIGH CHANNEL CARRIER LEVEL



Date: 9 JAN 2018 11:46:39

802.11n-20 MHz HIGH CHANNEL, SPURIOUS
30 MHz ~ 3 GHz


Date: 9 JAN 2018 11:46:59

802.11n-20 MHz HIGH CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


Date: 9 JAN 2018 11:47:06

A.4 Band Edge (Authorized-band band-edge)

Test Data

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low Channel	-48.46	3.88	-26.12	Pass
High Channel	-41.76	4.14	-25.86	Pass

802.11g Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low Channel	-40.80	2.07	-27.93	Pass
High Channel	-39.23	2.36	-27.64	Pass

802.11n-20 MHz Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low Channel	-40.75	1.40	-28.60	Pass
High Channel	-39.92	1.36	-28.64	Pass

Test Plots


802.11b LOW CHANNEL, Carrier level




802.11b LOW CHANNEL, Band Edge



802.11b HIGH CHANNEL, Carrier level



802.11b HIGH CHANNEL, Band Edge




802.11g LOW CHANNEL, Carrier level



802.11g LOW CHANNEL, Band Edge




802.11g HIGH CHANNEL, Carrier level




Date: 9 JAN 2018 11:42:42

802.11g HIGH CHANNEL, Band Edge




Date: 8 JAN 2018 09:17:34

802.11n-20 MHz LOW CHANNEL, Carrier level




Date: 9 JAN 2018 11:43:56

802.11n-20 MHz LOW CHANNEL, Band Edge




Date: 8 JAN 2018 09:13:36

802.11n-20 MHz HIGH CHANNEL, Carrier level



Date: 9 JAN 2018 11:46:39

802.11n-20 MHz HIGH CHANNEL, Band Edge



Date: 8 JAN 2018 09:16:15


A.5 Conducted Emissions

Note¹: The EUT is working in the Normal link mode.

Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Test Data and Plots

PHASE L



Frequency (MHz)	Peak Level (dBuV)	Q-peak Level (dBuV)	Average Level (dBuV)	Factor (dB)	QP Limit (dBuV)	AV Limit (dBuV)	Margin (dB)	Line	Verdict
0.162	46.35	40.60	28.68	10.01	65.4	55.4	24.80	L Line	Pass
0.198	45.19	41.00	30.22	10.01	63.7	53.7	22.70	L Line	Pass
0.266	40.15	34.96	26.39	10.01	61.2	51.2	24.81	L Line	Pass
0.600	44.80	41.01	29.57	10.02	56.0	46.0	14.99	L Line	Pass
1.604	39.43	34.53	25.18	10.05	56.0	46.0	20.82	L Line	Pass
2.554	38.58	33.58	25.47	10.08	56.0	46.0	20.53	L Line	Pass

PHASE N



Frequency (MHz)	Peak Level (dBuV)	Q-peak Level (dBuV)	Average Level (dBuV)	Factor (dB)	QP Limit (dBuV)	AV Limit (dBuV)	Margin (dB)	Line	Verdict
0.192	47.95	44.36	28.87	10.01	63.9	53.9	19.54	N Line	Pass
0.270	39.76	32.98	22.70	10.01	61.1	51.1	28.12	N Line	Pass
0.364	39.35	33.53	22.46	10.01	58.6	48.6	25.07	N Line	Pass
0.594	36.55	29.34	20.52	10.02	56.0	46.0	25.48	N Line	Pass
1.096	40.13	34.72	21.71	10.04	56.0	46.0	21.28	N Line	Pass
1.606	38.17	31.76	19.43	10.05	56.0	46.0	24.24	N Line	Pass

A.6 Radiated Emission

Note¹: The symbol of “--” in the table which means not application.

Note²: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note⁴: The EUT is working in the Normal link mode below 1 GHz.

Note⁵: The spurious above 18G is noise only, do not show on the report.


Test Data and Plots

30 MHz to 1 GHz, ANT H



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
164.759	27.69	24.33	--	-31.35	--	43.5	--	19.17	321.00	364	Horizontal	Pass
198.920	30.24	27.53	--	-28.72	--	43.5	--	15.97	305.00	168	Horizontal	Pass
218.573	25.84	18.94	--	-28.35	--	46.0	--	27.06	211.00	199	Horizontal	Pass
297.064	28.39	24.31	--	-26.70	--	46.0	--	21.69	281.00	138	Horizontal	Pass
382.501	31.59	27.24	--	-24.60	--	46.0	--	18.76	2.00	101	Horizontal	Pass
495.014	23.89	17.99	--	-21.99	--	46.0	--	28.01	341.00	220	Horizontal	Pass


30 MHz to 1 GHz, ANT V



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
198.991	31.19	28.00	--	-28.72	--	43.5	--	15.50	5.00	199	Vertical	Pass
298.375	26.22	22.20	--	-26.70	--	46.0	--	23.80	6.00	230	Vertical	Pass
218.749	27.35	22.05	--	-28.34	--	46.0	--	23.95	4.00	174	Vertical	Pass
395.831	28.49	23.81	--	-24.28	--	46.0	--	22.19	4.00	280	Vertical	Pass
165.801	23.66	20.24	--	-31.31	--	43.5	--	23.26	2.00	194	Vertical	Pass


Note: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

1 GHz to 7 GHz, ANT V 802.11b Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2396.651	48.08	--	45.4	0.03	74.0	--	54.0	8.60	6.00	100	Vertical	Pass
1398.400	43.34	--	41.5	-11.80	74.0	--	54.0	12.50	1.00	100	Vertical	Pass
1593.852	40.41	--	37.7	-12.00	74.0	--	54.0	16.30	13.00	100	Vertical	Pass
1195.951	39.76	--	37.9	-12.16	74.0	--	54.0	16.10	9.00	100	Vertical	Pass
2074.731	43.35	--	37.8	-7.71	74.0	--	54.0	16.20	5.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11b Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2418.645	49.38	--	47.3	-0.74	74.0	--	54.0	6.70	9.00	100	Horizontal	Pass
1188.453	38.13	--	35.9	-11.63	74.0	--	54.0	18.10	8.00	100	Horizontal	Pass
1511.372	39.55	--	37.8	-11.77	74.0	--	54.0	16.20	6.00	100	Horizontal	Pass
2922.519	46.10	--	42.2	-2.77	74.0	--	54.0	11.80	6.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11b Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2397.651	51.18	--	48.5	-0.02	74.0	--	54.0	5.50	2.00	100	Horizontal	Pass
1446.888	39.74	--	37.6	-11.64	74.0	--	54.0	16.40	14.00	100	Horizontal	Pass
1154.461	38.27	--	36.7	-11.77	74.0	--	54.0	17.30	15.00	100	Horizontal	Pass
1981.255	41.81	--	39.0	-8.96	74.0	--	54.0	15.00	8.00	100	Horizontal	Pass
2741.565	45.67	--	43.1	-3.45	74.0	--	54.0	10.90	4.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT H 802.11b Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2418.145	65.97	--	63.8	-0.72	74.0	--	54.0	-9.80	15.00	100	Horizontal	N.A
1396.401	41.68	--	38.4	-11.95	74.0	--	54.0	15.60	15.00	100	Horizontal	Pass
1197.451	39.80	--	37.7	-12.17	74.0	--	54.0	16.30	7.00	100	Horizontal	Pass
2864.034	46.72	--	44.1	-3.17	74.0	--	54.0	9.90	15.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11b High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2395.651	48.04	--	44.6	0.08	74.0	--	54.0	9.40	14.00	100	Vertical	Pass
1196.451	41.64	--	36.7	-12.16	74.0	--	54.0	17.30	4.00	100	Vertical	Pass
1394.901	40.65	--	38.4	-12.06	74.0	--	54.0	15.60	5.00	100	Vertical	Pass
1595.851	41.52	--	38.5	-12.23	74.0	--	54.0	15.50	9.00	100	Vertical	Pass
2917.021	47.62	--	44.7	-3.03	74.0	--	54.0	9.30	10.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11b High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2399.650	48.80	--	45.6	-0.07	74.0	--	54.0	8.40	8.00	100	Horizontal	Pass
1334.416	39.81	--	35.0	-11.70	74.0	--	54.0	19.00	2.00	100	Horizontal	Pass
1592.852	39.75	--	37.2	-11.99	74.0	--	54.0	16.80	10.00	100	Horizontal	Pass
1127.968	38.62	--	35.1	-11.74	74.0	--	54.0	18.90	3.00	100	Horizontal	Pass
2221.695	44.18	--	42.1	-6.59	74.0	--	54.0	11.90	3.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11g Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2459.135	69.53	--	66.5	-2.24	74.0	--	54.0	-12.50	7.00	100	Vertical	N.A
1595.351	45.98	--	45.0	-12.17	74.0	--	54.0	9.00	9.00	100	Vertical	Pass
1398.900	41.28	--	38.5	-11.79	74.0	--	54.0	15.50	1.00	100	Vertical	Pass
1195.951	40.85	--	37.5	-12.16	74.0	--	54.0	16.50	7.00	100	Vertical	Pass
1909.773	41.34	--	39.9	-8.95	74.0	--	54.0	14.10	9.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11g Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2393.152	53.30	--	50.9	0.21	74.0	--	54.0	3.10	6.00	100	Horizontal	Pass
1448.388	39.98	--	37.9	-11.74	74.0	--	54.0	16.10	11.00	100	Horizontal	Pass
1838.290	41.13	--	37.7	-10.03	74.0	--	54.0	16.30	2.00	100	Horizontal	Pass
2908.023	46.43	--	41.6	-3.22	74.0	--	54.0	12.40	14.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11g Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2425.644	64.73	--	62.3	-0.99	74.0	--	54.0	-8.30	9.00	100	Vertical	N.A
1594.851	44.24	--	43.6	-12.12	74.0	--	54.0	10.40	5.00	100	Vertical	Pass
1394.401	42.53	--	40.2	-12.10	74.0	--	54.0	13.80	15.00	100	Vertical	Pass
1196.951	40.22	--	37.3	-12.17	74.0	--	54.0	16.70	11.00	100	Vertical	Pass
2853.537	45.33	--	43.4	-2.89	74.0	--	54.0	10.60	7.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11g Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2473.632	62.79	--	59.9	-2.89	74.0	--	54.0	-5.90	1.00	100	Horizontal	N.A
2426.143	64.96	--	61.9	-1.01	74.0	--	54.0	-7.90	0.00	100	Horizontal	N.A
1485.879	39.50	--	37.9	-11.52	74.0	--	54.0	16.10	11.00	100	Horizontal	Pass
2003.749	42.12	--	39.0	-8.33	74.0	--	54.0	15.00	5.00	100	Horizontal	Pass
1084.979	38.04	--	34.8	-11.32	74.0	--	54.0	19.20	8.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11g High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2397.651	48.41	--	45.8	-0.02	74.0	--	54.0	8.20	1.00	100	Vertical	Pass
1594.851	45.90	--	44.8	-12.12	74.0	--	54.0	9.20	10.00	100	Vertical	Pass
1395.401	41.76	--	38.1	-12.02	74.0	--	54.0	15.90	9.00	100	Vertical	Pass
2853.537	45.57	--	43.0	-2.89	74.0	--	54.0	11.00	7.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11g High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2399.150	48.62	--	45.7	-0.06	74.0	--	54.0	8.30	14.00	100	Horizontal	Pass
1113.972	39.20	--	34.6	-11.35	74.0	--	54.0	19.40	6.00	100	Horizontal	Pass
1374.406	39.23	--	37.1	-12.12	74.0	--	54.0	16.90	2.00	100	Horizontal	Pass
1452.887	40.02	--	38.2	-11.74	74.0	--	54.0	15.80	8.00	100	Horizontal	Pass
1200.950	38.60	--	34.9	-12.31	74.0	--	54.0	19.10	4.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11n20 Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2393.152	52.30	--	50.1	0.21	74.0	--	54.0	3.90	12.00	100	Vertical	Pass
1597.851	41.90	--	39.2	-12.46	74.0	--	54.0	14.80	8.00	100	Vertical	Pass
1395.901	41.99	--	37.4	-11.99	74.0	--	54.0	16.60	7.00	100	Vertical	Pass
2142.714	43.36	--	40.9	-7.02	74.0	--	54.0	13.10	7.00	100	Vertical	Pass
1199.450	39.57	--	37.7	-12.21	74.0	--	54.0	16.30	14.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11n20 Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2393.152	51.34	--	46.0	0.21	74.0	--	54.0	8.00	5.00	100	Horizontal	Pass
1598.850	41.21	--	39.9	-12.51	74.0	--	54.0	14.10	15.00	100	Horizontal	Pass
2064.734	42.20	--	39.0	-8.35	74.0	--	54.0	15.00	7.00	100	Horizontal	Pass
2754.061	45.91	--	43.8	-3.97	74.0	--	54.0	10.20	9.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11n20 Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2395.651	50.62	--	48.3	0.08	74.0	--	54.0	5.70	3.00	100	Vertical	Pass
1595.851	42.11	--	38.8	-12.23	74.0	--	54.0	15.20	8.00	100	Vertical	Pass
1396.901	41.94	--	38.4	-11.91	74.0	--	54.0	15.60	4.00	100	Vertical	Pass
1194.951	39.41	--	35.8	-12.15	74.0	--	54.0	18.20	7.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11n20 Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2418.145	67.95	--	65.1	-0.72	74.0	--	54.0	-11.10	12.00	100	Horizontal	N.A
1596.351	40.29	--	39.9	-12.29	74.0	--	54.0	14.10	9.00	100	Horizontal	Pass
1086.478	38.23	--	35.7	-11.28	74.0	--	54.0	18.30	15.00	100	Horizontal	Pass
2851.037	45.50	--	42.4	-2.83	74.0	--	54.0	11.60	10.00	100	Horizontal	Pass

1 GHz to 7 GHz, ANT V 802.11n20 High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
1510.372	40.32	--	38.4	-11.76	74.0	--	54.0	15.60	13.00	100	Vertical	Pass
1909.773	41.64	--	40.0	-8.95	74.0	--	54.0	14.00	10.00	100	Vertical	Pass
2398.150	48.29	--	45.7	-0.03	74.0	--	54.0	8.30	12.00	100	Vertical	Pass
4067.733	43.68	--	39.9	-2.75	74.0	--	54.0	14.10	2.00	100	Vertical	Pass

1 GHz to 7 GHz, ANT H 802.11n20 High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
1397.901	42.25	--	39.6	-11.84	74.0	--	54.0	14.40	2.00	100	Horizontal	Pass
1592.852	41.15	--	37.8	-11.99	74.0	--	54.0	16.20	3.00	100	Horizontal	Pass
2426.143	66.72	--	63.1	-1.01	74.0	--	54.0	-9.10	3.00	100	Horizontal	N.A
4409.648	44.69	--	39.9	-2.06	74.0	--	54.0	14.10	13.00	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11b Low Channel




Frequency (MHz)	Peak Level (dBuV/ m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14084.000	39.16	--	30.4	14.82	74.0	--	54.0	23.60	66.80	100	Vertical	Pass
14595.500	36.25	--	26.3	10.36	74.0	--	54.0	27.70	168.70	100	Vertical	Pass
16009.000	37.03	--	27.1	10.46	74.0	--	54.0	26.90	109.30	100	Vertical	Pass
16597.500	37.68	--	28.1	12.08	74.0	--	54.0	25.90	3.00	100	Vertical	Pass
17791.001	34.75	--	25.2	6.82	74.0	--	54.0	28.80	0.00	100	Vertical	Pass
9252.250	20.41	--	10.9	-4.35	74.0	--	54.0	43.10	249.50	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11b Low Channel




Frequency (MHz)	Peak Level (dBuV/ m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14086.750	39.40	--	30.2	14.85	74.0	--	54.0	23.80	113.60	100	Horizontal	Pass
16564.500	37.64	--	28.7	11.31	74.0	--	54.0	25.30	187.50	100	Horizontal	Pass
14557.000	35.72	--	26.3	9.70	74.0	--	54.0	27.70	120.50	100	Horizontal	Pass
17818.499	33.86	--	24.0	6.03	74.0	--	54.0	30.00	187.50	100	Horizontal	Pass
10566.750	23.71	--	13.1	-2.03	74.0	--	54.0	40.90	360.00	100	Horizontal	Pass
9274.250	20.68	--	10.2	-4.11	74.0	--	54.0	43.80	165.00	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11b Middle Channel




Frequency (MHz)	Peak Level (dBuV/ m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14086.750	39.40	--	30.2	14.85	74.0	--	54.0	23.80	113.60	100	Vertical	Pass
16564.500	37.64	--	28.7	11.31	74.0	--	54.0	25.30	187.50	100	Vertical	Pass
14557.000	35.72	--	26.3	9.70	74.0	--	54.0	27.70	120.50	100	Vertical	Pass
17818.499	33.86	--	24.0	6.03	74.0	--	54.0	30.00	187.50	100	Vertical	Pass
10566.750	23.71	--	13.1	-2.03	74.0	--	54.0	40.90	360.00	100	Vertical	Pass
9274.250	20.68	--	10.2	-4.11	74.0	--	54.0	43.80	165.00	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11b Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14070.250	39.67	--	29.9	14.57	74.0	--	54.0	24.10	30.10	100	Horizontal	Pass
16603.000	38.73	--	28.1	12.04	74.0	--	54.0	25.90	228.20	100	Horizontal	Pass
16009.000	36.96	--	27.6	10.46	74.0	--	54.0	26.40	30.10	100	Horizontal	Pass
10602.500	23.05	--	12.7	-1.67	74.0	--	54.0	41.30	207.50	100	Horizontal	Pass
9244.000	18.98	--	9.4	-4.53	74.0	--	54.0	44.60	346.60	100	Horizontal	Pass
17807.499	34.11	--	25.3	6.54	74.0	--	54.0	28.70	36.80	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11b High Channel




Frequency (MHz)	Peak Level (dBuV/ m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14103.250	39.41	--	30.1	14.61	74.0	--	54.0	23.90	360.00	100	Vertical	Pass
16014.500	36.78	--	26.8	10.26	74.0	--	54.0	27.20	106.30	100	Vertical	Pass
16603.000	37.91	--	28.9	12.04	74.0	--	54.0	25.10	261.20	100	Vertical	Pass
14587.250	36.72	--	26.8	10.19	74.0	--	54.0	27.20	40.00	100	Vertical	Pass
10198.250	21.43	--	11.5	-2.64	74.0	--	54.0	42.50	18.80	100	Vertical	Pass
9293.500	19.22	--	10.3	-4.02	74.0	--	54.0	43.70	245.60	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11b High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14097.750	39.29	--	30.1	14.79	74.0	--	54.0	23.90	100.80	100	Horizontal	Pass
16055.750	36.73	--	26.3	9.08	74.0	--	54.0	27.70	274.10	100	Horizontal	Pass
16548.000	37.41	--	27.8	10.92	74.0	--	54.0	26.20	274.10	100	Horizontal	Pass
14584.500	35.83	--	26.3	10.15	74.0	--	54.0	27.70	181.10	100	Horizontal	Pass
10553.000	22.93	--	13.0	-2.24	74.0	--	54.0	41.00	294.60	100	Horizontal	Pass
9299.000	20.31	--	10.6	-4.01	74.0	--	54.0	43.40	360.00	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11g Low Channel




Frequency (MHz)	Peak Level (dBuV/ m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14084.000	39.16	--	30.4	14.82	74.0	--	54.0	23.60	66.80	100	Vertical	Pass
14595.500	36.25	--	26.3	10.36	74.0	--	54.0	27.70	168.70	100	Vertical	Pass
16009.000	37.03	--	27.1	10.46	74.0	--	54.0	26.90	109.30	100	Vertical	Pass
16597.500	37.68	--	28.1	12.08	74.0	--	54.0	25.90	3.00	100	Vertical	Pass
17791.001	34.75	--	25.2	6.82	74.0	--	54.0	28.80	0.00	100	Vertical	Pass
9252.250	20.41	--	10.9	-4.35	74.0	--	54.0	43.10	249.50	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11g Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14089.500	40.16	--	30.3	14.83	74.0	--	54.0	23.70	117.10	100	Horizontal	Pass
14573.500	37.25	--	26.9	10.06	74.0	--	54.0	27.10	283.60	100	Horizontal	Pass
16000.750	37.20	--	27.7	10.73	74.0	--	54.0	26.30	28.60	100	Horizontal	Pass
16553.500	38.36	--	27.9	10.99	74.0	--	54.0	26.10	325.30	100	Horizontal	Pass
9299.000	19.95	--	10.4	-4.01	74.0	--	54.0	43.60	89.10	100	Horizontal	Pass
8856.250	18.39	--	8.7	-5.75	74.0	--	54.0	45.30	256.20	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11g Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14084.000	39.35	--	29.8	14.82	74.0	--	54.0	24.20	263.80	100	Vertical	Pass
16020.000	37.01	--	27.4	10.08	74.0	--	54.0	26.60	359.80	100	Vertical	Pass
14625.750	36.21	--	25.1	9.84	74.0	--	54.0	28.90	149.90	100	Vertical	Pass
16605.750	37.56	--	27.7	11.93	74.0	--	54.0	26.30	0.00	100	Vertical	Pass
9301.750	19.66	--	10.6	-4.06	74.0	--	54.0	43.40	235.10	100	Vertical	Pass
8894.750	19.05	--	9.0	-5.03	74.0	--	54.0	45.00	0.00	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11g Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14045.500	39.52	--	29.2	14.33	74.0	--	54.0	24.80	190.70	100	Horizontal	Pass
15998.000	37.58	--	27.3	10.66	74.0	--	54.0	26.70	65.40	100	Horizontal	Pass
16572.750	37.61	--	27.9	11.42	74.0	--	54.0	26.10	344.10	100	Horizontal	Pass
14515.750	36.32	--	25.8	8.90	74.0	--	54.0	28.20	0.00	100	Horizontal	Pass
10514.500	23.44	--	13.4	-2.58	74.0	--	54.0	40.60	112.40	100	Horizontal	Pass
9321.000	19.63	--	9.7	-4.46	74.0	--	54.0	44.30	0.70	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11g High Channel




Frequency (MHz)	Peak Level (dBuV/ m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
9260.500	20.70	--	9.8	-4.28	74.0	--	54.0	44.20	162.70	100	Vertical	Pass
10566.750	23.67	--	13.7	-2.03	74.0	--	54.0	40.30	19.00	100	Vertical	Pass
11625.500	24.17	--	14.8	-0.81	74.0	--	54.0	39.20	56.00	100	Vertical	Pass
14081.250	39.79	--	30.4	14.77	74.0	--	54.0	23.60	204.50	100	Vertical	Pass
15998.000	36.61	--	27.9	10.66	74.0	--	54.0	26.10	153.30	100	Vertical	Pass
16589.250	37.51	--	28.1	11.83	74.0	--	54.0	25.90	325.20	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11n20 High Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14081.250	39.79	--	30.4	14.77	74.0	--	54.0	23.60	204.50	100	Horizontal	Pass
16047.500	36.69	--	26.6	9.31	74.0	--	54.0	27.40	134.80	100	Horizontal	Pass
14614.750	36.29	--	26.1	10.05	74.0	--	54.0	27.90	153.30	100	Horizontal	Pass
16589.250	37.51	--	28.1	11.83	74.0	--	54.0	25.90	325.20	100	Horizontal	Pass
9260.500	20.70	--	9.8	-4.28	74.0	--	54.0	44.20	162.70	100	Horizontal	Pass
10566.750	23.67	--	13.7	-2.03	74.0	--	54.0	40.30	19.00	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11n20 Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
8889.250	17.19	--	8.2	-5.22	74.0	--	54.0	45.80	0.00	100	Vertical	Pass
10533.750	21.69	--	12.2	-2.41	74.0	--	54.0	41.80	0.00	100	Vertical	Pass
12530.250	24.35	--	15.3	-0.26	74.0	--	54.0	38.70	0.00	100	Vertical	Pass
13847.500	37.59	--	27.5	11.40	74.0	--	54.0	26.50	0.00	100	Vertical	Pass
14559.750	35.00	--	26.8	9.73	74.0	--	54.0	27.20	0.00	100	Vertical	Pass
16033.750	35.50	--	27.3	9.66	74.0	--	54.0	26.70	0.00	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11n20 Low Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14086.750	39.48	--	30.0	14.85	74.0	--	54.0	24.00	205.80	100	Horizontal	Pass
16020.000	36.51	--	26.6	10.08	74.0	--	54.0	27.40	37.80	100	Horizontal	Pass
16559.000	38.05	--	27.8	11.17	74.0	--	54.0	26.20	350.20	100	Horizontal	Pass
9301.750	20.11	--	10.8	-4.06	74.0	--	54.0	43.20	159.40	100	Horizontal	Pass
11331.250	24.22	--	12.6	-1.71	74.0	--	54.0	41.40	61.00	100	Horizontal	Pass
8897.500	19.63	--	9.0	-4.93	74.0	--	54.0	45.00	103.50	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11n20 Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
8903.000	19.40	--	8.9	-4.96	74.0	--	54.0	45.10	34.00	100	Vertical	Pass
10261.500	21.34	--	11.5	-2.13	74.0	--	54.0	42.50	0.00	100	Vertical	Pass
11655.750	23.92	--	14.4	-0.87	74.0	--	54.0	39.60	205.50	100	Vertical	Pass
12607.250	25.62	--	15.7	0.29	74.0	--	54.0	38.30	167.90	100	Vertical	Pass
14031.750	38.95	--	29.4	14.28	74.0	--	54.0	24.60	0.00	100	Vertical	Pass
16592.000	37.49	--	28.4	11.90	74.0	--	54.0	25.60	359.30	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11n20 Middle Channel




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14095.000	39.86	--	30.0	14.78	74.0	--	54.0	24.00	279.50	100	Horizontal	Pass
14598.250	36.03	--	26.6	10.36	74.0	--	54.0	27.40	112.90	100	Horizontal	Pass
16011.750	37.49	--	27.4	10.36	74.0	--	54.0	26.60	131.50	100	Horizontal	Pass
16589.250	38.35	--	28.6	11.83	74.0	--	54.0	25.40	331.10	100	Horizontal	Pass
9263.250	20.16	--	10.0	-4.22	74.0	--	54.0	44.00	196.20	100	Horizontal	Pass
10564.000	23.51	--	13.9	-2.06	74.0	--	54.0	40.10	321.50	100	Horizontal	Pass

7 GHz to 18 GHz, ANT V 802.11n20 High Channel



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
8870.000	19.20	--	9.1	-5.51	74.0	--	54.0	44.90	308.70	100	Vertical	Pass
9310.000	20.09	--	10.1	-4.26	74.0	--	54.0	43.90	25.70	100	Vertical	Pass
11188.250	23.86	--	14.1	-2.10	74.0	--	54.0	39.90	156.20	100	Vertical	Pass
12629.250	25.52	--	15.2	0.16	74.0	--	54.0	38.80	151.50	100	Vertical	Pass
13998.750	39.56	--	29.3	14.15	74.0	--	54.0	24.70	114.40	100	Vertical	Pass
16556.250	37.94	--	28.0	11.08	74.0	--	54.0	26.00	35.10	100	Vertical	Pass

7 GHz to 18 GHz, ANT H 802.11n20 High Channel



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
14095.000	39.44	--	29.9	14.78	74.0	--	54.0	24.10	224.10	100	Horizontal	Pass
15998.000	36.67	--	27.1	10.66	74.0	--	54.0	26.90	256.70	100	Horizontal	Pass
16578.250	37.85	--	28.0	11.58	74.0	--	54.0	26.00	331.40	100	Horizontal	Pass
14562.500	36.61	--	26.1	9.77	74.0	--	54.0	27.90	354.30	100	Horizontal	Pass
10591.500	23.46	--	13.0	-1.73	74.0	--	54.0	41.00	158.90	100	Horizontal	Pass
9290.750	20.18	--	10.0	-4.01	74.0	--	54.0	44.00	0.00	100	Horizontal	Pass

A.7 Band Edge (Restricted-band band-edge)

Test Data

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
802.11b	Low	2390	49.59	74	24.41	PEAK	Pass
		2390	N/A	54	N/A	AVERAGE	Pass
	HIGH	2483.5	48.24	74	25.76	PEAK	Pass
		2483.5	N/A	54	N/A	AVERAGE	Pass
802.11g	Low	2390	52.31	74	21.69	PEAK	Pass
		2390	N/A	54	N/A	AVERAGE	Pass
	HIGH	2483.5	45.51	74	28.49	PEAK	Pass
		2483.5	N/A	54	N/A	AVERAGE	Pass
802.11n20	Low	2390	55.34	74	18.66	PEAK	Pass
		2390	41.04	54	12.96	AVERAGE	Pass
	HIGH	2483.5	54.18	74	19.82	PEAK	Pass
		2483.5	40.17	54	13.83	AVERAGE	Pass


802.11b Mode:

LOW CHANNEL, VERTICAL




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2376.931	47.70	--	40.5	35.94	74.0	--	54.0	13.50	124.40	100	Vertical	Pass
2390.000	45.48	--	39.6	36.09	74.0	--	54.0	14.40	171.62	100	Vertical	Pass
2400.000	45.32	--	39.1	35.93	74.0	--	54.0	14.90	163.20	100	Vertical	Pass
2411.222	84.42	--	77.7	35.93	74.0	--	54.0	-23.70	305.40	100	Vertical	N.A

LOW CHANNEL, HORIZONTAL




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2387.778	47.76	--	40.8	36.09	74.0	--	54.0	13.20	119.80	100	Horizontal	Pass
2390.000	45.86	--	39.9	36.09	74.0	--	54.0	14.10	73.16	100	Horizontal	Pass
2400.000	45.60	--	39.4	35.93	74.0	--	54.0	14.60	95.80	100	Horizontal	Pass
2412.372	84.53	--	77.7	35.91	74.0	--	54.0	-23.70	305.50	100	Horizontal	N.A

HIGH CHANNEL, VERTICAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2461.770	93.14	--	85.5	36.15	74.0	--	54.0	-31.50	45.20	100	Vertical	N.A
2483.500	50.22	--	42.9	35.93	74.0	--	54.0	11.10	263.72	100	Vertical	Pass
2487.503	52.52	--	43.5	35.88	74.0	--	54.0	10.50	357.70	100	Vertical	Pass


HIGH CHANNEL, HORIZONTAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2467.348	88.48	--	81.2	36.11	74.0	--	54.0	-27.20	320.30	100	Horizontal	N.A
2483.500	52.77	--	43.3	35.93	74.0	--	54.0	10.70	322.91	100	Horizontal	Pass
2495.421	52.28	--	43.1	35.82	74.0	--	54.0	10.90	279.00	100	Horizontal	Pass

802.11g Mode:


LOW CHANNEL, VERTICAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2380.980	47.49	--	40.4	35.92	74.0	--	54.0	13.60	263.10	100	Vertical	Pass
2390.000	46.37	--	39.8	36.09	74.0	--	54.0	14.20	190.47	100	Vertical	Pass
2400.000	47.54	--	41.8	35.93	74.0	--	54.0	12.20	203.30	100	Vertical	Pass
2405.774	81.31	--	74.5	35.98	74.0	--	54.0	-20.50	305.10	100	Vertical	N.A


LOW CHANNEL, HORIZONTAL

R Emission Test case_FCC_Part 15C_FCC 15.247(2.4G)_bandedge 2400




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2388.828	47.33	--	39.8	36.09	74.0	--	54.0	14.20	40.50	100	Horizontal	Pass
2390.000	45.57	--	40.0	36.09	74.0	--	54.0	14.00	151.59	100	Horizontal	Pass
2400.000	47.58	--	41.7	35.93	74.0	--	54.0	12.30	220.90	100	Horizontal	Pass
2415.721	81.52	--	72.8	35.90	74.0	--	54.0	-18.80	301.00	100	Horizontal	N.A

HIGH CHANNEL, VERTICAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2461.185	89.43	--	81.4	36.14	74.0	--	54.0	-27.40	46.10	100	Vertical	N.A
2483.500	51.14	--	43.3	35.93	74.0	--	54.0	10.70	133.87	100	Vertical	Pass
2491.777	52.35	--	43.1	35.85	74.0	--	54.0	10.90	65.40	100	Vertical	Pass


HIGH CHANNEL, HORIZONTAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2467.348	88.48	--	81.2	36.11	74.0	--	54.0	-27.20	320.30	100	Horizontal	N.A
2483.500	52.77	--	43.3	35.93	74.0	--	54.0	10.70	322.91	100	Horizontal	Pass
2495.421	52.28	--	43.1	35.82	74.0	--	54.0	10.90	279.00	100	Horizontal	Pass


802.11n-20 MHz Mode:

LOW CHANNEL, VERTICAL




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2381.880	47.29	--	40.2	35.95	74.0	--	54.0	13.80	29.20	100	Vertical	Pass
2390.000	45.38	--	39.6	36.09	74.0	--	54.0	14.40	280.03	100	Vertical	Pass
2400.000	48.48	--	43.3	35.93	74.0	--	54.0	10.70	240.45	100	Vertical	Pass
2407.023	84.77	--	76.9	35.98	74.0	--	54.0	-22.90	189.50	100	Vertical	N.A

LOW CHANNEL, HORIZONTAL




Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2383.479	47.81	--	40.3	35.99	74.0	--	54.0	13.70	309.30	100	Horizontal	Pass
2390.000	45.82	--	40.2	36.09	74.0	--	54.0	13.80	245.50	100	Horizontal	Pass
2400.000	47.89	--	42.4	35.93	74.0	--	54.0	11.60	237.65	100	Horizontal	Pass
2410.722	84.54	--	76.8	35.94	74.0	--	54.0	-22.80	188.20	100	Horizontal	N.A

HIGH CHANNEL, VERTICAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2455.651	88.08	--	80.6	36.05	74.0	--	54.0	-26.60	43.30	100	Vertical	N.A
2483.500	50.33	--	43.2	35.93	74.0	--	54.0	10.80	314.50	100	Vertical	Pass
2489.753	52.65	--	43.0	35.87	74.0	--	54.0	11.00	0.80	100	Vertical	Pass

HIGH CHANNEL, HORIZONTAL



Frequency (MHz)	Peak Level (dBuV/m)	Q-peak Level (dBuV/m)	Average Level (dBuV/m)	Factor (dB)	PK Limit (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Table (o)	Height (cm)	ANT	Verdict
2466.223	87.65	--	79.0	36.12	74.0	--	54.0	-25.00	36.80	100	Horizontal	N.A
2483.500	51.65	--	43.0	35.93	74.0	--	54.0	11.00	11.12	100	Horizontal	Pass
2491.777	52.39	--	43.2	35.85	74.0	--	54.0	10.80	159.10	100	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-19.92	8
Middle	-19.96	8
High	-20.15	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-22.75	8
Middle	-23.06	8
High	-24.92	8

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-23.83	8
Middle	-23.85	8
High	-25.40	8

Test plots

802.11b LOW CHANNEL



Date: 8 JAN 2018 09:20:16

802.11b MIDDLE CHANNEL




Date: 8 JAN 2018 09:21:14

802.11b HIGH CHANNEL




Date: 8 JAN 2018 09:22:10

802.11g LOW CHANNEL




Date: 8 JAN 2018 09:19:15

802.11g MIDDLE CHANNEL




Date: 8 JAN 2018 09:18:24

802.11g HIGH CHANNEL




Date: 8 JAN 2018 09:17:47

802.11n-20 MHz LOW CHANNEL




Date: 8 JAN 2018 09:12:58

802.11 n-20 MHz MIDDLE CHANNEL



Date: 8 JAN 2018 09:15:28

802.11n-20 MHz HIGH CHANNEL



Date: 8 JAN 2018 09:16:29

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-EC17C0360-AR.pdf”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-EC17C0360-AW.pdf”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-EC17C0360-AI.pdf”.

--END OF REPORT--