


TEST REPORT

Application No.: SZCR2505002062TL
Applicant: KE2 Therm Solutions, Inc.
Address of Applicant: 12 Chamber Drive, Washington, MO, 63090, United States
Manufacturer: KE2 Therm Solutions, Inc.
Address of Manufacturer: 12 Chamber Drive, Washington, MO, 63090, United States
Equipment Under Test (EUT):
EUT Name: KE2 Edge Manager Plus 2
Model No.: KE2-EM Plus 2
Trade Mark: 
FCC ID: 2AOPR-22243
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-05-21
Date of Test: 2025-05-31 to 2025-06-13
Date of Issue: 2025-06-20

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kenx. Xu

Kenx Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (EMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250500206203

Page: 2 of 76

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-06-20		Original

Authorized for issue by:				
		Donjon . Huang		
		Donjon Huang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Remark:

Model No.: KE2-EM Plus 2

This test report (reference number: SZCR250500206203) is based on the original FCC ID: 2AOPR-22243 change application C2PC.

According to the applicant's statement, the samples in this report have been assessed to identify items that may affect the original test report results for comprehensive retesting.

Therefore in this report the section 2 test items were fully retested on model and shown the data in this report, other tests please refer to original report SZCR250400168303.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	5
4.4 Test Location	6
4.5 Test Facility	6
4.6 Deviation from Standards	6
4.7 Abnormalities from Standard Conditions	6
5 Equipment List	7
6 Radio Spectrum Matter Test Results	9
6.1 Radiated Emissions which fall in the restricted bands	9
6.1.1 E.U.T. Operation	9
6.1.2 Test Mode Description	9
6.1.3 Test Setup Diagram	10
6.1.4 Measurement Procedure and Data	11
6.2 Radiated Spurious Emissions Below 1GHz	52
6.2.1 E.U.T. Operation	52
6.2.2 Test Mode Description	52
6.2.3 Test Setup Diagram	53
6.2.4 Measurement Procedure and Data	53
6.3 Radiated Spurious Emissions Above 1GHz	56
6.3.1 E.U.T. Operation	56
6.3.2 Test Mode Description	56
6.3.3 Test Setup Diagram	56
6.3.4 Measurement Procedure and Data	57
7 Test Setup Photo	76
8 EUT Constructional Details (EUT Photos)	76



4 General Information

4.1 Details of E.U.T.

Power supply:	Adapter Model: ICP30A-120-2500 Input: AC 100-240V 50/60Hz 0.8A Output: DC 12V 2.5A.
Cable(s):	Network cable: 0.8m
Operation Frequency:	802.11b/g/n(HT20)/ax(HEW20): 2412MHz to 2462MHz, 802.11n(HT40)/ax(HEW40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK); 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11ax: OFDM/OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Number of Channels:	802.11b/g/n(HT20)/ax(HEW20): 11, 802.11n(HT40)/ax(HEW40): 7
Channel Spacing:	5MHz
Antenna Type:	Dipole Antenna
Antenna Gain:	ANT1 & ANT2: 1.63dBi; Directional Gain: 4.64dBi.
Antenna Number:	2

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250500206203

Page: 6 of 76

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2025-01-07	2026-01-06
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21	2025-12-20
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2024-07-24	2025-07-23

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2024-08-14	2025-08-13
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2023-09-16	2025-09-15
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2024-07-06	2025-07-05



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250500206203

Page: 8 of 76

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-01-07	2026-01-06
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-01-08	2026-01-07
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21	2025-12-20
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25	2025-12-24
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2024-07-24	2025-07-23

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2024-07-24	2025-07-23
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2024-07-24	2025-07-23
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing and Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Matter Test Results

6.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH


Atmospheric Pressure: 1020 mbar

6.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n/ax(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n/ax(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



6.1.3 Test Setup Diagram



6.1.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.307	6.82	27.45	31.54	46.65	49.38	74.00	-24.62	peak
2	2390.000	6.82	27.46	31.54	43.94	46.68	74.00	-27.32	peak
3 p	2412.000	6.91	27.52	31.54	100.23	103.12	74.00	29.12	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2383.803	6.82	27.44	31.54	36.11	38.83	54.00	-15.17	Average
2	2390.000	6.82	27.46	31.54	32.54	35.28	54.00	-18.72	Average
3 q	2412.000	6.91	27.52	31.54	96.64	99.53	54.00	45.53	Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.098	6.82	27.44	31.54	49.24	51.96	74.00	-22.04	Peak
2	2390.000	6.82	27.46	31.54	46.28	49.02	74.00	-24.98	Peak
3 p	2412.000	6.91	27.52	31.54	104.65	107.54	74.00	33.54	Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.615	6.82	27.44	31.54	37.66	40.38	54.00	-13.62	Average
2	2390.000	6.82	27.46	31.54	34.14	36.88	54.00	-17.12	Average
3 q	2412.000	6.91	27.52	31.54	100.81	103.70	54.00	49.70	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	7.25	27.67	31.55	99.89	103.26	74.00	29.26	peak
2	2483.500	7.40	27.80	31.55	45.47	49.12	74.00	-24.88	peak
3	2488.310	7.43	27.83	31.55	47.38	51.09	74.00	-22.91	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2462.000	7.25	27.67	31.55	95.98	99.35	54.00	45.35	Average
2 2483.500	7.40	27.80	31.55	33.49	37.14	54.00	-16.86	Average
3 2488.813	7.43	27.83	31.55	37.31	41.02	54.00	-12.98	Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	7.25	27.67	31.55	103.87	107.24	74.00	33.24	Peak
2	2483.500	7.40	27.80	31.55	46.30	49.95	74.00	-24.05	Peak
3	2488.461	7.43	27.83	31.55	49.82	53.53	74.00	-20.47	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2462.000	7.25	27.67	31.55	100.09	103.46	54.00	49.46	Average
2 2483.500	7.40	27.80	31.55	36.14	39.79	54.00	-14.21	Average
3 2488.813	7.43	27.83	31.55	42.02	45.73	54.00	-8.27	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.000	6.82	27.46	31.54	48.61	51.35	74.00	-22.65	peak
2	2390.000	6.82	27.46	31.54	45.92	48.66	74.00	-25.34	peak
3 p	2412.000	6.91	27.52	31.54	98.88	101.77	74.00	27.77	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.484	6.82	27.46	31.54	33.92	36.66	54.00	-17.34	Average
2	2390.000	6.82	27.46	31.54	33.56	36.30	54.00	-17.70	Average
3 q	2412.000	6.91	27.52	31.54	88.03	90.92	54.00	36.92	Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.395	6.82	27.45	31.54	52.22	54.95	74.00	-19.05	Peak
2	2390.000	6.82	27.46	31.54	51.47	54.21	74.00	-19.79	Peak
3 p	2412.000	6.91	27.52	31.54	102.60	105.49	74.00	31.49	Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.000	6.82	27.46	31.54	36.02	38.76	54.00	-15.24	Average
2	2390.000	6.82	27.46	31.54	35.71	38.45	54.00	-15.55	Average
3 q	2412.000	6.91	27.52	31.54	92.49	95.38	54.00	41.38	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2462.000	7.25	27.67	31.55	98.37	101.74	74.00	27.74	peak
2 2483.500	7.40	27.80	31.55	49.20	52.85	74.00	-21.15	peak
3 2483.890	7.40	27.80	31.55	47.95	51.60	74.00	-22.40	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	7.25	27.67	31.55	88.00	91.37	54.00	37.37 Average
2	2483.500	7.40	27.80	31.55	33.93	37.58	54.00	-16.42 Average
3	2483.890	7.40	27.80	31.55	33.44	37.09	54.00	-16.91 Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2462.000	7.25	27.67	31.55	102.00	105.37	74.00	31.37	Peak
2 2483.500	7.40	27.80	31.55	52.59	56.24	74.00	-17.76	Peak
3 2484.442	7.40	27.81	31.55	49.78	53.44	74.00	-20.56	Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2462.000	7.25	27.67	31.55	91.88	95.25	54.00	41.25	Average
2 2483.500	7.40	27.80	31.55	36.62	40.27	54.00	-13.73	Average
3 2483.790	7.40	27.80	31.55	36.13	39.78	54.00	-14.22	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.925	6.82	27.46	31.54	49.79	52.53	74.00	-21.47 peak
2	2390.000	6.82	27.46	31.54	49.96	52.70	74.00	-21.30 peak
3 p	2422.000	6.98	27.54	31.54	96.70	99.68	74.00	25.68 peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 2389.677	6.82	27.46	31.54	37.28	40.02	54.00	-13.98	Average
2 2390.000	6.82	27.46	31.54	37.32	40.06	54.00	-13.94	Average
3 q 2422.000	6.98	27.54	31.54	85.85	88.83	54.00	34.83	Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.526	6.82	27.46	31.54	55.58	58.32	74.00	-15.68 Peak
2	2390.000	6.82	27.46	31.54	54.48	57.22	74.00	-16.78 Peak
3 p	2422.000	6.98	27.54	31.54	100.00	102.98	74.00	28.98 Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.827	6.82	27.46	31.54	40.75	43.49	54.00	-10.51 Average
2	2390.000	6.82	27.46	31.54	40.55	43.29	54.00	-10.71 Average
3 q	2422.000	6.98	27.54	31.54	89.56	92.54	54.00	38.54 Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.000	7.18	27.61	31.55	95.40	98.64	74.00	24.64	peak
2	2483.500	7.40	27.80	31.55	46.70	50.35	74.00	-23.65	peak
3	2484.923	7.41	27.81	31.55	49.05	52.72	74.00	-21.28	peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11n; Bandwidth: 40MHz; Channel: High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 2452.000		7.18	27.61	31.55	84.75	87.99	54.00	33.99 Average
2 2483.500		7.40	27.80	31.55	35.52	39.17	54.00	-14.83 Average
3 2484.358		7.40	27.81	31.55	36.15	39.81	54.00	-14.19 Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2452.000	7.18	27.61	31.55	99.39	102.63	74.00	28.63 Peak
2	2483.500	7.40	27.80	31.55	51.65	55.30	74.00	-18.70 Peak
3	2484.358	7.40	27.81	31.55	53.27	56.93	74.00	-17.07 Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2452.000	7.18	27.61	31.55	88.78	92.02	54.00	38.02	Average
2 2483.500	7.40	27.80	31.55	38.74	42.39	54.00	-11.61	Average
3 2484.006	7.40	27.80	31.55	39.66	43.31	54.00	-10.69	Average



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11ax(Full RU0); Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	6.82	27.46	31.54	51.49	54.23	74.00	-19.77	peak
2	2390.000	6.82	27.46	31.54	50.29	53.03	74.00	-20.97	peak
3 p	2412.000	6.91	27.52	31.54	100.65	103.54	74.00	29.54	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.363	6.82	27.46	31.54	34.39	37.13	54.00	-16.87	Average
2	2390.000	6.82	27.46	31.54	34.20	36.94	54.00	-17.06	Average
3 q	2412.000	6.91	27.52	31.54	82.28	85.17	54.00	31.17	Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 02062TL\02063TL
 Mode : 2412 Band edge
 : 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.670	6.82	27.45	31.54	55.05	57.78	74.00	-16.22	Peak
2	2390.000	6.82	27.46	31.54	52.97	55.71	74.00	-18.29	Peak
3 p	2412.000	6.91	27.52	31.54	104.22	107.11	74.00	33.11	Peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11ax(Full RU0); Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 Band edge
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	6.82	27.46	31.54	36.82	39.56	54.00	-14.44	Average
2	2390.000	6.82	27.46	31.54	36.44	39.18	54.00	-14.82	Average
3 q	2412.000	6.91	27.52	31.54	86.13	89.02	54.00	35.02	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2462.000	7.25	27.67	31.55	100.24	103.61	74.00	29.61	peak
2 2483.500	7.40	27.80	31.55	48.35	52.00	74.00	-22.00	peak
3 2484.041	7.40	27.80	31.55	48.31	51.96	74.00	-22.04	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	7.25	27.67	31.55	82.06	85.43	54.00	31.43 Average
2	2483.500	7.40	27.80	31.55	34.59	38.24	54.00	-15.76 Average
3	2483.790	7.40	27.80	31.55	34.21	37.86	54.00	-16.14 Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2462.000	7.25	27.67	31.55	103.82	107.19	74.00	33.19	Peak
2 2483.500	7.40	27.80	31.55	53.58	57.23	74.00	-16.77	Peak
3 2483.990	7.40	27.80	31.55	52.02	55.67	74.00	-18.33	Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 Band edge
: 2.4G Wi-Fi 11ax20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	7.25	27.67	31.55	85.31	88.68	54.00	34.68 Average
2	2483.500	7.40	27.80	31.55	37.09	40.74	54.00	-13.26 Average
3	2483.890	7.40	27.80	31.55	36.38	40.03	54.00	-13.97 Average



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11ax(Full RU0); Bandwidth: 40MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.071	6.82	27.44	31.54	51.97	54.69	74.00	-19.31 peak
2	2390.000	6.82	27.46	31.54	50.25	52.99	74.00	-21.01 peak
3 p	2422.000	6.98	27.54	31.54	98.37	101.35	74.00	27.35 peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11ax(Full RU0); Bandwidth: 40MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.677	6.82	27.46	31.54	37.47	40.21	54.00	-13.79	Average
2	2390.000	6.82	27.46	31.54	37.53	40.27	54.00	-13.73	Average
3 q	2422.000	6.98	27.54	31.54	80.45	83.43	54.00	29.43	Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.521	6.82	27.45	31.54	55.90	58.63	74.00	-15.37 Peak
2	2390.000	6.82	27.46	31.54	53.59	56.33	74.00	-17.67 Peak
3 p	2422.000	6.98	27.54	31.54	102.47	105.45	74.00	31.45 Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2422 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 2389.677	6.82	27.46	31.54	40.53	43.27	54.00	-10.73	Average
2 2390.000	6.82	27.46	31.54	40.44	43.18	54.00	-10.82	Average
3 q 2422.000	6.98	27.54	31.54	84.00	86.98	54.00	32.98	Average



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.000	7.18	27.61	31.55	97.94	101.18	74.00	27.18	peak
2	2483.500	7.40	27.80	31.55	56.04	59.69	74.00	-14.31	peak
3	2484.147	7.40	27.80	31.55	57.27	60.92	74.00	-13.08	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 2452.000		7.18	27.61	31.55	79.34	82.58	54.00	28.58 Average
2 2483.500		7.40	27.80	31.55	40.97	44.62	54.00	-9.38 Average
3 2483.865		7.40	27.80	31.55	40.79	44.44	54.00	-9.56 Average



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.000	7.18	27.61	31.55	101.87	105.11	74.00	31.11	Peak
2	2483.500	7.40	27.80	31.55	54.41	58.06	74.00	-15.94	Peak
3	2484.076	7.40	27.80	31.55	54.94	58.59	74.00	-15.41	Peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2452 Band edge
: 2.4G Wi-Fi 11ax40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2452.000	7.18	27.61	31.55	82.65	85.89	54.00	31.89	Average
2 2483.500	7.40	27.80	31.55	39.27	42.92	54.00	-11.08	Average
3 2484.076	7.40	27.80	31.55	39.57	43.22	54.00	-10.78	Average



6.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C

Humidity: 42.5 % RH


Atmospheric Pressure: 1020 mbar

6.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n/ax(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n/ax(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



6.2.3 Test Setup Diagram



6.2.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250500206203

Page: 54 of 76

Test Mode: 02; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL

Job No. : 02062TL/02063TL

Test Mode: 02

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.317	21.05	0.67	27.79	22.94	16.87	40.00	-23.13 QP
2	88.964	11.61	1.15	27.62	29.67	14.81	43.50	-28.69 QP
3	104.170	12.22	1.25	27.57	36.71	22.61	43.50	-20.89 QP
4	362.985	20.27	2.45	27.01	27.38	23.09	46.00	-22.91 QP
5	699.305	25.93	3.54	27.73	24.12	25.86	46.00	-20.14 QP
6 q	922.516	28.19	4.18	26.60	23.69	29.46	46.00	-16.54 QP




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : 02062TL/02063TL

Test Mode: 02

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	45.855	13.99	0.83	27.75	39.51	26.58	40.00	-13.42	QP
2	79.521	10.43	1.09	27.65	42.48	26.35	40.00	-13.65	QP
3	95.427	12.15	1.19	27.60	40.35	26.09	43.50	-17.41	QP
4	362.985	20.27	2.45	27.01	24.78	20.49	46.00	-25.51	QP
5	689.565	25.69	3.51	27.75	24.23	25.68	46.00	-20.32	QP
6	776.878	26.93	3.79	27.54	26.47	29.65	46.00	-16.35	QP



6.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

6.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n/ax(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n/ax(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

6.3.3 Test Setup Diagram



Above 1GHz



6.3.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 02062TL\02063TL
 Mode : 2412 TX RSE
 : 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1162.182	7.16	25.38	54.70	55.14	32.98	74.00	-41.02	peak
2	4074.388	8.30	30.35	55.65	55.15	38.15	74.00	-35.85	peak
3	4824.000	8.92	32.00	56.18	56.91	41.65	74.00	-32.35	peak
4	7236.000	11.10	36.60	56.51	52.28	43.47	74.00	-30.53	peak
5	9648.000	12.49	38.70	54.42	50.30	47.07	74.00	-26.93	peak
6	11906.070	14.62	39.71	53.77	49.49	50.05	74.00	-23.95	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	7.17	25.36	54.70	54.69	32.52	74.00	-41.48	peak
2	3123.039	7.71	29.15	55.07	58.61	40.40	74.00	-33.60	peak
3	4824.000	8.92	32.00	56.18	60.21	44.95	74.00	-29.05	peak
4	7236.000	11.10	36.60	56.51	53.80	44.99	74.00	-29.01	peak
5	9648.000	12.49	38.70	54.42	51.80	48.57	74.00	-25.43	peak
6	12798.240	15.15	40.30	54.36	48.92	50.01	74.00	-23.99	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1175.697	7.17	25.35	54.70	54.84	32.66	74.00	-41.34	peak
2	3069.345	7.86	29.16	55.04	55.35	37.33	74.00	-36.67	peak
3	4874.000	8.97	32.15	56.21	54.06	38.97	74.00	-35.03	peak
4	7311.000	11.11	36.72	56.45	53.38	44.76	74.00	-29.24	peak
5	9748.000	12.80	38.60	54.33	49.58	46.65	74.00	-27.35	peak
6	11335.190	14.29	39.70	53.60	48.62	49.01	74.00	-24.99	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1112.872	7.11	25.55	54.70	55.31	33.27	74.00	-40.73	peak
2	3123.039	7.71	29.15	55.07	58.34	40.13	74.00	-33.87	peak
3	4874.000	8.97	32.15	56.21	54.44	39.35	74.00	-34.65	peak
4	7311.000	11.11	36.72	56.45	52.66	44.04	74.00	-29.96	peak
5	9748.000	12.80	38.60	54.33	49.56	46.63	74.00	-27.37	peak
6	p10980.470	14.10	39.38	53.51	49.30	49.27	74.00	-24.73	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	7.16	25.36	54.70	55.46	33.28	74.00	-40.72	peak
2	4193.872	8.50	30.76	55.74	55.12	38.64	74.00	-35.36	peak
3	4924.000	9.03	32.20	56.25	58.38	43.36	74.00	-30.64	peak
4	7386.000	11.19	36.73	56.39	52.31	43.84	74.00	-30.16	peak
5	9848.000	12.84	37.83	54.24	50.36	46.79	74.00	-27.21	peak
6	11433.910	14.14	39.67	53.63	49.42	49.60	74.00	-24.40	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1145.507	7.14	25.42	54.70	54.48	32.34	74.00	-41.66	peak
2	3123.039	7.71	29.15	55.07	57.44	39.23	74.00	-34.77	peak
3	4924.000	9.03	32.20	56.25	59.35	44.33	74.00	-29.67	peak
4	7386.000	11.19	36.73	56.39	52.43	43.96	74.00	-30.04	peak
5	9848.000	12.84	37.83	54.24	49.87	46.30	74.00	-27.70	peak
6	p10698.510	13.55	39.40	53.68	50.01	49.28	74.00	-24.72	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1158.828	7.15	25.38	54.70	54.38	32.21	74.00	-41.79	peak
2	3935.493	8.09	30.04	55.56	55.23	37.80	74.00	-36.20	peak
3	4824.000	8.92	32.00	56.18	54.02	38.76	74.00	-35.24	peak
4	7236.000	11.10	36.60	56.51	52.03	43.22	74.00	-30.78	peak
5	9648.000	12.49	38.70	54.42	50.52	47.29	74.00	-26.71	peak
6	12184.580	14.48	39.87	53.93	49.07	49.49	74.00	-24.51	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1220.714	7.18	25.30	54.70	54.65	32.43	74.00	-41.57	peak
2	3123.039	7.71	29.15	55.07	57.55	39.34	74.00	-34.66	peak
3	4824.000	8.92	32.00	56.18	54.61	39.35	74.00	-34.65	peak
4	7236.000	11.10	36.60	56.51	52.35	43.54	74.00	-30.46	peak
5	9648.000	12.49	38.70	54.42	50.95	47.72	74.00	-26.28	peak
6	11135.190	14.29	39.70	53.60	48.92	49.31	74.00	-24.69	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1119.323	7.12	25.52	54.70	53.88	31.82	74.00	-42.18	peak
2	2407.703	7.39	27.52	54.82	58.62	38.71	74.00	-35.29	peak
3	4874.000	8.97	32.15	56.21	54.26	39.17	74.00	-34.83	peak
4	7311.000	11.11	36.72	56.45	52.90	44.28	74.00	-29.72	peak
5	9748.000	12.80	38.60	54.33	49.57	46.64	74.00	-27.36	peak
6	p11237.330	14.30	39.64	53.57	48.70	49.07	74.00	-24.93	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1498.781	7.22	24.90	54.70	54.79	32.21	74.00	-41.79	peak
2	3123.039	7.71	29.15	55.07	56.99	38.78	74.00	-35.22	peak
3	4874.000	8.97	32.15	56.21	53.71	38.62	74.00	-35.38	peak
4	7311.000	11.11	36.72	56.45	52.98	44.36	74.00	-29.64	peak
5	9748.000	12.80	38.60	54.33	50.40	47.47	74.00	-26.53	peak
6	11140.310	14.17	39.54	53.54	49.14	49.31	74.00	-24.69	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1175.697	7.17	25.35	54.70	54.74	32.56	74.00	-41.44	peak
2	4267.237	8.47	31.17	55.79	54.37	38.22	74.00	-35.78	peak
3	4924.000	9.03	32.20	56.25	53.74	38.72	74.00	-35.28	peak
4	7386.000	11.19	36.73	56.39	52.97	44.50	74.00	-29.50	peak
5	9848.000	12.84	37.83	54.24	52.10	48.53	74.00	-25.47	peak
6	p11269.860	14.35	39.67	53.58	49.17	49.61	74.00	-24.39	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	7.16	25.36	54.70	54.85	32.67	74.00	-41.33	peak
2	3123.039	7.71	29.15	55.07	58.29	40.08	74.00	-33.92	peak
3	4924.000	9.03	32.20	56.25	53.93	38.91	74.00	-35.09	peak
4	7386.000	11.19	36.73	56.39	52.15	43.68	74.00	-30.32	peak
5	9848.000	12.84	37.83	54.24	51.11	47.54	74.00	-26.46	peak
6	12909.700	15.24	40.39	54.44	48.56	49.75	74.00	-24.25	peak



Test Mode: 02; Polarity: Horizontal; Modulation: 802.11ax(Full RU0); Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1165.546	7.16	25.37	54.70	53.60	31.43	74.00	-42.57	peak
2	4039.212	8.21	30.28	55.63	54.17	37.03	74.00	-36.97	peak
3	4824.000	8.92	32.00	56.18	53.32	38.06	74.00	-35.94	peak
4	7236.000	11.10	36.60	56.51	51.94	43.13	74.00	-30.87	peak
5	9648.000	12.49	38.70	54.42	49.82	46.59	74.00	-27.41	peak
6	p12835.290	15.18	40.34	54.38	47.89	49.03	74.00	-24.97	peak



Test Mode: 02; Polarity: Vertical; Modulation: 802.11ax(Full RU0); Bandwidth: 20MHz; Channel: Low




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	7.17	25.36	54.70	54.20	32.03	74.00	-41.97	peak
2	3123.039	7.71	29.15	55.07	57.86	39.65	74.00	-34.35	peak
3	4824.000	8.92	32.00	56.18	55.16	39.90	74.00	-34.10	peak
4	7236.000	11.10	36.60	56.51	51.95	43.14	74.00	-30.86	peak
5	9648.000	12.49	38.70	54.42	49.85	46.62	74.00	-27.38	peak
6	11269.860	14.35	39.67	53.58	48.97	49.41	74.00	-24.59	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1109.660	7.11	25.56	54.70	53.70	31.67	74.00	-42.33	peak
2	3132.079	7.71	29.16	55.08	55.72	37.51	74.00	-36.49	peak
3	4874.000	8.97	32.15	56.21	53.67	38.58	74.00	-35.42	peak
4	7311.000	11.11	36.72	56.45	52.36	43.74	74.00	-30.26	peak
5	9748.000	12.80	38.60	54.33	49.18	46.25	74.00	-27.75	peak
6	p11433.910	14.14	39.67	53.63	48.69	48.87	74.00	-25.13	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1165.546	7.16	25.37	54.70	54.01	31.84	74.00	-42.16	peak
2	3123.039	7.71	29.15	55.07	57.02	38.81	74.00	-35.19	peak
3	4874.000	8.97	32.15	56.21	52.91	37.82	74.00	-36.18	peak
4	7311.000	11.11	36.72	56.45	53.24	44.62	74.00	-29.38	peak
5	9748.000	12.80	38.60	54.33	48.95	46.02	74.00	-27.98	peak
6	p11302.480	14.39	39.70	53.59	48.32	48.82	74.00	-25.18	peak



Test Mode: 02; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 02062TL\02063TL
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1135.617	7.13	25.46	54.70	54.86	32.75	74.00	-41.25	peak
2	4206.011	8.51	30.84	55.74	54.66	38.27	74.00	-35.73	peak
3	4924.000	9.03	32.20	56.25	53.58	38.56	74.00	-35.44	peak
4	7386.000	11.19	36.73	56.39	51.92	43.45	74.00	-30.55	peak
5	9848.000	12.84	37.83	54.24	50.52	46.95	74.00	-27.05	peak
6	p11335.190	14.29	39.70	53.60	49.24	49.63	74.00	-24.37	peak



Test Mode: 02; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 02062TL\02063TL
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11ax20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1185.936	7.18	25.33	54.70	54.62	32.43	74.00	-41.57	peak
2	3252.005	7.64	29.30	55.15	56.22	38.01	74.00	-35.99	peak
3	4924.000	9.03	32.20	56.25	52.83	37.81	74.00	-36.19	peak
4	7386.000	11.19	36.73	56.39	51.66	43.19	74.00	-30.81	peak
5	9848.000	12.84	37.83	54.24	50.16	46.59	74.00	-27.41	peak
6	p10575.540	13.35	39.25	53.75	50.75	49.60	74.00	-24.40	peak



7 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2505002062TL

8 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2505002062TL

- End of the Report -

