

RF Exposure Evaluation

FCC ID:2AOQ6-UE01

1. Client Information

Applicant	:	ChongQing Lavid Industrial Co., Ltd.
Address	:	No.2 Workshop, Electronic and Electrical Manufacturing Base, Union Community, Chenjiaba Street, Wanzhou District, Chongqing, China
Manufacturer	:	ChongQing Lavid Industrial Co., Ltd.
Address	:	No.2 Workshop, Electronic and Electrical Manufacturing Base, Union Community, Chenjiaba Street, Wanzhou District, Chongqing, China

2. General Description of EUT

EUT Name	:	WiFi USB Repeater
Model(s) No.	:	UE01, UE02, UE03, UE05, UE06, UE01T, UE07T
Model Difference	:	All PCB boards and circuit diagrams are the same, the only difference is that appearance color.
Product Description	Operation Frequency:	2.4G Wi-Fi: 2412MHz~2462MHz
	Antenna Gain:	3dBi Sheet Iron Antenna
Power Supply	:	Input: DC 5V
Software Version	:	220716
Hardware Version	:	V1.0
Remark:		
(1) The antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.		
(2) The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.		

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$$

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2. Summary simultaneous transmission for SAR Exclusion

The SAR exemption limits outlined in clause 4.3.2(b) of KDB 447498 have been derived based on an approximate SAR value of 0.4 W/kg using half-wave dipole antennas Footnote 1. As such, when simultaneous transmitter SAR evaluations include transmitters that have been exempt from routine SAR evaluation, the SAR must be estimated based on the ratio between the maximum tune-up tolerance limit of the transmitter that has been exempt and the exemption limit at the specific distance and frequency for that transmitter. This ratio must be multiplied by 0.4 W/kg (2.0 W/kg for controlled use and 1.0 W/kg for limb worn devices) in order to calculate the estimated SAR level.

The estimated SAR value is calculated based on the following equation:

(maximum power level including tune-up tolerance for transmitter A / maximum power level of exemption at the same frequency and distance) * 0.4W/kg

- 1) $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg, for test separation distances} \leq 50 \text{ mm};$
where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.
- 2) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distance is > 50 mm.³⁷

The $[\sum \text{ (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg} + [\sum \text{ of MPE ratios}]] \leq 1.0$.

The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\sum \text{ of MPE ratios}]$ is ≤ 1.0 .

3. Calculation:

Test separation: 5mm						
2.4 G Wi-Fi CDD Ant1 802.11b						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	5.74	6±1	7	5.012	1.557	3.0
2.437	4.77	5±1	6	3.981	1.243	3.0
2.462	5.47	5±1	6	3.981	1.249	3.0
2.4 G Wi-Fi Ant1 802.11g						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	4.05	4±1	5	3.162	0.982	3.0
2.437	5.96	6±1	7	5.012	1.565	3.0
2.462	4.52	5±1	6	3.981	1.249	3.0
2.4 G Wi-Fi Ant1 802.11n20						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	4.46	4±1	5	3.162	0.982	3.0
2.437	5.66	6±1	7	5.012	1.565	3.0
2.462	4.92	5±1	6	3.981	1.249	3.0
2.4 G Wi-Fi Ant1 802.11n40						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.422	5.26	5±1	6	3.981	1.239	3.0
2.437	5.51	6±1	7	5.012	1.565	3.0
2.452	5.24	5±1	6	3.981	1.247	3.0

Test separation: 5mm						
2.4 G Wi-Fi CDD Ant2 802.11b						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	3.65	4±1	5	3.162	0.982	3.0
2.437	3.37	3±1	4	2.512	0.784	3.0
2.462	2.78	3±1	4	2.512	0.788	3.0
2.4 G Wi-Fi Ant2 802.11g						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	1.39	1±1	2	1.585	0.492	3.0
2.437	4.35	4±1	5	3.162	0.987	3.0
2.462	2.52	3±1	4	2.512	0.788	3.0
2.4 G Wi-Fi Ant2 802.11n20						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	2.47	2±1	3	1.995	0.620	3.0
2.437	3.95	4±1	5	3.162	0.987	3.0
2.462	3.78	4±1	5	3.162	0.992	3.0
2.4 G Wi-Fi Ant2 802.11n40						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.422	3.04	3±1	4	2.512	0.782	3.0
2.437	3.72	4±1	5	3.162	0.987	3.0
2.452	3.59	4±1	5	3.162	0.990	3.0

Test separation: 5mm						
2.4 G Wi-Fi Ant1 802.11b						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	6.79	7±1	8	6.310	1.960	3.0
2.437	8.06	8±1	9	7.943	2.480	3.0
2.462	7.95	8±1	9	7.943	2.493	3.0
2.4 G Wi-Fi Ant1 802.11g						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	7.19	7±1	8	6.310	1.960	3.0
2.437	7.49	7±1	8	6.310	1.970	3.0
2.462	7.76	8±1	9	7.943	2.493	3.0

Test separation: 5mm						
2.4 G Wi-Fi Ant2 802.11b						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	7.20	7±1	8	6.310	1.960	3.0
2.437	6.83	7±1	8	6.310	1.970	3.0
2.462	8.24	8±1	9	7.943	2.493	3.0
2.4 G Wi-Fi Ant2 802.11g						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	7.55	8±1	9	7.943	2.467	3.0
2.437	7.87	8±1	9	7.943	2.480	3.0
2.462	6.07	7±1	8	6.310	2.493	3.0

Summary simultaneous transmission results

Simultaneous Transmission for SAR Exclusion

The sample support one Wi-Fi modular, they supports difference antenna, need consider simultaneous transmission;

$$\sum \text{ of (the highest measured or estimated SAR Wi-Fi Ant1+SAR Wi-Fi Ant2)/1.6} = (0.209+0.132)/1.6 = 0.2915 < 1.0;$$

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----