



TEST REPORT

Applicant: Gouldin Technologies, LLC

Address: 3220 Keller Springs Rd, #106, Carrollton, Texas 75006, United States

FCC ID: 2AOQ7-W480

Product Name: Watchman

Model Number: W480

**Standard(s): FCC Part 15B
ANSI C63.4-2014**

The above equipment has been tested and found compliance with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR21100016-00B

Date Of Issue: 2021-10-29

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 DESCRIPTION OF TEST CONFIGURATION	5
1.2.2 Support Equipment List and Details	5
1.2.3 Support Cable List and Details	5
1.2.4 Block Diagram of Test Setup.....	5
1.3 MEASUREMENT UNCERTAINTY	6
2. SUMMARY OF TEST RESULTS.....	7
3. REQUIREMENTS AND TEST PROCEDURES	8
3.1 AC LINE CONDUCTED EMISSIONS	8
3.1.1 EUT Setup.....	8
3.1.2 EMI Test Receiver Setup	8
3.1.3 Test Procedure	9
3.1.4 Corrected Amplitude & Margin Calculation.....	9
3.2 RADIATION SPURIOUS EMISSIONS	10
3.2.1 EUT Setup.....	10
3.2.2 EMI Test Receiver Setup	10
3.2.3 Test Procedure	10
3.2.4 Corrected Amplitude & Margin Calculation.....	11
4. TEST DATA AND RESULTS.....	12
4.1 AC LINE CONDUCTED EMISSIONS	12
4.2 RADIATION SPURIOUS EMISSIONS	15

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Watchman
EUT Model:	W480
Highest Operation Frequency:	24 MHz
Rated Input Voltage:	DC 12V from DC input Port
Serial Number:	CR21100016-RF-S1
EUT Received Date:	2021.10.10
EUT Received Status:	Good

Accessory Information:

No Accessory.

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Typical Use Mode, which was provided by the manufacturer. Test Mode: Operating
Equipment Modifications:	No
EUT Exercise Software:	No


1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	MB-R210-00
Gouldin Technologies, LLC	Relay	Unknown	Relay-1
Gouldin Technologies, LLC	Relay	Unknown	Relay-2
Aohai	Adapter	E256123DC	12V1A02520

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	Yes	No	5.0	EUT	Relay
Relay Cable	Yes	No	5.0	EUT	Relay
Relay Cable	Yes	No	5.0	EUT	Relay
DC Cable	No	No	1.2	Adapter	EUT

1.2.4 Block Diagram of Test Setup



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Temperature	±1°C
Humidity	±5%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)


2. SUMMARY OF TEST RESULTS

Standard(s) Section	Description of Test	Result
§15.107	Conducted emissions	Compliance
§15.109	Radiated emissions	Compliance

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.2 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.3 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT, the report shall list the six emissions with the smallest margin relative to the limit, unless the margin is greater than 20 dB.

All data was recorded in the Quasi-peak and average detection mode.

The report shall list the six emissions with the smallest margin relative to the limit, unless the margin is greater than 20 dB.

3.1.4 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN


The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions

3.2.1 EUT Setup

Below 1GHz:



The radiated emission were performed in the 3 meters chamber test site , using the setup accordance with the ANSI C63.4-2014. The specification used was with the FCC Part 15 B Class B limits.

3.2.2 EMI Test Receiver Setup

The system was investigated from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	Reduced video bandwidth	/	AVG

If the maximized peak measured value complies with under the limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.3 Test Procedure

During the radiated emissions, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.4 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4. TEST DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	CR21100016-RF-S1	Test Date:	2021-10-25
Test Site:	CE	Test Mode:	Operating
Tester:	Nick Tang	Test Result:	Pass


Environmental Conditions:					
Temperature: (°C)	21.5	Relative Humidity: (%)	74	ATM Pressure: (kPa)	101.3

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101132	2021-04-25	2022-04-24
R&S	EMI Test Receiver	ESR3	102726	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2021-08-08	2022-08-07
Audix	Test Software	E3	190306 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Line:



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.159	27.72	9.61	37.33	55.53	18.21	Average
2	0.159	32.78	9.61	42.39	65.53	23.14	QP
3	0.314	32.74	9.61	42.35	49.86	7.51	Average
4	0.314	39.07	9.61	48.68	59.86	11.19	QP
5	0.410	30.15	9.61	39.76	47.64	7.88	Average
6	0.410	39.09	9.61	48.70	57.64	8.94	QP
7	0.696	15.94	9.62	25.56	46.00	20.44	Average
8	0.696	34.60	9.62	44.22	56.00	11.78	QP
9	1.228	25.48	9.62	35.10	46.00	10.90	Average
10	1.228	35.75	9.62	45.37	56.00	10.63	QP
11	2.166	23.57	9.63	33.20	46.00	12.80	Average
12	2.166	34.50	9.63	44.13	56.00	11.87	QP

Neutral:



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.321	21.82	9.61	31.43	49.69	18.26	Average
2	0.321	35.05	9.61	44.66	59.69	15.03	QP
3	0.471	21.00	9.61	30.61	46.49	15.88	Average
4	0.471	33.09	9.61	42.70	56.49	13.80	QP
5	1.241	23.10	9.62	32.72	46.00	13.28	Average
6	1.241	33.52	9.62	43.14	56.00	12.86	QP
7	2.166	21.60	9.63	31.23	46.00	14.77	Average
8	2.166	32.56	9.63	42.19	56.00	13.81	QP
9	3.209	21.29	9.65	30.94	46.00	15.06	Average
10	3.209	35.00	9.65	44.65	56.00	11.35	QP
11	4.601	21.97	9.66	31.63	46.00	14.37	Average
12	4.601	36.03	9.66	45.69	56.00	10.31	QP

4.2 Radiation Spurious Emissions

Serial Number:	DG6210824-36276E-RF-S1	Test Date:	2021-10-26
Test Site:	966-1, 966-2	Test Mode:	Operating
Tester:	Great Qiao	Test Result:	Pass


Environmental Conditions:					
Temperature: (°C)	25.7	Relative Humidity: (%)	62	ATM Pressure: (kPa)	101.3

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
Audix	Test Software	E3	201021 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

1) 30MHz-1GHz:

Horizontal:

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	108.647	49.21	-12.82	36.39	43.50	7.11	Peak
2	138.874	44.35	-12.07	32.28	43.50	11.22	Peak
3	250.301	51.95	-13.25	38.70	46.00	7.30	QP
4	400.432	44.39	-9.00	35.40	46.00	10.60	Peak
5	528.246	43.60	-6.17	37.43	46.00	8.57	QP
6	860.035	38.94	-1.48	37.46	46.00	8.54	QP

Vertical:

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.531	38.74	-4.20	34.54	40.00	5.46	QP
2	58.613	50.15	-17.60	32.55	40.00	7.45	Peak
3	106.759	46.37	-13.22	33.15	43.50	10.35	Peak
4	141.330	44.62	-12.18	32.44	43.50	11.06	Peak
5	250.301	50.79	-13.25	37.54	46.00	8.46	Peak
6	528.246	41.18	-6.17	35.01	46.00	10.99	Peak

*****END OF REPORT*****