

TEST REPORT

Reference No. : WTS19S04021633W002
FCC ID..... : 2AOT9-NBDVR522GW
Applicant..... : Portable Multimedia Limited
Address..... : Unit 2,Caerphilly Business Park, Caerphilly, Mid Glamorgan
CF833ED, United Kingdom
Manufacturer : Shenzhen Samoon Technology Co.,Ltd
Address..... : Floor5-6&9, Building 7, Zhongyuntai Ind. Park, Yingrenshi Road
Crossing,Shiyan Town, Bao'an District, Shenzhen, Guangdong,China.
Post code: 518108.
Product..... : Dash Cam
Model(s)..... : NBDVR522GW, FE-NBDVR522GW, NBDVR522GW-WHT,
FE-NBDVR522GW-WHT, VYDVR522GW, FE VYDVR522GW,
NBDVR523GW, FE-NBDVR523GW, NBDVR524GW,
FE-NBDVR524GW, NBDVR522GWL, FE-NBDVR522GWL
Standards..... : FCC CFR47 Part 15 C Section 15.247:2018
Date of Receipt sample..... : 2019-04-12
Date of Test..... : 2019-04-19 to 2019-04-24
Date of Issue..... : 2019-04-25
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Jack Wen

Jack Wen / Test Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

1. Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation, the certification number is 4243.01) of USA, CNAS (China National Accreditation Service for Conformity Assessment, the registration number is L3110) of China. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC (The Federal Communications Commission), CEC (California energy efficiency), ISED (Innovation, Science and Economic Development Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek (ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

1.1 Test Facility

A. Accreditations for Conformity Assessment (International)

In Preparations for Conformity Assessment (International)			
Country/Region	Scope Covered By	Scope	Note
USA	ISO/IEC 17025	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		WPC	-
Thailand		NTC	-
Singapore		IDA	-
Note:			
1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.			
2. ISED CAB identifier: CN0013.			

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd.	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

2. Contents

	Page
COVER PAGE.....	1
1. LABORATORIES INTRODUCTION.....	2
1.1 TEST FACILITY.....	3
2. CONTENTS.....	4
3. REVISION HISTORY.....	5
4. GENERAL INFORMATION.....	6
4.1 GENERAL DESCRIPTION OF E.U.T.....	6
4.2 DETAILS OF E.U.T.....	6
4.3 CHANNEL LIST.....	7
4.4 TEST MODE.....	7
5. EQUIPMENT USED DURING TEST.....	8
5.1 EQUIPMENTS LIST.....	8
5.2 MEASUREMENT UNCERTAINTY.....	9
5.3 TEST EQUIPMENT CALIBRATION.....	9
6. TEST SUMMARY.....	10
7. RADIATED EMISSIONS.....	11
7.1 EUT OPERATION.....	11
7.2 TEST SETUP.....	12
7.3 SPECTRUM ANALYZER SETUP.....	13
7.4 TEST PROCEDURE.....	14
7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	14
7.6 SUMMARY OF TEST RESULTS.....	15
8. BAND EDGE MEASUREMENT.....	24
8.1 TEST PRODUCE.....	24
8.2 TEST RESULT.....	25
9. BANDWIDTH MEASUREMENT.....	28
9.1 TEST PROCEDURE:.....	28
9.2 TEST RESULT:.....	28
10. MAXIMUM PEAK OUTPUT POWER.....	33
10.1 TEST PROCEDURE:.....	33
10.2 TEST RESULT:.....	33
11. POWER SPECTRAL DENSITY.....	34
11.1 TEST PROCEDURE:.....	34
11.2 TEST RESULT:.....	34
12. ANTENNA REQUIREMENT.....	40
13. PHOTOGRAPHS – TEST SETUP PHOTOS.....	41
13.1 RADIATED EMISSION.....	41
14. PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	43

3. Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS19S04021633W002	2019-04-12	2019-04-19 to 2019-04-24	2019-04-25	original	-	Valid

4. General Information

4.1 General Description of E.U.T

Product Name:	Dash Cam
Model No.:	NBDVR522GW, FE-NBDVR522GW, NBDVR522GW-WHT, FE-NBDVR522GW-WHT, VYDVR522GW, FE VYDVR522GW, NBDVR523GW, FE-NBDVR523GW, NBDVR524GW, FE-NBDVR524GW, NBDVR522GWL, FE-NBDVR522GWL
Model Descriptions:	Only the model names are different.
Operation Frequency:	802.11b/g/n HT20: 2412MHz ~ 2462MHz
RF output power:	21.11dBm
Antenna installation:	Ceramic Antenna
Antenna Gain:	1.5dBi
Type of modulation:	IEEE 802.11b (CCK/QPSK/BPSK,11Mbps max.) IEEE 802.11g (BPSK/QPSK/16QAM/64QAM,54Mbps max.) IEEE 802.11n (BPSK/QPSK/16QAM/64QAM,HT20:72Mbps max.)

4.2 Details of E.U.T

Ratings:	Input: DC 12V/24V Battery: DC 3.7V 320mAh 1.18Wh
----------	---

4.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
Frequency Range	802.11b	11 Mbps	1/11	TX
	802.11g	54 Mbps	1/11	TX
	802.11n HT20	108 Mbps	1/11	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

5. Equipment Used during Test

5.1 Equipments List

3m Semi-anechoic Chamber for Radiation Emissions						
1	Spectrum Analyzer	R&S	FSP30	100091	2018.04.29	2019.04.28
2	Broad-band Horn Antenna(1-18GHz)	SCHWARZBECK	BBHA 9120 D	667	2018.04.29	2019.04.28
3	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2018.04.29	2019.04.28
4	Coaxial Cable (above 1GHz)	Top	1GHz-18GHz	EW02014-7	2018.04.29	2019.04.28
5	Spectrum Analyzer	R&S	FSP40	100501	2018.10.24	2019.10.23
6	Broad-band Horn Antenna(18-40GHz)	SCHWARZBECK	BBHA 9170	BBHA917065 1	2018.10.24	2019.10.23
7	Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	100472	2018.10.24	2019.10.23
8	Cable	Top	18-40GHz	-	2018.10.24	2019.10.23
3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2019.04.19	2020.04.18
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2019.04.19	2020.04.18
3	Amplifier	ANRITSU	MH648A	M43381	2019.04.19	2020.04.18
4	Cable	HUBER+SUHNER	CBL2	525178	2019.04.19	2020.04.18
5	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2019.04.19	2020.04.18
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2018-09-13	2019-09-12
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2018-09-11	2019-09-10
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2018-09-11	2019-09-10

5.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by GUANG ZHOU GRG METROLOGY & TEST CO., LTD. address is No.163, Pingyun Rd. West of Huangpu Ave, Tianhe District, Guangzhou, Guangdong, China.

6. Test Summary

Test Items	Test Requirement	Result
Radiated Emissions	15.247 15.205(a) 15.209(a)	Pass
Bandwidth	15.247(a)(2)	Pass
Maximum Peak Output Power	15.247(b)(3),(4)	Pass
Power Spectral Density	15.247(e)	Pass
Band Edge	15.247(d)	Pass
Antenna Requirement	15.203	Pass
Note: Pass=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

Remark: Conducted Emissions testing are inapplicable for EUT powered by battery.

7. Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth.....10kHz
Video Bandwidth.....10kHz
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....100kHz
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....1MHz
Video Bandwidth.....3MHz
DetectorAve.
Resolution Bandwidth.....1MHz
Video Bandwidth.....10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane;
For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high -pass filter is used during radiated emissions above 1GHz measurement.

7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

7.6 Summary of Test Results

Test Frequency : 9kHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
486.22	12.81	PK	26	1.2	H	21.09	33.90	45.00	-11.10
486.22	12.22	PK	256	1.8	V	21.09	33.31	45.00	-11.69
4824.00	50.49	PK	199	1.8	V	-1.05	49.44	74.00	-24.56
4824.00	42.74	Ave	199	1.8	V	-1.05	41.69	54.00	-12.31
7236.00	46.19	PK	27	1.6	H	1.34	47.53	74.00	-26.47
7236.00	41.24	Ave	27	1.6	H	1.34	42.58	54.00	-11.42
2310.09	46.79	PK	181	1.7	V	-13.19	33.60	74.00	-40.40
2310.09	39.44	Ave	181	1.7	V	-13.19	26.25	54.00	-27.75
2354.84	43.38	PK	7	1.1	H	-13.15	30.23	74.00	-43.77
2354.84	36.68	Ave	7	1.1	H	-13.15	23.53	54.00	-30.47
2484.96	43.48	PK	168	1.9	V	-13.08	30.40	74.00	-43.60
2484.96	37.80	Ave	168	1.9	V	-13.08	24.72	54.00	-29.28

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
486.22	13.53	PK	39	1.4	H	21.09	34.62	45.00	-10.38
486.22	13.82	PK	60	1.5	V	21.09	34.91	45.00	-10.09
4874.00	49.46	PK	320	1.6	V	-0.63	48.83	74.00	-25.17
4874.00	44.24	Ave	320	1.6	V	-0.63	43.61	54.00	-10.39
7311.00	45.24	PK	121	1.3	H	2.21	47.45	74.00	-26.55
7311.00	42.79	Ave	121	1.3	H	2.21	45.00	54.00	-9.00
2322.84	45.87	PK	272	1.7	V	-13.19	32.68	74.00	-41.32
2322.84	37.99	Ave	272	1.7	V	-13.19	24.80	54.00	-29.20
2354.82	43.05	PK	24	1.4	H	-13.14	29.91	74.00	-44.09
2354.82	37.81	Ave	24	1.4	H	-13.14	24.67	54.00	-29.33
2493.23	43.48	PK	160	1.7	V	-13.09	30.39	74.00	-43.61
2493.23	38.78	Ave	160	1.7	V	-13.09	25.69	54.00	-28.31

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
486.22	14.71	PK	48	1.7	H	21.09	35.80	45.00	-9.20
486.22	13.78	PK	254	1.3	V	21.09	34.87	45.00	-10.13
4924.00	50.34	PK	20	1.6	V	-0.25	50.09	74.00	-23.91
4924.00	44.75	Ave	20	1.6	V	-0.25	44.50	54.00	-9.50
7386.00	48.22	PK	23	1.8	H	2.85	51.07	74.00	-22.93
7386.00	41.31	Ave	23	1.8	H	2.85	44.16	54.00	-9.84
2349.66	45.56	PK	198	1.6	V	-13.19	32.37	74.00	-41.63
2349.66	39.90	Ave	198	1.6	V	-13.19	26.71	54.00	-27.29
2384.07	42.94	PK	202	1.5	H	-13.14	29.80	74.00	-44.20
2384.07	38.31	Ave	202	1.5	H	-13.14	25.17	54.00	-28.83
2494.68	42.77	PK	240	1.6	V	-13.09	29.68	74.00	-44.32
2494.68	37.56	Ave	240	1.6	V	-13.09	24.47	54.00	-29.53

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
486.22	14.33	PK	312	1.8	H	21.09	35.42	45.00	-9.58
486.22	13.18	PK	321	1.3	V	21.09	34.27	45.00	-10.73
4824.00	51.66	PK	241	1.9	V	-1.06	50.60	74.00	-23.40
4824.00	48.37	Ave	241	1.9	V	-1.06	47.31	54.00	-6.69
7236.00	47.10	PK	47	1.3	H	1.35	48.45	74.00	-25.55
7236.00	46.46	Ave	47	1.3	H	1.35	47.81	54.00	-6.19
2311.17	45.90	PK	264	1.2	V	-13.19	32.71	74.00	-41.29
2311.17	37.21	Ave	264	1.2	V	-13.19	24.02	54.00	-29.98
2382.30	43.32	PK	243	1.3	H	-13.14	30.18	74.00	-43.82
2382.30	38.65	Ave	243	1.3	H	-13.14	25.51	54.00	-28.49
2488.22	44.62	PK	331	1.3	V	-13.08	31.54	74.00	-42.46
2488.22	37.21	Ave	331	1.3	V	-13.08	24.13	54.00	-29.87

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
486.22	13.51	PK	40	1.2	H	21.09	34.60	45.00	-10.40
486.22	13.75	PK	328	1.6	V	21.09	34.84	45.00	-10.16
4874.00	49.64	PK	210	1.7	V	-0.62	49.02	74.00	-24.98
4874.00	48.79	Ave	210	1.7	V	-0.62	48.17	54.00	-5.83
7311.00	47.47	PK	350	1.3	H	2.20	49.67	74.00	-24.33
7311.00	46.28	Ave	350	1.3	H	2.20	48.48	54.00	-5.52
2339.15	46.19	PK	76	1.8	V	-13.19	33.00	74.00	-41.00
2339.15	39.59	Ave	76	1.8	V	-13.19	26.40	54.00	-27.60
2360.74	42.86	PK	353	1.6	H	-13.15	29.71	74.00	-44.29
2360.74	38.01	Ave	353	1.6	H	-13.15	24.86	54.00	-29.14
2495.98	43.98	PK	34	1.0	V	-13.09	30.89	74.00	-43.11
2495.98	38.22	Ave	34	1.0	V	-13.09	25.13	54.00	-28.87

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
486.22	13.71	PK	222	1.9	H	21.09	34.80	45.00	-10.20
486.22	13.79	PK	156	1.9	V	21.09	34.88	45.00	-10.12
4924.00	50.76	PK	223	1.7	V	-0.25	50.51	74.00	-23.49
4924.00	46.47	Ave	223	1.7	V	-0.25	46.22	54.00	-7.78
7386.00	47.69	PK	356	1.1	H	2.86	50.55	74.00	-23.45
7386.00	42.41	Ave	356	1.1	H	2.86	45.27	54.00	-8.73
2320.82	46.89	PK	235	1.1	V	-13.19	33.70	74.00	-40.30
2320.82	37.61	Ave	235	1.1	V	-13.19	24.42	54.00	-29.58
2353.84	43.59	PK	193	1.1	H	-13.14	30.45	74.00	-43.55
2353.84	37.04	Ave	193	1.1	H	-13.14	23.90	54.00	-30.10
2490.43	43.59	PK	234	1.5	V	-13.08	30.51	74.00	-43.49
2490.43	38.37	Ave	234	1.5	V	-13.08	25.29	54.00	-28.71

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n20: Low Channel 2412MHz									
486.22	14.74	PK	224	1.0	H	21.09	35.83	45.00	-9.17
486.22	14.14	PK	242	1.9	V	21.09	35.23	45.00	-9.77
4824.00	50.58	PK	24	1.7	V	-1.06	49.52	74.00	-24.48
4824.00	48.90	Ave	24	1.7	V	-1.06	47.84	54.00	-6.16
7236.00	47.07	PK	160	1.9	H	1.34	48.41	74.00	-25.59
7236.00	45.54	Ave	160	1.9	H	1.34	46.88	54.00	-7.12
2327.80	45.76	PK	328	1.8	V	-13.19	32.57	74.00	-41.43
2327.80	37.17	Ave	328	1.8	V	-13.19	23.98	54.00	-30.02
2371.59	42.63	PK	31	1.6	H	-13.14	29.49	74.00	-44.51
2371.59	38.92	Ave	31	1.6	H	-13.14	25.78	54.00	-28.22
2492.88	44.99	PK	113	1.9	V	-13.08	31.91	74.00	-42.09
2492.88	36.09	Ave	113	1.9	V	-13.08	23.01	54.00	-30.99

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n20: Middle Channel 2437MHz									
486.22	14.50	PK	340	1.4	H	21.09	35.59	45.00	-9.41
486.22	13.27	PK	150	1.9	V	21.09	34.36	45.00	-10.64
4874.00	50.37	PK	221	1.4	V	-0.61	49.76	74.00	-24.24
4874.00	48.41	Ave	221	1.4	V	-0.61	47.80	54.00	-6.20
7311.00	47.65	PK	210	1.3	H	2.21	49.86	74.00	-24.14
7311.00	45.35	Ave	210	1.3	H	2.21	47.56	54.00	-6.44
2316.81	45.18	PK	4	1.2	V	-13.19	31.99	74.00	-42.01
2316.81	39.21	Ave	4	1.2	V	-13.19	26.02	54.00	-27.98
2372.87	42.29	PK	341	1.3	H	-13.14	29.15	74.00	-44.85
2372.87	38.48	Ave	341	1.3	H	-13.14	25.34	54.00	-28.66
2491.74	42.06	PK	323	1.2	V	-13.09	28.97	74.00	-45.03
2491.74	36.09	Ave	323	1.2	V	-13.09	23.00	54.00	-31.00

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
n20: High Channel 2462MHz									
486.22	14.39	PK	212	1.9	H	21.09	35.48	45.00	-9.52
486.22	13.44	PK	263	1.4	V	21.09	34.53	45.00	-10.47
4924.00	50.65	PK	44	1.8	V	-0.24	50.41	74.00	-23.59
4924.00	48.86	Ave	44	1.8	V	-0.24	48.62	54.00	-5.38
7386.00	47.37	PK	305	1.6	H	2.83	50.20	74.00	-23.80
7386.00	45.05	Ave	305	1.6	H	2.83	47.88	54.00	-6.12
2321.98	45.31	PK	124	1.2	V	-13.19	32.12	74.00	-41.88
2321.98	38.37	Ave	124	1.2	V	-13.19	25.18	54.00	-28.82
2350.03	44.59	PK	282	1.4	H	-13.14	31.45	74.00	-42.55
2350.03	37.23	Ave	282	1.4	H	-13.14	24.09	54.00	-29.91
2496.48	43.55	PK	50	1.8	V	-13.08	30.47	74.00	-43.53
2496.48	38.56	Ave	50	1.8	V	-13.08	25.48	54.00	-28.52

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

8. Band Edge Measurement


Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	558074 D01 15.247 Meas Guidance v05
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

8.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.2 Test Result


Test result plots shown as follows:




TX 11b: Band edge-right side





TX 11g: Band edge-left side



TX 11g: Band edge-right side





9. Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: 558074 D01 15.247 Meas Guidance v05

9.1 Test Procedure:


- 1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



9.2 Test Result:



Operation mode	6dB Bandwidth (MHz)			99% Bandwidth (MHz)		
TX 11b	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
	9.166	9.581	8.942	13.669	13.669	13.669
TX 11g	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
	15.685	16.018	16.018	16.317	16.317	16.317
TX 11n HT20	Channel 1	Channel 6	Channel 11	Channel 1	Channel 6	Channel 11
	16.329	16.275	16.669	17.461	17.461	17.461



Wifi: Test result plot as follows:



Mode: TX 11b channel 1











10. Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

558074 D01 15.247 Meas Guidance v05

10.1 Test Procedure:

558074 D01 DTS Meas Guidance V04

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

10.2 Test Result:

Test mode :TX 11b		
Maximum Peak Output Power (dBm)		
2412MHz	2437MHz	2462MHz
21.11	20.39	20.02
Limit: 1W/30dBm		

Test mode :TX 11g		
Maximum Peak Output Power (dBm)		
2412MHz	2437MHz	2462MHz
17.39	17.03	16.87
Limit: 1W/30dBm		

Test mode :TX 11n HT20		
Maximum Peak Output Power (dBm)		
2412MHz	2437MHz	2462MHz
20.61	19.71	19.42
Limit: 1W/30dBm		

11. Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: 558074 D01 15.247 Meas Guidance v05

11.1 Test Procedure:

558074 D01 DTS Meas Guidance V04



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.



11.2 Test Result:



Test mode :TX 11b		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-8.22	-8.99	-7.33
Limit: 8dBm per 3kHz		



Test mode :TX 11g		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-16.86	-16.87	-17.17
Limit: 8dBm per 3kHz		


Test mode :TX 11n HT20		
Power Spectral (dBm per 3kHz)		
2412MHz	2437MHz	2462MHz
-12.94	-13.73	-14.72
Limit: 8dBm per 3kHz		











12. Antenna Requirement


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has a Ceramic Antenna, meets the requirements of FCC 15.203.


BT & 2.4G Wi-Fi ANT




13. Photographs – Test Setup Photos

13.1 Radiated Emission

Test frequency Below 30MHz



Test frequency from 30MHz to 1GHz



Test frequency above 1GHz



14. Photographs - Constructional Details

Please refer to the appendix NBDVR522GW-Photos.

=====End of Report=====