

# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

## 1.1 General Information

### Client Information

Applicant: Portable Multimedia Limited  
Address of applicant: Unit 2, Caerphilly Business Park, Van Road, Caerphilly.  
CF83 3ED. United Kingdom

Manufacturer: Shenzhen Samoon Technology Co.,Ltd  
Address of manufacturer: Floor5-6&9, Building 7, Zhongyuntai Ind. Park, Yingrenshi  
Road Crossing, Shiyan Town, Bao'an District, Shenzhen,  
Guangdong,China. Post code: 518108.

### General Description of EUT:

Product Name: Dash Cam  
Trade Name: /  
Model No.: 2AOT9-NBDVR622GW  
FE-NBDVR622GW, NBDVR622GW-WHT, FE-NBDVR622GW-WHT,  
VYDVR622GW, FE-VYDVR622GW, NBDVR623GW,  
FE-NBDVR623GW, NBDVR624GW, FE-NBDVR624GW,  
NBDVR622GWL, FE-NBDVR622GWL  
Rated Voltage: DC3.7V  
Battery Capacity: 370mAh  
FCC ID: 2AOT9-NBDVR622GW  
Equipment Type: Mobile

### Technical Characteristics of EUT:

#### Bluetooth

Bluetooth Version: V4.2 (BR/EDR mode)  
Frequency Range: 2402-2480MHz  
RF Output Power: 5.05dBm (Conducted)  
Data Rate: 1Mbps, 2Mbps, 3Mbps  
Modulation: GFSK, Pi/4 DQPSK, 8DPSK  
Quantity of Channels: 79  
Channel Separation: 1MHz  
Type of Antenna: Integral Antenna  
Antenna Gain: 0.27dBi

#### 2.4G Wi-Fi

Support Standards: 802.11b, 802.11g, 802.11n  
2412-2462MHz for 802.11b/g/n-HT20  
Frequency Range: 2422-2452MHz for 802.11n-HT40  
RF Output Power: 13.85dBm (Conducted)  
Type of Modulation: DSSS,OFDM

Data Rate: 1-11Mbps, 6-54Mbps, up to 150Mbps

Quantity of Channels: 11 for 802.11b/g/n-HT20

7 for 802.11n-HT40

Channel Separation: 5MHz

Type of Antenna: Integral Antenna

Antenna Gain: 0.27dBi

### 5G Wi-Fi

Support Standards: 802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40, 802.11ac-VHT80

Frequency Range: 5150-5250MHz,

RF Output Power: 10.96dBm (Conducted)

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, 256QAM

Data Rate: 6-54Mbps, up to 200Mbps

Type of Antenna: Integral Antenna

Antenna Gain: 4.09dBi

## 1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

### (a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

### (b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; \* = Plane-wave equivalents power density

## 1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,  
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 1.4 MPE Calculation Result

For Bluetooth

Maximum Tune-Up output power: 6(dBm)

Maximum peak output power at antenna input terminal: 3.98(mW)

Prediction distance: >20(cm)

Prediction frequency: 2480 (MHz)

Antenna gain: 0.27(dBi)

Directional gain (numeric gain): 1.06

The worst case is power density at prediction frequency at 20cm: 0.0008(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

For 2.4G Wi-Fi

Maximum Tune-Up output power: 14(dBm)

Maximum peak output power at antenna input terminal: 25.12(mW)

Prediction distance: >20(cm)

Prediction frequency: 2437(MHz)

Antenna gain: 0.27(dBi)

Directional gain (numeric gain): 1.06

The worst case is power density at prediction frequency at 20cm: 0.0053(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

For 5G Wi-Fi

Maximum Tune-Up output power: 11(dBm)

Maximum peak output power at antenna input terminal: 12.59(mW)

Prediction distance: >20(cm)

Prediction frequency: 5180(MHz)

Antenna gain: 4.09 (dBi)

Directional gain (numeric gain): 2.56

The worst case is power density at prediction frequency at 20cm: 0.0064(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

WIFI and BT is the use the same antenna cannot simultaneous transmission;

Result: Pass