

TEST REPORT

Product Name : Handset
Model Number : KDH283A
FCC ID : 2AOTUKDH283A

Prepared for : Changzhou Kaidi Electrical Inc.
Address : JiangCun, Henglin Town, Changzhou City, Jiangsu
Province, China

Prepared by : EMTEK (NINGBO) CO., LTD.
Address : No. 8, Building 8, Lane 216, Qingyi Road, Ningbo High-Tech
Zone, Ningbo, Zhejiang, China

Tel: +86-574-27907998
Fax: +86-574-27721538

Report Number : ENB2412090056W00602R
Date(s) of Tests : December 09, 2024 to January 15, 2025
Date of Issue : March 17, 2025

TABLE OF CONTENT

TEST REPORT	1
1. FACILITIES AND ACCREDITATIONS	5
1.1. TEST FACILITY.....	5
1.2. LABORATORY ACCREDITATIONS AND LISTINGS.....	5
2. GENERAL PRODUCT INFORMATION	6
3. LIMIT	7
4. TEST RESULTS	8



Test Report Description

Applicant : Changzhou Kaidi Electrical Inc.
Address : JiangCun, Henglin Town, Changzhou City, Jiangsu Province, China
Manufacturer : Changzhou Kaidi Electrical Inc.
Address : JiangCun, Henglin Town, Changzhou City, Jiangsu Province, China
EUT : Handset
Model Name : KDH283A
Trademark : N/A

The device described above is tested by EMTEK (NINGBO) CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the FCC 1.1310 and KDB 447498 D01 General RF Exposure Guidance v07 requirements. The test results are contained in this report and EMTEK (NINGBO) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of EMTEK (NINGBO) CO., LTD.

Date of Test : December 09, 2024 to January 15, 2025

Prepared by : 
WK Luo /Engineer

Reviewer : 
June Gao /Supervisor

Approved & Authorized Signer : 
Tony Wei/Manager

Modified Information

Version	Report No.	Revision Date	Summary
/	ENB2412090056W00602R	/	Original Report



1. Facilities And Accreditations

1.1. Test Facility

All measurement facilities used to collect the measurement data are located at
EMTEK (NINGBO) CO., LTD.

No. 8, Building 8, Lane 216, Qingyi Road, Ningbo Hi-Tech Zone, Ningbo, Zhejiang, China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 32.

1.2. LABORATORY ACCREDITATIONS AND LISTINGS

Site Description
EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L6666.

The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

Designation by FCC

Designation Number: CN1354

Test Firm Registration Number: 427606

Accredited by A2LA

The Certificate Number is 4321.03.

The certificate is valid until May 31, 2025

Designation by Industry Canada

The Conformity Assessment Body Identifier is CN0114

Name of Firm

: EMTEK (NINGBO) CO., LTD.

Site Location

: No. 8, Building 8, Lane 216, Qingyi Road, Hi-Tech Zone, Ningbo,
Zhejiang, China

2. General Product Information

Characteristics	Description
Product:	Handset
Model Number:	KDH283A
Sample Number:	ENB2412090056W006-1-1
Modulation:	GFSK
Operating Frequency:	2440 MHz
Number of Channels:	1 channel
Max Transmit Power:	92.03 dBuV/m
Antenna Type :	PCB Antenna
Antenna Gain:	4.07 dBi
Power supply:	DC 4.5V for Battery
Temperature Range:	-40°C ~ +85°C
Date of Received:	December 09, 2024

Note: for more details, please refer to the User's manual of the EUT.

3. Limit

According to §15.249(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V07

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

4. Test Results

Maximum measured transmitter power:
 $EIRP = E + 20 \log(d) - 104.7 = 92.03 + 9.54 - 104.7 = -3.13 \text{ dBm}$

Transmit Frequency (MHz)	Mode	EIRP Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
2440	GFSK	-3.13 dBm	-3.0	0.16	3

Conclusion:
 For the max result : $0.16 \leq 3.0$ for 1-g SAR extremity SAR.

*** End of Report ***



声明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效；

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.