

Appendix S1

Test Information:

Sample No.:	34AK-1	Test Date:	2025/07/03
Test Site:	RF	Test Mode:	Transmitting
Tester:	Leo Lin	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	57	ATM Pressure: (kPa)	100.2
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Frequency Stability

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (1850MHz)	Upper Edge(MHz) (Result)	Limit (1910MHz)	Environment
20MHz Bandwidth QPSK						
2	1860/1900	1850.038	1850.000	1909.997	1910.000	20°C/3.45V _{DC}
2	1860/1900	1850.048	1850.000	1909.963	1910.000	20°C/4.40V _{DC}
2	1860/1900	1850.139	1850.000	1909.975	1910.000	-30°C/3.85V _{DC}
2	1860/1900	1850.123	1850.000	1909.984	1910.000	-20°C/3.85V _{DC}
2	1860/1900	1850.052	1850.000	1909.961	1910.000	-10°C/3.85V _{DC}
2	1860/1900	1850.070	1850.000	1909.969	1910.000	0°C/3.85V _{DC}
2	1860/1900	1850.013	1850.000	1909.973	1910.000	10°C/3.85V _{DC}
2	1860/1900	1850.003	1850.000	1909.980	1910.000	20°C/3.85V _{DC}
2	1860/1900	1850.059	1850.000	1909.976	1910.000	30°C/3.85V _{DC}
2	1860/1900	1850.150	1850.000	1909.988	1910.000	40°C/3.85V _{DC}
2	1860/1900	1850.000	1850.000	1909.955	1910.000	50°C/3.85V _{DC}
20MHz Bandwidth 16QAM						
2	1860/1900	1850.017	1850.000	1909.995	1910.000	20°C/3.45V _{DC}
2	1860/1900	1850.020	1850.000	1909.994	1910.000	20°C/4.40V _{DC}
2	1860/1900	1850.051	1850.000	1909.966	1910.000	-30°C/3.85V _{DC}
2	1860/1900	1850.118	1850.000	1909.989	1910.000	-20°C/3.85V _{DC}
2	1860/1900	1850.032	1850.000	1909.982	1910.000	-10°C/3.85V _{DC}
2	1860/1900	1850.084	1850.000	1909.952	1910.000	0°C/3.85V _{DC}
2	1860/1900	1850.147	1850.000	1909.994	1910.000	10°C/3.85V _{DC}
2	1860/1900	1850.053	1850.000	1909.956	1910.000	20°C/3.85V _{DC}
2	1860/1900	1850.107	1850.000	1909.967	1910.000	30°C/3.85V _{DC}
2	1860/1900	1850.092	1850.000	1909.957	1910.000	40°C/3.85V _{DC}
2	1860/1900	1850.149	1850.000	1909.953	1910.000	50°C/3.85V _{DC}

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (1710MHz)	Upper Edge(MHz) (Result)	Limit (1755MHz)	Environment
20MHz Bandwidth QPSK						
4	1720/1745	1710.117	1710.000	1754.962	1755.000	20°C/3.45V _{DC}
4	1720/1745	1710.095	1710.000	1754.978	1755.000	20°C/4.40V _{DC}
4	1720/1745	1710.009	1710.000	1754.989	1755.000	-30°C/3.85V _{DC}
4	1720/1745	1710.095	1710.000	1754.962	1755.000	-20°C/3.85V _{DC}
4	1720/1745	1710.095	1710.000	1754.996	1755.000	-10°C/3.85V _{DC}
4	1720/1745	1710.134	1710.000	1754.950	1755.000	0°C/3.85V _{DC}
4	1720/1745	1710.108	1710.000	1754.988	1755.000	10°C/3.85V _{DC}
4	1720/1745	1710.100	1710.000	1754.998	1755.000	20°C/3.85V _{DC}
4	1720/1745	1710.042	1710.000	1754.956	1755.000	30°C/3.85V _{DC}
4	1720/1745	1710.114	1710.000	1754.993	1755.000	40°C/3.85V _{DC}
4	1720/1745	1710.104	1710.000	1754.952	1755.000	50°C/3.85V _{DC}
20MHz Bandwidth 16QAM						
4	1720/1745	1710.144	1710.000	1754.957	1755.000	20°C/3.45V _{DC}
4	1720/1745	1710.012	1710.000	1754.977	1755.000	20°C/4.40V _{DC}
4	1720/1745	1710.060	1710.000	1754.967	1755.000	-30°C/3.85V _{DC}
4	1720/1745	1710.009	1710.000	1754.979	1755.000	-20°C/3.85V _{DC}
4	1720/1745	1710.107	1710.000	1754.977	1755.000	-10°C/3.85V _{DC}
4	1720/1745	1710.038	1710.000	1754.977	1755.000	0°C/3.85V _{DC}
4	1720/1745	1710.157	1710.000	1754.995	1755.000	10°C/3.85V _{DC}
4	1720/1745	1710.086	1710.000	1754.957	1755.000	20°C/3.85V _{DC}
4	1720/1745	1710.169	1710.000	1754.965	1755.000	30°C/3.85V _{DC}
4	1720/1745	1710.122	1710.000	1754.967	1755.000	40°C/3.85V _{DC}
4	1720/1745	1710.144	1710.000	1754.992	1755.000	50°C/3.85V _{DC}

Band 5

Test Modulation:	10MHz QPSK		Test Channel:	836.5MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	9.26	0.01107	2.5
	-20	3.85	6.10	0.00729	2.5
	-10	3.85	-1.63	-0.00195	2.5
	0	3.85	2.29	0.00274	2.5
	10	3.85	3.03	0.00362	2.5
	20	3.85	5.28	0.00631	2.5
	30	3.85	8.26	0.00987	2.5
	40	3.85	6.58	0.00787	2.5
	50	3.85	6.11	0.00730	2.5
Frequency Stability vs. Voltage	20	3.45	0.28	0.00033	2.5
	20	4.40	-2.40	-0.00287	2.5

Test Modulation:	10MHz QPSK		Test Channel:	836.5MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	7.23	0.00864	2.5
	-20	3.85	2.21	0.00264	2.5
	-10	3.85	-5.90	-0.00705	2.5
	0	3.85	9.68	0.01157	2.5
	10	3.85	10.23	0.01223	2.5
	20	3.85	-3.83	-0.00458	2.5
	30	3.85	2.89	0.00345	2.5
	40	3.85	7.74	0.00925	2.5
	50	3.85	-6.90	-0.00825	2.5
Frequency Stability vs. Voltage	20	3.45	4.80	0.00574	2.5
	20	4.40	3.29	0.00393	2.5

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (2500MHz)	Upper Edge(MHz) (Result)	Limit (2570MHz)	Environment
20MHz Bandwidth QPSK						
7	2510/2560	2500.120	2500.000	2569.984	2570.000	20°C/3.45V _{DC}
7	2510/2560	2500.083	2500.000	2569.993	2570.000	20°C/4.40V _{DC}
7	2510/2560	2500.084	2500.000	2569.968	2570.000	-30°C/3.85V _{DC}
7	2510/2560	2500.097	2500.000	2569.986	2570.000	-20°C/3.85V _{DC}
7	2510/2560	2500.039	2500.000	2569.985	2570.000	-10°C/3.85V _{DC}
7	2510/2560	2500.141	2500.000	2569.958	2570.000	0°C/3.85V _{DC}
7	2510/2560	2500.214	2500.000	2569.961	2570.000	10°C/3.85V _{DC}
7	2510/2560	2500.049	2500.000	2569.990	2570.000	20°C/3.85V _{DC}
7	2510/2560	2500.078	2500.000	2569.981	2570.000	30°C/3.85V _{DC}
7	2510/2560	2500.215	2500.000	2569.958	2570.000	40°C/3.85V _{DC}
7	2510/2560	2500.222	2500.000	2569.953	2570.000	50°C/3.85V _{DC}
20MHz Bandwidth 16QAM						
7	2510/2560	2500.141	2500.000	2569.988	2570.000	20°C/3.45V _{DC}
7	2510/2560	2500.117	2500.000	2569.959	2570.000	20°C/4.40V _{DC}
7	2510/2560	2500.106	2500.000	2569.975	2570.000	-30°C/3.85V _{DC}
7	2510/2560	2500.112	2500.000	2569.963	2570.000	-20°C/3.85V _{DC}
7	2510/2560	2500.079	2500.000	2569.964	2570.000	-10°C/3.85V _{DC}
7	2510/2560	2500.111	2500.000	2569.974	2570.000	0°C/3.85V _{DC}
7	2510/2560	2500.159	2500.000	2569.961	2570.000	10°C/3.85V _{DC}
7	2510/2560	2500.076	2500.000	2569.966	2570.000	20°C/3.85V _{DC}
7	2510/2560	2500.061	2500.000	2569.984	2570.000	30°C/3.85V _{DC}
7	2510/2560	2500.193	2500.000	2569.959	2570.000	40°C/3.85V _{DC}
7	2510/2560	2500.182	2500.000	2569.965	2570.000	50°C/3.85V _{DC}

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (699MHz)	Upper Edge(MHz) (Result)	Limit (716MHz)	Environment
10MHz Bandwidth QPSK						
12	704/711	699.111	699.000	715.955	716.000	20°C/3.45V _{DC}
12	704/711	699.253	699.000	715.987	716.000	20°C/4.40V _{DC}
12	704/711	699.024	699.000	715.962	716.000	-30°C/3.85V _{DC}
12	704/711	699.092	699.000	715.995	716.000	-20°C/3.85V _{DC}
12	704/711	699.115	699.000	715.994	716.000	-10°C/3.85V _{DC}
12	704/711	699.361	699.000	715.953	716.000	0°C/3.85V _{DC}
12	704/711	699.044	699.000	715.986	716.000	10°C/3.85V _{DC}
12	704/711	699.163	699.000	715.978	716.000	20°C/3.85V _{DC}
12	704/711	699.240	699.000	715.954	716.000	30°C/3.85V _{DC}
12	704/711	699.480	699.000	715.981	716.000	40°C/3.85V _{DC}
12	704/711	699.275	699.000	715.973	716.000	50°C/3.85V _{DC}
10MHz Bandwidth 16QAM						
12	704/711	699.240	699.000	715.955	716.000	20°C/3.45V _{DC}
12	704/711	699.112	699.000	715.990	716.000	20°C/4.40V _{DC}
12	704/711	699.497	699.000	715.962	716.000	-30°C/3.85V _{DC}
12	704/711	699.413	699.000	715.987	716.000	-20°C/3.85V _{DC}
12	704/711	699.290	699.000	715.954	716.000	-10°C/3.85V _{DC}
12	704/711	699.021	699.000	715.973	716.000	0°C/3.85V _{DC}
12	704/711	699.036	699.000	715.982	716.000	10°C/3.85V _{DC}
12	704/711	699.260	699.000	715.972	716.000	20°C/3.85V _{DC}
12	704/711	699.228	699.000	715.981	716.000	30°C/3.85V _{DC}
12	704/711	699.214	699.000	715.986	716.000	40°C/3.85V _{DC}
12	704/711	699.307	699.000	715.962	716.000	50°C/3.85V _{DC}

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (777MHz)	Upper Edge(MHz) (Result)	Limit (787MHz)	Environment
10MHz Bandwidth QPSK						
13	782	777.218	777.000	786.958	787.000	20°C/3.45V _{DC}
13	782	777.125	777.000	786.954	787.000	20°C/4.40V _{DC}
13	782	777.234	777.000	786.941	787.000	-30°C/3.85V _{DC}
13	782	777.131	777.000	786.816	787.000	-20°C/3.85V _{DC}
13	782	777.243	777.000	786.901	787.000	-10°C/3.85V _{DC}
13	782	777.073	777.000	786.940	787.000	0°C/3.85V _{DC}
13	782	777.059	777.000	786.838	787.000	10°C/3.85V _{DC}
13	782	777.127	777.000	786.933	787.000	20°C/3.85V _{DC}
13	782	777.111	777.000	786.844	787.000	30°C/3.85V _{DC}
13	782	777.070	777.000	786.843	787.000	40°C/3.85V _{DC}
13	782	777.202	777.000	786.871	787.000	50°C/3.85V _{DC}
10MHz Bandwidth 16QAM						
13	782	777.046	777.000	786.981	787.000	20°C/3.45V _{DC}
13	782	777.015	777.000	786.994	787.000	20°C/4.40V _{DC}
13	782	777.124	777.000	786.979	787.000	-30°C/3.85V _{DC}
13	782	777.182	777.000	786.793	787.000	-20°C/3.85V _{DC}
13	782	777.112	777.000	786.883	787.000	-10°C/3.85V _{DC}
13	782	777.151	777.000	786.938	787.000	0°C/3.85V _{DC}
13	782	777.095	777.000	786.865	787.000	10°C/3.85V _{DC}
13	782	777.199	777.000	786.956	787.000	20°C/3.85V _{DC}
13	782	777.073	777.000	786.856	787.000	30°C/3.85V _{DC}
13	782	777.211	777.000	786.814	787.000	40°C/3.85V _{DC}
13	782	777.023	777.000	786.879	787.000	50°C/3.85V _{DC}

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (704MHz)	Upper Edge(MHz) (Result)	Limit (716MHz)	Environment
10MHz Bandwidth QPSK						
17	709/711	704.062	704.000	715.981	716.000	20°C/3.45V _{DC}
17	709/711	704.153	704.000	715.998	716.000	20°C/4.40V _{DC}
17	709/711	704.378	704.000	715.983	716.000	-30°C/3.85V _{DC}
17	709/711	704.297	704.000	715.982	716.000	-20°C/3.85V _{DC}
17	709/711	704.317	704.000	715.959	716.000	-10°C/3.85V _{DC}
17	709/711	704.372	704.000	715.965	716.000	0°C/3.85V _{DC}
17	709/711	704.148	704.000	715.978	716.000	10°C/3.85V _{DC}
17	709/711	704.022	704.000	715.961	716.000	20°C/3.85V _{DC}
17	709/711	704.394	704.000	715.994	716.000	30°C/3.85V _{DC}
17	709/711	704.433	704.000	715.960	716.000	40°C/3.85V _{DC}
17	709/711	704.022	704.000	715.984	716.000	50°C/3.85V _{DC}
10MHz Bandwidth 16QAM						
17	709/711	704.303	704.000	715.986	716.000	20°C/3.45V _{DC}
17	709/711	704.403	704.000	715.977	716.000	20°C/4.40V _{DC}
17	709/711	704.081	704.000	715.954	716.000	-30°C/3.85V _{DC}
17	709/711	704.114	704.000	715.984	716.000	-20°C/3.85V _{DC}
17	709/711	704.183	704.000	715.991	716.000	-10°C/3.85V _{DC}
17	709/711	704.161	704.000	715.977	716.000	0°C/3.85V _{DC}
17	709/711	704.129	704.000	715.965	716.000	10°C/3.85V _{DC}
17	709/711	704.314	704.000	715.988	716.000	20°C/3.85V _{DC}
17	709/711	704.369	704.000	715.975	716.000	30°C/3.85V _{DC}
17	709/711	704.402	704.000	715.953	716.000	40°C/3.85V _{DC}
17	709/711	704.222	704.000	715.980	716.000	50°C/3.85V _{DC}

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (1850MHz)	Upper Edge(MHz) (Result)	Limit (1915MHz)	Environment
20MHz Bandwidth QPSK						
25	1860/1905	1850.062	1850.000	1914.971	1915.000	20°C/3.45V _{DC}
25	1860/1905	1850.065	1850.000	1914.989	1915.000	20°C/4.40V _{DC}
25	1860/1905	1850.061	1850.000	1914.992	1915.000	-30°C/3.85V _{DC}
25	1860/1905	1850.055	1850.000	1914.995	1915.000	-20°C/3.85V _{DC}
25	1860/1905	1850.063	1850.000	1914.998	1915.000	-10°C/3.85V _{DC}
25	1860/1905	1850.034	1850.000	1914.962	1915.000	0°C/3.85V _{DC}
25	1860/1905	1850.050	1850.000	1914.960	1915.000	10°C/3.85V _{DC}
25	1860/1905	1850.092	1850.000	1914.953	1915.000	20°C/3.85V _{DC}
25	1860/1905	1850.044	1850.000	1914.957	1915.000	30°C/3.85V _{DC}
25	1860/1905	1850.047	1850.000	1914.997	1915.000	40°C/3.85V _{DC}
25	1860/1905	1850.052	1850.000	1914.986	1915.000	50°C/3.85V _{DC}
20MHz Bandwidth 16QAM						
25	1860/1905	1850.051	1850.000	1914.965	1915.000	20°C/3.45V _{DC}
25	1860/1905	1850.045	1850.000	1914.961	1915.000	20°C/4.40V _{DC}
25	1860/1905	1850.056	1850.000	1914.968	1915.000	-30°C/3.85V _{DC}
25	1860/1905	1850.059	1850.000	1914.988	1915.000	-20°C/3.85V _{DC}
25	1860/1905	1850.005	1850.000	1914.958	1915.000	-10°C/3.85V _{DC}
25	1860/1905	1850.076	1850.000	1914.960	1915.000	0°C/3.85V _{DC}
25	1860/1905	1850.056	1850.000	1914.965	1915.000	10°C/3.85V _{DC}
25	1860/1905	1850.058	1850.000	1914.979	1915.000	20°C/3.85V _{DC}
25	1860/1905	1850.046	1850.000	1914.978	1915.000	30°C/3.85V _{DC}
25	1860/1905	1850.047	1850.000	1914.961	1915.000	40°C/3.85V _{DC}
25	1860/1905	1850.048	1850.000	1914.989	1915.000	50°C/3.85V _{DC}

Band 26_1

Test Modulation:	15MHz QPSK		Test Channel:	821.5MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	-19.32	-0.02352	2.5
	-20	3.85	-25.81	-0.03142	2.5
	-10	3.85	-17.53	-0.02134	2.5
	0	3.85	-18.54	-0.02257	2.5
	10	3.85	-22.46	-0.02734	2.5
	20	3.85	-18.56	-0.02259	2.5
	30	3.85	-24.49	-0.02981	2.5
	40	3.85	-20.09	-0.02446	2.5
	50	3.85	-18.47	-0.02248	2.5
Frequency Stability vs. Voltage	20	3.45	-19.16	-0.02332	2.5
	20	4.40	-21.74	-0.02646	2.5

Test Modulation:	15MHz 16QAM		Test Channel:	821.5MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	-25.09	-0.03054	2.5
	-20	3.85	-21.10	-0.02568	2.5
	-10	3.85	-20.96	-0.02551	2.5
	0	3.85	-21.17	-0.02577	2.5
	10	3.85	-21.68	-0.02639	2.5
	20	3.85	-22.08	-0.02688	2.5
	30	3.85	-24.13	-0.02937	2.5
	40	3.85	-19.19	-0.02336	2.5
	50	3.85	-18.76	-0.02284	2.5
Frequency Stability vs. Voltage	20	3.45	-14.07	-0.01713	2.5
	20	4.40	-23.23	-0.02828	2.5

Band 26_2

Test Modulation:	15MHz QPSK		Test Channel:	836.5MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	-15.69	-0.01876	2.5
	-20	3.85	-20.18	-0.02412	2.5
	-10	3.85	-10.30	-0.01231	2.5
	0	3.85	-4.93	-0.00589	2.5
	10	3.85	-7.74	-0.00925	2.5
	20	3.85	-15.21	-0.01818	2.5
	30	3.85	-6.88	-0.00822	2.5
	40	3.85	-7.81	-0.00934	2.5
	50	3.85	-13.38	-0.01600	2.5
Frequency Stability vs. Voltage	20	3.45	-7.56	-0.00904	2.5
	20	4.40	-20.63	-0.02466	2.5

Test Modulation:	15MHz 16QAM		Test Channel:	836.5MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	7.94	0.00900	2.5
	-20	3.85	-3.76	-0.00400	2.5
	-10	3.85	-7.26	-0.00868	2.5
	0	3.85	-0.55	-0.00066	2.5
	10	3.85	0.36	0.00043	2.5
	20	3.85	9.56	0.01143	2.5
	30	3.85	19.37	0.02316	2.5
	40	3.85	15.88	0.01898	2.5
	50	3.85	-14.30	-0.01710	2.5
Frequency Stability vs. Voltage	20	3.45	8.99	0.01075	2.5
	20	4.40	-6.64	-0.00794	2.5

Band 26_3

Test Modulation:	15MHz QPSK		Test Channel:	824MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	-7.61	-0.00924	2.5
	-20	3.85	-14.03	-0.01703	2.5
	-10	3.85	-16.18	-0.01964	2.5
	0	3.85	0.77	0.00093	2.5
	10	3.85	4.18	0.00507	2.5
	20	3.85	-16.38	-0.01988	2.5
	30	3.85	-4.19	-0.00508	2.5
	40	3.85	-6.15	-0.00746	2.5
	50	3.85	-2.41	-0.00292	2.5
Frequency Stability vs. Voltage	20	3.45	-10.33	-0.01254	2.5
	20	4.40	-7.19	-0.00873	2.5

Test Modulation:	15MHz 16QAM		Test Channel:	824MHz	
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	-5.55	-0.00674	2.5
	-20	3.85	-12.35	-0.01499	2.5
	-10	3.85	-11.15	-0.01353	2.5
	0	3.85	-1.25	-0.00152	2.5
	10	3.85	-3.99	-0.00484	2.5
	20	3.85	-15.00	-0.01820	2.5
	30	3.85	-2.77	-0.00336	2.5
	40	3.85	-8.94	-0.01085	2.5
	50	3.85	-5.10	-0.00619	2.5
Frequency Stability vs. Voltage	20	3.45	-7.45	-0.00904	2.5
	20	4.40	-11.37	-0.01380	2.5

Band	Freq (MHz)	Lower Edge (MHz) (Result)	Limit (1710MHz)	Upper Edge(MHz) (Result)	Limit (1780MHz)	Environment
20MHz Bandwidth QPSK						
66	1720/1770	1710.083	1710.000	1779.954	1780.000	20°C/3.45V _{DC}
66	1720/1770	1710.124	1710.000	1779.970	1780.000	20°C/4.40V _{DC}
66	1720/1770	1710.047	1710.000	1779.982	1780.000	-30°C/3.85V _{DC}
66	1720/1770	1710.115	1710.000	1779.974	1780.000	-20°C/3.85V _{DC}
66	1720/1770	1710.150	1710.000	1779.967	1780.000	-10°C/3.85V _{DC}
66	1720/1770	1710.124	1710.000	1779.952	1780.000	0°C/3.85V _{DC}
66	1720/1770	1710.010	1710.000	1779.954	1780.000	10°C/3.85V _{DC}
66	1720/1770	1710.082	1710.000	1779.981	1780.000	20°C/3.85V _{DC}
66	1720/1770	1710.129	1710.000	1779.985	1780.000	30°C/3.85V _{DC}
66	1720/1770	1710.128	1710.000	1779.992	1780.000	40°C/3.85V _{DC}
66	1720/1770	1710.000	1710.000	1779.963	1780.000	50°C/3.85V _{DC}
20MHz Bandwidth 16QAM						
66	1720/1770	1710.020	1710.000	1779.998	1780.000	20°C/3.45V _{DC}
66	1720/1770	1710.024	1710.000	1779.994	1780.000	20°C/4.40V _{DC}
66	1720/1770	1710.020	1710.000	1779.955	1780.000	-30°C/3.85V _{DC}
66	1720/1770	1710.089	1710.000	1779.954	1780.000	-20°C/3.85V _{DC}
66	1720/1770	1710.139	1710.000	1779.995	1780.000	-10°C/3.85V _{DC}
66	1720/1770	1710.105	1710.000	1779.951	1780.000	0°C/3.85V _{DC}
66	1720/1770	1710.149	1710.000	1779.994	1780.000	10°C/3.85V _{DC}
66	1720/1770	1710.084	1710.000	1779.971	1780.000	20°C/3.85V _{DC}
66	1720/1770	1710.090	1710.000	1779.963	1780.000	30°C/3.85V _{DC}
66	1720/1770	1710.112	1710.000	1779.985	1780.000	40°C/3.85V _{DC}
66	1720/1770	1710.116	1710.000	1779.962	1780.000	50°C/3.85V _{DC}