

FCC TEST REPORT

No. 170800863SHA-001

Applicant : Jiangsu Selon Electric Appliances Co., Ltd.
19 LiangfengRoad, 1st district ,Yuanshan Industrial Park,
Changshu, Jiangsu, P.R.China

Manufacturing Site : Same as applicant

Product Name : Beverage cooler

Type/Model : RB-RDC ECO LED

TEST RESULT : PASS

SUMMARY

The equipment complies with the requirements according to the following standard(s) or specification:

47CFR Part 15 (2016): Radio Frequency Devices

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Date of issue: December 11, 2017

Prepared by:



Eric Li (Project Engineer)

Reviewed by:



Daniel Zhao (Reviewer)

Description of Test Facility

Name: Intertek Testing Service Limited Shanghai
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R. China

FCC Registration Number: 236597
IC Assigned Code: 2402B-1

Name of contact: Jonny Jing
Tel: 86 21 61278271
Fax: 86 21 54262353

Content

SUMMARY.....	1
1 GENERAL INFORMATION.....	5
1.1 Description of Client	5
1.2 Identification of the EUT	5
1.3 Technical Specification.....	6
2 TEST SPECIFICATIONS.....	8
2.1 Standards or specification	8
2.2 Antenna Requirement:	8
2.3 Instrument list.....	9
2.4 Test Summary	10
2.5 Frequency Hopping System Requirement	11
2.6 Measurement uncertainty	12
3 20 dB BANDWIDTH.....	13
3.1 Limit	13
3.2 Test Configuration.....	13
3.3 Test Procedure and test setup.....	13
3.4 Test Protocol.....	14
4 CARRIER FREQUENCY SEPARATION	21
4.1 Limit	21
4.2 Test Configuration.....	21
4.3 Test Procedure and test setup.....	21
4.4 Test Protocol.....	22
5 MAXIMUM PEAK OUTPUT POWER	29
5.1 Test limit	29
5.2 Test Configuration.....	29
5.3 Test procedure and test setup.....	29
5.4 Test protocol	31
6 RADIATED SPURIOUS EMISSIONS.....	37
6.1 Test limit	37
6.2 Test Configuration.....	37
6.3 Test procedure and test setup.....	38
6.4 Test protocol	39
7 CONDUCTED SPURIOUS EMISSIONS & BAND EDGE.....	42
7.1 Limit	42
7.2 Test Configuration.....	42
7.3 Test procedure and test setup.....	42
7.4 Test protocol	43
8 POWER LINE CONDUCTED EMISSION.....	57
8.1 Limit	57
8.2 Test configuration	57
8.3 Test procedure and test set up	58
8.4 Test protocol	59
9 NUMBER OF HOPPING FREQUENCIES	61
9.1 Limit	61

9.2	Test Configuration.....	61
9.3	Test procedure and test setup.....	61
9.4	Test protocol.....	61
10	DWELL TIME.....	64
10.1	Limit	64
10.2	Test Configuration.....	64
10.3	Test procedure and test setup.....	64
10.4	Test protocol.....	65
11	OCCUPIED BANDWIDTH.....	69
11.1	Test limit	69
11.2	Test Configuration.....	69
11.3	Test procedure and test setup.....	69
11.4	Test protocol.....	69

1 GENERAL INFORMATION

1.1 Description of Client

Applicant : Jiangsu Selon Electric Appliances Co., Ltd.
19 Liangfeng Road, 1st district ,Yuanshan Industrial Park, Changshu, Jiangsu, P.R.China

Name of contact : Ni Xiaojun

Tel : 0512-52852999

Fax : 0512-52852999

Email : qc@chinabaixue.com

Manufacturing Site : Same as applicant

19 Lianfeng Road, 1st District, Yushan Industrial Park, Changshu, Jiangsu, P.R.CHINA

1.2 Identification of the EUT


Product Name : Beverage cooler

Type/model : RB-RDC ECO LED

FCC ID : 2AOWQ-VC214677

1.3 Technical Specification

Operation Frequency : 2402 - 2480 MHz
 Band
 Type of Modulation : BT 2.1 (BR+EDR)
 EUT Modes of Modulation : GFSK, $\pi/4$ DQPSK, 8DPSK



GFSK is different from $\pi/4$ DQPSK and 8DPSK. 8DPSK is similar with $\pi/4$ DQPSK but more complex, and with a bigger data rate. So all the tests except output power, occupied bandwidth, dwell time and number of hopping frequencies were performed with GFSK modulation and 8DPSK modulation for representative.

Channel Number : 79
 Description of EUT : The EUT is a portable active speaker, which contains a Bluetooth function, and there have only one model, We tested it and listed the BT results in this report.
 Port identification : DC Input *1;
 Antenna : Internal PCB antenna 0.5dBi
 Rating : DC IN 13.5V
 Category of EUT : Class B
 EUT type : Table top
 Floor standing
 Sample received date : November 10,2017
 Sample Identification No : NA
 Date of test : November 20,2017~ November 30,2017

1.4 Mode of operation during the test / Test peripherals used

While testing the transmitter mode of the EUT, the internal modulation is applied. All the functions of the host device except the BT module were set on stand-by mode.

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

Three axes (X, Y, Z) were observed while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded. Compare with the test results that Z axis is the worst case.

Radiated test mode:

Mode 1: EUT transmitted signal with BT antenna;

Conducted test mode:

Mode 2: EUT transmitted signal from BT RF port connected to SPA directly;

The worst case modulation configuration:

Worst Modulation Used for Conformance Testing			
Bluetooth Mode	Packet Type	Data Rate	Worst Mode
GFSK	BR-1Mbps	DH1,DH3,DH5	BR-1Mbps DH5
$\pi/4$ DQPSK	EDR-2Mbps	2DH1,2DH3,2DH5	EDR-2Mbps 2DH5
8DPSK	EDR-3Mbps	3DH1,3DH3,3DH5	EDR-3Mbps 3DH5

Note: The BR-1Mbps DH5 mode was chosen for radiation emission bellow 1GHz and Conducted emission testing as representative in this report.

The power setting parameter:

The worst case power setting parameter			
Test software Version	CSR Bluesuite 2.4.8		
Modulation Mode	2402MHz	2441MHz	2480MHz
BR-1Mbps	Default	Default	Default
EDR-2Mbps	Default	Default	Default
EDR-3Mbps	Default	Default	Default

Test Peripherals:

Equipment	Brand Name	Model	Note
Notebook	HP	6470b	

Note: The accessories are used for configuration only and not used during test.

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2014)

ANSI C63.10 (2013)

KDB 558074 (V03R02)

2.2 Antenna Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The EUT used an internal PCB antenna, so fulfill these requirements.

2.3 Instrument list

Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2018-10-18
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2018-05-30
<input checked="" type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2018-09-22
<input type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2018-08-23
<input checked="" type="checkbox"/>	Pre-amplifier	R&S	Pre-amp 18	EC5881	2018-06-19
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2018-09-08
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2018-09-10
<input checked="" type="checkbox"/>	Power sensor	Agilent	U2021XA	EC 5338-1	2018-03-03
<input checked="" type="checkbox"/>	Vector Signal Generator	Agilent	N5182B	EC 5175	2018-03-06
<input checked="" type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2018-03-03
<input checked="" type="checkbox"/>	Mobile Test System	Litepoint	Iqxel	EC 5176	2018-01-11
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCI 7	EC 4501	2018-02-23
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3323	2018-06-14
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3324	2018-04-09
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3325	2018-03-23
<input checked="" type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 3320	2018-06-28

2.4 Test Summary

This report applies to tested sample only. The test results have been compared directly with the limits, and the measurement uncertainty is recorded. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

TEST ITEM	FCC REFERANCE	RESULT
20 dB Bandwidth	15.247(a)(1)	Pass
Carrier Frequency Separation	15.247(a)(1)	Pass
Output power	15.247(b)(1)	Pass
Radiated Spurious Emissions	15.205 & 15.209	Pass
Conducted Spurious Emissions & Band Edge	15.247(d)	Pass
Power line conducted emission	15.207	Pass
Number of Hopping Frequencies	15.247(a)(1)(iii)	Pass
Dwell time	15.247(a)(1)(iii)	Pass
Occupied bandwidth	-	Tested
Spurious emission for receiver	15B	NA

Notes: 1: NA =Not Applicable

2: This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

2.5 Frequency Hopping System Requirement

Test Requirement: Section 15.247 (a)(1), (g), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)


According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

2.6 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	± 0.74dB
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Emission outside the frequency band	± 2.89dB
Power line conducted emission	± 3.19dB


3 20 dB Bandwidth

Test result: Pass

3.1 Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

3.2 Test Configuration



3.3 Test Procedure and test setup

The 20 bandwidth per FCC §15.247(a)(1) is measured using the Spectrum Analyzer with Span =2 to 3 times the 20 dB bandwidth, RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW, Sweep = auto, Detector = peak, Trace = max hold.

The test was performed at 3 channels (lowest, middle and highest channel).

The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

3.4 Test Protocol


Temperature: 24°C

Relative Humidity: 52%


Modulation	CH	Bandwidth (kHz)	Two-thirds of Bandwidth (kHz)	Result
GFSK	L	1040	693	Pass
	M	1043	695	Pass
	H	1050	700	Pass

Modulation	Channel	99% Occupied Bandwidth (kHz)
GFSK	L	981.51
	M	984.03
	H	1000.2

Channel L



Channel M




Channel H



Modulation	CH	Bandwidth (kHz)	Two-thirds of Bandwidth (kHz)	Result
$\pi/4$ DQPSK	L	1094	729	Pass
	M	1082	721	Pass
	H	1164	776	Pass

Modulation	Channel	99% Occupied Bandwidth (kHz)
$\pi/4$ DQPSK	L	1046.3
	M	1063.4
	H	1144.4

Channel L



Channel M




Channel H




Modulation	CH	Bandwidth (kHz)	Two-thirds of Bandwidth (kHz)	Result
8DPSK	L	1120	746	Pass
	M	1177	785	Pass
	H	1197	798	Pass

Modulation	Channel	99% Occupied Bandwidth (kHz)
8DPSK	L	1108.9
	M	1161.3
	H	1247.1

Channel L



Channel M



Channel H




4 Carrier Frequency Separation

Test result: Pass

4.1 Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

4.2 Test Configuration



4.3 Test Procedure and test setup

The Carrier Frequency Separation per FCC §15.247(a)(1) is measured using the Spectrum Analyzer with Span can capture two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector = peak, Trace = max hold. The test was performed at 3 channels (lowest, middle and highest channel). The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

4.4 Test Protocol

Temperature : 25°C
 Relative Humidity : 55 %

Mode	CH	Frequency Separation (kHz)	Limit (kHz)	Result
GFSK	L	993	≥693	Pass
	M	993	≥695	Pass
	H	996	≥700	Pass



Channel M



Channel H



Mode	CH	Frequency Separation (kHz)	Limit (kHz)	Result
$\pi/4$ DQPSK	L	1002	≥ 729	Pass
	M	999	≥ 721	Pass
	H	1002	≥ 776	Pass

Channel L



Channel M



Channel H



Mode	CH	Frequency Separation (kHz)	Limit (kHz)	Result
8DPSK	L	999	≥746	Pass
	M	1029	≥785	Pass
	H	975	≥798	Pass

Channel L



Channel M



Channel H



5 Maximum peak output power

Test result: Pass


5.1 Test limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts
If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

5.2 Test Configuration



5.3 Test procedure and test setup

The power output per FCC §15.247(b) is measured using the Spectrum Analyzer with Span = 5 times the 20 dB bandwidth, RBW \geq the 20 dB bandwidth, VBW \geq RBW, Sweep = auto, Detector = peak, Trace = max hold.

The test was performed at 3 channels (lowest, middle and highest channel).



Total Quality. Assured.

The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

Test report no. 170901163SHA-001
Page 30 of 69

5.4 Test protocol

Temperature : 25 °C
 Relative Humidity : 55 %

Mode	CH	Cable loss (dB)	Corrected reading (dBm)	Limit (dBm)
GFSK (DH5)	L	0.8	-0.570	≤21.00
	M	0.8	-1.351	
	H	0.8	-2.252	

Channel L




Channel M




Channel H




Mode	CH	Cable loss (dB)	Corrected reading (dBm)	Limit (dBm)
$\pi/4$ DQPSK (2DH5)	L	0.8	-0.603	≤ 21.00
	M	0.8	-1.351	
	H	0.8	-2.267	



Channel M




Channel H



Mode	CH	Cable loss (dB)	Corrected reading (dBm)	Limit (dBm)
8DPSK (3DH5)	L	0.8	-0.609	≤ 21.00
	M	0.8	-1.378	
	H	0.8	-2.279	



Channel M



Channel H



6 Radiated Spurious Emissions


Test result: Pass

6.1 Test limit

The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

6.2 Test Configuration



6.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, if applied, the pre-amplifier would be equipped just at the output terminal of the antenna.

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m.

The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

The radiated emission was measured using the Spectrum Analyzer with the resolutions bandwidth set as:

RBW = 100 kHz, VBW = 300 kHz (30MHz~1GHz)
RBW = 1MHz, VBW = 3MHz (>1GHz for PK);



Remark: 1. For fundamental emission, no amplifier is employed.
2. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
3. Corrected Reading = Original Receiver Reading + Correct Factor
4. Margin = limit – Corrected Reading
5. If the PK reading is lower than AV limit, the AV test can be elided.
6. The emission was conducted from 30MHz to 25GHz.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV.
Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$; Corrected Reading
= $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$
Assuming limit = 54dBuV/m, Corrected Reading = 10.20dBuV/m, then
Margin = $54 - 10.20 = 43.80\text{dBuV/m}$

6.4 Test protocol

Temperature : 25 °C
 Relative Humidity : 55 %

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



Test data (30MHz~1GHz, GFSK (DH5) Mode):

Polarization	Frequency (MHz)	Measured level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
H	30.00	20.70	40.00	19.30	PK
	49.44	22.00	40.00	18.00	PK
	64.99	20.30	40.00	19.70	PK
	119.42	21.30	43.50	22.20	PK
	123.31	25.30	43.50	18.20	PK
	197.17	29.60	43.50	13.90	PK
	344.91	26.00	46.00	20.00	PK
	368.24	35.90	46.00	10.10	PK
	541.24	30.60	46.00	15.40	PK
	955.29	30.40	46.00	15.60	PK
V	30.00	20.90	40.00	19.10	PK
	43.61	13.80	40.00	26.20	PK
	74.71	14.00	40.00	26.00	PK
	121.36	17.30	43.50	26.20	PK
	123.31	21.20	43.50	22.30	PK
	245.77	34.20	46.00	11.80	PK
	294.37	32.00	46.00	14.00	PK
	418.78	33.00	46.00	13.00	PK
	585.95	28.00	46.00	18.00	PK
	955.29	30.20	46.00	15.80	PK

Test Data (>1GHz):

GFSK (DH5) Modulation:

H	Antenna	Frequency (MHz)	Corrected Reading (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
L	H	2402.00	71.50	Fundamental	/	PK
	H	2390.00	43.80	74.00	30.20	PK
	H	7206.00	41.10	74.00	32.90	PK
M	V	2442.00	71.70	Fundamental	/	PK
	V	4882.00	32.20	74.00	41.80	PK
H	H	2480.00	69.70	Fundamental	/	PK
	V	2483.50	44.40	74.00	29.60	PK
	V	4960.00	37.60	74.00	36.40	PK

π/4DQPSK (2DH5) Modulation:

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	72.10	Fundamental	/	PK
	H	2389.98	42.90	74.00	31.10	PK
	H	4804.00	32.80	74.00	41.20	PK
M	V	2442.00	71.90	Fundamental	/	PK
	V	4882.00	33.60	74.00	40.40	PK
H	H	2480.00	70.50	Fundamental	/	PK
	V	2483.50	44.90	74.00	29.10	PK
	V	4960.00	36.60	74.00	37.40	PK

8DPSK (3DH5) Modulation:

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	74.80	Fundamental	/	PK
	H	2390.00	42.10	74.00	31.90	PK
	H	4804.00	30.20	74.00	43.80	PK
M	V	2442.00	73.40	Fundamental	/	PK
	V	4882.00	34.30	74.00	39.70	PK
H	H	2480.00	71.10	Fundamental	/	PK
	V	2483.50	43.50	74.00	30.50	PK
	V	4960.00	36.90	74.00	37.10	PK


7 Conducted Spurious Emissions & Band Edge

Test result: Pass

7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Test procedure and test setup

The Conducted Spurious Emissions per FCC §15.247(d) is measured using the Spectrum Analyzer with Span wide enough capturing all spurious from the lowest emission frequency of the EUT up to 10th harmonics, RBW = 100kHz, VBW \geq RBW, Sweep = auto, Detector = peak, Trace = max hold.

The test was performed at 2 channels (lowest and highest channel).



The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

7.4 Test protocol


Temperature : 25 °C
 Relative Humidity : 55 %



GFSK Channel- L









GFSK Channel- H









$\pi/4$ DQPSK Channel- L








π/4 DQPSK Channel- H









8DPSK Channel- L








8DPSK Channel- H





Hopping





8 Power line conducted emission


Test result: Pass

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

8.2 Test configuration



- For table top equipment, wooden support is 0.8m height table
- For floor standing equipment, wooden support is 0.12m height rack.

8.3 Test procedure and test set up

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50Ω/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50Ω/50uH coupling impedance with 50Ω termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement.

The bandwidth of the test receiver is set at 9 kHz.


The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems)

8.4 Test protocol

Temperature :23 °C

Relative Humidity :48 %


Test Curve:



Test Data:

Frequency (MHz)	Quasi-peak			Average			Line
	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	
0.52	38.87	56.00	17.13	24.53	46.00	21.47	24.53
0.54	41.65	56.00	14.35	23.20	46.00	22.80	23.20
0.64	42.50	56.00	13.50	25.57	46.00	20.43	25.57
0.68	42.14	56.00	13.86	24.10	46.00	21.90	24.10
0.73	41.71	56.00	14.29	24.81	46.00	21.19	24.81
0.80	41.81	56.00	14.19	28.00	46.00	18.00	28.00

Note: * means the emission level 20dB below the relevant limit.

N line

Test Data:

Frequency (MHz)	Quasi-peak			Average			Line
	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	Corrected Reading (dBuV)	Limit (dBuV)	Margin (dB)	
0.28	42.49	60.76	18.27	32.02	50.76	18.74	32.02
0.29	40.92	60.56	19.64	27.73	50.56	22.83	27.73
0.37	34.53	58.44	23.91	23.50	48.44	24.94	23.50
0.43	31.25	57.31	26.06	18.61	47.31	28.70	18.61
0.52	36.49	56.00	19.51	23.80	46.00	22.20	23.80
0.60	36.60	56.00	19.40	22.99	46.00	23.01	22.99

Note: * means the emission level 20dB below the relevant limit.


9 Number of Hopping Frequencies

Test result: Pass

9.1 Limit

Number of Hopping Frequencies in the 2400-2483.5 MHz band shall use at least 15 channels.

9.2 Test Configuration



9.3 Test procedure and test setup



The channel number per FCC §15.247(a)(1)(iii) is measured using the Spectrum Analyzer with RBW=100kHz, VBW≥RBW, Sweep = auto, Detector = peak, Trace = max hold.



The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems).

9.4 Test protocol

Temperature : 25 °C
Relative Humidity : 55 %

Channel Number	Limit
79	≥15






10 Dwell Time

Test result: **Pass**

10.1 Limit

The dwell time on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2 Test Configuration



10.3 Test procedure and test setup

Dwell time per FCC §15.247(a)(1)(iii) is measured using the Spectrum Analyzer with Span = 0, RBW=1MHz, VBW \geq RBW, Sweep can capture the entire dwell time, Detector = peak, Trace = max hold.

The EUT was tested according to DA 00-705 (Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems).

10.4 Test protocol

Temperature : 25 °C
 Relative Humidity : 55 %

8DPSK Modulation:



Packet	Occupancy time for single hop (ms) O	CH	Real observed period (s) P	Hops among Observed period I	Dwell time (ms) T	Limit (s)
DH1	0.426	L	3.16	31	132.06	≤0.4
		M	3.16	31	132.06	
		H	3.16	31	132.06	
DH3	1.695	L	3.16	15	254.25	≤0.4
		M	3.16	15	254.25	
		H	3.16	15	254.25	
DH5	2.948	L	3.16	11	324.48	≤0.4
		M	3.16	11	324.48	
		H	3.16	11	324.48	

Remark: 1. There are 79 channels in all. So the complete observed period $P = 0.4 * 79 = 31.6$ s.


2. Average time of occupancy $T = O * I * 31.6 / P$

DH1





DH5




11 Occupied Bandwidth

Test result: Same as the 20

11.1 Test limit

None

11.2 Test Configuration



11.3 Test procedure and test setup

The occupied bandwidth per RSS-Gen Issue 4 Clause 6.6 was measured using the Spectrum Analyzer with the RBW in the range of 1% to 5% of the occupied bandwidth (OBW)

, VBW = 3 * RBW Detector = peak hold.

11.4 Test protocol