

RF TEST REPORT

Test Equipment : Smart Bluetooth Receiver
Model Name : POLA-BTR01
FCC ID : 2AOXPPOLA-BTR01
Date of receipt : 2018.03.08
Test duration : 2018.04.09 ~ 2018.04.12
Date of issue : 2018.04.12

Applicant : GMK Co., Ltd.
Rm#1308, Kolon Digital Tower Aston, Gasan digital 1-ro
Geumcheon-gu, Seoul, Republic of Korea

Test Laboratory : Lab-T, Inc.
2182-42 Baegok-daero, Mohyeon-myeon, Cheoin-gu, Yongin-si
Gyeonggi-do 17036, Korea


Test specification : FCC Part 15 Subpart C 15.247
RF Output Power : 2.67 dBm
Test result : Pass

The above equipment was tested by Lab-T Testing Laboratory for compliance
with the requirements of FCC,IC Rules and Regulations.
The test results presented in this test report are limited only to the sample supplied by applicant
and the use of this test report is inhibited other than its purpose.
This test report shall not be reproduced except in full, without the written approval of Lab-T, Inc

Tested by:


Engineer
SungSin Kim

Reviewed by:


Technical Manager
SangHoon Yu

CONTENTS

1. Applicant Information.....	3
2. Laboratory Information.....	3
3. Information About Test Equipment	4
3.1 Equipment Information	4
3.2 Antenna Information	4
3.3 Test Frequency	4
3.4 Worst-Case	4
3.5 Tested Companion Device Information	4
4. Test Report.....	5
4.1 Summary	5
4.2 Measurement Uncertainty.....	6
4.3 Test Report Version	6
4.4 Transmitter Requirements	7
4.4.1 Antenna Requirement.....	7
4.4.2 20 dB Bandwidth and Occupied Bandwidth.....	8
4.4.3 Number of Hopping Frequencies	13
4.4.4 Time of occupancy (Dwell Time)	15
4.4.5 Carrier Frequencies Separation	17
4.4.6 Peak Output Power	21
4.4.7 Spurious Emission, Band Edge, and Restricted bands	25
4.4.8 Conducted Emission	42
APPENDIX I.....	44

1. Applicant Information

Applicant : GMK Co., Ltd.
Address : Rm#1308, Kolon Digital Tower Aston, Gasan digital 1-ro, Geumcheon-gu
Telephone No. : +82-2-2082-8270
Person in charge : Wayne Son / wayne.son@gmkay.com

Manufacturer : GMK Co., Ltd.
Address : Rm#1308, Kolon Digital Tower Aston, Gasan digital 1-ro, Geumcheon-gu
Seoul, Republic of Korea

2. Laboratory Information

Test Laboratory : Lab-T, Inc.
Address : 2182-42 Baegok-daero, Mohyeon-myeon, Cheoin-gu, Yongin-si Gyeonggi-do
17036, Korea
Telephone No. : +82 31-322-6767
Facsimile No. : +82 31-322-6768

Certificate

FCC Designation No. : KR0159
FCC Registration No. : 133186
IC Site Registration No. : 22000-1

3. Information About Test Equipment

3.1 Equipment Information

Equipment type	Scan Tool
Equipment model name	G-scan3
Equipment add model name	-
Frequency range	2 402 ~ 2 480 MHz
Modulation type	GFSK
Modulation technology	F1D
Power supply	DC 3.7 V
H/W version	V1.0
S/W version	V1.0

Note1:The above EUT information was declared by the manufacturer.

3.2 Antenna Information

Antenna 1	type	Chip Antenna
	gain	-0.2 dBi

3.3 Test Frequency

Test mode	Test frequency (MHz)		
	Lowest frequency	Middle frequency	Highest frequency
GFSK	2 402	2 441	2 480

3.4 Worst-Case

BDR	DH5(GFSK)
-----	-----------

Note:The power measurement has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

3.5 Tested Companion Device Information

Type	Manufacturer	Model	Note
-	-	-	-

4. Test Report

4.1 Summary

FCC Rule	Parameter	Clause	Status
Transmitter Requirements			
15.203 15.247(b)(4)	Antenna Requirement	4.4.1	C
15.247(a)(1)	20 dB Channel Bandwidth	4.4.2	C
-	Occupied Bandwidth	4.4.2	
15.247(a)(1)(iii)	Number of Hopping Frequencies	4.4.3	C
15.247(a)(1)(iii)	Time of occupancy (Dwell Time)	4.4.4	C
15.247(a)(1)	Carrier Frequencies Separation	4.4.5	C
15.247(b)(1)	Peak Output Power	4.4.6	C
15.247(d) 15.205(a) 15.209(a)	Spurious Emission, Band Edge and Restricted bands	4.4.7	C
15.207(a)	Conducted Emissions	4.4.8	C

NOTE 1 : C = Comply N/C = Not Comply N/T = Not Tested N/A = Not Applicable

* The general test methods used to test this device is ANSI C63.10:2013

4.2 Measurement Uncertainty

Mesurement items	Expanded Uncertainty	
RF Output Power	0.75 dB	(The confidence level is about 95 %, $k=2$)
Occupied Channel Bandwidth	10.22 kHz	(The confidence level is about 95 %, $k=2$)
Conducted Spurious Emissions	0.44 dB	(The confidence level is about 95 %, $k=2$)
Radiated Spurious Emissions (1 GHz under)	4.56 dB	(The confidence level is about 95 %, $k=2$)
Radiated Spurious Emissions (Above 1 GHz)	4.46 dB	(The confidence level is about 95 %, $k=2$)
Conducted emission	4.08 dB	(The confidence level is about 95 %, $k=2$)

4.3 Test Report Version

Test Report No.	Date	Description
TRRFCC18-0010	18.04.12	Initial issue

4.4 Transmitter Requirements

4.4.1 Antenna Requirement

4.4.1.1 Regulation

According to §15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to §15.247(b)(4) e conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.4.1.4 Result

Comply

(The transmitter has a Internal Chip Antenna. The directional peak gain of the antenna is -0.20 dBi.)

4.4.2 20 dB Bandwidth and Occupied Bandwidth

4.4.2.1 Regulation

Not Applicable

4.4.2.2 Measurement Procedure

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
ANSI C63.10 § 6.9.2 Occupied bandwidth 20dB Relative procedure
ANSI C63.10 § 6.9.3 Occupied bandwidth 99% procedure

4.4.2.3 Result

Comply (measurement data : refer to the next page)

4.4.2.4 Measurement data

Test mode : GFSK

Frequency (MHz)	20 dB Bandwidth (MHz)	Min. Limit (MHz)	Occupied Bandwidth (99 % Bandwidth)(MHz)
2 402.00	0.82	0.25	0.86
2 441.00	0.82	0.25	0.86
2 480.00	0.81	0.25	0.86

4.4.2.5 Test Plot

GFSK_2 402 MHz(20 dB Bandwidth)




GFSK_2 441 MHz(20 dB Bandwidth)




GFSK_2 480 MHz(20 dB Bandwidth)




GFSK_2 402 MHz(Occupied Bandwidth)



GFSK_2 441 MHz(Occupied Bandwidth)



GFSK_2 480 MHz(Occupied Bandwidth)



4.4.3 Number of Hopping Frequencies

4.4.4.2 Regulation

According to §15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

4.4.3.2 Measurement Procedure

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines
ANSI C63.10 § 7.8.3 Number of hopping frequencies

4.4.3.3 Result



Comply (measurement data : refer to the next page)

4.4.3.4 Measurement data

Total number of Hopping Channels is 79

4.4.3.5 Test Plot

GFSK



4.4.4 Time of occupancy (Dwell Time)

4.4.4.2 Regulation

According to §15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

4.4.4.2 Measurement Procedure

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines
ANSI C63.10 § 7.8.3 Time of Occupancy

4.4.4.3 Result

Comply (measurement data : refer to the next page)

4.4.4.4 Measurement data

Test mode : Hopping


Time of occupancy				
Packet Type	Number of hopping Channels	Burst On Time (ms)	Result (sec)	Limit (sec)
DH5(non-AFH)	79	2.898	0.309	0.400
DH5(AFH)	20	2.898	0.155	0.400

NOTE1 : Result = 0.4 * Hopping Channel * Burst On Time * ((Hopping rate/Time slots)/Hopping channel)

- Time slots for DH5 = 6 slots(TX = 5 slot, RX = 1 slot)
- Hopping Rate = 1600 for FH mode
- Hopping Rate = 800 for AFH mode

4.4.4.5 Test Plot

GFSK_2 441 MHz



4.4.5 Carrier Frequencies Separation

4.4.5.2 Regulation

According to §15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

4.4.5.2 Measurement Procedure

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines
ANSI C63.10 § 7.8.2 Carrier frequency separation

4.4.5.3 Result

Comply (measurement data : refer to the next page)

4.4.5.4 Measurement data


Test mode : GFSK

Carrier Frequency Separation		
Test Channel	Result (MHz)	Min. Limit (MHz)
Channel 1 to Channel 2	1.00	0.54
Channel 39 to Channel 40	1.00	0.54
Channel 78 to Channel 79	1.00	0.54


NOTE1 : Limit(kHz) : Result of 20 dB Bandwidth*2/3

4.4.5.5 Test Plot


GFSK_2 402 MHz to 2 403 MHz



GFSK_2 441 MHz to 2 442 MHz



GFSK_2 479 MHz to 2 480 MHz



4.4.6 Peak Output Power

4.4.6.1 Regulation

According to §15.247(b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 nonoverlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

4.4.6.2 Measurement Procedure

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines
ANSI C63.10 § 7.8.5 Output Power test procedure for FHSS

4.4.6.3 Result

Comply (measurement data : refer to the next page)

4.4.6.4 Measurement data

Test mode : GFSK

Frequency (MHz)	Peak Output Power Result (dBm)	Peak Output Power Result (mW)	Avg Output Power Result (dBm)
2 402.00	1.34	1.36	-0.65
2 441.00	2.67	1.85	0.54
2 480.00	1.86	1.54	0.35

NOTE1 : Since the directional gain of the PCB Antenna declared by the manufacturer (GANT =3.00 dBi), does not exceed 6.0 dBi ,there was no need to reduce the output power.

NOTE2 : We took the insertion loss of the cable loss into consideration within the measuring instrument.


NOTE3 : Peak Output Power Result(W) = (10^(Peak Output Power Result(dBm)/10))

4.4.6.5 Test Plot


GFSK_2 402 MHz



GFSK_2 441 MHz



GFSK_2 480 MHz



4.4.7 Spurious Emission, Band Edge, and Restricted bands

4.4.7.1 Regulation

According to §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

According to §15.205(a),(b) only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	156.7 - 156.9	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 - 4 400	Above 38.6
13.36 - 13.41			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurement

4.4.7.2 Measurement Procedure

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines
ANSI C63.10 § 6.10.4 Authorized band-edge relative method (lower bandedge)
ANSI C63.10 § 6.10.6 Marker Delta Method (upper restricted bandedge)
ANSI C63.10 § 11.11.1 General Information
ANSI C63.10 § 11.11.3 Emission level measurement

4.4.7.2.1 Band-edge Compliance of RF Conducted Emissions

Span : wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation
RBW : $\geq 1\%$ of the span
VBW : \geq RBW
Sweep : Auto
Detector : Peak
Trace : Max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section. Submit this plot.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit. Submit this plot.

4.4.7.2.2 Conducted Spurious Emissions

Span : wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation
RBW : $\geq 1\%$ of the span
VBW : \geq RBW
Sweep : Auto
Detector : Peak
Trace : Max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section. Submit these plots.

4.4.7.2.3 Radiated Spurious Emissions

- 1) The preliminary and final radiated measurements were performed to determine the frequency producing the maximum emissions in a 10m anechoic chamber. The EUT was tested at a distance 3 m(Below 1 GHz) and 1 m(Above 1 GHz).
- 2) The EUT was placed on the top of the 0.8-meter height, 1 x 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360°.
- 3) The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 kHz to 30 MHz using the loop antenna, and from 30 to 1 000 MHz using the BILOG broadband antenna, and from 1 000 MHz to 10 000 MHz using the horn antenna.
- 4) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

Span : wide enough to fully capture the emission being measured
RBW : ≥ 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz
VBW : \geq RBW
Sweep : Auto
Detector : Peak
Trace : Max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

NOTE1 : The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.

NOTE2 : The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.

NOTE3 : The 0.8 m height is for below 1 GHz testing, and 1.5 m is for above 1 GHz testing

4.4.7.3 Result

Comply (measurement data : refer to the next page)

4.4.7.4 Measurement data_Radiated Spurious Emissions

Test mode : Below 1 GHz (Worst case : GFSK_2 480 MHz)

Frequency (MHz)	Detector	Pol. (V/H)	Reading (dB μ V)	Ant Factor (dB)	Loss (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
469.03	QP	H	36.70	17.40	-26.70	27.40	46.00	18.60

Note 1 : Loss : Cable loss - Amp gain

Note 2 : Result : Reading + Ant Factor + Loss

Test mode : Above 1 GHz _ GFSK_2 402

Frequency (MHz)	Detector	Pol. (V/H)	Reading (dB μ V)	Ant Factor (dB)	Loss	DCCF (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 346.50	PK	V	49.20	31.80	-27.40	-	53.60	83.54	29.94
	AV	V	49.20	31.80	-27.40	-24.76	28.84	63.54	34.70
4 803.40	PK	H	50.40	33.80	-24.50	-	59.70	83.54	23.84
	AV	H	50.40	33.80	-24.50	-24.76	34.94	63.54	28.60
4 803.40	PK	V	51.30	33.80	-24.50	-	60.60	83.54	22.94
	AV	V	51.30	33.80	-24.50	-24.76	35.84	63.54	27.70
Above 5 GHz	Not Detected	-	-	-	-	-	-	-	-

Note 1 : Loss : Cable loss - Amp gain

Note 2 : Peak Result : Reading + Ant Factor + Loss

 Note 3 : DCCF(Duty Cycle Correction Factor) : $20 \times \log(\text{worst case dwell time} / 100 \text{ ms})$ dB, refer to 4.4.7.7

Average Reasult : Peak Result + DCCF

Note 4 : Below 1 GHz Measured distance : 3 m, Above 1 GHz Measured distance : 1 m

 Above 1 GHz Distance Factor = $20\log(1 / 3) = -9.54$

 Above 1 GHz Limit Peak = $74 - (-9.54) = 83.54$

 Above 1 GHz Limit Average = $54 - (-9.54) = 63.54$

Note 5 : Average measurement did not take place because the peak data did not exceed Average Limit.

Note 6 : Not Detected means that peak data does not exceed the average limit.

Test mode : Above 1 GHz _ GFSK_2 441

Frequency (MHz)	Detector	Pol. (V/H)	Reading (dB μ V)	Ant Factor (dB)	Loss	Dutycycle Factor (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4 882.13	PK	H	54.60	33.80	-24.40	-	64.00	83.54	19.54
	AV	H	54.60	33.80	-24.40	-24.76	39.24	63.54	24.30
4 882.13	PK	V	54.40	33.80	-24.40	-	63.80	83.54	19.74
	AV	V	54.40	33.80	-24.40	-24.76	39.04	63.54	24.50
7 322.50	PK	H	52.00	33.50	-12.10	-	73.40	83.54	10.14
	AV	H	52.00	33.50	-12.10	-24.76	48.64	63.54	14.90
7 322.50	PK	V	50.10	33.50	-12.10	-	71.50	83.54	12.04
	AV	V	50.10	33.50	-12.10	-24.76	46.74	63.54	16.80
Above 1 GHz	Not Detected	-	-	-	-	-	-	-	-

Note 1 : Loss : Cable loss - Amp gain

Note 2 : Peak Result : Reading + Ant Factor + Loss

 Note 3 : DCCF(Duty Cycle Correction Factor) : $20 \times \log(\text{worst case dwell time} / 100 \text{ ms})$ dB, refer to 4.4.7.7

Average Reasult : Peak Result + DCCF

Note 4 : Below 1 GHz Measured distance : 3 m, Above 1 GHz Measured distance : 1 m

 Above 1 GHz Distance Factor = $20\log(1 / 3) = -9.54$

 Above 1 GHz Limit Peak = $74 - (-9.54) = 83.54$

 Above 1 GHz Limit Average = $54 - (-9.54) = 63.54$

Note 5 : Average measurement did not take place because the peak data did not exceed Average Limit.

Note 6 : Not Detected means that peak data does not exceed the average limit.

Test mode : Above 1 GHz _ GFSK_2 480

Frequency (MHz)	Detector	Pol. (V/H)	Reading (dB μ V)	Ant Factor (dB)	Loss	Dutycycle Factor (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 496.00	PK	H	47.80	32.00	-27.20	-	52.60	83.54	30.94
	AV	H	47.80	32.00	-27.20	-24.76	27.84	63.54	35.70
4 959.16	PK	H	51.10	33.70	-24.40	-	60.40	83.54	23.14
	AV	H	51.10	33.70	-24.40	-24.76	35.64	63.54	27.90
4 959.16	PK	V	51.30	33.70	-24.40	-	60.60	83.54	22.94
	AV	V	51.30	33.70	-24.40	-24.76	35.84	63.54	27.70
7 440.50	PK	H	50.20	35.60	-21.90	-	63.90	83.54	19.64
	AV	H	50.20	35.60	-21.90	-24.76	39.14	63.54	24.40
7 440.50	PK	V	45.50	35.60	-21.90	-	59.20	83.54	24.34
	AV	V	45.50	35.60	-21.90	-24.76	34.44	63.54	29.10
Above 18 GHz	Not Detected	-	-	-	-		-	-	-

Note 1 : Loss : Cable loss - Amp gain

Note 2 : Peak Result : Reading + Ant Factor + Loss

 Note 3 : DCCF(Duty Cycle Correction Factor) : $20 \times \log(1 / 3) = -9.54$ dB, refer to 4.4.7.7

Average Result : Peak Result + DCCF

Note 4 : Below 1 GHz Measured distance : 3 m, Above 1 GHz Measured distance : 1 m

 Above 1 GHz Distance Factor = $20\log(1 / 3) = -9.54$

 Above 1 GHz Limit Peak = $74 - (-9.54) = 83.54$


 Above 1 GHz Limit Average = $54 - (-9.54) = 63.54$

Note 5 : Average measurement did not take place because the peak data did not exceed Average Limit.

Note 6 : Not Detected means that peak data does not exceed the average limit.


4.4.7.5 Measurement Plot_Radiated Spurious Emissions

Test mode : 9 kHz ~ 30 MHz Worst Case(GFSK_2 480 MHz)




No.	FREQ [MHz]	READING [dBuV]	ANT PEAK [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
-----	---------------	-------------------	---------------------	--------------	--------------	--------------------	-------------------	----------------	-----------------	----------------

Test mode : 30 MHz ~ 1 GHz Worst Case(GFSK_2 480 MHz)



No.	FREQ [MHz]	READING [dBuV]	ANT QP FACTOR	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	469.034	36.7	17.4	-26.7	0.0	27.4	46.0	18.6	100	19

Test mode : 1 GHz ~ 3 GHz Peak Worst Case(GFSK_2 480 MHz)




No.	Freq.	Reading	Ant.Fac	Loss	Gain	Result	Limit	Margin	Pola.	Height	Angle	Ant.	Comment
							<PK>	<PK>					
1	2496.000	47.8	32.0	7.2	34.4	52.6	83.5	30.9	Hori.	0	214	8719R	

Note 1 : Measured distance : 1 m

 Note 2 : Limit : Peak : 83.5 dBμV/m
 Average : 63.5 dBμV/m

Test mode : 3 GHz ~ 10 GHz Peak Worst Case(GFSK_2 480 MHz)




No.	Freq.	Reading	Ant.Fac	Loss	Gain	Result	Limit	Margin	Pola.	Height	Angle	Ant.	Comment
							<PK>	<PK>					
1	4959.163	51.1	33.7	10.1	34.5	60.4	83.5	23.1	Hori.	0	358	8719R	
2	4959.163	51.3	33.7	10.1	34.5	60.6	83.5	22.9	Vert.	0	137	8719R	
3	7440.499	50.2	35.6	12.9	34.8	63.9	83.5	19.6	Hori.	0	186	8719R	
4	7440.499	45.5	35.6	12.9	34.8	59.2	83.5	24.3	Vert.	0	165	8719R	


Note 1 : Measured distance : 1 m

 Note 2 : Limit : Peak : 83.5 dBμV/m
 Average : 63.5 dBμV/m

Test mode : 10 GHz ~ 18 GHz Peak Worst Case(GFSK_2 480 MHz)




Test mode : 18 GHz ~ 25 GHz Peak Worst Case(GFSK_2 480 MHz)




4.4.7.6 Measurement data_Conducted Spurious Emissions


GFSK_2 402 MHz(reference)



GFSK_2 402 MHz(Bandedge_Single)




GFSK_2 402 MHz(Bandedge_Hopping)




NOTE: F1 : 2 390 MHz, F2 : 2 400 MHz

GFSK_2 402 MHz(Spurious)




GFSK_2 441 MHz(reference)




NOTE: Limit : 2.54 dBm - 20 dB = -17.46 dBm


GFSK_2 441 MHz(Spurious)




GFSK_2 480 MHz(reference)



GFSK_2 480 MHz(Bandedge_Single)




GFSK_2 480 MHz(Bandedge_Hopping)




NOTE: F1 : 2 483.5 MHz, F2 : 2 500 MHz

GFSK_2 480 MHz(Spurious)



4.4.7.7 Measurement Plot_Dutycycle

Test mode : GFSK_2 441 MHz



NOTE: Dwell time: on time*No. of hop
 Dutycycle Factor : $20\log(\text{dwell time}/100) = 20\log((2.8896*2)/100) = -24.76$

4.4.8 Conducted Emission

4.4.8.1 Regulation

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Qausi-peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

4.4.6.2 Measurement Procedure


- 1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5 m away from the side wall of the shielded room.
- 2) Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.
- 3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
- 4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
- 5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 kHz or to QUASIEPICK and AVERAGE within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

4.4.8.3 Result

Comply (measurement data : refer to the next page)

4.4.8.4 Measurement data

Test mode : worst case of all modulation.(WLAN2.4 GHz_802.11n_HT20_2 462 MHz)



NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16179	27.1	14.3	20.0	47.1	34.3	65.4	55.4	18.3	21.1	N (+)
2	0.22793	23.9	11.2	19.8	43.7	31.0	62.5	52.5	18.8	21.5	N (+)
3	0.58959	27.8	11.5	20.0	47.8	31.5	56.0	46.0	8.2	14.5	N (+)
4	0.23544	20.8	6.6	19.8	40.6	26.4	62.3	52.3	21.7	25.9	L1 (-)
5	0.58949	27.3	15.2	20.0	47.3	35.2	56.0	46.0	8.7	10.8	L1 (-)
6	2.02333	19.7	7.6	19.8	39.5	27.4	56.0	46.0	16.5	18.6	L1 (-)

APPENDIX I

TEST EQUIPMENT USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment.

Equipment	Manufacturer	Model	Serial No.	Cal. Date (yy.mm.dd)	Next Cal.Date (yy.mm.dd)
FSV Signal Analyzer	ROHDE&SCHWARZ	FSV30	103370	2017-10-17	2018-10-17
Power Sensor	KEYSIGHT	U2022XA	MY55320008	2017-08-16	2018-08-16
DC Power Supply	AGILENT	E3632A	MY51160055	2017-04-26	2018-04-26
Digital MultiMeter	HP	34401A	US36025428	2018-01-11	2019-01-11
Signal Generator	ROHDE&SCHWARZ	SMB100A	178384	2017-10-16	2018-10-16
EMI Test Receiver	ROHDE&SCHWARZ	ESU40	100445	2017-12-15	2018-12-15
BiLog Antenna	Schwarzbeck	VULB9160	9160-3381	2017-06-15	2019-06-15
Preamplifier	TSJ	MLA-10k01-b01-27	1870369	2017-04-24	2018-04-24
Antenna Mast(10 m)	TOKIN	5977	-	-	-
Antenna Mast(10 m)	Innco	MA4640-XPET-0800	578	-	-
Controller(10 m)	TOKIN	5909L	141909L-1	-	-
Controller(10 m)	Innco	CO3000	40040217	-	-
Turn Table(10 m)	TOKIN	5983-1.5	-	-	-
10 m Semi-Anechoic Chamber	SY CORPORATION	-	-	-	-
Active Loop H-Field	ETS	6502	00150598	2017-06-01	2019-06-01
Double Ridge Horn Antenna	ETS	3117	00168719	2017-09-01	2019-09-01
Double Ridge Horn Antenna	A.H Systems, Inc	SAS-574	465	2017-04-25	2019-04-25
PREAMPLIFIER	Agilent	8449B	3008A02110	2018-01-15	2019-01-15
PREAMPLIFIER	A.H Systems, Inc	PAM-1840VH	166	2018-01-15	2019-01-15
High pass filter	Wainwright Instruments GmbH	WHKX10-2580-3000-18000-60SS	14	2018-01-11	2019-01-11
EMI Test Receiver	ROHDE&SCHWARZ	ESR7	101440	2017-12-15	2018-12-15
LISN	ROHDE&SCHWARZ	ENV216	101883	2017-04-24	2018-04-24
Pulse Limiter	Schwarzbeck	VTSD 9561-F	9561-F189	2017-04-24	2018-04-24