

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180100017103
Page: 1 of 8

1 Cover Page

RF MPE REPORT

Application No.:	SZEM1801000171CR (SHEM1712008946CR)
Applicant:	YONGKANG CITY HUAXI SCAL FACTORY
FCC ID:	2AOXR-HXZ2830
Equipment Under Test (EUT):	
NOTE: The following sample(s) was/were submitted and identified by the client as	
Product Name:	BLUETOOTH BODY FAT SCALE
Model No.(EUT):	HX-Z2830
Add Model No.:	HX-Z2626, HX-Z2125, HX-Z2313, HX-ZR28, HX-ZR33, HX-Z3030, HX-ZS1712, HX-ZJ1713, HX-ZAL23, HX-ZAL22, HX-ZCL26
Standards:	FCC Rules 47 CFR §2.1093 KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt:	2017-12-28
Date of Test:	2018-02-04
Date of Issue:	2018-02-06
Test Result:	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above



Keny Xu
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-02-06		Original

Authorized for issue by:				
		 Foray Chen /Project Engineer		
		 Eric Fu /Reviewer		

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF E.U.T.....	4
3.3 TECHNICAL SPECIFICATIONS.....	4
3.4 TEST LOCATION.....	5
3.5 TEST FACILITY	5
4 TEST STANDARDS AND LIMITS.....	6
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5 MEASUREMENT AND CALCULATION.....	7
5.1 MAXIMUM TRANSMIT POWER	7
5.2 MPE CALCULATION.....	8

3 General Information

3.1 Client Information

Applicant:	YONGKANG CITY HUAXI SCAL FACTORY
Address of Applicant:	No.153 huachuan Road, Xicheng Industrial, Yongkang City, Zhejiang Province, China
Manufacturer:	YONGKANG CITY HUAXI SCAL FACTORY
Address of Manufacturer:	No.153 huachuan Road, Xicheng Industrial, Yongkang City, Zhejiang Province, China
Factory:	YONGKANG CITY HUAXI SCAL FACTORY
Address of Factory:	No.153 huachuan Road, Xicheng Industrial, Yongkang City, Zhejiang Province, China

3.2 General Description of E.U.T.

Power supply:	DC 4.5V, 3* AAA size batteries
Test voltage:	DC 4.5V

3.3 Technical Specifications

Antenna Type	PIFA Antenna
Channel Spacing	2MHz
Modulation Type	GFSK
Number of Channels	40
Operation Frequency	2402MHz to 2480MHz

3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong,
China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max power of channel})/(\text{min test separation distance})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

For 2.4G band device, the limit of worse case is

$$P_{\text{max}} \leq 3.0 * D_{\text{min}} / \sqrt{f} = 3.0 * 5 / \sqrt{2.480} = 9.525 \text{ mW}$$

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SZEM180100017102

Test Mode	Test Channel	Ant	Power[dBm]	Power[mW]	Limit[dBm]
BLE	2402	Ant1	-9.018	0.13	30
BLE	2440	Ant1	-9.172	0.12	30
BLE	2480	Ant1	-9.411	0.11	30

5.2 MPE Calculation

The Max Conducted Peak Output Power is 0.13mW;

The best case gain of the antenna is -1.76dBi. -1.76dB logarithmic terms convert to numeric result is nearly 0.667.

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 0.62 \text{ mW} \times 0.667 = 0.41354 \text{ mW} < 9.525 \text{ mW}$$

So the device is exclusion from SAR test.

--End of the Report--