

### FCC Report (Bluetooth)

**Applicant:** Guangzhou Yufeng Electronic Co., Ltd

**Address of Applicant:** NO.42 Xiangbei street, Xinlou cun, Jianggao town, Baiyun district, Guangzhou, China

**Manufacturer/Factory:** Guangzhou Yufeng Electronic Co., Ltd

**Address of Manufacturer/Factory:** NO.42 Xiangbei street, Xinlou cun, Jianggao town, Baiyun district, Guangzhou, China

**Equipment Under Test (EUT)**

Product Name: 2.0 CH ACTIVE SPEAKER SYSTEM

Model No.: JP-510

Trade mark: JIEPAK

**FCC ID:** 2AOYNJP-510

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** January 25, 2018

**Date of Test:** January 25, 2018-March 06, 2018

**Date of report issued:** March 06, 2018

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



**Robinson Lo**

**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date           | Description |
|-------------|----------------|-------------|
| 00          | March 06, 2018 | Original    |
|             |                |             |
|             |                |             |
|             |                |             |
|             |                |             |

Prepared By:




Date:

March 06, 2018

Project Engineer

Check By:



Date:

March 06, 2018

Reviewer

## 3 Contents

|                                                      | Page      |
|------------------------------------------------------|-----------|
| <b>1 COVER PAGE .....</b>                            | <b>1</b>  |
| <b>2 VERSION .....</b>                               | <b>2</b>  |
| <b>3 CONTENTS .....</b>                              | <b>3</b>  |
| <b>4 TEST SUMMARY .....</b>                          | <b>4</b>  |
| <b>5 GENERAL INFORMATION .....</b>                   | <b>5</b>  |
| 5.1 GENERAL DESCRIPTION OF EUT .....                 | 5         |
| 5.2 TEST MODE .....                                  | 7         |
| 5.3 TEST FACILITY.....                               | 7         |
| 5.4 TEST LOCATION.....                               | 7         |
| 5.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER..... | 7         |
| 5.6 DESCRIPTION OF SUPPORT UNITS .....               | 7         |
| 5.7 ADDITIONAL INSTRUCTIONS .....                    | 8         |
| <b>6 TEST INSTRUMENTS LIST .....</b>                 | <b>9</b>  |
| <b>7 TEST RESULTS AND MEASUREMENT DATA .....</b>     | <b>10</b> |
| 7.1 ANTENNA REQUIREMENT .....                        | 10        |
| 7.2 CONDUCTED EMISSIONS .....                        | 11        |
| 7.3 CONDUCTED PEAK OUTPUT POWER.....                 | 14        |
| 7.4 20dB EMISSION BANDWIDTH.....                     | 19        |
| 7.5 CARRIER FREQUENCIES SEPARATION.....              | 22        |
| 7.6 HOPPING CHANNEL NUMBER .....                     | 25        |
| 7.7 DWELL TIME.....                                  | 26        |
| 7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....    | 29        |
| 7.9 BAND EDGE.....                                   | 30        |
| 7.9.1 Conducted Emission Method .....                | 30        |
| 7.9.2 Radiated Emission Method .....                 | 33        |
| 7.10 SPURIOUS EMISSION .....                         | 35        |
| 7.10.1 Conducted Emission Method.....                | 35        |
| 7.10.2 Radiated Emission Method.....                 | 37        |
| <b>8 TEST SETUP PHOTO .....</b>                      | <b>44</b> |
| <b>9 EUT CONSTRUCTIONAL DETAILS.....</b>             | <b>46</b> |

## 4 Test Summary

| Test Item                               | Section in CFR 47 | Result |
|-----------------------------------------|-------------------|--------|
| Antenna Requirement                     | 15.203/15.247 (c) | Pass   |
| AC Power Line Conducted Emission        | 15.207            | Pass   |
| Conducted Peak Output Power             | 15.247 (b)(1)     | Pass   |
| 20dB Occupied Bandwidth                 | 15.247 (a)(1)     | Pass   |
| Carrier Frequencies Separation          | 15.247 (a)(1)     | Pass   |
| Hopping Channel Number                  | 15.247 (a)(1)     | Pass   |
| Dwell Time                              | 15.247 (a)(1)     | Pass   |
| Pseudorandom Frequency Hopping Sequence | 15.247(b)(4)      | Pass   |
| Radiated Emission                       | 15.205/15.209     | Pass   |
| Band Edge                               | 15.247(d)         | Pass   |

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.4:2014 and ANSI C63.10:2013

### Measurement Uncertainty

| Test Item                                                                                             | Frequency Range | Measurement Uncertainty | Notes |
|-------------------------------------------------------------------------------------------------------|-----------------|-------------------------|-------|
| Radiated Emission                                                                                     | 9kHz ~ 30MHz    | $\pm 4.34\text{dB}$     | (1)   |
| Radiated Emission                                                                                     | 30MHz ~ 1000MHz | $\pm 4.24\text{dB}$     | (1)   |
| Radiated Emission                                                                                     | 1GHz ~ 26.5GHz  | $\pm 4.68\text{dB}$     | (1)   |
| AC Power Line Conducted Emission                                                                      | 0.15MHz ~ 30MHz | $\pm 3.45\text{dB}$     | (1)   |
| Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%. |                 |                         |       |

## 5 General Information

### 5.1 General Description of EUT

|                                                                                                                                                                                    |                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| Product Name:                                                                                                                                                                      | 2.0 CH ACTIVE SPEAKER SYSTEM |
| Model No.:                                                                                                                                                                         | JP-510                       |
| Test Model No:                                                                                                                                                                     | JP-510                       |
| <i>Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are color and model name for commercial purpose.</i> |                              |
| Quantity of tested samples                                                                                                                                                         | 1                            |
| Serial No.:                                                                                                                                                                        | T180881                      |
| Tested Sample(s) ID:                                                                                                                                                               | N/A                          |
| Hardware Version:                                                                                                                                                                  | N/A                          |
| Software Version:                                                                                                                                                                  | N/A                          |
| Operation Frequency:                                                                                                                                                               | 2402MHz~2480MHz              |
| Channel numbers:                                                                                                                                                                   | 79                           |
| Channel separation:                                                                                                                                                                | 1MHz                         |
| Modulation type:                                                                                                                                                                   | GFSK, Pi/4 QPSK              |
| Antenna Type:                                                                                                                                                                      | PCB antenna                  |
| Antenna gain:                                                                                                                                                                      | -0.68dBi                     |
| Power supply:                                                                                                                                                                      | DC 12V by battery            |

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2402MHz   | 21      | 2422MHz   | 41      | 2442MHz   | 61      | 2462MHz   |
| 2                                   | 2403MHz   | 22      | 2423MHz   | 42      | 2443MHz   | 62      | 2463MHz   |
| 3                                   | 2404MHz   | 23      | 2424MHz   | 43      | 2444MHz   | 63      | 2464MHz   |
| 4                                   | 2405MHz   | 24      | 2425MHz   | 44      | 2445MHz   | 64      | 2465MHz   |
| 5                                   | 2406MHz   | 25      | 2426MHz   | 45      | 2446MHz   | 65      | 2466MHz   |
| 6                                   | 2407MHz   | 26      | 2427MHz   | 46      | 2447MHz   | 66      | 2467MHz   |
| 7                                   | 2408MHz   | 27      | 2428MHz   | 47      | 2448MHz   | 67      | 2468MHz   |
| 8                                   | 2409MHz   | 28      | 2429MHz   | 48      | 2449MHz   | 68      | 2469MHz   |
| 9                                   | 2410MHz   | 29      | 2430MHz   | 49      | 2450MHz   | 69      | 2470MHz   |
| 10                                  | 2411MHz   | 30      | 2431MHz   | 50      | 2451MHz   | 70      | 2471MHz   |
| 11                                  | 2412MHz   | 31      | 2432MHz   | 51      | 2452MHz   | 71      | 2472MHz   |
| 12                                  | 2413MHz   | 32      | 2433MHz   | 52      | 2453MHz   | 72      | 2473MHz   |
| 13                                  | 2414MHz   | 33      | 2434MHz   | 53      | 2454MHz   | 73      | 2474MHz   |
| 14                                  | 2415MHz   | 34      | 2435MHz   | 54      | 2455MHz   | 74      | 2475MHz   |
| 15                                  | 2416MHz   | 35      | 2436MHz   | 55      | 2456MHz   | 75      | 2476MHz   |
| 16                                  | 2417MHz   | 36      | 2437MHz   | 56      | 2457MHz   | 76      | 2477MHz   |
| 17                                  | 2418MHz   | 37      | 2438MHz   | 57      | 2458MHz   | 77      | 2478MHz   |
| 18                                  | 2419MHz   | 38      | 2439MHz   | 58      | 2459MHz   | 78      | 2479MHz   |
| 19                                  | 2420MHz   | 39      | 2440MHz   | 59      | 2460MHz   | 79      | 2480MHz   |
| 20                                  | 2421MHz   | 40      | 2441MHz   | 60      | 2461MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel             | Frequency |
|---------------------|-----------|
| The lowest channel  | 2402MHz   |
| The middle channel  | 2441MHz   |
| The Highest channel | 2480MHz   |

## 5.2 Test mode

|                                                                                                                                                                                                                                              |                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                            | Keep the Bluetooth in continuously transmitting mode |
| <i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i> |                                                      |

## 5.3 Test Facility

|                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| The test facility is recognized, certified, or accredited by the following organizations:<br>● <b>Industry Canada (IC) —Registration No.: 9079A-2</b><br>The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016. |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## 5.4 Test Location

|                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| All tests were performed at:                                                                                                                                                                                                                     |
| Global United Technology Services Co., Ltd.<br>Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102<br>Tel: 0755-27798480<br>Fax: 0755-27798960 |

## 5.5 Other Information Requested by the Customer

|       |
|-------|
| None. |
|-------|

## 5.6 Description of Support Units

|       |
|-------|
| None. |
|-------|

## 5.7 Additional instructions

Software (Used for test) from client

|      |                                                                                                                                                                        |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mode | Special software is used.<br>The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually. |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                |             |                 |                                                                         |
|------------------------------------------------|-------------|-----------------|-------------------------------------------------------------------------|
| Power level setup in software                  |             |                 |                                                                         |
| Test Software Name                             | FCC ASSIST  |                 |                                                                         |
| Test Software Version                          | 2.4         |                 |                                                                         |
| Support Units<br>(Software installation media) | Description | Manufacturer    | Model                                                                   |
|                                                | Laptop      | Apple           | A1278                                                                   |
| Mode                                           | Channel     | Frequency (MHz) | Soft Set                                                                |
| GFSK, Pi/4 QPSK                                | CH1         | 2402            | TX LEVEL is built-in set parameters and cannot be changed and selected. |
|                                                | CH40        | 2441            |                                                                         |
|                                                | CH79        | 2480            |                                                                         |

### Run Software



## 6 Test Instruments list


| Radiated Emission: |                               |                                |                             |               |                     |                         |
|--------------------|-------------------------------|--------------------------------|-----------------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment                | Manufacturer                   | Model No.                   | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | 3m Semi- Anechoic Chamber     | ZhongYu Electron               | 9.0(L)*6.0(W)* 6.0(H)       | GTS250        | July. 03 2015       | July. 02 2020           |
| 2                  | Control Room                  | ZhongYu Electron               | 6.2(L)*2.5(W)* 2.4(H)       | GTS251        | N/A                 | N/A                     |
| 3                  | Spectrum Analyzer             | Agilent                        | E4440A                      | GTS533        | June 28 2017        | June 27 2018            |
| 4                  | EMI Test Receiver             | Rohde & Schwarz                | ESU26                       | GTS203        | June 28 2017        | June 27 2018            |
| 5                  | BiConiLog Antenna             | SCHWARZBECK<br>MESS-ELEKTRONIK | VULB9163                    | GTS214        | June 28 2017        | June 27 2018            |
| 6                  | Double -ridged waveguide horn | SCHWARZBECK<br>MESS-ELEKTRONIK | 9120D-829                   | GTS208        | June 28 2017        | June 27 2018            |
| 7                  | Horn Antenna                  | ETS-LINDGREN                   | 3160                        | GTS217        | June 28 2017        | June 27 2018            |
| 8                  | Power Meter                   | Anritsu                        | ML2495A                     | GTS540        | June 28 2017        | June 27 2018            |
| 9                  | Coaxial Cable                 | GTS                            | N/A                         | GTS213        | June 28 2017        | June 27 2018            |
| 10                 | Coaxial Cable                 | GTS                            | N/A                         | GTS211        | June 28 2017        | June 27 2018            |
| 11                 | Coaxial cable                 | GTS                            | N/A                         | GTS210        | June 28 2017        | June 27 2018            |
| 12                 | Coaxial Cable                 | GTS                            | N/A                         | GTS212        | June 28 2017        | June 27 2018            |
| 13                 | Amplifier(100kHz-3GHz)        | HP                             | 8347A                       | GTS204        | June 28 2017        | June 27 2018            |
| 14                 | Amplifier(2GHz-20GHz)         | HP                             | 8349B                       | GTS206        | June 28 2017        | June 27 2018            |
| 15                 | Amplifier (18-26GHz)          | Rohde & Schwarz                | AFS33-18002<br>650-30-8P-44 | GTS218        | June 28 2017        | June 27 2018            |
| 16                 | Power Sensor                  | Anritsu                        | MA2411B                     | GTS541        | June 28 2017        | June 27 2018            |

| Conducted Emission: |                          |                     |                      |               |                     |                         |
|---------------------|--------------------------|---------------------|----------------------|---------------|---------------------|-------------------------|
| Item                | Test Equipment           | Manufacturer        | Model No.            | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                   | Shielding Room           | ZhongYu Electron    | 7.3(L)x3.1(W)x2.9(H) | GTS252        | May.16 2014         | May.15 2019             |
| 2                   | EMI Test Receiver        | R&S                 | ESCI 7               | GTS552        | June 28 2017        | June 27 2018            |
| 3                   | Coaxial Switch           | ANRITSU CORP        | MP59B                | GTS225        | June 28 2017        | June 27 2018            |
| 4                   | Artificial Mains Network | SCHWARZBECK<br>MESS | NSLK8127             | GTS226        | June 28 2017        | June 27 2018            |
| 5                   | Coaxial Cable            | GTS                 | N/A                  | GTS227        | N/A                 | N/A                     |
| 6                   | EMI Test Software        | AUDIX               | E3                   | N/A           | N/A                 | N/A                     |
| 7                   | Thermo meter             | KTJ                 | TA328                | GTS233        | June 28 2017        | June 27 2018            |

| General used equipment: |                |              |           |               |                     |                         |
|-------------------------|----------------|--------------|-----------|---------------|---------------------|-------------------------|
| Item                    | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                       | Barometer      | ChangChun    | DYM3      | GTS257        | June 28 2017        | June 27 2018            |

## 7 Test results and Measurement Data

### 7.1 Antenna requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | FCC Part15 C Section 15.203 /247(c) |
| <p><b>15.203 requirement:</b></p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p><b>15.247(c) (1)(i) requirement:</b></p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> |                                     |
| <p><b>E.U.T Antenna:</b></p> <p><i>The antenna is PCB antenna, the best case gain of the antenna is -0.68dBi</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                     |

## 7.2 Conducted Emissions

|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |           |           |
|--------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|-----------|
| Test Requirement:                                | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |              |           |           |
| Test Method:                                     | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |           |
| Test Frequency Range:                            | 150KHz to 30MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |           |           |
| Class / Severity:                                | Class B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |              |           |           |
| Receiver setup:                                  | RBW=9KHz, VBW=30KHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |              |           |           |
| Limit:                                           | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Limit (dBuV) |           |           |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Quasi-peak   | Average   |           |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0.15-0.5     | 66 to 56* | 56 to 46* |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0.5-5        | 56        | 46        |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 5-30         | 60        | 50        |
| * Decreases with the logarithm of the frequency. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |           |           |
| Test setup:                                      | <div><p style="text-align: center;"><b>Reference Plane</b></p><p style="text-align: center;">Test table/Insulation plane</p><p><i>Remark</i><br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |           |
| Test procedure:                                  | <div><ol style="list-style-type: none"><li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li><li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li><li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li></ol></div> |              |           |           |
| Test Instruments:                                | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |           |
| Test mode:                                       | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |           |           |
| Test results:                                    | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |              |           |           |

### Measurement data:

Line:


## Conducted Emission Measurement

File :JP-510

Data :#1

Date: 2018-1-26

Time: 12:20:58



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1   | *   | 0.1680       | 51.84                    | 9.73                    | 61.57                    | 65.06         | -3.49        | QP       |         |
| 2   |     | 0.1680       | 33.70                    | 9.73                    | 43.43                    | 55.06         | -11.63       | AVG      |         |
| 3   |     | 0.1890       | 49.73                    | 9.74                    | 59.47                    | 64.08         | -4.61        | QP       |         |
| 4   |     | 0.1890       | 32.34                    | 9.74                    | 42.08                    | 54.08         | -12.00       | AVG      |         |
| 5   |     | 0.2280       | 45.25                    | 9.75                    | 55.00                    | 62.52         | -7.52        | QP       |         |
| 6   |     | 0.2280       | 27.89                    | 9.75                    | 37.64                    | 52.52         | -14.88       | AVG      |         |
| 7   |     | 0.3270       | 40.18                    | 9.77                    | 49.95                    | 59.53         | -9.58        | QP       |         |
| 8   |     | 0.3270       | 31.92                    | 9.77                    | 41.69                    | 49.53         | -7.84        | AVG      |         |
| 9   |     | 0.5520       | 39.12                    | 9.79                    | 48.91                    | 56.00         | -7.09        | QP       |         |
| 10  |     | 0.5520       | 27.20                    | 9.79                    | 36.99                    | 46.00         | -9.01        | AVG      |         |
| 11  |     | 5.2170       | 32.87                    | 10.20                   | 43.07                    | 60.00         | -16.93       | peak     |         |

\*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

## Neutral:


### Conducted Emission Measurement

File :JP-510

Data :#2

Date: 2018-1-26

Time: 12:25:59



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1   | *   | 0.1650       | 51.05                    | 9.73                    | 60.78                    | 65.21         | -4.43        | QP       |         |
| 2   |     | 0.1650       | 33.47                    | 9.73                    | 43.20                    | 55.21         | -12.01       | AVG      |         |
| 3   |     | 0.1860       | 46.02                    | 9.74                    | 55.76                    | 64.21         | -8.45        | QP       |         |
| 4   |     | 0.1860       | 31.53                    | 9.74                    | 41.27                    | 54.21         | -12.94       | AVG      |         |
| 5   |     | 0.2880       | 39.54                    | 9.76                    | 49.30                    | 60.58         | -11.28       | QP       |         |
| 6   |     | 0.2880       | 24.35                    | 9.76                    | 34.11                    | 50.58         | -16.47       | AVG      |         |
| 7   |     | 0.5429       | 39.99                    | 9.79                    | 49.78                    | 56.00         | -6.22        | peak     |         |
| 8   |     | 0.5429       | 36.90                    | 9.79                    | 46.69                    | 56.00         | -9.31        | QP       |         |
| 9   |     | 0.5429       | 24.75                    | 9.79                    | 34.54                    | 46.00         | -11.46       | AVG      |         |
| 10  |     | 1.0740       | 35.94                    | 9.84                    | 45.78                    | 56.00         | -10.22       | peak     |         |
| 11  |     | 1.5180       | 29.09                    | 9.88                    | 38.97                    | 56.00         | -17.03       | QP       |         |
| 12  |     | 1.5180       | 15.04                    | 9.88                    | 24.92                    | 46.00         | -21.08       | AVG      |         |


\*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

#### Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss


## 7.3 Conducted Peak Output Power

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Limit:            | 30dBm(for GFSK),20.97dBm(for EDR)                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Test setup:       |  <p>The diagram illustrates the test setup. A Power Meter, shown with a green waveform on its screen, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Power Meter and the E.U.T. are positioned on a table labeled 'Non-Conducted Table'. This table is supported by two vertical legs, which are in turn supported by a thick grey bar at the bottom labeled 'Ground Reference Plane'.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

### Measurement Data

| Mode     | Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
|----------|--------------|-------------------------|-------------|--------|
| GFSK     | Lowest       | 2.291                   | 30.00       | Pass   |
|          | Middle       | 2.653                   |             |        |
|          | Highest      | 1.233                   |             |        |
| Pi/4QPSK | Lowest       | 0.427                   | 20.97       | Pass   |
|          | Middle       | 1.147                   |             |        |
|          | Highest      | -0.040                  |             |        |

## 7.4 20dB Emission Bandwidth

|                   |                                                                                                                                                                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2)                                                                                                                                                                                                                                                                                |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                  |
| Limit:            | N/A                                                                                                                                                                                                                                                                                                               |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                  |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                  |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                              |


### Measurement Data

| Mode     | Test channel | 20dB Emission Bandwidth (MHz) | Result |
|----------|--------------|-------------------------------|--------|
| GFSK     | Lowest       | 0.748                         | Pass   |
|          | Middle       | 0.746                         |        |
|          | Highest      | 0.838                         |        |
| Pi/4QPSK | Lowest       | 1.118                         | Pass   |
|          | Middle       | 1.117                         |        |
|          | Highest      | 1.118                         |        |




Test plot as follows:


|            |           |
|------------|-----------|
| Test mode: | GFSK mode |
|------------|-----------|



Lowest channel



Middle channel




Highest channel




Test mode:


PI/4QPSK mode



Lowest channel




Middle channel



Highest channel

## 7.5 Carrier Frequencies Separation

|                   |                                                                                                                                                                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                  |
| Receiver setup:   | RBW=20KHz, VBW=62KHz, detector=Peak                                                                                                                                                                                                                                                                               |
| Limit:            | 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)                                                                                                                                                                                                                                                      |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                  |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                  |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                              |

### Measurement Data

| Mode     | Test channel | Carrier Frequencies Separation (kHz) | Limit (kHz) | Result |
|----------|--------------|--------------------------------------|-------------|--------|
| GFSK     | Lowest       | 1000                                 | 559         | Pass   |
|          | Middle       | 1000                                 | 559         | Pass   |
|          | Highest      | 1000                                 | 559         | Pass   |
| Pi/4QPSK | Lowest       | 1000                                 | 792         | Pass   |
|          | Middle       | 1000                                 | 792         | Pass   |
|          | Highest      | 1000                                 | 792         | Pass   |

Note: According to section 7.4

| Mode     | 20dB bandwidth (kHz)<br>(worse case) | Limit (kHz)<br>(Carrier Frequencies Separation) |
|----------|--------------------------------------|-------------------------------------------------|
| GFSK     | 837.90                               | 559                                             |
| Pi/4QPSK | 1188.00                              | 792                                             |

Test plot as follows:

|                  |      |
|------------------|------|
| Modulation mode: | GFSK |
|------------------|------|



Lowest channel



Middle channel



Highest channel

Test mode:


PI/4QPSK mode



Lowest channel




Middle channel




Highest channel

## 7.6 Hopping Channel Number


|                   |                                                                                                                                                                                                                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                             |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                               |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak                                                                                                                                                                                                                                       |
| Limit:            | 15 channels                                                                                                                                                                                                                                                                                                    |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an Equipment Under Test (E.U.T.). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                               |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                               |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                           |

### Measurement Data:

| Mode     | Hopping channel numbers | Limit | Result |
|----------|-------------------------|-------|--------|
| GFSK     | 79                      | 15    | Pass   |
| Pi/4QPSK | 79                      | 15    | Pass   |



## 7.7 Dwell Time

|                   |                                                                                                                                                                                                                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                             |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                               |
| Receiver setup:   | RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak                                                                                                                                                                                                                                                                    |
| Limit:            | 0.4 Second                                                                                                                                                                                                                                                                                                     |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                               |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                               |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                           |

## Measurement Data

| Mode      | Frequency (MHz) | Burst Type | Pulse Width (ms) | Dwell Time (ms) | Limit (ms) | Verdict |
|-----------|-----------------|------------|------------------|-----------------|------------|---------|
| GFSK      | 2441            | DH1        | 0.356            | 113.92          | 400        | PASS    |
|           |                 | DH3        | 1.609            | 257.44          |            |         |
|           |                 | DH5        | 2.862            | 305.28          |            |         |
| π/4-DQPSK | 2441            | DH1        | 0.373            | 119.36          | 400        | PASS    |
|           |                 | DH3        | 1.600            | 256.00          |            |         |
|           |                 | DH5        | 2.862            | 305.28          |            |         |

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2402MHz/2441MHz/2480MHz as blow


DH1/2-DH1/3-DH1 time slot= Pulse time (ms)\*(1600/ (2\*79))\*31.6=113.92ms

DH3/2-DH3/3-DH3 time slot= Pulse time (ms)\*(1600/ (4\*79))\*31.6=257.44ms


DH5/2-DH5/3-DH5 time slot= Pulse time (ms)\*(1600/ (6\*79))\*31.6=305.28ms

Test plot as follows:


|               |         |
|---------------|---------|
| Test channel: | 2441MHz |
|---------------|---------|



DH1/2-DH1/3-DH1




DH3/2-DH3/3-DH3




DH5/2-DH5/3-DH5

Test channel:


2441MHz



DH1/2-DH1/3-DH1



DH3/2-DH3/3-DH3



DH5/2-DH5/3-DH5




## 7.8 Pseudorandom Frequency Hopping Sequence

| Test Requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | FCC Part15 C Section 15.247 (a)(1) requirement: |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <p><i>Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</i></p> <p><i>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</i></p>                                                                                                                                                                   |                                                 |
| EUT Pseudorandom Frequency Hopping Sequence                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                 |
| <p><i>The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</i></p> <ul style="list-style-type: none"> <li>• Number of shift register stages: 9</li> <li>• Length of pseudo-random sequence: <math>2^9 - 1 = 511</math> bits</li> <li>• Longest sequence of zeros: 8 (non-inverted signal)</li> </ul> <div data-bbox="242 1014 1295 1164"> </div> <p><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p><i>An example of Pseudorandom Frequency Hopping Sequence as follow:</i></p> <div data-bbox="242 1265 1240 1415"> </div> <p><i>Each frequency used equally on the average by each transmitter.</i></p> <p><i>The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</i></p> |                                                 |

## 7.9 Band Edge


### 7.9.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                             |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                            |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, Detector=Peak                                                                                                                                                                                                                                                                                                                                                       |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.     |
| Test setup:       |  <p>The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                            |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                            |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                        |

Test plot as follows:


## GFSK Mode:

Test channel:



No-hopping mode

Lowest channel




Hopping mode

Test channel:



No-hopping mode


Highest channel



Hopping mode


## Pi/4QPSK Mode:

Test channel:



No-hopping mode

Lowest channel



Hopping mode

Test channel:




No-hopping mode

Highest channel



Hopping mode

## 7.9.2 Radiated Emission Method

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          |                    |      |               |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------------------|------|---------------|
| Test Requirement:     | FCC Part15 C Section 15.209 and 15.205                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |                    |      |               |
| Test Method:          | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test Frequency Range: | All restriction band have been tested, and 2.3GHz to 2.5GHz band is the worse case                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |                    |      |               |
| Test site:            | Measurement Distance: 3m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |          |                    |      |               |
| Receiver setup:       | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Detector | RBW                | VBW  | Remark        |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Peak     | 1MHz               | 3MHz | Peak Value    |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Peak     | 1MHz               | 10Hz | Average Value |
| Limit:                | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |          | Limit (dBuV/m @3m) |      | Remark        |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |          | 54.00              |      | Average Value |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          | 74.00              |      | Peak Value    |
| Test setup:           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |                    |      |               |
| Test Procedure:       | <div>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</div> <div>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</div> <div>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</div> <div>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</div> <div>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</div> <div>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</div> |          |                    |      |               |
| Test Instruments:     | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test mode:            | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |
| Test results:         | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |          |                    |      |               |

**Remark:**

- During the test, pre-scan the GFSK, Pi/4QPSK modulation, and found the GFSK modulation which it is worse case.

|               |        |
|---------------|--------|
| Test channel: | Lowest |
|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 45.75             | 27.59                 | 5.38            | 30.18              | 48.54          | 74                  | -25.46          | Horizontal   |
| 2400.00         | 51.18             | 27.58                 | 5.39            | 30.18              | 53.97          | 74                  | -20.03          | Horizontal   |
| 2390.00         | 46.31             | 27.59                 | 5.38            | 30.18              | 49.10          | 74                  | -24.90          | Vertical     |
| 2400.00         | 50.37             | 27.58                 | 5.39            | 30.18              | 53.16          | 74                  | -20.84          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 35.61             | 27.59                 | 5.38            | 30.18              | 38.40          | 54                  | -15.60          | Horizontal   |
| 2400.00         | 37.32             | 27.58                 | 5.39            | 30.18              | 40.11          | 54                  | -13.89          | Horizontal   |
| 2390.00         | 36.19             | 27.59                 | 5.38            | 30.18              | 38.98          | 54                  | -15.02          | Vertical     |
| 2400.00         | 38.34             | 27.58                 | 5.39            | 30.18              | 41.13          | 54                  | -12.87          | Vertical     |

|               |         |
|---------------|---------|
| Test channel: | Highest |
|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 48.18             | 27.53                 | 5.47            | 29.93              | 51.25          | 74                  | -22.75          | Horizontal   |
| 2500.00         | 46.59             | 27.55                 | 5.49            | 29.93              | 49.70          | 74                  | -24.30          | Horizontal   |
| 2483.50         | 49.80             | 27.53                 | 5.47            | 29.93              | 52.87          | 74                  | -21.13          | Vertical     |
| 2500.00         | 47.75             | 27.55                 | 5.49            | 29.93              | 50.86          | 74                  | -23.14          | Vertical     |

**Average value:**


| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 38.44             | 27.53                 | 5.47            | 29.93              | 41.51          | 54                  | -12.49          | Horizontal   |
| 2500.00         | 36.26             | 27.55                 | 5.49            | 29.93              | 39.37          | 54                  | -14.63          | Horizontal   |
| 2483.50         | 40.00             | 27.53                 | 5.47            | 29.93              | 43.07          | 54                  | -10.93          | Vertical     |
| 2500.00         | 36.17             | 27.55                 | 5.49            | 29.93              | 39.28          | 54                  | -14.72          | Vertical     |

**Remark:**

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.10 Spurious Emission

### 7.10.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                   |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 Meas Guidance V04                                                                                                                                                                                                                                                                                                                                              |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.           |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                  |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                  |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                              |

**Remark:**

During the test, pre-scan the GFSK, Pi/4QPSK modulation, and found the GFSK modulation which it is worse case.



Test channel:

Lowest channel



30MHz~25GHz

Test channel:

Middle channel



30MHz~25GHz

Test channel:


Highest channel




30MHz~25GHz



## 7.10.2 Radiated Emission Method

|                       |                                                                                                 |            |                    |        |                  |
|-----------------------|-------------------------------------------------------------------------------------------------|------------|--------------------|--------|------------------|
| Test Requirement:     | FCC Part15 C Section 15.209                                                                     |            |                    |        |                  |
| Test Method:          | ANSI C63.10:2013                                                                                |            |                    |        |                  |
| Test Frequency Range: | 30MHz to 25GHz                                                                                  |            |                    |        |                  |
| Test site:            | Measurement Distance: 3m                                                                        |            |                    |        |                  |
| Receiver setup:       | Frequency                                                                                       | Detector   | RBW                | VBW    | Remark           |
|                       | 30MHz-1GHz                                                                                      | Quasi-peak | 120KHz             | 300KHz | Quasi-peak Value |
|                       | Above 1GHz                                                                                      | Peak       | 1MHz               | 3MHz   | Peak Value       |
|                       |                                                                                                 | Peak       | 1MHz               | 10Hz   | Average Value    |
| Limit:                | Frequency                                                                                       |            | Limit (dBuV/m @3m) |        | Remark           |
|                       | 30MHz-88MHz                                                                                     |            | 40.0               |        | Quasi-peak Value |
|                       | 88MHz-216MHz                                                                                    |            | 43.5               |        | Quasi-peak Value |
|                       | 216MHz-960MHz                                                                                   |            | 46.0               |        | Quasi-peak Value |
|                       | 960MHz-1GHz                                                                                     |            | 54.0               |        | Quasi-peak Value |
|                       | Above 1GHz                                                                                      |            | 54.0               |        | Average Value    |
|                       |                                                                                                 |            | 74.0               |        | Peak Value       |
| Test setup:           | Below 1GHz                                                                                      |            |                    |        |                  |
|                       | <div></div> |            |                    |        |                  |
|                       | Above 1GHz                                                                                      |            |                    |        |                  |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <p>Test Procedure:</p>   | <ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol> |
| <p>Test Instruments:</p> | <p>Refer to section 6.0 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <p>Test mode:</p>        | <p>Refer to section 5.2 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <p>Test results:</p>     | <p>Pass</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |


**Remark:**

1. During the test, pre-scan the GFSK, Pi/4QPSK modulation, and found the GFSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

## Measurement data:

### Vertical:

#### Radiated Emission Measurement




| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measure-ment | Limit  | Margin | Antenna Height | Table Degree |        |
|-----|-----|----------|---------------|----------------|--------------|--------|--------|----------------|--------------|--------|
|     |     | MHz      | dBuV          | dB             | dBuV/m       | dBuV/m | dB     | Detector       | cm           | degree |
| 1   | *   | 124.4826 | 25.87         | 12.89          | 38.76        | 43.50  | -4.74  | QP             | 100          | 360    |
| 2   |     | 138.3873 | 24.69         | 13.73          | 38.42        | 43.50  | -5.08  | peak           |              |        |
| 3   |     | 173.6263 | 23.24         | 13.19          | 36.43        | 43.50  | -7.07  | QP             | 100          | 360    |
| 4   |     | 202.8104 | 27.58         | 10.43          | 38.01        | 43.50  | -5.49  | peak           |              |        |
| 5   |     | 319.9370 | 22.71         | 13.87          | 36.58        | 46.00  | -9.42  | QP             | 100          | 300    |
| 6   |     | 410.3825 | 23.61         | 15.93          | 39.54        | 46.00  | -6.46  | peak           |              |        |

Note:1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

## Horizontal:

### Radiated Emission Measurement



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measure-ment | Limit  | Margin | Antenna Height | Table Degree |         |
|-----|-----|----------|---------------|----------------|--------------|--------|--------|----------------|--------------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m       | dBuV/m | dB     | cm             | degree       | Comment |
| 1   | *   | 124.5690 | 27.32         | 12.89          | 40.21        | 43.50  | -3.29  | QP             | 100          | 360     |
| 2   |     | 138.3873 | 25.19         | 13.73          | 38.92        | 43.50  | -4.58  | peak           |              |         |
| 3   |     | 173.8135 | 21.73         | 13.15          | 34.88        | 43.50  | -8.62  | QP             |              |         |
| 4   |     | 203.5226 | 26.40         | 10.46          | 36.86        | 43.50  | -6.64  | peak           |              |         |
| 5   |     | 319.9370 | 26.07         | 13.87          | 39.94        | 46.00  | -6.06  | QP             |              |         |
| 6   |     | 404.6664 | 26.22         | 15.66          | 41.88        | 46.00  | -4.12  | peak           |              |         |

Note:1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

## ■ Above 1GHz

|               |        |
|---------------|--------|
| Test channel: | Lowest |
|---------------|--------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4804.00         | 37.77             | 31.78                 | 8.60            | 32.09                    | 46.06          | 74.00               | -27.94          | Vertical     |
| 7206.00         | 32.39             | 36.15                 | 11.65           | 32.00                    | 48.19          | 74.00               | -25.81          | Vertical     |
| 9608.00         | 31.81             | 37.95                 | 14.14           | 31.62                    | 52.28          | 74.00               | -21.72          | Vertical     |
| 12010.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14412.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4804.00         | 42.56             | 31.78                 | 8.60            | 32.09                    | 50.85          | 74.00               | -23.15          | Horizontal   |
| 7206.00         | 33.76             | 36.15                 | 11.65           | 32.00                    | 49.56          | 74.00               | -24.44          | Horizontal   |
| 9608.00         | 31.16             | 37.95                 | 14.14           | 31.62                    | 51.63          | 74.00               | -22.37          | Horizontal   |
| 12010.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14412.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4804.00         | 26.99             | 31.78                 | 8.60            | 32.09                    | 35.28          | 54.00               | -18.72          | Vertical     |
| 7206.00         | 20.61             | 36.15                 | 11.65           | 32.00                    | 36.41          | 54.00               | -17.59          | Vertical     |
| 9608.00         | 20.06             | 37.95                 | 14.14           | 31.62                    | 40.53          | 54.00               | -13.47          | Vertical     |
| 12010.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14412.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4804.00         | 31.03             | 31.78                 | 8.60            | 32.09                    | 39.32          | 54.00               | -14.68          | Horizontal   |
| 7206.00         | 23.00             | 36.15                 | 11.65           | 32.00                    | 38.80          | 54.00               | -15.20          | Horizontal   |
| 9608.00         | 19.92             | 37.95                 | 14.14           | 31.62                    | 40.39          | 54.00               | -13.61          | Horizontal   |
| 12010.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14412.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

### Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

|               |        |
|---------------|--------|
| Test channel: | Middle |
|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4882.00         | 38.17             | 31.85                 | 8.67            | 32.12                    | 46.57          | 74.00               | -27.43          | Vertical     |
| 7323.00         | 31.94             | 36.37                 | 11.72           | 31.89                    | 48.14          | 74.00               | -25.86          | Vertical     |
| 9764.00         | 32.22             | 38.35                 | 14.25           | 31.62                    | 53.20          | 74.00               | -20.80          | Vertical     |
| 12205.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14646.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4882.00         | 42.28             | 31.85                 | 8.67            | 32.12                    | 50.68          | 74.00               | -23.32          | Horizontal   |
| 7323.00         | 34.48             | 36.37                 | 11.72           | 31.89                    | 50.68          | 74.00               | -23.32          | Horizontal   |
| 9764.00         | 31.69             | 38.35                 | 14.25           | 31.62                    | 52.67          | 74.00               | -21.33          | Horizontal   |
| 12205.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14646.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4882.00         | 27.05             | 31.85                 | 8.67            | 32.12                    | 35.45          | 54.00               | -18.55          | Vertical     |
| 7323.00         | 20.92             | 36.37                 | 11.72           | 31.89                    | 37.12          | 54.00               | -16.88          | Vertical     |
| 9764.00         | 20.31             | 38.35                 | 14.25           | 31.62                    | 41.29          | 54.00               | -12.71          | Vertical     |
| 12205.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14646.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4882.00         | 31.37             | 31.85                 | 8.67            | 32.12                    | 39.77          | 54.00               | -14.23          | Horizontal   |
| 7323.00         | 22.96             | 36.37                 | 11.72           | 31.89                    | 39.16          | 54.00               | -14.84          | Horizontal   |
| 9764.00         | 19.52             | 38.35                 | 14.25           | 31.62                    | 40.50          | 54.00               | -13.50          | Horizontal   |
| 12205.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14646.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

|               |         |
|---------------|---------|
| Test channel: | Highest |
|---------------|---------|

## Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4960.00         | 38.30             | 31.93                 | 8.73            | 32.16                    | 46.80          | 74.00               | -27.20          | Vertical     |
| 7440.00         | 32.49             | 36.59                 | 11.79           | 31.78                    | 49.09          | 74.00               | -24.91          | Vertical     |
| 9920.00         | 32.18             | 38.81                 | 14.38           | 31.88                    | 53.49          | 74.00               | -20.51          | Vertical     |
| 12400.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14880.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4960.00         | 42.57             | 31.93                 | 8.73            | 32.16                    | 51.07          | 74.00               | -22.93          | Horizontal   |
| 7440.00         | 34.21             | 36.59                 | 11.79           | 31.78                    | 50.81          | 74.00               | -23.19          | Horizontal   |
| 9920.00         | 31.33             | 38.81                 | 14.38           | 31.88                    | 52.64          | 74.00               | -21.36          | Horizontal   |
| 12400.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14880.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

## Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4960.00         | 26.55             | 31.93                 | 8.73            | 32.16                    | 35.05          | 54.00               | -18.95          | Vertical     |
| 7440.00         | 20.67             | 36.59                 | 11.79           | 31.78                    | 37.27          | 54.00               | -16.73          | Vertical     |
| 9920.00         | 20.09             | 38.81                 | 14.38           | 31.88                    | 41.40          | 54.00               | -12.60          | Vertical     |
| 12400.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14880.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4960.00         | 30.92             | 31.93                 | 8.73            | 32.16                    | 39.42          | 54.00               | -14.58          | Horizontal   |
| 7440.00         | 22.74             | 36.59                 | 11.79           | 31.78                    | 39.34          | 54.00               | -14.66          | Horizontal   |
| 9920.00         | 19.80             | 38.81                 | 14.38           | 31.88                    | 41.11          | 54.00               | -12.89          | Horizontal   |
| 12400.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14880.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.