


Prüfbericht-Nr.: <i>Test Report No.:</i>	50113682 001	Auftrags-Nr.: <i>Order No.:</i>	144168698	Seite 1 von 14 <i>Page 1 of 14</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	05.12.2017	
Auftraggeber: <i>Client:</i>	Glen Dimplex Ireland Barn Road, Dunleer, Co. Louth, Ireland			
Prüfgegenstand: <i>Test item:</i>	Bluetooth Low Energy Module			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	EP4106			
Auftrags-Inhalt: <i>Order content:</i>	TUV Rheinland - EMC service			
Prüfgrundlage: <i>Test specification:</i>	FCC Part 15 Subpart C ANSI C63.10-2013			
Wareneingangsdatum: <i>Date of receipt:</i>	06.03.2018			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000703213-001			
Prüfzeitraum: <i>Testing period:</i>	11.05.2018 - 14.05.2018			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Hong Kong Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Hong Kong Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:	kontrolliert von / reviewed by:			
 09.01.2019 Mika Chan / Project Manager		 09.01.2019 Sharon Li / Unit Senior Manager		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
Sonstiges / Other: FCC ID: 2AP2M4106				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>			Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>	
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(fail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(fail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	4
Manufacturers declarations	4
Product function and intended use.....	4
Submitted documents.....	4
Independent Operation Modes	4
Related Submittal(s) Grants	4
Remark	4
Test Set-up and Operation Mode.....	5
Principle of Configuration Selection	5
Test Operation and Test Software.....	5
Special Accessories and Auxiliary Equipment.....	5
Countermeasures to achieve EMC Compliance.....	5
Test Methodology	6
Radiated Emission	6
Field Strength Calculation.....	6
Test Setup Diagram	7
Test Facility	9
Test Laboratory Information	9
List of Test and Measurement Instruments.....	10
Measurement Uncertainty	11
Results FCC Part 15 – Subpart C	12
FCC 15.203 – Antenna Requirement 1.....	Pass.....
FCC 15.204 – Antenna Requirement 2.....	N/A.....
FCC 15.247 (a)(2) – 6dB Bandwidth Measurement	Pass.....
FCC 15.247(b)(3) – Maximum Peak Coudected Output Power	Pass.....
FCC 15.247(e) – Power Spectral Density.....	Pass.....
FCC 15.247(d) – Spurious Conducted Emissions.....	Pass.....
Appendix 1 – Test protocols	15 pages

Appendix 2 – EUT External Photos	2 pages
Appendix 3 – EUT Internal Photos	2 pages
Appendix 4 – RF exposure information.....	2 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK
Number of channels	40
Channel separation	2 MHz
Type of antenna	PCB Antenna
Antenna gain (dBi)	1.6 dBi
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	Yes
Nominal voltage	V _{nor} : 100-240VAC and 3.3 VDC
Independent Operation Modes	Transmitting

Product function and intended use

The equipment under test (EUT) is a Bluetooth low energy device.

FCC ID: 2AP2M4106

Models	Product description
EP4106	Bluetooth Low Energy Module

Submitted documents

Circuit Diagram
 Block Diagram
 Technical Description
 User manual
 Label

Independent Operation Modes

The basic operation modes are:

- Transmitting mode.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- During test, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power was selected according to the instruction given by the manufacturer. The setting of the RF output power expected by the customer shall be fixed on the firmware of the final end product.

Special Accessories and Auxiliary Equipment

- AC-DC adaptor model: VEL05US050-EU-JA (Provided by Applicant)

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)





Diagram of Equipment Configuration for Antenna-port Conducted Measurement (if applicable)



Test Facility

Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.

Address: 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong

Tel.: +852 2192 1000

Fax: +852 2192 1001

Email service-gc@tuv.com

Web: www.tuv.com

The test facility is recognized or accredited by the following organizations:

Type	: Accredited Test Firm
Designation Number	: HK0013
Test Firm Registration Number	: 371735
Scope	: Intentional Radiators

List of Test and Measurement Instruments

TÜV Rheinland Hong Kong Ltd

Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R & S	FSP30	28-Sep-2017	27-Sep-2018

Measurement Uncertainty

The estimated combined standard uncertainty for antenna conducted emission is $\pm 2.1\text{dB}$

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for the level of confidence is approximately 95%.

Results FCC Part 15 – Subpart C

FCC 15.203 – Antenna Requirement 1		Pass
FCC Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	a) Antenna type: b) Manufacturer and model no: c) Peak Gain:	Integral PCB antenna N/A 1.6 dBi
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		N/A
FCC Requirement:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.	
Results:	Only one integral antenna can be used.	
Verdict:	N/A	

FCC 15.247 (a)(2) – 6dB Bandwidth Measurement		Pass	
FCC Requirement:	Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.		
Test Specification	: ANSI C63.10 – 2013		
Test date	: 11.05.2018		
Mode of operation	: Tx mode		
Port of testing	: Temporary antenna port		
Supply voltage	: 120VAC		
Temperature	: 23°C		
Humidity	: 50%		
Results:	For test protocols please refer to Appendix 1		
Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (kHz)
2402	2401.634	2402.360	726.0
2440	2439.634	2440.354	720.0
2480	2479.628	2480.348	720.0

FCC 15.247(b)(3) – Maximum Peak Coudected Output Power		Pass																
FCC Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt (30dBm)																		
Test Specification : ANSI C63.10 – 2013 Test date : 11.05.2018 Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 120VAC Temperature : 23°C Humidity : 50%																		
Results: For test protocols please refer to Appendix 1																		
<table border="1"> <thead> <tr> <th>Frequency (MHz)</th><th>Measured Output Power (dBm)</th><th>Limit (W/dBm)</th><th>Verdict</th></tr> </thead> <tbody> <tr> <td>2402</td><td>-0.98</td><td>1 / 30.0</td><td>Pass</td></tr> <tr> <td>2440</td><td>-1.05</td><td>1 / 30.0</td><td>Pass</td></tr> <tr> <td>2480</td><td>-1.23</td><td>1 / 30.0</td><td>Pass</td></tr> </tbody> </table>			Frequency (MHz)	Measured Output Power (dBm)	Limit (W/dBm)	Verdict	2402	-0.98	1 / 30.0	Pass	2440	-1.05	1 / 30.0	Pass	2480	-1.23	1 / 30.0	Pass
Frequency (MHz)	Measured Output Power (dBm)	Limit (W/dBm)	Verdict															
2402	-0.98	1 / 30.0	Pass															
2440	-1.05	1 / 30.0	Pass															
2480	-1.23	1 / 30.0	Pass															

FCC 15.247(e) – Power Spectral Density		Pass																
FCC Requirement: For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.																		
Test Specification : ANSI C63.10 – 2013 Test date : 11.05.2018 Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 120VAC Temperature : 23°C Humidity : 50%																		
Results: For test protocols please refer to Appendix 1.																		
<table border="1"> <thead> <tr> <th>Operating frequency (MHz)</th><th>Power density (dBm)</th><th>Limit (dBm)</th><th>Verdict</th></tr> </thead> <tbody> <tr> <td>2402</td><td>-1.67</td><td>8.0</td><td>Pass</td></tr> <tr> <td>2440</td><td>-1.75</td><td>8.0</td><td>Pass</td></tr> <tr> <td>2480</td><td>-1.96</td><td>8.0</td><td>Pass</td></tr> </tbody> </table>			Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict	2402	-1.67	8.0	Pass	2440	-1.75	8.0	Pass	2480	-1.96	8.0	Pass
Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict															
2402	-1.67	8.0	Pass															
2440	-1.75	8.0	Pass															
2480	-1.96	8.0	Pass															

FCC 15.247(d) – Spurious Conducted Emissions		Pass			
Test Specification	:	ANSI C63.10 – 2013			
Test date	:	14.05.2018			
Mode of operation	:	Tx mode			
Port of testing	:	Temporary antenna port			
Supply voltage	:	120VAC			
Temperature	:	23°C			
Humidity	:	50%			
FCC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Only the worst cases is shown below. For test protocols refer to Appendix 1				
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	4800	-34.84	-1.67	-33.17	Pass
2440	4880	-34.59	-1.75	-32.84	Pass
2480	4960	-34.83	-1.96	-32.87	Pass