



■ Report No.: DDT-R19090307-1E12

■ Issued Date: Nov. 27, 2019

RF EXPOSURE REPORT

FOR

Applicant	:	GUANGZHOU FLYAUDIO CAR AUDIO CO.,LIMITED
Address	:	Building 2 & 3, No. 11, Nanxiang 3rd Road, High-Tech Industrial Development Zon, Guangzhou
Equipment under Test	:	Car Navigation
Model No.	:	G6124K01B9, G6124K02B9, G6124K03B9, G6124K04B9, G6124K05B9
Trade Mark	:	FlyAudio 飞乐
FCC ID	DONG D	TESTING
FCC ID	:	2AP3L-G6124K
Manufacturer	:	Guangdong Creator & Flyaudio Ele & Tech Co LTD
Address	:	Floor 1&3&4, Building D1 Banxian Shan No. 3 Industrial District, Heng Li Town Dongguang City.

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

Test report declares.....	3
1. General information.....	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory.....	6
2. RF Exposure evaluation.....	6
2.1. Requirement.....	6
2.2. Calculation Method	7
2.3. Estimation Result	7

TEST REPORT DECLARE

Applicant	:	GUANGZHOU FLYAUDIO CAR AUDIO CO.,LIMITED
Address	:	Building 2 & 3, No. 11, Nanxiang 3rd Road, High-Tech Industrial Development Zon, Guangzhou
Equipment under Test	:	Car Navigation
Model No.	:	G6124K01B9, G6124K02B9, G6124K03B9, G6124K04B9, G6124K05B9
Trade mark	:	FlyAUDIO 飞歌
Manufacturer	:	Guangdong Creator & Flyaudio Ele & Tech Co LTD
Address	:	Floor 1&3&4, Building D1 Banxian Shan No. 3 Industrial District, Heng Li Town Dongguang City.

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R19090307-1E12
Date of Receipt:	Oct. 09, 2019

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Nov. 04, 2019	

1. General information

1.1. Description of Equipment

EUT* Name	: Car Navigation
Model Number	: G6124K01B9, G6124K02B9, G6124K03B9, G6124K04B9, G6124K05B9
Difference of models	: G6124K01B9, G6124K02B9, G6124K03B9, G6124K04B9, G6124K05B9, all models have the same Antenna shape, circuit diagram and RF module, but only difference appearance, so choose G6124K01B9 for testing.
EUT function description	: Please reference user manual of this device
Power supply	: DC 12V
Radio Specification	: Bluetooth V4.1, IEEE802.11b/g/n
Operation frequency	: Bluetooth: 2402MHz-2480MHz 2412MHz-2462MHz
Modulation	: Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, QPSK, BPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Data rate	: Bluetooth: 1Mbps, 2Mbps, 3Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11n HT20: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65, 78, 104, 117, 130 Mbps IEEE 802.11n HT40: 13.5, 27, 40.5, 54, 81, 108, 121.5, 135, 162, 216, 243, 270 Mbps
Antenna Type	: Integrated antenna, maximum PK gain: 2.5 dBi
Sample Type	: Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
Bluetooth Max power	7.28	5.35	2.5	1.78	0.002	1
2.4G WIFI Max power	22.50	177.83	2.5	1.78	0.063	1

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

END OF REPORT