



MPE TEST REPORT

Applicant Flextronics (Shanghai) Co., Ltd

FCC ID 2AP3PTRINITY

Product FT700 series - In-cab advanced telematics tracker
HT800 series - Rugged advanced telematics tracker

Model FT700-LM0Q-GL, HT800-LM0Q-GL,
HT801-LM0Q-GL

Report No. R1908A0467-M1

Issue Date December 30, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Yu Wang

Approved by: Guangchang Fan

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test Laboratory.....	3
1.1	Notes of the Test Report	3
1.2	Testing Location.....	3
1.3	Laboratory Environment.....	3
2	Description of Equipment under Test.....	4
3	Maximum conducted output power (measured) and antenna Gain	5
4	Test Result	6



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

1.3 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment under Test

Client Information

Applicant	Flextronics (Shanghai) Co., Ltd
Applicant address	4F, Bldg. 10, No. 3000 Longdong Ave., Pudong New District, Shanghai, China, 201203
Manufacturer	Flex Industrial, Ltd.
Manufacturer address	Level 3, Alexander House, 35 Cybercity, Ebene, Mauritius

General Technologies

Model	FT700-LM0Q-GL, HT800-LM0Q-GL, HT801-LM0Q-GL
IMEI	015578001000015
Hardware Version	P2.1
Software Version	2.2.5
Date of Testing:	October 15, 2019~ November 19, 2019

3 Maximum conducted output power (measured) and antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G)=10^{^(antenna gain/10)}

Band	Burst Turn up Power(dBm)	Division Factors (dB)	Time-Averaged Tune up Power (dBm)
GSM 850	33.00	-3.01	29.99
GSM 1900	30.00	-3.01	26.99

Note:

Division Factors

To average the power, the division factor is as follows:

1Txslot = 1 transmit time slot out of 8 time slots

=> conducted power divided by (8/1) => -9.03 dB

2Txslots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3Txslots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4Txslots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

Band	Maximum Conducted Output Power (dBm)		Antenna Gain (dBi)	Numeric gain
	(dBm)	(mW)		
GSM 850	29.99	997.700	0.0	1.000
GSM 1900	26.99	500.035	1.0	1.259
LTE Band 2	24.00	251.189	2.5	1.778
LTE Band 4	23.00	199.526	2.5	1.778
LTE Band 5	24.00	251.189	2.5	1.778
LTE Band 12	24.00	251.189	2.5	1.778
LTE Band 13	24.00	251.189	2.5	1.778
LTE Band 26	24.00	251.189	2.5	1.778
NB-IOT Band 2	24.00	251.189	2.5	1.778
NB-IOT Band 4	23.00	199.526	2.5	1.778
NB-IOT Band 5	24.00	251.189	2.5	1.778
NB-IOT Band 12	24.00	251.189	2.5	1.778
NB-IOT Band 13	24.00	251.189	2.5	1.778
NB-IOT Band 26	24.00	251.189	2.5	1.778
Wi-Fi 2.4G	16.52	44.875	2.0	1.585
Bluetooth (Low Energy)	8.10	6.457	1.0	1.259

4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



The maximum permissible exposure for 300~1500 MHz is f/1500, for 1500~100,000MHz is 1.0. So

Band	The maximum permissible exposure
GSM850	0.55mW/cm ²
GSM1900	1.0mW/cm ²
LTE Band 2	1.0mW/cm ²
LTE Band 4	1.0mW/cm ²
LTE Band 5	0.55mW/cm ²
LTE Band 12	0.47mW/cm ²
LTE Band 13	0.52mW/cm ²
LTE Band 26	0.55mW/cm ²
NB-IOT Band 2	1.0mW/cm ²
NB-IOT Band 4	1.0mW/cm ²
NB-IOT Band 5	0.55mW/cm ²
NB-IOT Band 12	0.47mW/cm ²
NB-IOT Band 13	0.52mW/cm ²
NB-IOT Band 26	0.55mW/cm ²
Wi-Fi 2.4G	1.00mW/cm ²
Bluetooth (Low Energy)	1.00mW/cm ²

**RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	PG (mW)	Test Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE ratio	Conclusion
GSM 850	997.700	0.198	0.550	0.361	Pass
GSM 1900	629.506	0.125	1.000	0.125	Pass
LTE Band 2	446.684	0.089	1.000	0.089	Pass
LTE Band 4	354.813	0.071	1.000	0.071	Pass
LTE Band 5	446.684	0.089	0.550	0.162	Pass
LTE Band 12	446.684	0.089	0.470	0.189	Pass
LTE Band 13	446.684	0.089	0.520	0.171	Pass
LTE Band 26	446.684	0.089	0.550	0.162	Pass
NB-IOT Band 2	446.684	0.089	1.000	0.089	Pass
NB-IOT Band 4	354.813	0.071	1.000	0.071	Pass
NB-IOT Band 5	446.684	0.089	0.550	0.162	Pass
NB-IOT Band 12	446.684	0.089	0.470	0.189	Pass
NB-IOT Band 13	446.684	0.089	0.520	0.171	Pass
NB-IOT Band 26	446.684	0.089	0.550	0.162	Pass
Wi-Fi 2.4G	71.121	0.014	1.000	0.014	Pass
Bluetooth (Low Energy)	8.128	0.002	1.000	0.002	Pass
Note: R = 20cm $\pi = 3.1416$ The MPE ratio = Mac Test Result ÷ Limit Value					

So the simultaneous transmitting antenna pairs as below:

Σ of MPE ratios= Main Antenna + Wi-Fi 2.4G = 0.361+0.014 = 0.375 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.