



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190400302E-02
Applicant: Shenzhen Pu Chuang Technology Industrial Co., Ltd.
Address of Applicant: 6/F, Building C, Mianshang Youth Pioneering Park, Hangcheng Avenue, Gushu, Bao'an District, Shenzhen, China
Manufacturer: Shenzhen Pu Chuang Technology Industrial Co., Ltd.
Address of Manufacturer: 6/F, Building C, Mianshang Youth Pioneering Park, Hangcheng Avenue, Gushu, Bao'an District, Shenzhen, China
Factory: Shenzhen Pu Chuang Technology Industrial Co., Ltd.
Address of Factory: 6/F, Building C, Mianshang Youth Pioneering Park, Hangcheng Avenue, Gushu, Bao'an District, Shenzhen, China
Equipment Under Test (EUT):
Product: Smart Bracelet
All Model No.: G18, G20, G20Plus, G21, G22, G26, G28, G29, G30, G30Pro, G100, G100Plus
Test Model No.: G20
Brand Name: N/A
FCC ID: 2AP5B-G20
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Test: 2019-04-30 to 2019-05-08
Date of Issue: 2019-05-08
Test Result : PASS*

Tested By:

Daisy Qin

(Daisy Qin)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190400302E-02	Rev.01	Initial report	2019-05-08

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits	5
4.1.3 EUT RF Exposure.....	6

3 General Information

3.1 Client Information

Applicant:	Shenzhen Pu Chuang Technology Industrial Co., Ltd.
Address of Applicant:	6/F, Building C, Mianshang Youth Pioneering Park, Hangcheng Avenue, Gushu, Bao 'an District, Shenzhen, China
Manufacturer:	Shenzhen Pu Chuang Technology Industrial Co., Ltd.
Address of Manufacturer:	6/F, Building C, Mianshang Youth Pioneering Park, Hangcheng Avenue, Gushu, Bao 'an District, Shenzhen, China
Factory:	Shenzhen Pu Chuang Technology Industrial Co., Ltd.
Address of Factory:	6/F, Building C, Mianshang Youth Pioneering Park, Hangcheng Avenue, Gushu, Bao 'an District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Smart Bracelet
All Model No.:	G18, G20, G20Plus, G21, G22, G26, G28, G29, G30, G30Pro, G100, G100Plus
Test Model No.:	G20
Trade Mark:	N/A
Hardware Version:	56
Software Version:	RH122V03
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	RTL8762C_RFTestTool_v1.0.1.1 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	lithium battery:DC3.7V, Charge by DC5.0V

Note:

All model: G18, G20, G20Plus, G21, G22, G26, G28, G29, G30, G30Pro, G100, G100Plus

Only the model G20 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)		(dBm)
Lowest(2402MHz)	1.77	1.0±1		2.0
Middle(2440MHz)	1.97	1.0±1		-2.0
Highest(2480MHz)	2.15	1.5±1		2.5
				1.585
				1.585
				1.778

Worst case: GFSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	1.77	1.0±1	2.0	1.585	0.49	3.0
Middle (2440MHz)	1.97	1.0±1	2.0	1.585	0.50	
Highest (2480MHz)	2.15	1.5±1	2.5	1.778	0.56	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190400302E-01