



FCC SAR TEST REPORT

Report No.: STS2301306H01

Issued for

WHOOP INTERNATIONAL TRADING LIMITED

Flat-B 8/F Chong Gming Building 72 Cheung Sha Wan Road,
Kowloon, Hong Kong

Product Name:	10.1 inch Quad Core 4G Tablet PC
Brand Name:	ROVER
Model Name:	R10
Series Model:	N/A
FCC ID:	2AP7LR10
Test Standard:	ANSI/IEEE Std. C95.1
	FCC 47 CFR Part 2 (2.1093)
	IEEE 1528: 2013
Max. Report SAR (1g):	Body: 1.510 W/kg

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





Test Report Certification

Applicant's name : WHOOP INTERNATIONAL TRADING LIMITED
Address : Flat-B 8/F Chong Gming Building 72 Cheung Sha Wan Road,
Kowloon, Hong Kong
Manufacturer's Name : Shenzhen Teleone Technology Co., Ltd
Address : Tower B 5/F, Shanshui Building, Nanshan Yungu Innovation
Industry Park, 4093 Liuxian Avenue, Shenzhen, China

Product description

Product name : 10.1 inch Quad Core 4G Tablet PC
Brand name : ROVER
Model name : R10
Series Model..... : N/A

Standards..... : ANSI/IEEE Std. C95.1-1992
FCC 47 CFR Part 2 (2.1093)
IEEE 1528: 2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test..... :

Date (s) of performance of tests..... : 28 Feb. 2023 ~ 06 Mar. 2023

Date of Issue..... : 08 Mar. 2023

Test Result..... : **Pass**

Testing Engineer :

(Shifan. Long)

Technical Manager :

(Sean she)

Authorized Signatory :

(Bovey Yang)





Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	15
5.1 Validation System	15
5.2 Validation Result	15
6. SAR Evaluation Procedures	16
7. EUT Antenna Location Sketch	17
7.1 SAR test exclusion consider table	18
8. EUT Test Position	23
8.1 Body-worn Position Conditions	23
9. Uncertainty	24
9.1 Measurement Uncertainty	24
10. Conducted Power Measurement	25
10.1 Test Result	25
11. EUT and Test Setup Photo	43
11.1 EUT Photo	43
11.2 Setup Photo	46
12. SAR Result Summary	49
12.1 Body-worn and Hotspot SAR	49
13. Equipment List	59
Appendix A. System Validation Plots	60
Appendix B. SAR Test Plots	72
Appendix C. Probe Calibration and Dipole Calibration Report	85

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	08 Mar. 2023	STS2301306H01	ALL	Initial Issue





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	10.1 inch Quad Core 4G Tablet PC		
Brand Name	ROVER		
Model Name	R10		
Series Model	N/A		
Model Difference	N/A		
Battery	Rated Voltage:3.8V Charge Limit Voltage: 4.35V Capacity: 5100mAH		
Device Category	Portable		
Product stage	Production unit		
RF Exposure Environment	General Population / Uncontrolled		
Hardware Version	J865_610&310_D3EF_V1.1		
Software Version	ROVER_R10_12_V01_20221229		
Frequency Range	GSM 850: 824 MHz ~ 849 MHz PCS1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 66: 1710 MHz ~ 1780 MHz WLAN802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz Bluetooth: 2402 MHz to 2480 MHz		
Max. Reported SAR(1g): (Limit:1.6W/kg)	Band	Mode	Body Worn and Hotspot(W/kg)
	PCE	GSM 850	0.728
	PCE	GSM 1900	1.510
	PCE	WCDMA Band II	1.273
	PCE	WCDMA Band V	1.194
	PCE	WCDMA Band IV	1.218
	PCE	LTE Band 2	0.938
	PCE	LTE Band 4	0.685
	PCE	LTE Band 5	1.034
	PCE	LTE Band 12	1.113
	PCE	LTE Band 66	1.032
	DTS	2.4G WLAN	0.309
	DSS	BT	0.042
	NII	5.2G WLAN	0.436
1-g Sum SAR			1.577
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX(NII)		



Operating Mode:	GSM: GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN : 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 5G WLAN: 802.11a(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM):BPSK,QPSK,16-QAM,64-QAM,256-QAM Bluetooth: GFSK + π /4DQPSK+8DPSK BLE: GFSK
Antenna Specification:	GSM/WCDMA/LTE: PIFA Antenna Bluetooth: PIFA Antenna WLAN: PIFA Antenna
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot transmitting at the same time
Hotspot Mode	Support
DTM Mode	Not Support
Note: 1. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active) 2. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to perform all tests. 3. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power	



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01





2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg


3.1 Definition of Specific Absorption Rate (SAR)

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

Where: σ is the conductivity of the tissue,
 ρ is the mass density of the tissue and E is the RMS electrical field strength.

MVG SAR System Diagram:



- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 07/21 EPGO352 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


SN 32/14 SAM115



Figure-SN 21/21 ELLI48



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

4. Tissue Simulating Liquids



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Head Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity σ	Permittivity ϵ_r
750	0.2	/	/	1.4	0.2	57.0	/	41.1	0.89	41.9
835	0.2	/	/	1.4	0.2	57.9	/	40.3	0.90	41.5
900	0.2	/	/	1.4	0.2	57.9	/	40.3	0.97	41.5
1800	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
1900	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
2000	/	44.5	/	0.3	/	/	/	55.2	1.4	40.0
2450	/	44.9	/	0.1	/	/	/	55.0	1.80	39.2
2600	/	45.0	/	0.1	/	/	/	54.9	1.96	39.0

Body Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity σ	Permittivity ϵ_r
750	0.2	/	/	0.9	0.1	47.2	/	51.7	0.96	55.5
835	0.2	/	/	0.9	0.1	48.2	/	50.8	0.97	55.2
900	0.2	/	/	0.9	0.1	48.2	/	50.8	1.05	55.0
1800	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
1900	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
2000	/	29.4	/	0.4	/	/	/	70.2	1.52	53.3
2450	/	31.3	/	0.1	/	/	/	68.6	1.95	52.7
2600	/	31.7	/	0.1	/	/	/	68.2	2.16	52.3

Tissue dielectric parameters for head and body phantoms				
Frequency	ϵ_r		σ S/m	
	Head	Body	Head	Body
300	45.3	58.2	0.87	0.92
450	43.5	56.7	0.87	0.94
900	41.5	55.0	0.97	1.05
1450	40.5	54.0	1.20	1.30
1800	40.0	53.3	1.40	1.52
2450	39.2	52.7	1.80	1.95
3000	38.5	52.0	2.40	2.73
5800	35.3	48.2	5.27	6.00


**LIQUID MEASUREMENT RESULTS**

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2023-02-28	23.1	44	704	22.8	Permittivity	42.15	43.23	2.57	±5
					Conductivity	0.89	0.89	0.35	±5
2023-02-28	23.2	44	708	22.9	Permittivity	42.13	42.60	1.12	±5
					Conductivity	0.89	0.88	-0.81	±5
2023-02-28	23.2	45	711	22.9	Permittivity	42.11	42.87	1.81	±5
					Conductivity	0.89	0.92	3.67	±5
2023-02-28	23.2	45	750	22.9	Permittivity	41.90	42.57	1.60	±5
					Conductivity	0.89	0.86	-3.37	±5
2023-03-01	20.2	41	824.2	19.9	Permittivity	41.55	40.80	-1.81	±5
					Conductivity	0.90	0.89	-0.97	±5
2023-03-01	20.3	41	826.4	19.9	Permittivity	41.54	41.38	-0.39	±5
					Conductivity	0.90	0.91	1.22	±5
2023-03-01	20.3	41	829	20.1	Permittivity	41.53	41.57	0.10	±5
					Conductivity	0.90	0.93	3.41	±5
2023-03-01	20.4	41	835	20.1	Permittivity	41.50	41.77	0.65	±5
					Conductivity	0.90	0.86	-4.44	±5
2023-03-01	20.3	41	836.5	20.0	Permittivity	41.49	40.84	-1.57	±5
					Conductivity	0.90	0.88	-2.24	±5
2023-03-01	20.3	42	836.6	20.0	Permittivity	41.49	40.90	-1.43	±5
					Conductivity	0.90	0.88	-2.24	±5
2023-03-01	20.3	41	844	19.9	Permittivity	41.46	41.35	-0.26	±5
					Conductivity	0.90	0.89	-1.23	±5
2023-03-01	20.4	42	846.6	20.2	Permittivity	41.45	41.20	-0.59	±5
					Conductivity	0.90	0.87	-3.48	±5
2023-03-02	23.0	51	1712.6	22.8	Permittivity	40.12	41.29	2.90	±5
					Conductivity	1.35	1.36	0.74	±5
2023-03-02	23.1	51	1720	22.8	Permittivity	40.11	41.01	2.23	±5
					Conductivity	1.35	1.38	1.90	±5
2023-03-02	23.2	51	1740	22.9	Permittivity	40.09	41.15	2.66	±5
					Conductivity	1.37	1.35	-1.15	±5
2023-03-02	23.3	52	1745	23.1	Permittivity	40.08	40.34	0.65	±5
					Conductivity	1.37	1.39	1.57	±5



2023-03-02	23.1	51	1752.4	22.8	Permittivity	40.07	40.95	2.20	±5
					Conductivity	1.37	1.37	-0.20	±5
2023-03-02	23.1	51	1770	22.8	Permittivity	40.04	40.33	0.72	±5
					Conductivity	1.38	1.39	0.52	±5
2023-03-02	23.2	52	1800	22.9	Permittivity	40.00	40.20	0.50	±5
					Conductivity	1.40	1.42	1.43	±5
2023-03-03	22.1	50	1850.2	21.9	Permittivity	40.00	40.92	2.30	±5
					Conductivity	1.40	1.44	2.86	±5
2023-03-03	23.3	52	1852.4	23.0	Permittivity	40.00	41.00	2.50	±5
					Conductivity	1.40	1.35	-3.57	±5
2023-03-03	23.3	52	1860	23.0	Permittivity	40.00	40.46	1.15	±5
					Conductivity	1.40	1.38	-1.43	±5
2023-03-03	23.3	52	1880	23.0	Permittivity	40.00	40.96	2.40	±5
					Conductivity	1.40	1.45	3.57	±5
2023-03-03	23.4	52	1900	23.1	Permittivity	40.00	40.49	1.23	±5
					Conductivity	1.40	1.42	1.43	±5
2023-03-03	22.1	50	1907.6	21.8	Permittivity	40.00	39.99	-0.02	±5
					Conductivity	1.40	1.37	-2.14	±5
2023-03-03	22.2	51	1909.8	21.9	Permittivity	40.00	40.35	0.88	±5
					Conductivity	1.40	1.41	0.71	±5
2023-03-06	21.1	45	2440	20.8	Permittivity	39.22	40.50	3.27	±5
					Conductivity	1.79	1.75	-2.30	±5
2023-03-06	21.2	45	2450	20.9	Permittivity	39.20	40.12	2.35	±5
					Conductivity	1.80	1.78	-1.11	±5
2023-03-06	21.3	46	2462	21.0	Permittivity	39.18	40.52	3.42	±5
					Conductivity	1.81	1.88	3.83	±5
2023-03-06	20.5	55	5180	20.2	Permittivity	36.02	36.57	1.53	±5
					Conductivity	4.64	4.61	-0.63	±5
2023-03-06	20.6	55	5200	20.3	Permittivity	36.00	36.48	1.33	±5
					Conductivity	4.66	4.63	-0.64	±5

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.



1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position


- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a TABLET CON CHIP (4G), support GSM/WCDMA/LTE/WLAN/BT mode.



Antenna Separation Distance(cm)					
ANT	Back Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤0.5	5.5	10	14.9	≤0.5
WWAN	≤0.5	12.5	8.5	≤0.5	14.7

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA V
	Calculated Frequency(GHz)	0.8242	1.8522	1.8524	0.8264
	Maximum Turn-up power (dBm)	31.5	26	23.5	23
	Maximum rated power(mW)	1412.54	398.11	223.87	199.53
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	9.42	3.43	3.43	9.38
	Testing required?	YES	YES	YES	YES
Left Side	Separation distance (cm)	5.5	5.5	5.5	5.5
	exclusion threshold(mW)	273.92	283.99	283.98	274.04
	Testing required?	YES	YES	NO	NO
Right Side	Separation distance (cm)	10	10	10	10
	exclusion threshold(mW)	634.68	853.89	853.87	635.61
	Testing required?	YES	NO	NO	NO
Top Side	Separation distance (cm)	14.9	14.9	14.9	14.9
	exclusion threshold(mW)	1111.67	1779.54	1779.53	1114.07
	Testing required?	YES	NO	NO	NO
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	9.42	3.43	3.43	9.38
	Testing required?	YES	YES	YES	YES



Exposure Position	Wireless Interface	WCDMA IV	LTE Band 2	LTE Band 4	LTE Band 5
	Calculated Frequency(GHz)	1.7524	1.86	1.745	0.844
	Maximum Turn-up power (dBm)	23.5	24	24	23.5
	Maximum rated power(mW)	223.87	251.19	251.19	223.87
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.59	3.42	3.60	9.11
	Testing required?	YES	YES	YES	YES
Left Side	Separation distance (cm)	5.5	5.5	5.5	5.5
	exclusion threshold(mW)	288.43	283.65	288.77	274.96
	Testing required?	NO	NO	NO	NO
Right Side	Separation distance (cm)	10	10	10	10
	exclusion threshold(mW)	861.04	853.35	861.58	643.00
	Testing required?	NO	NO	NO	NO
Top Side	Separation distance (cm)	14.9	14.9	14.9	14.9
	exclusion threshold(mW)	1785.85	1779.06	1786.34	1133.20
	Testing required?	NO	NO	NO	NO
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	3.59	3.42	3.60	9.11
	Testing required?	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 12	LTE Band 66	BLE	2.4G WLAN	5.2G WLAN
	Calculated Frequency(GHz)	0.711	1.77	2.44	2.462	5.18
	Maximum Turn-up power (dBm)	24	24	6.6	10.5	9
	Maximum rated power(mW)	251.19	251.19	4.57	11.22	7.94
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	11.59	3.56	2.75	2.73	1.51
	Testing required?	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	5.5	5.5	12.5	12.5	12.5
	exclusion threshold(mW)	267.56	287.63	1252.09	1250.94	1159.49
	Testing required?	NO	NO	NO	NO	NO
Right Side	Separation distance (cm)	10	10	8.5	8.5	8.5
	exclusion threshold(mW)	585.28	859.74	601.44	600.43	522.93
	Testing required?	NO	NO	NO	NO	NO
Top Side	Separation distance (cm)	14.9	14.9	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	986.54	1784.71	2.75	2.73	1.51
	Testing required?	NO	NO	YES	YES	YES
Bottom Side	Separation distance (cm)	≤0.5	≤0.5	14.7	14.7	14.7
	exclusion threshold(mW)	11.59	3.56	1704.11	1703.09	1620.47
	Testing required?	YES	YES	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, if the maximum time-averaged power available does not exceed 1 mW. This stand-alone SAR exemption test.



4. Per KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

5. Per KDB 447498 D04, An alternative to the SAR-based exemption is using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in below table to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.



6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.




8. EUT Test Position

This EUT was tested in Back Side, Left Side, Right Side, Bottom Side and Top Side.

8.1 Body-worn Position Conditions

Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	vi
Measurement System								
Probe calibration	5.72	N	1	1	1	5.72	5.72	∞
Axial Isotropy	0.18	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.07	0.07	∞
Hemispherical Isotropy	1.04	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.42	0.42	∞
Boundary effect	0.8	R	$\sqrt{3}$	1	1	0.46	0.46	∞
Linearity	1.25	R	$\sqrt{3}$	1	1	0.72	0.72	∞
System detection limits	1.20	R	$\sqrt{3}$	1	1	0.69	0.69	∞
Modulation response	3.42	R	$\sqrt{3}$	1	1	3.42	3.42	∞
Readout Electronics	0.26	N	1	1	1	0.26	0.26	∞
Response Time	0.17	R	$\sqrt{3}$	1	1	0.10	0.10	∞
Integration Time	1.43	R	$\sqrt{3}$	1	1	0.83	0.83	∞
RF ambient conditions- Noise	3.51	R	$\sqrt{3}$	1	1	2.03	2.03	∞
RF ambient conditions- reflections	3.15	R	$\sqrt{3}$	1	1	1.82	1.82	∞
Probe positioner mechanical tolerance	1.2	R	$\sqrt{3}$	1	1	0.69	0.69	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Post-processing	2.1	R	$\sqrt{3}$	1	1	1.21	1.21	∞
Test sample Related								
Test sample positioning	3.1	N	1	1	1	3.10	3.10	∞
Device holder uncertainty	3.8	N	1	1	1	3.80	3.80	∞
SAR drift measurement	4.5	R	$\sqrt{3}$	1	1	2.60	2.60	∞
SAR scaling	1.8	R	$\sqrt{3}$	1	1	1.04	1.04	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	3.7	R	$\sqrt{3}$	1	1	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2.1	N	1	1	0.84	2.10	1.76	∞
Liquid conductivity (temperature uncertainty)	2.4	R	$\sqrt{3}$	0.78	0.71	1.87	1.70	∞
Liquid conductivity (measured)	4.1	N	1	0.78	0.71	0.94	1.07	M
Liquid permittivity (temperature uncertainty)	2.7	R	$\sqrt{3}$	0.23	0.26	2.11	1.92	∞
Liquid permittivity (measured)	4.8	N	1	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty		RSS				10.37	10.27	
Expanded Uncertainty (95% Confidence interval)		K=2				20.74	20.53	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GPRS (GMSK, 1-Slot)	33.36	33.17	33.11	30.36	30.33	30.25
GPRS (GMSK, 2-Slot)	31.27	31.10	30.86	28.34	28.04	27.80
GPRS (GMSK, 3-Slot)	29.33	29.19	28.99	26.70	26.42	26.16
GPRS (GMSK, 4-Slot)	27.21	27.13	27.01	25.57	24.29	24.04
EGPRS(8PSK, 1-Slot)	25.88	26.24	26.45	26.70	26.60	26.31
EGPRS(8PSK, 2-Slot)	25.66	25.86	25.89	25.35	25.30	24.33
EGPRS(8PSK, 3-Slot)	23.14	23.31	23.56	23.55	23.26	22.79
EGPRS(8PSK, 4-Slot)	20.64	20.96	20.97	21.47	21.26	20.46
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GPRS (GMSK, 1-Slot)	24.33	24.14	24.08	21.33	21.30	21.22
GPRS (GMSK, 2-Slot)	25.25	25.08	24.84	22.32	22.02	21.78
GPRS (GMSK, 3-Slot)	25.07	24.93	24.73	22.44	22.16	21.90
GPRS (GMSK, 4-Slot)	24.20	24.12	24.00	22.56	21.28	21.03
EGPRS(8PSK, 1-Slot)	16.85	17.21	17.42	17.67	17.57	17.28
EGPRS(8PSK, 2-Slot)	19.64	19.84	19.87	19.33	19.28	18.31
EGPRS(8PSK, 3-Slot)	18.88	19.05	19.30	19.29	19.00	18.53
EGPRS(8PSK, 4-Slot)	17.63	17.95	17.96	18.46	18.25	17.45
Remark : 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						

**WCDMA**

Band	WCDMA Band II			WCDMA Band V			WCDMA Band IV		
Channel	9262	9400	9538	4132	4183	4233	1312	1413	1513
Frequency (MHz)	1852.4	1880	1907.6	826.4	836.6	846.6	1712.6	1740	1752.4
RMC 12.2Kbps	23.35	23.16	23.09	22.94	22.76	22.89	22.99	23.03	23.11
HSDPA Subtest-1	23.16	23.00	22.77	22.86	22.49	22.25	22.77	22.25	22.13
HSDPA Subtest-2	22.58	23.11	22.94	22.16	22.44	22.21	22.04	22.97	22.76
HSDPA Subtest-3	22.65	22.48	22.89	21.74	21.68	22.74	22.46	22.16	22.65
HSDPA Subtest-4	22.75	22.21	22.02	22.47	22.23	22.18	22.38	22.01	22.06
HSUPA Subtest-1	22.95	23.01	22.54	22.66	22.65	22.46	22.58	22.58	22.41
HSUPA Subtest-2	23.11	22.67	22.95	22.63	22.27	22.42	22.59	22.23	22.61
HSUPA Subtest-3	23.04	22.77	23.08	22.42	22.31	22.35	22.85	22.68	22.90
HSUPA Subtest-4	22.91	22.71	22.80	22.26	22.52	22.74	22.44	22.44	22.49
HSUPA Subtest-5	22.38	22.84	22.76	22.42	22.67	22.59	22.10	22.58	22.38

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

**2.4G WLAN**

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
802.11b	1	2412	8.02	6.34
	6	2437	9.22	8.36
	11	2462	10.15	10.35
802.11g	1	2412	4.51	2.82
	6	2437	6.48	4.45
	11	2462	6.22	4.19
802.11 n-HT20	1	2412	4.86	3.06
	6	2437	6.65	4.62
	11	2462	6.44	4.41

Bluetooth

BT				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	-0.1	0.98
	39	2441	0.92	1.24
	78	2480	-1.9	0.65

BLE

BLE				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	5.73	3.74
	19	2440	6.49	4.46
	39	2480	3.76	2.38
GFSK(2Mbps)	0	2402	5.61	3.64
	19	2440	6.57	4.54
	39	2480	3.7	2.34

**WLAN (5.2Gband)**

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	36	5180	7.68	5.86
	40	5200	7.26	5.32
	48	5240	6.55	4.52
802.11 n-HT20	36	5180	8.46	7.01
	40	5200	8.1	6.46
	48	5240	6.98	4.99
802.11 n-HT40	38	5190	8.11	6.47
	46	5230	7.08	5.11
802.11ac-VHT20	36	5180	8.66	7.35
	40	5200	8.2	6.61
	48	5240	6.92	4.92
802.11ac-VHT40	38	5190	8.15	6.53
	46	5230	7.06	5.08
802.11ac-VHT80	42	5210	7.19	5.24



LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.78	23.76	23.39
1.4	1	2		23.77	23.80	23.44
1.4	1	5		23.83	23.74	23.49
1.4	3	0		23.68	23.56	23.50
1.4	3	1		23.75	23.62	23.51
1.4	3	2		23.71	23.61	23.51
1.4	6	0		22.76	22.54	22.46
1.4	1	0	16-QAM	23.13	22.87	23.08
1.4	1	2		23.21	22.96	23.13
1.4	1	5		23.18	22.90	23.17
1.4	3	0		23.19	22.72	22.64
1.4	3	1		23.24	22.67	22.66
1.4	3	2		23.24	22.71	22.64
1.4	6	0		22.22	21.88	21.48
3	1	0	QPSK	23.71	23.52	23.44
3	1	7		23.81	23.57	23.48
3	1	14		23.76	23.50	23.48
3	8	0		22.76	22.58	22.50
3	8	4		22.79	22.60	22.42
3	8	7		22.67	22.56	22.54
3	15	0		22.76	22.56	22.56
3	1	0	16-QAM	23.23	23.06	23.15
3	1	7		23.21	23.10	23.11
3	1	14		23.13	23.13	23.14
3	8	0		22.13	21.54	21.77
3	8	4		22.01	21.54	21.74
3	8	7		21.79	21.52	21.82
3	15	0		22.07	21.76	21.61



LTE BAND 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.72	23.55	23.50
5	1	12		23.66	23.50	23.54
5	1	24		23.63	23.47	23.55
5	12	0		22.73	22.58	22.50
5	12	6		22.75	22.70	22.54
5	12	11		22.65	22.53	22.43
5	25	0		22.62	22.57	22.52
5	1	0	16-QAM	22.75	22.73	22.24
5	1	12		22.69	22.74	22.25
5	1	24		22.73	22.72	22.31
5	12	0		22.04	21.55	21.48
5	12	6		21.77	21.58	21.41
5	12	11		21.71	21.56	21.48
5	25	0		21.73	21.77	21.66
10	1	0	QPSK	23.86	23.46	23.54
10	1	24		23.72	23.50	23.54
10	1	49		23.77	23.59	23.57
10	25	0		22.72	22.57	22.65
10	25	12		22.65	22.61	22.61
10	25	24		22.61	22.60	22.42
10	50	0		22.65	22.54	22.50
10	1	0	16-QAM	22.89	23.67	22.63
10	1	24		22.74	23.67	22.59
10	1	49		22.72	23.72	22.60
10	25	0		21.75	21.73	21.60
10	25	12		21.71	21.60	21.60
10	25	24		21.75	21.68	21.68
10	50	0		21.73	21.64	21.64



LTE BAND 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.75	23.55	23.66
15	1	37		23.58	23.55	23.62
15	1	74		23.61	23.51	23.62
15	36	0		22.64	22.73	22.58
15	36	18		22.74	22.66	22.59
15	36	39		22.74	22.64	22.52
15	75	0		22.74	22.68	22.69
15	1	0	16-QAM	23.57	23.24	23.27
15	1	38		23.53	23.23	23.24
15	1	75		23.47	23.23	23.18
15	36	0		21.77	21.80	21.73
15	36	18		21.75	21.79	21.63
15	36	39		21.72	21.78	21.70
15	75	0		21.81	21.69	21.70
20	1	0	QPSK	23.87	23.70	23.76
20	1	49		23.65	23.68	23.69
20	1	99		23.62	23.69	23.70
20	50	0		22.60	22.57	22.51
20	50	24		22.77	22.71	22.48
20	50	49		22.68	22.57	22.60
20	100	0		22.61	22.60	22.58
20	1	0	16-QAM	22.53	22.33	22.58
20	1	49		22.48	22.36	22.49
20	1	99		22.43	22.35	22.50
20	50	0		21.78	21.68	21.95
20	50	24		21.80	21.66	21.71
20	50	49		21.79	21.67	21.62
20	100	0		21.74	21.72	21.68



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.56	23.45	23.76
1.4	1	2		23.56	23.43	23.77
1.4	1	5		23.62	23.43	23.59
1.4	3	0		23.49	23.60	23.62
1.4	3	1		23.49	23.59	23.58
1.4	3	2		23.46	23.50	23.61
1.4	6	0		22.55	22.50	22.58
1.4	1	0	16-QAM	23.52	22.63	23.05
1.4	1	2		23.51	22.64	23.05
1.4	1	5		23.52	22.63	23.13
1.4	3	0		22.69	22.54	22.99
1.4	3	1		22.69	22.59	23.00
1.4	3	2		22.73	22.54	22.90
1.4	6	0		21.60	21.78	21.78
3	1	0	QPSK	23.35	23.43	23.69
3	1	7		23.44	23.39	23.65
3	1	14		23.41	23.48	23.68
3	8	0		22.55	22.52	22.51
3	8	4		22.40	22.56	22.57
3	8	7		22.45	22.51	22.56
3	15	0		22.37	22.54	22.55
3	1	0	16-QAM	23.60	23.20	23.05
3	1	7		23.55	23.20	23.17
3	1	14		23.53	23.20	23.08
3	8	0		21.45	21.84	21.63
3	8	4		21.42	21.87	21.64
3	8	7		21.46	21.83	21.65
3	15	0		21.64	21.60	21.59



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.33	23.68	23.46
5	1	12		23.44	23.60	23.48
5	1	24		23.40	23.67	23.47
5	12	0		22.61	22.57	22.56
5	12	6		22.42	22.57	22.56
5	12	11		22.44	22.59	22.63
5	25	0		22.54	22.59	22.61
5	1	0	16-QAM	22.59	22.25	22.70
5	1	12		22.64	22.28	22.75
5	1	24		22.66	22.19	22.78
5	12	0		21.49	21.52	21.68
5	12	6		21.50	21.48	21.65
5	12	11		21.43	21.47	21.64
5	25	0		21.63	21.66	21.64
10	1	0	QPSK	23.43	23.63	23.67
10	1	24		23.53	23.60	23.79
10	1	49		23.52	23.59	23.77
10	25	0		22.37	22.58	22.69
10	25	12		22.50	22.61	22.72
10	25	24		22.52	22.48	22.66
10	50	0		22.58	22.52	22.66
10	1	0	16-QAM	23.67	22.62	22.80
10	1	24		23.62	22.66	22.96
10	1	49		23.64	22.58	22.87
10	25	0		21.50	21.66	21.64
10	25	12		21.48	21.70	21.85
10	25	24		21.50	21.68	21.65
10	50	0		21.58	21.66	21.73



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.44	23.71	23.68
15	1	37		23.53	23.59	23.74
15	1	74		23.55	23.59	23.78
15	36	0		22.47	22.60	22.63
15	36	18		22.54	22.52	22.52
15	36	39		22.49	22.48	22.57
15	75	0		22.52	22.54	22.65
15	1	0	16-QAM	23.69	22.68	23.32
15	1	38		23.67	22.64	23.32
15	1	75		23.74	22.62	23.37
15	36	0		21.56	21.76	21.66
15	36	18		21.60	21.77	21.63
15	36	39		21.59	21.72	21.67
15	75	0		21.69	21.70	21.76
20	1	0	QPSK	23.48	23.58	23.57
20	1	49		23.56	23.56	23.68
20	1	99		23.60	23.55	23.81
20	50	0		22.58	22.52	22.65
20	50	24		22.61	22.63	22.48
20	50	49		22.66	22.60	22.76
20	100	0		22.56	22.50	22.55
20	1	0	16-QAM	22.19	22.71	22.69
20	1	49		22.25	22.82	22.73
20	1	99		22.35	22.81	22.88
20	50	0		21.70	21.71	21.64
20	50	24		21.70	21.70	21.61
20	50	49		21.77	21.68	21.76
20	100	0		21.57	21.64	21.72



LTE BAND 5

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.11	22.69	22.84
1.4	1	2		23.10	22.79	23.03
1.4	1	5		23.08	22.71	23.02
1.4	3	0		23.08	22.78	22.81
1.4	3	1		23.07	22.80	22.95
1.4	3	2		23.09	22.78	22.93
1.4	6	0		22.02	21.81	21.93
1.4	1	0	16-QAM	22.93	22.29	22.03
1.4	1	2		23.00	22.56	22.08
1.4	1	5		22.96	22.49	22.07
1.4	3	0		22.23	21.95	21.80
1.4	3	1		22.21	21.90	21.83
1.4	3	2		22.23	21.91	21.89
1.4	6	0		21.47	20.66	21.28
3	1	0	QPSK	23.01	22.76	22.81
3	1	7		22.98	22.79	22.89
3	1	14		23.04	22.77	22.93
3	8	0		22.07	21.73	21.82
3	8	4		22.03	21.75	21.89
3	8	7		22.10	21.76	21.87
3	15	0		21.98	21.86	21.94
3	1	0	16-QAM	22.90	22.38	22.64
3	1	7		22.92	22.51	22.63
3	1	14		22.88	22.47	22.69
3	8	0		21.18	20.98	20.94
3	8	4		21.16	20.88	21.05
3	8	7		20.95	20.79	21.19
3	15	0		21.34	20.76	21.04



LTE BAND 5

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.95	22.68	22.95
5	1	12		22.92	22.67	22.80
5	1	24		22.79	22.68	22.87
5	12	0		22.03	21.77	21.82
5	12	6		21.98	21.76	21.89
5	12	11		21.94	21.79	21.89
5	25	0		22.07	21.82	21.88
5	1	0	16-QAM	22.12	21.49	21.74
5	1	12		22.04	21.55	21.83
5	1	24		21.87	21.35	21.91
5	12	0		21.19	20.65	21.20
5	12	6		20.93	20.56	20.93
5	12	11		20.81	20.64	21.06
5	25	0		20.97	20.73	21.09
10	1	0	QPSK	23.17	22.90	22.70
10	1	24		22.94	22.90	22.88
10	1	49		22.89	22.86	22.99
10	25	0		21.91	21.83	21.81
10	25	12		21.79	21.85	21.84
10	25	24		22.14	21.70	21.93
10	50	0		21.68	21.82	21.84
10	1	0	16-QAM	22.95	22.75	21.52
10	1	24		22.73	22.40	21.66
10	1	49		22.80	22.34	21.97
10	25	0		20.80	20.76	21.16
10	25	12		20.72	20.66	21.21
10	25	24		21.04	20.82	20.98
10	50	0		20.82	20.75	21.24



LTE BAND 12

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.63	23.88	23.84
1.4	1	2		23.58	23.70	23.68
1.4	1	5		23.57	23.67	23.67
1.4	3	0		23.49	23.58	23.79
1.4	3	1		23.59	23.61	23.74
1.4	3	2		23.57	23.68	23.73
1.4	6	0		22.55	22.47	22.61
1.4	1	0	16-QAM	23.34	23.49	23.16
1.4	1	2		23.35	23.52	23.13
1.4	1	5		23.37	23.47	23.24
1.4	3	0		22.96	22.68	22.72
1.4	3	1		22.95	22.72	22.74
1.4	3	2		22.91	22.60	22.67
1.4	6	0		21.72	21.46	21.58
3	1	0	QPSK	23.51	23.65	23.82
3	1	7		23.54	23.53	23.82
3	1	14		23.49	23.45	23.71
3	8	0		22.65	22.45	22.60
3	8	4		22.66	22.43	22.64
3	8	7		22.52	22.51	22.63
3	15	0		22.54	22.46	22.71
3	1	0	16-QAM	23.58	22.97	23.40
3	1	7		23.62	22.90	23.43
3	1	14		23.28	22.94	23.35
3	8	0		21.56	21.54	21.36
3	8	4		21.52	21.58	21.45
3	8	7		21.87	21.56	21.44
3	15	0		21.63	21.44	21.41



LTE BAND 12

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.45	23.74	23.62
5	1	12		23.46	23.51	23.69
5	1	24		23.45	23.45	23.58
5	12	0		22.65	22.47	22.78
5	12	6		22.40	22.40	22.63
5	12	11		22.47	22.46	22.61
5	25	0		22.54	22.36	22.64
5	1	0	16-QAM	22.72	22.46	22.65
5	1	12		22.51	22.44	23.16
5	1	24		22.52	23.03	23.12
5	12	0		21.39	21.27	21.97
5	12	6		21.82	21.25	21.51
5	12	11		21.89	21.25	21.49
5	25	0		22.03	21.32	21.72
10	1	0	QPSK	23.47	23.51	23.92
10	1	24		23.50	23.63	23.61
10	1	49		23.59	23.77	23.77
10	25	0		22.50	22.42	22.53
10	25	12		22.48	22.48	22.92
10	25	24		22.53	23.06	22.76
10	50	0		22.62	22.46	22.96
10	1	0	16-QAM	23.60	22.42	22.30
10	1	24		23.45	22.41	22.83
10	1	49		23.38	22.74	22.64
10	25	0		21.94	21.53	21.49
10	25	12		21.43	21.38	22.00
10	25	24		21.46	22.05	21.62
10	50	0		21.55	21.35	21.94



LTE BAND 66

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.57	23.42	23.72
1.4	1	2		23.58	23.45	23.75
1.4	1	5		23.63	23.39	23.77
1.4	3	0		23.44	23.66	23.67
1.4	3	1		23.51	23.71	23.62
1.4	3	2		23.48	23.63	23.67
1.4	6	0		22.57	22.60	22.76
1.4	1	0	16-QAM	23.50	23.20	22.86
1.4	1	2		23.53	23.16	22.87
1.4	1	5		23.52	23.19	22.89
1.4	3	0		22.76	22.99	23.04
1.4	3	1		22.79	22.96	23.03
1.4	3	2		22.78	23.05	23.04
1.4	6	0		22.00	21.75	21.91
3	1	0	QPSK	23.37	23.41	23.71
3	1	7		23.44	23.43	23.77
3	1	14		23.41	23.42	23.84
3	8	0		22.56	22.63	22.62
3	8	4		22.41	22.66	22.63
3	8	7		22.46	22.59	22.70
3	15	0		22.37	22.63	22.73
3	1	0	16-QAM	23.63	23.19	22.89
3	1	7		23.58	23.15	22.91
3	1	14		23.59	23.19	22.81
3	8	0		21.74	22.12	21.77
3	8	4		21.67	22.06	21.77
3	8	7		21.49	22.07	21.75
3	15	0		21.95	21.97	21.83



LTE BAND 66

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.34	23.61	23.67
5	1	12		23.34	23.58	23.63
5	1	24		23.50	23.60	23.67
5	12	0		22.52	22.66	22.74
5	12	6		22.55	22.55	22.64
5	12	11		22.58	22.57	22.76
5	25	0		22.44	22.64	22.71
5	1	0	16-QAM	22.69	22.26	22.74
5	1	12		22.67	22.31	22.60
5	1	24		22.79	22.39	22.63
5	12	0		21.79	21.50	21.75
5	12	6		21.54	21.72	21.74
5	12	11		21.58	21.54	21.69
5	25	0		21.64	21.91	21.72
10	1	0	QPSK	23.44	23.58	23.70
10	1	24		23.53	23.59	23.78
10	1	49		23.56	23.67	23.76
10	25	0		22.50	22.60	22.67
10	25	12		22.63	22.58	22.59
10	25	24		22.52	22.65	22.65
10	50	0		22.71	22.62	22.76
10	1	0	16-QAM	23.66	22.60	22.64
10	1	24		23.72	22.64	22.60
10	1	49		23.76	22.69	22.70
10	25	0		21.50	21.73	21.71
10	25	12		21.55	21.87	21.76
10	25	24		21.63	21.69	21.74
10	50	0		21.66	21.94	21.80



LTE BAND 66

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.44	23.58	23.67
15	1	37		23.54	23.63	23.60
15	1	74		23.56	23.64	23.74
15	36	0		22.51	22.63	22.60
15	36	18		22.58	22.64	22.73
15	36	39		22.74	22.63	22.72
15	75	0		22.65	22.64	22.68
15	1	0	16-QAM	23.70	22.63	23.54
15	1	38		23.70	23.12	23.54
15	1	75		23.76	23.21	23.45
15	36	0		21.63	21.75	21.63
15	36	18		21.65	22.04	21.62
15	36	39		21.72	21.75	21.74
15	75	0		21.72	21.84	21.80
20	1	0	QPSK	23.50	23.66	23.83
20	1	49		23.56	23.72	23.85
20	1	99		23.62	23.79	23.88
20	50	0		22.48	22.60	22.63
20	50	24		22.61	22.66	22.63
20	50	49		22.64	22.77	22.67
20	100	0		22.50	22.57	22.59
20	1	0	16-QAM	22.20	22.86	22.60
20	1	49		22.25	22.90	22.57
20	1	99		22.36	23.05	22.62
20	50	0		21.70	21.63	21.70
20	50	24		21.79	21.92	21.68
20	50	49		21.78	21.61	21.67
20	100	0		21.71	21.84	21.72

11. EUT and Test Setup Photo

11.1 EUT Photo

Front side




Back side






Top side




Bottom side






Left side




Right side



11.2 Setup Photo

Body Back side(separation distance is 0mm)



Body Left side(separation distance is 0mm)



Body Right Side (separation distance is 0mm)



Body Top Side (separation distance is 0mm)






Body Bottom Side (separation distance is 0mm)



Liquid depth (15 cm)





12. SAR Result Summary

12.1 Body-worn and Hotspot SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas.No.
GSM850	GPRS Data-2 Slot	Back Side	824.2	0.69	1.57	31.50	31.27	0.728	1
		Left Side	824.2	0.022	-2.16	31.50	31.27	0.023	/
		Right Side	824.2	0.021	3.31	31.50	31.27	0.022	/
		Top Side	824.2	0.022	1.24	31.50	31.27	0.023	/
		Bottom Side	824.2	0.512	-1.75	31.50	31.27	0.540	/
GSM1900	GPRS Data-4 Slot	Back Side	1850.2	0.755	3.59	26.00	25.57	0.834	/
		Back Side	1880	0.688	1.67	26.00	24.29	1.020	/
		Back Side	1909.8	0.711	-1.43	26.00	24.04	1.117	/
		Bottom Side	1850.2	1.368	-1.69	26.00	25.57	1.510	2
		Bottom Side	1880	1.002	0.76	26.00	24.29	1.485	/
		Bottom Side	1909.8	0.859	-1.19	26.00	24.04	1.349	/
WCDMA Band II	RMC	Back Side	1852.4	1.102	-2.60	23.50	23.35	1.141	/
		Back Side	1880	1.022	1.98	23.50	23.16	1.105	/
		Back Side	1907.6	1.023	-3.84	23.50	23.09	1.124	/
		Bottom Side	1852.4	1.23	1.30	23.50	23.35	1.273	3
		Bottom Side	1880	1.115	1.35	23.50	23.16	1.206	/
		Bottom Side	1907.6	1.025	3.18	23.50	23.09	1.126	/
WCDMA Band V	RMC	Back Side	826.4	1.055	0.79	23.00	22.94	1.070	/
		Back Side	836.6	0.98	0.91	23.00	22.76	1.036	/
		Back Side	846.6	0.933	-3.38	23.00	22.89	0.957	/
		Bottom Side	826.4	1.178	-3.68	23.00	22.94	1.194	4
		Bottom Side	836.6	1.022	-0.58	23.00	22.76	1.080	/
		Bottom Side	846.6	1.036	-1.48	23.00	22.89	1.063	/
WCDMA Band IV	RMC	Back Side	1712.6	1.002	1.22	23.50	22.99	1.127	/
		Back Side	1740	0.958	1.84	23.50	23.03	1.067	/
		Back Side	1752.4	1.113	3.10	23.50	23.11	1.218	5
		Bottom Side	1712.6	0.995	-3.72	23.50	22.99	1.119	/
		Bottom Side	1740	0.963	2.27	23.50	23.03	1.073	/
		Bottom Side	1752.4	0.947	-1.38	23.50	23.11	1.036	/
2.4GHz WLAN	802.11b	Back Side	2462	0.285	1.99	10.50	10.15	0.309	6
		Top Side	2462	0.188	1.02	10.50	10.15	0.204	/
		Bottom Side	2462	0.023	-1.83	10.50	10.15	0.025	/



BLE	GFSK(2Mbps)	Back Side	2440	0.042	-1.96	6.60	6.57	0.042	7
		Top Side	2440	0.022	-3.48	6.60	6.57	0.022	/
		Bottom Side	2440	0.010	-3.86	6.60	6.57	0.010	/
5.2GHz WLAN	802.11ac- VHT20	Back Side	5180	0.403	-2.85	9.00	8.66	0.436	8
		Top Side	5180	0.305	-1.18	9.00	8.66	0.330	/
		Bottom Side	5180	0.025	1.63	9.00	8.66	0.027	/

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.588	2.89	24	23.87	0.606	/
			50	24	Back Side	1880	0.485	-0.19	23	22.77	0.511	/
			1	0	Bottom Side	1860	0.910	-3.24	24	23.87	0.938	9
			1	0	Bottom Side	1880	0.798	-0.79	24	23.7	0.855	/
			1	0	Bottom Side	1900	0.766	2.22	24	23.76	0.810	/
			50	24	Bottom Side	1860	0.696	2.85	23	22.77	0.734	/
LTE Band 4	20M	QPSK	1	0	Back Side	1745	0.395	0.31	24	23.81	0.413	/
			50	0	Back Side	1745	0.233	-0.33	23	22.76	0.246	/
			1	0	Bottom Side	1745	0.656	-0.56	24	23.81	0.685	10
			50	0	Bottom Side	1745	0.562	1.06	23	22.76	0.594	/
LTE Band 5	10M	QPSK	1	0	Back Side	829	0.958	1.93	23.5	23.17	1.034	11
			1	0	Back Side	836.5	0.855	-3.96	23.5	22.9	0.982	/
			1	0	Back Side	844	0.852	0.59	23.5	22.7	1.024	/
			25	0	Back Side	829	0.715	-0.05	22.5	22.14	0.777	/
			1	0	Bottom Side	829	0.376	-1.86	23.5	23.17	0.406	/
			25	0	Bottom Side	829	0.266	3.00	22.5	22.14	0.289	/
LTE Band 12	10M	QPSK	1	0	Back Side	704	0.952	-3.14	24	23.47	1.076	/
			1	0	Back Side	707.5	0.912	3.58	24	23.51	1.021	/
			1	0	Back Side	711	1.093	2.09	24	23.92	1.113	12
			25	24	Back Side	707.5	0.714	-1.61	23.5	23.06	0.790	/
			1	0	Bottom Side	704	0.885	-1.51	24	23.47	1.000	/
			1	0	Bottom Side	707.5	0.863	-2.97	24	23.51	0.966	/
			1	0	Bottom Side	711	1.007	-0.42	24	23.92	1.026	/
			25	24	Bottom Side	707.5	0.713	-3.58	23.5	23.06	0.789	/



LTE Band 66	20M	QPSK	1	0	Back Side	1770	0.642	2.11	24	23.88	0.660	/
			50	49	Back Side	1745	0.522	-2.03	23	22.77	0.550	/
			1	0	Bottom Side	1720	0.885	-0.26	24	23.62	0.966	/
			1	0	Bottom Side	1745	0.847	-3.51	24	23.79	0.889	/
			1	0	Bottom Side	1770	1.004	-1.00	24	23.88	1.032	13

Note:

1. The test separation of all above table is 0mm.
2. Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
3. Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was **0.133W/Kg** for Body)
4. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



Repeated SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn -up Power(d Bm)	Meas.Outp ut Power(dB m)	Scaled SAR(W/ Kg)	Meas. No.
GSM1900	GPRS Data-4 Slot	Back Side	1850.2	0.753	-2.35	26.00	25.57	0.831	-
		Back Side	1880	0.663	0.21	26.00	24.29	0.983	-
		Back Side	1909.8	0.685	-3.53	26.00	24.04	1.076	-
		Bottom Side	1850.2	1.337	1.79	26.00	25.57	1.476	-
		Bottom Side	1880	0.991	-2.24	26.00	24.29	1.469	-
		Bottom Side	1909.8	0.820	-0.43	26.00	24.04	1.288	-
WCDMA Band II	RMC	Back Side	1852.4	1.061	-1.35	23.50	23.35	1.098	-
		Back Side	1880	0.992	1.39	23.50	23.16	1.073	-
		Back Side	1907.6	1.021	2.61	23.50	23.09	1.122	-
		Bottom Side	1852.4	1.216	-2.56	23.50	23.35	1.259	-
		Bottom Side	1880	1.103	-0.24	23.50	23.16	1.193	-
		Bottom Side	1907.6	0.991	0.10	23.50	23.09	1.089	-
WCDMA Band V	RMC	Back Side	826.4	1.031	0.40	23.00	22.94	1.045	-
		Back Side	836.6	0.960	2.47	23.00	22.76	1.015	-
		Back Side	846.6	0.895	0.25	23.00	22.89	0.918	-
		Bottom Side	826.4	1.131	-1.16	23.00	22.94	1.147	-
		Bottom Side	836.6	1.002	1.44	23.00	22.76	1.059	-
		Bottom Side	846.6	1.024	-1.15	23.00	22.89	1.050	-
WCDMA Band IV	RMC	Back Side	1712.6	0.983	-3.51	23.50	22.99	1.105	-
		Back Side	1740	0.935	-1.45	23.50	23.03	1.042	-
		Back Side	1752.4	1.068	1.63	23.50	23.11	1.168	-
		Bottom Side	1712.6	0.990	-3.77	23.50	22.99	1.113	-
		Bottom Side	1740	0.933	-1.43	23.50	23.03	1.040	-
		Bottom Side	1752.4	0.944	-3.10	23.50	23.11	1.033	-



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR(W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Bottom Side	1860	0.893	-0.33	24	23.87	0.920	-
			1	0	Bottom Side	1880	0.788	0.83	24	23.7	0.844	-
			1	0	Bottom Side	1900	0.741	-3.10	24	23.76	0.783	-
LTE Band 5	10M	QPSK	1	0	Back Side	829	0.912	-0.41	23.5	23.17	0.984	-
			1	0	Back Side	836.5	0.822	-1.49	23.5	22.9	0.944	-
			1	0	Back Side	844	0.828	1.84	23.5	22.7	0.995	-
LTE Band 12	10M	QPSK	1	0	Back Side	704	0.934	-3.35	24	23.47	1.055	-
			1	0	Back Side	707.5	0.698	1.49	24	23.51	0.781	-
			1	0	Back Side	711	0.674	0.77	24	23.92	0.687	-
			1	0	Bottom Side	704	0.760	1.34	24	23.47	0.859	-
			1	0	Bottom Side	707.5	0.651	-2.84	24	23.51	0.729	-
			1	0	Bottom Side	711	0.622	-3.08	24	23.92	0.634	-
LTE Band 66	20M	QPSK	1	0	Bottom Side	1720	0.880	-3.79	24	23.62	0.960	-
			1	0	Bottom Side	1745	0.844	0.53	24	23.79	0.886	-
			1	0	Bottom Side	1770	0.967	-1.27	24	23.88	0.994	-

**Repeated SAR measurement**

Band	Mode	Test Position	Ch.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(W/kg)	2nd Repeated SAR 1g	Ratio
GSM1900	GPRS Data-4 Slot	Back Side	1850.2	0.755	0.753	1.003	-	-	-
		Back Side	1880	0.688	0.663	1.038	-	-	-
		Back Side	1909.8	0.711	0.685	1.038	-	-	-
		Bottom Side	1850.2	1.368	1.337	1.023	-	-	-
		Bottom Side	1880	1.002	0.991	1.011	-	-	-
		Bottom Side	1909.8	0.859	0.820	1.048	-	-	-
WCDMA Band II	RMC	Back Side	1852.4	1.102	1.061	1.039	-	-	-
		Back Side	1880	1.022	0.992	1.030	-	-	-
		Back Side	1907.6	1.023	1.021	1.002	-	-	-
		Bottom Side	1852.4	1.23	1.216	1.012	-	-	-
		Bottom Side	1880	1.115	1.103	1.011	-	-	-
		Bottom Side	1907.6	1.025	0.991	1.034	-	-	-
WCDMA Band V	RMC	Back Side	826.4	1.055	1.031	1.023	-	-	-
		Back Side	836.6	0.98	0.960	1.021	-	-	-
		Back Side	846.6	0.933	0.895	1.042	-	-	-
		Bottom Side	826.4	1.178	1.131	1.042	-	-	-
		Bottom Side	836.6	1.022	1.002	1.020	-	-	-
		Bottom Side	846.6	1.036	1.024	1.012	-	-	-
WCDMA Band IV	RMC	Back Side	1712.6	1.002	0.983	1.019	-	-	-
		Back Side	1740	0.958	0.935	1.025	-	-	-
		Back Side	1752.4	1.113	1.068	1.042	-	-	-
		Bottom Side	1712.6	0.995	0.990	1.005	-	-	-
		Bottom Side	1740	0.963	0.933	1.032	-	-	-
		Bottom Side	1752.4	0.947	0.944	1.003	-	-	-



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured	2nd Repeated SAR 1g	Ratio
LTE Band 2	20M	QPSK	1	0	Bottom Side	1860	0.910	0.893	1.019	-	-	-
			1	0	Bottom Side	1880	0.798	0.788	1.013	-	-	-
			1	0	Bottom Side	1900	0.766	0.741	1.034	-	-	-
LTE Band 5	10M	QPSK	1	0	Back Side	829	0.958	0.912	1.050	-	-	-
			1	0	Back Side	836.5	0.855	0.822	1.040	-	-	-
			1	0	Back Side	844	0.852	0.828	1.029	-	-	-
LTE Band 12	10M	QPSK	1	0	Back Side	704	0.952	0.934	1.019			
			1	0	Back Side	707.5	0.912	0.901	1.012	-	-	-
			1	0	Back Side	711	1.093	1.040	1.051	-	-	-
			1	0	Bottom Side	704	0.885	0.871	1.016	-	-	-
			1	0	Bottom Side	707.5	0.863	0.843	1.024	-	-	-
			1	0	Bottom Side	711	1.007	0.965	1.044	-	-	-
LTE Band 66	20M	QPSK	1	0	Bottom Side	1720	0.885	0.880	1.006	-	-	-
			1	0	Bottom Side	1745	0.847	0.844	1.004	-	-	-
			1	0	Bottom Side	1770	1.004	0.967	1.038	-	-	-

**Simultaneous Multi-band Transmission Evaluation:**

Application Simultaneous Transmission information:

Position	Simultaneous State
Body	1. GSM + 2.4GHz WLAN/5G WLAN
	2. GSM + Bluetooth
	3. WCDMA + 2.4GHz WLAN/5G WLAN
	4. WCDMA + Bluetooth
	5. LTE + 2.4GHz WLAN/5G WLAN
	6. LTE + Bluetooth

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. KDB 447498 Appendix E, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 $SAR_{est} = 1.6 \cdot P_{ant} / P_{th}$ [W/kg].
 P_{ant} is maximum time-averaged power or effective radiated power (ERP), whichever is greater, and P_{th} is defined in Formula KDB 447498 (B.2).




Simultaneous Mode	Position	Mode	Max. 1-g SAR	1-g Sum SAR
			(W/kg)	(W/kg)
GSM + 2.4G WLAN	Body Bottom Side	GSM	1.510	1.535
		2.4G WLAN	0.025	
	Body Back Side	GSM	1.117	1.425
		2.4G WLAN	0.309	
GSM + Bluetooth	Body Bottom Side	GSM	1.510	1.520
		Bluetooth	0.010	
	Body Back Side	GSM	1.117	1.159
		Bluetooth	0.042	
GSM + 5G WLAN	Body Bottom Side	GSM	1.510	1.537
		5G WLAN	0.027	
	Body Back Side	GSM	1.117	1.552
		5G WLAN	0.436	
WCDMA + 2.4G WLAN	Body Bottom Side	WCDMA	1.273	1.298
		2.4G WLAN	0.025	
	Body Back Side	WCDMA	1.141	1.450
		2.4G WLAN	0.309	
WCDMA + Bluetooth	Body Bottom Side	WCDMA	1.273	1.283
		Bluetooth	0.010	
	Body Back Side	WCDMA	1.141	1.183
		Bluetooth	0.042	
WCDMA + 5G WLAN	Body Bottom Side	WCDMA	1.273	1.300
		5G WLAN	0.027	
	Body Back Side	WCDMA	1.141	1.577
		5G WLAN	0.436	
LTE + 2.4G WLAN	Body Bottom Side	LTE	1.032	1.057
		2.4G WLAN	0.025	
	Body Back Side	LTE	1.113	1.422
		2.4G WLAN	0.309	



LTE + Bluetooth	Body Bottom Side	LTE	1.032	1.042
		Bluetooth	0.010	
	Body Back Side	LTE	1.113	1.156
		Bluetooth	0.042	
LTE + 5G WLAN	Body Bottom Side	LTE	1.032	1.059
		5G WLAN	0.027	
	Body Back Side	LTE	1.113	1.549
		5G WLAN	0.436	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.





13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	SID750	SN 30/14 DIP0G750-331	2020.07.14	2023.07.13
835MHz Dipole	MVG	SID835	SN 30/14 DIP0G835-332	2020.07.14	2023.07.13
1800MHz Dipole	MVG	SID1800	SN 30/14 DIP1G800-329	2020.07.14	2023.07.13
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2020.07.14	2023.07.13
2450MHzDipole	MVG	SID2450	SN 30/14 DIP2G450-335	2020.07.14	2023.07.13
Waveguide	MVG	SWG5500	SN 13/14 WGA32	2020.07.14	2023.07.13
E-Field Probe	MVG	SSE2	SN 07/21 EPOG352	2023.02.24	2024.02.23
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2022.11.15	2023.11.14
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom3	MVG	SAM	SN 21/21 ELLI48	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	99899	DC-18GHz	N/A	N/A
Directional coupler	Narda	4226-20	3305	N/A	N/A
Network Analyzer	Agilent	8753ES	US38432810	2022.09.28	2023.09.27
Multi Meter	Keithley	Multi Meter 2000	4050073	2022.09.29	2023.09.28
Signal Generator	Agilent	N5182A	MY50140530	2022.09.28	2023.09.27
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2022.09.28	2023.09.27
Wireless Communication Test Set	R&S	CMW500	156324	2022.09.29	2023.09.28
Power Amplifier	DESAY	ZHL-42W	9638	2022.10.08	2023.10.07
Power Meter	R&S	NRP	100510	2022.09.28	2023.09.27
Power Sensor	R&S	NRP-Z11	101919	2022.09.28	2023.09.27
Power Sensor	Keysight	U2021XA	MY56280002	2022.09.29	2023.09.28
Temperature hygrometer	SuWei	SW-108	N/A	2022.09.30	2023.09.29
Thermograph	Elitech	RC-4	S/N EF7176501537	2022.09.30	2023.09.29

Note:

Per KDB 865664 D01, Dipole SAR Validation Verification, STS LAB has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole
2. System validation with specific dipole is within 10% of calibrated value Return-loss in within 20% of calibrated measurement



Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2023-02-28

Experimental conditions




Phantom	Validation plane
Device Position	-
Band	750MHz
Channels	-
Signal	CW
Frequency (MHz)	750MHz
Relative permittivity	42.57
Conductivity (S/m)	0.86
Probe	SN 07/21 EPG0352
ConvF	1.58
Crest factor	1:1



Maximum location: X=2.00, Y=1.00

SAR 10g (W/Kg)	0.543713
SAR 1g (W/Kg)	0.887138

Z Axis Scan





System Performance Check Data (835MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2023-03-01

Experimental conditions




Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity	41.77
Conductivity (S/m)	0.86
Probe	SN 07/21 EPG0352
ConvF:	1.57
Crest factor:	1:1



Maximum location: X=-7.00, Y=-1.00

SAR 10g (W/Kg)	0.631845
SAR 1g (W/Kg)	0.976379

Z Axis Scan



**System Performance Check Data(1800MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2023-03-02




Experimental conditions.

Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity	40.20
Conductivity (S/m)	1.42
Probe	SN 07/21 EPGO352
ConvF	1.60
Crest factor:	1:1

**Maximum location: X=5.00, Y=1.00**

SAR 10g (W/Kg)	2.033864
SAR 1g (W/Kg)	3.958982

Z Axis Scan



**System Performance Check Data (1900MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2023-03-03




Experimental conditions.

Phantom	Validation plane
Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900MHz
Relative permittivity	40.49
Conductivity (S/m)	1.42
Probe	SN 07/21 EPGO352
ConvF:	1.78
Crest factor:	1:1

**Maximum location: X=3.00, Y=-2.00**

SAR 10g (W/Kg)	2.043795
SAR 1g (W/Kg)	3.911311

Z Axis Scan



**System Performance Check Data (2450MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2023-03-06




Experimental conditions.

Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	40.12
Conductivity (S/m)	1.78
Probe	SN 07/21 EPGO352
ConvF	1.75
Crest factor:	1:1

**Maximum location: X=1.00, Y=0.00**

SAR 10g (W/Kg)	2.429518
SAR 1g (W/Kg)	5.556391

Z Axis Scan





System Performance Check Data (5200MHz)

Type: Dipole measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2023-03-06

Experimental conditions.

Device Position	Validation plane
Band	5200 MHz
Channels	-
Signal	CW
Frequency (MHz)	5200
Relative permittivity	36.48
Conductivity (S/m)	4.63
Probe	SN 07/21 EPGO352
ConvF	1.47
Crest factor:	1:1




Maximum location: X=7.00, Y=2.00

SAR 10g (W/Kg)	5.509563
SAR 1g (W/Kg)	15.246924



Z Axis Scan





Appendix B. SAR Test Plots


Plot 1: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-01
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS 850
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	824.2
Relative permittivity (real part)	40.80
Conductivity (S/m)	0.89

Maximum location: X=1.00, Y=-33.00

SAR Peak: 1.20 W/kg

SAR 10g (W/Kg)	0.372286
SAR 1g (W/Kg)	0.688248






Plot 2: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-03
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Bottom Side
Band	GPRS 1900
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.92
Conductivity (S/m)	1.44

Maximum location: X=0.00, Y=-39.00

SAR Peak: 2.48 W/kg

SAR 10g (W/Kg)	0.610443
SAR 1g (W/Kg)	1.368241




**Plot 3: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10**

Test Date	2023-03-03
Probe	SN 07/21 EPG0352
ConvF	1.84
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Bottom Side
Band	WCDMA II
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1852.4
Relative permittivity (real part)	41.00
Conductivity (S/m)	1.35

Maximum location: X=8.00, Y=38.00

SAR Peak: 2.44 W/kg

SAR 10g (W/Kg)	0.505344
SAR 1g (W/Kg)	1.229567





Plot 4: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-01
Probe	SN 07/21 EPGO352
ConvF	1.60
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Bottom Side
Band	WCDMA V
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	826.4
Relative permittivity (real part)	41.38
Conductivity (S/m)	0.91

Maximum location: X=-21.00, Y=19.00

SAR Peak: 2.50 W/kg

SAR 10g (W/Kg)	0.769289
SAR 1g (W/Kg)	1.178126






Plot 5: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-02
Probe	SN 07/21 EPGO352
ConvF	1.60
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	WCDMA Band IV
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1752.4
Relative permittivity (real part)	40.95
Conductivity (S/m)	1.37

Maximum location: X=-8.00, Y=-27.00

SAR Peak: 1.90 W/kg

SAR 10g (W/Kg)	0.587352
SAR 1g (W/Kg)	1.113369





Plot 6: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-06
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11b ISM
Signal	IEEE802.b (Crest factor: 1.0)
Frequency (MHz)	2462
Relative permittivity (real part)	40.52
Conductivity (S/m)	1.88

Maximum location: X=-7.00, Y=25.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.126428
SAR 1g (W/Kg)	0.285308





Plot 7 : DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-06
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	BLE
Signal	GFSK (Crest factor: 1.0)
Frequency (MHz)	2440
Relative permittivity (real part)	40.50
Conductivity (S/m)	1.75

Maximum location: X=-16.00, Y=16.00

SAR Peak: 0.07 W/kg

SAR 10g (W/Kg)	0.024797
SAR 1g (W/Kg)	0.041729






Plot 8: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-06
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12, dx=4mm, dy=4mm, dz=2mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11a ISM
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5180
Relative permittivity (real part)	36.57
Conductivity (S/m)	4.61

Maximum location: X=-8.00, Y=23.00

SAR Peak: 1.29 W/kg

SAR 10g (W/Kg)	0.150377
SAR 1g (W/Kg)	0.403033







**Plot 9: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10**

Test Date	2023-03-03
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE Band 2(RB 1)
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1860
Relative permittivity (real part)	40.46
Conductivity (S/m)	1.38

Maximum location: X=15.00, Y=38.00

SAR Peak: 1.76 W/kg

SAR 10g (W/Kg)	0.385963
SAR 1g (W/Kg)	0.909628

SURFACE SAR**VOLUME SAR****3D screen shot****Z Axis Scan**




Plot 10: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-02
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE Band 4 (RB 1)
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	40.34
Conductivity (S/m)	1.39

Maximum location: X=-13.00, Y=-39.00

SAR Peak: 2.49 W/kg

SAR 10g (W/Kg)	0.656194
SAR 1g (W/Kg)	1.376027






Plot 11: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10

Test Date	2023-03-01
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 5 (RB 1)
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	829
Relative permittivity (real part)	41.57
Conductivity (S/m)	0.93

Maximum location: X=-1.00, Y=17.00

SAR Peak: 3.22 W/kg

SAR 10g (W/Kg)	0.958040
SAR 1g (W/Kg)	1.830424







**Plot 12: DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10**

Test Date	2023-02-28
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 12 (RB 1)
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	711
Relative permittivity (real part)	42.87
Conductivity (S/m)	0.92

Maximum location: X=-9.00, Y=-33.00

SAR Peak: 1.79 W/kg

SAR 10g (W/Kg)	0.606727
SAR 1g (W/Kg)	1.093007

SURFACE SAR**VOLUME SAR****3D screen shot****Z Axis Scan**


**Plot 13 : DUT: TABLET CON CHIP(4G); EUT Model: Astro Pad10**

Test Date	2023-03-02
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE Band 66 (RB 1)
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1770
Relative permittivity (real part)	40.33
Conductivity (S/m)	1.39

Maximum location: X=16.00, Y=40.00

SAR Peak: 1.88 W/kg

SAR 10g (W/Kg)	0.449699
SAR 1g (W/Kg)	1.003938





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※

