



Annex C Plots of System Performance Check

System Performance Check Data (835MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.07.06


Measurement duration: 13 minutes 37 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	835MHz
Channels	
Signal	CW

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.185285
Conductivity (S/m)	0.875717
Power drift (%)	1.010000
Ambient Temperature:	22.2°C
Liquid Temperature:	21.4°C
ConvF:	6.13
Crest factor:	1:1





Maximum location: X=7.00, Y=-1.00

SAR 10g (W/Kg)	0.625122
SAR 1g (W/Kg)	0.969154

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5209	1.6629	1.1437	0.8075	0.5889	0.4143



**System Performance Check Data (835MHz Body)**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.07.02


Measurement duration: 13 minutes 47 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	835MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	835.000000
Relative permittivity (real part)	55.3842702
Conductivity (S/m)	0.968174
Power drift (%)	0.970000
Ambient Temperature:	22.7°C
Liquid Temperature:	21.8°C
ConvF:	6.37
Crest factor:	1:1





Maximum location: X=7.00, Y=-1.00

SAR 10g (W/Kg)	0.629542
SAR 1g (W/Kg)	0.987475

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5209	1.6629	1.1437	0.8075	0.5889	0.4143



**System Performance Check Data(1800MHz Head)**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.06.30


Measurement duration: 13 minutes 27 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	1800MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	1800.000000
Relative permittivity (real part)	40.095167
Conductivity (S/m)	1.365073
Power drift (%)	0.310000
Ambient Temperature:	22.3°C
Liquid Temperature:	21.5°C
ConvF:	5.21
Crest factor:	1:1





Maximum location: X=3.00, Y=1.00

SAR 10g (W/Kg)	2.048472
SAR 1g (W/Kg)	3.695054

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.0621	5.6445	3.6226	2.1642	1.4521	0.9078



**System Performance Check Data(1800MHz Body)**

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.07.05


Measurement duration: 13 minutes 27 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	1800MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.294148
Conductivity (S/m)	1.517075
Power drift (%)	0.520000
Ambient Temperature:	22.6°C
Liquid Temperature:	21.4°C
ConvF:	5.38
Crest factor:	1:1





Maximum location: X=3.00, Y=1.00

SAR 10g (W/Kg)	2.039173
SAR 1g (W/Kg)	3.760455

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.0621	5.6445	3.6226	2.1642	1.4521	0.9078





System Performance Check Data(2000MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.06.30

Measurement duration: 13 minutes 27 seconds


A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	2000MHz
Channels	
Signal	CW

B. SAR Measurement Results

Band SAR



Frequency (MHz)	2000.000000
Relative permittivity (real part)	39.984477
Conductivity (S/m)	1.414283
Power drift (%)	-0.830000
Ambient Temperature:	22.1°C
Liquid Temperature:	21.5°C
ConvF:	5.61
Crest factor:	1:1



SAR 10g (W/Kg)	1.992518
SAR 1g (W/Kg)	4.255954

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2075	7.3996	5.4654	4.1101	3.1286	2.4128





System Performance Check Data(2000MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.07.05

Measurement duration: 13 minutes 27 seconds


A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	2000MHz
Channels	
Signal	CW

B. SAR Measurement Results

Band SAR

Frequency (MHz)	2000.000000
Relative permittivity (real part)	53.285167
Conductivity (S/m)	1.514073
Power drift (%)	-1.860000
Ambient Temperature:	22.1°C
Liquid Temperature:	21.4°C
ConvF:	5.71
Crest factor:	1:1





Maximum location: X=7.00, Y=1.00

SAR 10g (W/Kg)	2.092518
SAR 1g (W/Kg)	4.119540

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2075	7.3996	5.4654	4.1101	3.1286	2.4128



**System Performance Check Data(2450MHz Head)**

Type: Phone measurement (Complete)

Area scan resolution: dx=12mm,dy=12mm

Zoom scan resolution: dx=5mm, dy=5mm, dz=4mm

Date of measurement: 2018.07.10

Measurement duration: 13 minutes 26 seconds


A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	2450MHz
Channels	
Signal	CW

B. SAR Measurement Results**Band SAR**

Frequency (MHz)	2450.000000
Relative permittivity (real part)	39.291348
Conductivity (S/m)	1.840166
Power Drift (%)	0.980000
Ambient Temperature:	22.2°C
Liquid Temperature:	21.3°C
ConvF:	4.82
Crest factor:	1:1

SURFACE SAR	VOLUME SAR
--------------------	-------------------




Maximum location: X=6.00, Y=1.00


SAR 10g (W/Kg)	2.381254
SAR 1g (W/Kg)	5.326168

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	12.9615	6.2096	3.8187	2.4504	1.5036	1.0219



3D scene shot	Hot spot position
---------------	-------------------



System Performance Check Data(2450MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=12mm,dy=12mm

Zoom scan resolution: dx=5mm, dy=5mm, dz=4mm

Date of measurement: 2018.07.11

Measurement duration: 13 minutes 26 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	2450MHz
Channels	
Signal	CW

B. SAR Measurement Results


Band SAR

Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.887643
Conductivity (S/m)	1.965147
Power Drift (%)	1.080000
Ambient Temperature:	22.4°C
Liquid Temperature:	21.5°C



REPORT No. : SZ18060085S01

ConvF:	4.93
Crest factor:	1:1




Maximum location: X=6.00, Y=1.00


SAR 10g (W/Kg)	2.378054
SAR 1g (W/Kg)	5.090178

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	12.9615	6.2096	3.8187	2.4504	1.5036	1.0219



3D scene shot	Hot spot position
---------------	-------------------



System Performance Check Data(2600MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=12mm,dy=12mm

Zoom scan resolution: dx=5mm, dy=5mm, dz=5mm

Date of measurement: 2018.06.30

Measurement duration: 13 minutes 27 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	2600MHz
Channels	
Signal	CW

B. SAR Measurement Results


Band SAR

Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.025532
Conductivity (S/m)	1.969234
Power Drift (%)	0.920000
Ambient Temperature:	22.3°C
Liquid Temperature:	21.5°C



REPORT No. : SZ18060085S01

ConvF:	4.74
Crest factor:	1:1




Maximum location: X=6.00, Y=1.00


SAR 10g (W/Kg)	2.501150
SAR 1g (W/Kg)	5.682471

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	12.9745	6.2193	3.8245	2.4624	1.5033	1.0220



3D scene shot	Hot spot position
---------------	-------------------



System Performance Check Data(2600MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2018.07.05

Measurement duration: 13 minutes 31 seconds

A. Experimental conditions.

Phantom File	surf_sam_plan.txt
Phantom	Flat
Device Position	
Band	2600MHz
Channels	
Signal	CW

B. SAR Measurement Results


Band SAR

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.370564
Conductivity (S/m)	2.110258
Power Drift (%)	1.380000
Ambient Temperature:	22.6°C
Liquid Temperature:	21.4°C



REPORT No. : SZ18060085S01

ConvF:	4.93
Crest factor:	1:1




Maximum location: X=6.00, Y=1.00

SAR 10g (W/Kg)	2.370851
SAR 1g (W/Kg)	5.385472

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	12.9745	6.2193	3.8245	2.4624	1.5033	1.0220



3D scene shot	Hot spot position
---------------	-------------------

