TEST REPORT
FCC Part 15C

Equipment under test Wireless Charger

Model name NAW-001

FCC ID 2APEP-NAW-001

Applicant Newscon Corporation

Manufacturer Newscon Corporation

Date of test(s) 2018.04.23 ~ 2018.05.12

Date of issue 2018.05.14

Issued to

Newscon Corporation
#922 9F Yaekyung Bldg., Olympic-ro 651,
Gangdong-gu, Seoul, Republic of Korea
Tel: +82-2-6953-1552

Issued by

KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	**Report approval by :**
Young-Jin Lee Test engineer	Hyeon-Su Jang Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Revision history

Revision	Date of issue	Test report No.	Description
-	2018.05.03	KES-RF-18T0054	Initial
R1	2018.05.14	KES-RF-18T0054-R1	Retest 20dB Bandwidth

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 4
1.3. Test frequency 4
1.4. Test mode 4
1.5. Information about derivative model 5
1.6. Device modifications 5
1.7. Accessory information 5
1.8. Measurement Uncertainty 5
2. Summary of tests 6
3. Test results 7
3.1. Radiated spurious emission 7
3.2. 20dB Bandwidth 15
3.3. AC conducted emissions 16
Appendix A. Measurement equipment 18
Appendix B. Test setup photo 19

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1. General information

Applicant	Newscon Corporation
Applicant address	#922 9F Yaekyung Bldg., Olympic-ro 651, Gangdong-gu, Seoul, Republic of Korea
Test site	KES Co., Ltd.
Test site address	3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s):	Part 15C
FCC ID:	2APEP-NAW-001
Test device serial No.	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Wireless Charger
Frequency	0.112 ㎒ ~ 0.181 ㎒
Modulation type	ASK
Model:	NAW-001
Antenna specification	Internal type(Coil antenna)
Power source	DC 9.0V

1.2. Test configuration

The **Newscon Corporation Wireless Charger FCC ID: 2APEP-NAW-001** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15C
ANSI C63.10-2013

1.3. Test frequency

		Frequency Range
Power source	DC 9.0 V	0.112 ㎒ ~ 0.181 ㎒

1.4. Test mode

Mode	Charging current	Description
Charging mode With load	90%	Using Max load
	50%	Using Mid load
	10%	Using Min load

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.5. Information about derivative model

N/A

1.6. Device modifications

N/A

1.7. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

1.8. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.62 dB
Uncertainty for Radiation emission test (include Fundamental emission)	9㎑ - 30㎒	4.54 dB
	30㎒ - 1㎓	4.36 dB
	Above 1㎓	5.00 dB
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2. Summary of tests

FCC Part Sections	Parameter	Test results
15.209	Radiated spurious emission	Pass
-	20dB bandwidth	Pass
15.207	AC conducted emissions	Pass

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3. Test results

3.1. Radiated spurious emission

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test procedure

[9 ㎑ to 30 ㎒]

The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Quasi-peak function and specified bandwidth with maximum hold mode.

The spectrum analyzer is set to:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer 200 ㎐ / 300 ㎐ for peak detection (PK) at frequency below 9 ㎑~ 150 ㎑.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer 9 ㎑ / 10 ㎑ for peak detection (PK) at frequency below 150 ㎑~ 30 ㎒.
3. For the frequency bands 9~ 90 ㎑, 110~490 ㎑ the radiated emission limits are based on measurements employing an average detector.

[30 ㎒ to 1 ㎓]

The height of the measuring antenna was varied between 1 to 4 m and the table was rotated a full revolution in order to obtain maximum values of the electric field intensity.
The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

The spectrum analyzer is set to:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer 120 ㎑ for Peak detection (PK) or Quasi-peak detection (QP) at frequency below 1 ㎓.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Note:

1. According to exploratory test no any obvious emission were detected from 9 ㎑ to 30 ㎒. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
2. Measurement distance : 3 m.
3. Field strength = Level + Correction factor + F_d
4. $F_d = 40\log(D_m / D_s)$
   Where:
   F_d = Distance factor in dB
   D_m = Measurement distance in meters
   D_s = Specification distance in meters
   For 300m: 40log(300/3) = 80 dB for frequency band 0.009 ㎒ to 0.490 ㎒
   For 30m: 40log(30/3) = 40 dB for frequency band 0.490 ㎒ to 30 ㎒
5. No significant emissions were found in the 90 - 110㎑ restricted band.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2400 / F(㎑)
0.490 ~ 1.705	30	24000 / F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test results (Below 30 ㎒)

Mode: 9W // 10 % charger

Distance of measurement: 3 meter

Horizontal



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	o.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	0.125	H	67.0	19.8	86.8	105.6	18.8	
2	0.384	H	44.0	20.3	64.3	95.9	31.6	
3	0.643	H	35.7	20.8	56.5	71.5	15.0	
4	0.897	H	30.3	21.0	51.3	68.6	17.3	

Vertical



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	o.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	0.125	V	61.3	19.8	81.1	105.6	24.5	
2	0.384	V	38.5	20.3	58.8	95.9	37.1	
3	0.643	V	32.3	20.8	53.1	71.5	18.4	
4	0.897	V	26.5	21.0	47.5	68.6	21.1	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Mode: 9W // 50 % charge

Distance of measurement: 3 meter

Horizontal



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	o.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	0.125	H	65.7	19.8	85.5	105.7	20.2	
2	0.384	H	44.6	20.3	64.9	95.9	31.0	
3	0.643	H	35.7	20.8	56.5	71.5	15.0	
4	0.901	H	31.1	21.0	52.1	68.5	16.4	

Vertical



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	o.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	0.125	V	61.7	19.8	81.5	105.6	24.1	
2	0.384	V	40.9	20.3	61.2	95.9	34.7	
3	0.643	V	33.1	20.8	53.9	71.5	17.6	
4	0.901	V	28.6	21.0	49.6	68.5	18.9	
5	1.156	V	26.1	20.9	47.0	66.4	19.4	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Mode: 9W // 90 % charge

Distance of measurement: 3 meter

Horizontal



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	o.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	0.125	H	59.6	19.8	79.4	105.7	26.3	
2	0.388	H	40.5	20.3	60.8	95.8	35.0	
3	0.650	H	32.3	20.8	53.1	71.4	18.3	
4	0.912	H	28.2	21.0	49.2	68.4	19.2	

Vertical



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	o.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	0.125	V	65.1	19.8	84.9	105.6	20.7	
2	0.376	V	43.2	20.3	63.5	96.1	32.6	
3	0.628	V	35.5	20.8	56.3	71.7	15.4	
4	0.882	V	29.3	21.0	50.3	68.7	18.4	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test results (Below 1 000 ㎒)

Mode: 9W // 10 % charge (Worst case)

Distance of measurement: 3 meter

Horizontal // Vertical



Spectrum Selection

No.	Frequency [MHz]	(P)	Reading [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Remark
1	36.548	H	51.3	-31.7	19.6	40.0	20.4	
2	93.050	H	55.9	-30.9	25.0	43.5	18.5	
3	213.815	H	57.7	-28.4	29.3	43.5	14.2	
4	360.285	H	50.4	-23.6	26.8	46.0	19.2	
5	750.104	H	40.2	-15.0	25.2	46.0	20.8	
6	220.363	H	56.3	-28.2	28.1	46.0	17.9	
7	36.548	V	60.2	-31.7	28.5	40.0	11.5	
8	65.284	V	62.0	-31.1	30.9	40.0	9.1	
9	156.828	V	60.3	-32.4	27.9	43.5	15.6	
10	226.061	V	54.1	-28.0	26.1	46.0	19.9	
11	371.440	V	50.8	-23.2	27.6	46.0	18.4	
12	268.014	V	53.0	-26.5	26.5	46.0	19.5	
13	837.525	V	49.9	-13.9	36.0	46.0	10.0	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3.2. 20dB Bandwidth

Test setup



Test procedures

The transmitter output is connected to a spectrum analyzer. The RBW is set to ≥ 1% of the emission bandwidth. The VBW is set to ≥RBW. The sweep time is coupled.

Limit

None; for reporting purposes only.

Test results

Power source(W)	Frequency(㎒)	Measured bandwidth(㎑)
9.0	0.125	0.420

9W // Middle channel



Note.

Because the measured signal is CW/CW-like, adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

3.3. AC conducted emissions

Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (㎒)	Conducted limit (dB㎶/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test results

Mode: 9W // 10 % charge (Worst case)

Hot Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.515000	---	32.94	46.00	13.06	1000.0	9.000	L1	9.8
0.515000	39.90	---	56.00	16.10	1000.0	9.000	L1	9.8
0.650000	---	30.83	46.00	15.17	1000.0	9.000	L1	9.8
0.650000	35.22	---	56.00	20.78	1000.0	9.000	L1	9.8
2.210000	---	31.84	46.00	14.16	1000.0	9.000	L1	10.1
2.210000	38.80	---	56.00	17.20	1000.0	9.000	L1	10.1
3.250000	---	30.50	46.00	15.50	1000.0	9.000	L1	10.1
3.250000	35.65	---	56.00	20.35	1000.0	9.000	L1	10.1
8.060000	---	28.34	50.00	21.66	1000.0	9.000	L1	9.8
8.060000	34.70	---	60.00	25.30	1000.0	9.000	L1	9.8
11.960000	---	27.38	50.00	22.62	1000.0	9.000	L1	9.8
11.960000	33.87	---	60.00	26.13	1000.0	9.000	L1	9.8

Neutral Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.515000	---	31.82	46.00	14.18	1000.0	9.000	N	9.8
0.515000	37.95	---	56.00	18.05	1000.0	9.000	N	9.8
0.520000	---	27.49	46.00	18.51	1000.0	9.000	N	9.8
0.520000	35.53	---	56.00	20.47	1000.0	9.000	N	9.8
1.950000	---	30.09	46.00	15.91	1000.0	9.000	N	10.2
1.950000	35.09	---	56.00	20.91	1000.0	9.000	N	10.2
2.210000	---	30.75	46.00	15.25	1000.0	9.000	N	10.2
2.210000	37.25	---	56.00	18.75	1000.0	9.000	N	10.2
11.705000	---	28.44	50.00	21.56	1000.0	9.000	N	9.8
11.705000	35.49	---	60.00	24.51	1000.0	9.000	N	9.8
29.930000	---	24.22	50.00	25.78	1000.0	9.000	N	10.3
29.930000	36.35	---	60.00	23.65	1000.0	9.000	N	10.3

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV40	101002	1 year	2018.07.04
Loop Antenna	Schwarzbeck	FMZB1513	225	2 years	2019.05.10
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	9168-714	2 years	2018.11.28
Preamplifier	AGILENT	8449B	3008A01729	1 year	2018.05.31
EMI Test Receiver	R&S	ESU26	100551	1 year	2019.04.11
Pulse Limiter	R&S	ESH3-Z2	101915	1 year	2018.11.27
LISN	R&S	ENV216	101787	1 year	2019.01.31

Peripheral device

Device	Manufacturer	Model No.	S/N	Note
AC/DC Adapter	WEIHAI PNTELECOM	MCS-H06KP	PB7Y0000322	Output Power : 9.0V / 5.0 V
10/50/90% Load	PNTELECOM CO.,LTD	N/A	N/A	N/A
Load	Newscon Corporation	N/A	N/A	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.