



Test Report

Report No. : MTi250612003-0102E1
Date of issue : 2025-07-22
Applicant : Electronic Silk Road (Shenzhen) Tech Co., Ltd
Product : ESR Magnetic Car Charger
Model(s) : 2B528, 2B529, 2B528-01
FCC ID : 2APEW-2B528

Shenzhen Microtest Co., Ltd.

TEST REPORT

Report No.: MTi250612003-0102E1

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	5
1.3	Environmental Conditions	6
1.4	Description of support units	6
1.5	Measurement uncertainty	6
2	Summary of Test Result	7
3	Test Facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Evaluation Results (Evaluation)	10
5.1	Antenna requirement	10
6	Radio Spectrum Matter Test Results (RF)	11
6.1	20dB Occupied Bandwidth	11
6.2	Emissions in frequency bands (below 30MHz)	15
6.3	Emissions in frequency bands (30MHz - 1GHz)	20
	Photographs of the test setup	24
	Photographs of the EUT	25

TEST REPORT

Report No.: MTi250612003-0102E1


Test Result Certification

Applicant	Electronic Silk Road (Shenzhen) Tech Co., Ltd
Applicant Address	Room 1601, Building 1D, Creative City, Liu Xian Avenue, Nan Shan District, Shenzhen, Guangdong, China
Manufacturer	Electronic Silk Road (Shenzhen) Tech Co., Ltd
Manufacturer Address	Room 1601, Building 1D, Creative City, Liu Xian Avenue, Nan Shan District, Shenzhen, Guangdong, China

Product description

Product name	ESR Magnetic Car Charger
Trademark	ESR
Model name	2B528
Series Model(s)	2B529, 2B528-01
Standards	47 CFR Part 15C
Test Method	ANSI C63.10-2013

Testing Information

Date of test	2025-07-09 to 2025-07-11	
Test result	Pass	
Prepared by:	Maleah Deng	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

TEST REPORT

Report No.: MTi250612003-0102E1

1 General Description

1.1 Description of the EUT

Product name:	ESR Magnetic Car Charger
Model name:	2B528
Series Model(s):	2B529, 2B528-01
Model difference:	All the models are the same circuit and module, except the model name and bracket.
Electrical rating:	Input: DC 12V/2.75A, DC 15V/2.2A Wireless Output: 5W/7.5W/10W/15W/25W
Accessories:	Cable: USB-C to USB-C cable 100cm*1 ESR 58W Car charger Model: M9C0903 Input: DC 12V-24V, 7A Output: USB-A: DC 5V/3A, DC 9V/2A, DC 12V/1.5A; USB-C: DC 5V/3A, DC 9V/3A, DC 12V/3A, DC 15V/2.66A, DC 20/2A, PSS: DC 5-16V/2.5A Total Output: 58W
Hardware version:	V1.0
Software version:	V1.0
Test sample(s) number:	MTi250612003-02-R001

RF specification

Operating frequency range:	115-205kHz(5W, 7.5W, 10W, 15W(EPP)); 360kHz(15W(MPP), 25W)
Modulation type:	ASK
Antenna(s) type:	Coil Antenna

TEST REPORT

Report No.: MTi250612003-0102E1

1.2 Description of test modes

No.	Emission test modes
Mode1	Powered by Accumulator(12V)+Wireless Output(5W)
Mode2	Powered by Accumulator(12V)+Wireless Output(7.5W)
Mode3	Powered by Accumulator(12V)+Wireless Output(10W)
Mode4	Powered by Accumulator(12V)+Wireless Output(15W EPP)
Mode5	Powered by Accumulator(12V)+Wireless Output(15W MPP)
Mode6	Powered by Accumulator(12V)+Wireless Output(25W)
Mode7	Powered by Accumulator(24V)+Wireless Output(5W)
Mode8	Powered by Accumulator(24V)+Wireless Output(7.5W)
Mode9	Powered by Accumulator(24V)+Wireless Output(10W)
Mode10	Powered by Accumulator(24V)+Wireless Output(15W EPP)
Mode11	Powered by Accumulator(24V)+Wireless Output(15W MPP)
Mode12	Powered by Accumulator(24V)+Wireless Output(25W)
Mode13	Powered by Accumulator(12V)+Standby
Mode14	Powered by Accumulator(24V)+Standby

TEST REPORT

Report No.: MTi250612003-0102E1

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
wireless charging load	YBZ1.1	/	YBZ
Accumulator	6-QW-45(370)-L	/	Camel Group Co., Ltd.
wireless charging load	YBZ3.0(MPP15W&25W)	/	YBZ

Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Occupied channel bandwidth	±3 %
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



TEST REPORT

Report No.: MTi250612003-0102E1

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15C	47 CFR Part 15.203	Pass
2	20dB Occupied Bandwidth	47 CFR Part 15C	47 CFR Part 15.215(c)	Pass
3	Emissions in frequency bands (below 30MHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass
4	Emissions in frequency bands (30MHz - 1GHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass

TEST REPORT

Report No.: MTi250612003-0102E1

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

TEST REPORT

Report No.: MTi250612003-0102E1

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
20dB Occupied Bandwidth						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2025-03-18	2026-03-17
2	ESG Series Analog Signal Generator	Agilent	E4421B	GB400512 40	2025-03-14	2026-03-13
3	PXA Signal Analyzer	Agilent	N9030A	MY513502 96	2025-03-14	2026-03-13
4	Synthesized Sweeper	Agilent	83752A	3610A019 57	2025-03-14	2026-03-13
5	MXA Signal Analyzer	Agilent	N9020A	MY501434 83	2025-03-14	2026-03-13
6	RF Control Unit	Tonscend	JS0806-1	19D80601 52	2025-03-18	2026-03-17
7	Band Reject Filter Group	Tonscend	JS0806-F	19D80601 60	2025-03-14	2026-03-13
8	ESG Vector Signal Generator	Agilent	N5182A	MY501437 62	2025-03-14	2026-03-13
9	DC Power Supply	Agilent	E3632A	MY400276 95	2025-03-18	2026-03-17
Emissions in frequency bands (below 30MHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2025-03-14	2026-03-13
2	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2026-03-22
3	Amplifier	Hewlett-Packard	8447F	3113A0618 4	2025-03-18	2026-03-17
Emissions in frequency bands (30MHz - 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2025-03-14	2026-03-13
2	TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1338	2025-05-23	2027-05-22
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2026-03-22
4	Amplifier	Hewlett-Packard	8447F	3113A0618 4	2025-03-18	2026-03-17

TEST REPORT

Report No.: MTi250612003-0102E1

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached.
The EUT complies with the requirement of FCC PART 15.203.

TEST REPORT

Report No.: MTi250612003-0102E1

6 Radio Spectrum Matter Test Results (RF)

6.1 20dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15.215(c)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2013, section 6.9.2
Procedure:	<p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.</p> <p>i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).</p> <p>j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-</p>

TEST REPORT

Report No.: MTi250612003-0102E1


	delta frequency reading at this point is the specified emission bandwidth. k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
--	---

6.1.1 E.U.T. Operation:

Operating Environment:

Temperature:	24.5 °C	Humidity:	56 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode10, Mode12) is recorded in the report				

6.1.2 Test Setup Diagram:



TEST REPORT


Report No.: MTi250612003-0102E1

6.1.3 Test Data:

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

15W(EPP)

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
128.005	810	689




TEST REPORT

Report No.: MTi250612003-0102E1

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

25W



TEST REPORT

Report No.: MTi250612003-0102E1

6.2 Emissions in frequency bands (below 30MHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.


In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

| Test Method: | ANSI C63.10-2013 section 6.4 | | |
| Procedure: | ANSI C63.10-2013 section 6.4 | | |

6.2.1 E.U.T. Operation:

Operating Environment:				
Temperature:	21.1 °C	Humidity:	52 %	Atmospheric Pressure:
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14			
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode4, Mode6) is recorded in the report			

6.2.2 Test Setup Diagram:




TEST REPORT

Report No.: MTi250612003-0102E1

6.2.3 Test Data:

Mode4 / EUT direction: X-axis




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1		0.1281	22.64	20.47	43.11	125.47	-82.36	peak
2	*	0.1281	20.83	20.47	41.30	105.47	-64.17	AVG

TEST REPORT


Report No.: MTi250612003-0102E1

Mode4 / EUT direction: X-axis



TEST REPORT

Report No.: MTi250612003-0102E1


Mode4 / EUT direction: X-axis


No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	0.1281	5.89	20.47	26.36	125.47	-99.11	peak	
2 *	0.1281	2.67	20.47	23.14	105.47	-82.33	AVG	

TEST REPORT

Report No.: MTi250612003-0102E1

Mode6 / EUT direction: X-axis



No.	Mk.	Freq.	Reading	Correct	Measure-		Limit	Over	Comment
			Level	Factor	ment	dBuV/m			
MHz			dBuV	dB	dBuV/m	dB	Detector		
1	0.3598	37.94	21.08	59.02	116.49	-57.47	peak		
2	0.3598	37.94	21.08	59.02	96.49	-37.47	AVG		
3	0.7752	17.53	22.07	39.60	69.83	-30.23	QP		
4 *	1.0824	18.28	22.76	41.04	66.94	-25.90	QP		
5	1.3958	7.81	23.42	31.23	64.73	-33.50	QP		
6	2.0441	6.66	24.74	31.40	69.50	-38.10	QP		
7	2.5266	7.19	25.75	32.94	69.50	-36.56	QP		

TEST REPORT

Report No.: MTi250612003-0102E1

6.3 Emissions in frequency bands (30MHz - 1GHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

| Test Method: | ANSI C63.10-2013 section 6.5 | | |
| Procedure: | ANSI C63.10-2013 section 6.5 | | |

6.3.1 E.U.T. Operation:


Operating Environment:				
Temperature:	25.6 °C	Humidity:	58 %	Atmospheric Pressure:
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5, Mode6, Mode7, Mode8, Mode9, Mode10, Mode11, Mode12, Mode13, Mode14			
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode4) is recorded in the report			

6.3.2 Test Setup Diagram:



TEST REPORT


Report No.: MTi250612003-0102E1



TEST REPORT


Report No.: MTi250612003-0102E1

6.3.3 Test Data:

Mode4 / Polarization: Horizontal


TEST REPORT

Report No.: MTi250612003-0102E1

Mode4 / Polarization: Vertical


TEST REPORT

Report No.: MTi250612003-0102E1

Photographs of the test setup

Refer to Appendix - Test Setup Photos





TEST REPORT

Report No.: MTi250612003-0102E1

Photographs of the EUT

Refer to Appendix - EUT Photos



TEST REPORT

Report No.: MTi250612003-0102E1

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****