

COMPLIANCE WORLDWIDE INC. TEST REPORT 197-24

In Accordance with the Requirements of
Federal Communications Commission CFR Title 47 Part 15.225, Subpart C
Innovation, Science and Economic Development Canada
RSS 210, Issue 11

Low Power License-Exempt Radio Communication Devices
Intentional Radiators


Issued to
STATSports Group Ltd
Drumalane Mill, The Quays
Newry, Co Down BT35 8QS, United Kingdom

for the
Apex Next Dock Basic
Model: V4 X

FCC ID: 2APHS-APD200
IC: 25854-APD200

Report Issued on January 16, 2025

Tested by



Sean P. Defelice

Sean P. Defelice

Reviewed by



Larry K. Stillings

This test report shall not be reproduced, except in full, without written permission from Compliance Worldwide, Inc.

Table of Contents

1 Scope.....	3
2 Product Details	3
2.1. Manufacturer	3
2.2. Model Number.....	3
2.3. Serial Number	3
2.4. Description	3
2.5. Power Source.....	3
2.6. Hardware Revision.....	3
2.7. Software Revision	3
2.8. Modulation Type.....	3
2.9. Operating Frequencies	3
2.10. EMC Modifications	3
3. Product Configuration.....	3
3.1. Operational Characteristics & Software	3
3.2. EUT Hardware	3
3.3. EUT Cables/Transducers.....	3
3.4. Support Equipment	4
3.5. Block Diagram.....	4
4. Measurements Parameters	5
4.1. Measurement Equipment Used to Perform Test	5
4.2. Measurement & Equipment Setup	6
4.3. Measurement Procedure	6
5. Choice of Equipment for Test Suits	7
5.1. Choice of Model	7
5.2. Presentation	7
5.3. Choice of Operating Frequencies	7
6. Measurement Summary	7
7. Measurement Data	8
7.1. Antenna Requirement	8
7.2. Operation within the Band 13.110 MHz – 14.010 MHz.....	9
7.3. Transmitter Spurious Radiated Emissions.....	12
7.4. Frequency Stability.....	17
7.5. Occupied Bandwidth	18
7.6. 99% Power Bandwidth	19
7.7. Power Line Conducted Emissions	20
8. Test Site Description	23
9. Test Setup Photographs.....	24

1. Scope

This test report certifies that the STASTSports Group Ltd Apex Next Dock V4 X Basic, as tested, meets the FCC Part 15.225 Subpart C, and ISED Canada RSS 210 requirements. The scope of this test report is limited to the test samples provided by the client, only in as much as those samples represent other production units. If any significant changes are made to the units, the changes shall be evaluated, and a retest may be required. Measurement Uncertainty will not be applied to any of the measurement / testing results in this test report to determine pass/fail criteria per the Decision Rule as defined in ISO/IEC Guide 17025-2017 Clause 3.7.

2. Product Details

2.1. Manufacturer:	STASTSports Group Ltd.
2.2. Model Number:	V4 X
2.3. Serial Number:	BDL0130
2.4. Description:	Docking and Charging Station.
2.5. Power Source:	120 VAC, 60 Hz
2.6. Hardware Revision:	v4.41
2.7. Software Revision:	N/A
2.8. Modulation Type:	ASK
2.9. Operating Frequency:	13.56 MHz
2.10. EMC Modifications:	None

3. Product Configuration

3.1. Operational Characteristics & Software

The device under test is powered up normally. Initial tests across USB to ensure data can be transferred successfully, checksums verified.

Further tests reading NFC Tag

3.2. EUT Hardware

Device	Manufacturer	Model	Serial No.
Apex Next Dock	Statsports	V4 X	BDL0130
Power Supply	Fidus Power	ATS090A1-P120	None

3.3. EUT Cables/Transducers


Cable Type	Shield	Length	From	To
USB Type A – USB-C	Yes	1.5M	Laptop	Dock (UUT)
Power cable	No	2M + 2M	Dock (UUT)	AC Mains

3. Product Configuration (continued)

3.4. Support Equipment

Device	Manufacturer	Model	Serial No.
Laptop	Lenovo	ThinkPad T440P	PB-031DX9
Pods (4) (only used for conducted emissions)	STATSports	ApexNXT	8DD81BB2FC1F, C4D65120E808, B19D13EB3D9, AC0B791900F5

3.5. Block Diagram



4. Measurements Parameters

4.1. Measurement Equipment and Software Used to Perform Test

Device	Manufacturer	Model No.	Serial No.	Cal Due	Interval
EMI Test Receiver, 9 kHz - 7GHz ¹	Rohde & Schwarz	ESR7	101156	10/26/2025	4 Years
EMI Test Receiver, 10 Hz - 7GHz ¹	Rohde & Schwarz	ESR7	101770	7/23/2025	1 Year
EMI Test Receiver, 9 kHz – 26.5 GHz ¹	Rohde & Schwarz	ESR26	101693	6/26/2025	2 Years
Spectrum Analyzer, 9 kHz to 40 GHz ²	Rohde & Schwarz	FSV40	100899	6/27/2025	1 Year
Spectrum Analyzer 10 Hz to 40 GHz ³	Rohde & Schwarz	FSVR40	100909	9/18/2025	5 Years
Biconilog Antenna, 30 MHz - 2 GHz	Sunol Sciences	JB1	A050913	7/1/2024	3 Years
Loop Antenna 9 kHz - 30 MHz	EMCO	6512	9309-1139	4/14/2025	3 Years
Barometric Pressure/Humidity & Temp Datalogger	Extech Instruments	SD700	Q590483	4/4/2025	1 Year
Digital Barometer	Control Company	4195	ID236	3/15/2025	1 Year
Multimeter with Thermocouple	Fluke	187	80350579	9/14/2025	2 Years
Temperature / Thermal Chamber	Associated Environmental	SD-308	10782	CNR	

¹ ESR7/26 Firmware revision: V3.48 SP3, Date installed: 09/30/2020

Previous V3.48 SP2, installed 07/23/2020.

² FSV40 Firmware revision: V2.30 SP4, Date installed: 05/04/2016

Previous V2.30 SP1, installed 10/22/2014.

³ FSVR40 Firmware revision: V2.23 SP1, Date installed: 08/19/2016

Previous V2.23, installed 10/22/2014.

Manufacturer	Software Description	Title or Model #	Rev.	Report Sections
Compliance Worldwide	Test Report Generation Software	Test Report Generator	1.0	Used to process conducted emissions data

4. Measurements Parameters (continued)

4.2. Measurement & Equipment Setup

Test Dates:	6/19/2024, 6/20/2024, 7/3/2024
Test Engineer:	Sean Defelice
Normal Site Temperature (15 – 35 °C):	21
Relative Humidity (20 - 75% RH):	42
Frequency Range:	9 kHz to 1 GHz
Measurement Distance:	3 & 1 Meters
EMI Receiver IF Bandwidth:	200 Hz – 10 to 150 kHz 9 kHz – 150 kHz to 30 MHz 120 kHz - 30 MHz to 1 GHz
EMI Receiver Avg Bandwidth:	>= 3 * RBW
Detector Function:	Peak, QP - 30 MHz to 1 GHz Peak, Avg - Above 1 GHz Unless otherwise specified.

4.3 Measurement Procedure

The test measurements contained in this report are based on the requirements detailed in FCC Part 15, Subpart C - Intentional Radiators, notably Section 15.225, Operation within the band 13.110 – 14.010 MHz and ISED RSS-210, Issue 11 Annex B.6. The test procedures for these measurements are detailed in ANSI C63.10-2013.

5. Choice of Equipment for Test Suits

5.1. Choice of Model

This test report is based on the test samples supplied by the manufacturer and are reported by the manufacturer to be equivalent to the production units.

5.2. Presentation

The test sample was tested complete with all required ancillary equipment. Refer to Section 3 of this report for the product equipment configuration.

5.3. Choice of Operating Frequencies

The transmitter in the unit under test utilizes a single operating frequency at approximately 13.56 MHz.

6. Measurement Summary

Test Requirement	FCC Part 15 Reference	RSS Reference	Test Report Section	Result	Comment
Antenna Requirement	15.203	RSS-GEN Section 7.1.2	7.1	Compliant	
Operation within the Band 13.110 MHz – 14.010 MHz (Radiated Field Strength)	15.225 (a), (b), (c)	RSS-210 Section B6	7.2	Compliant	
Spurious Radiated Emissions	15.209		7.3	Compliant	
Operation within the Band 13.110 MHz – 14.010 MHz (Frequency Stability)	15.225 (e)	RSS-210 Section B6	7.4	Compliant	
Occupied Bandwidth/ Lower and Upper Band Edges	15.215(c) C63.10	N/A	7.5	Compliant	
99% Power Bandwidth	N/A	RSS-GEN Section 4.6.1	7.6	Compliant	
Power Line Conducted Emissions	15.207	RSS-GEN Section 7.2.4	7.7	Compliant	

7. Measurement Data

7.1. Antenna Requirement (Section 15.203, RSS-GEN 7.1.2)

Requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

Status: The RFID antenna utilized by the device under test is a PCB antenna contained inside a non-user accessible enclosure.

Result: Compliant

7. Measurement Data (continued)

7.2. Operation within the Band 13.110 MHz – 14.010 MHz (15.225 (a), (b) and (c))

Radiated Field Strength of Fundamental (15.225 (a), (b) and (c))

Requirement: (a) The field strength of any emissions within the band 13.553 - 13.567 MHz shall not exceed 15,848 microvolts/meter (84 dB μ V/m) at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter (50.5 dB μ V/m) at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter (40.5 dB μ V/m) at 30 meters.

Test Note: Reference ANSI C63.10-2013 sections 5.3.2 and 6.4.4.2. The following formula was used to extrapolate the measurement distance to the limit distance:

$$FS_{\text{limit}} = FS_{\text{max}} - 40 \log\left(\frac{d_{\text{near field}}}{d_{\text{measure}}}\right) - 20 \log\left(\frac{d_{\text{limit}}}{d_{\text{near field}}}\right) \quad \text{Equation 1}$$

FS_{limit} is the calculation of field strength at the limit distance (dB μ V/m)

25.53

46.92

FS_{max} is the measured field strength, expressed in (dB μ V/m QP @ 3M)

3.52

d_{near field} is the $\lambda / 2\pi$ distance (Meters)

3.00

d_{measure} is the distance of the measurement point from the EUT (Meters)

30.00

d_{limit} is the reference limit distance (Meters)

The screen captures on the following pages display the value measured at a distance of 3 meters. This distance value was adjusted to the limit distance using the formula detailed in Equation 1.

Result: Compliant - The fundamental frequency radiated field strength of the device under test complies with the requirements detailed in FCC Part 15.225, Section (a).

The peak field strength of the device under test met the average requirement. For this reason, the quasi-peak field strength was not factored using a duty cycle correction factor.

Freq. (MHz)	Ampl. ¹ (dB μ V/m) Peak	Corr. Ampl. ² (dB μ V/m) (3M) QP	Corr. Ampl. ² (dB μ V/m) (30M) QP	FCC 15.225 Limit (dB μ V/m) QP 30M	Margin (dB)	Ant Pos. Par/Per Gnd Par	Ant Height (cm)	Turntable Azimuth (Deg)	Result
13.56	52.53	46.92	25.53	84.00	-37.58	Gnd Par	100	354	Compliant


¹ Measurement has been extrapolated from 3 meters to 30 meters using Equation 1 on this page.

7. Measurement Data (continued)

7.2. Operation within the Band 13.110 MHz – 14.010 MHz (15.225 (a), (b) and (c))


Radiated Field Strength of Fundamental (15.225 (a), (b) and (c)) (continued)

7.2.1. Worst Case Field Strength of the Fundamental – Parallel Antenna



Date: 19.JUN.2024 10:14:03

7.2.2. Worst Case Field Strength of the Fundamental – Perpendicular Antenna




Date: 19.JUN.2024 10:24:06

7. Measurement Data (continued)

7.2. Operation within the Band 13.110 MHz – 14.010 MHz (15.225 (a), (b) and (c))

Radiated Field Strength of Fundamental (15.225 (a), (b) and (c)) (continued)

7.2.3. Worst Case Field Strength of the Fundamental – Ground Parallel Antenna



Date: 19 JUN 2024 11:32:40

7. Measurement Data (continued)

7.3. Transmitter Spurious Radiated Emissions (15.225 (d), 15.209)

Requirement: The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table (Reference FCC 15.209):

Frequency (MHz)	Field Strength (μ V/m)	Meas. Dist. (meters)	Field Strength (dB μ V/m)	Distance (Meters)
0.009–0.490	2400/F(kHz)	300	128.5 to 93.8	3
0.490–1.705	24000/F(kHz)	30	73.8 to 63.0	3
1.705–30.0	30	30	69.5	3
30–88	100	3	40	3
88–216	150	3	43.5	3
216–960	200	3	46	3
Above 960	500	3	54	3

¹ Measurements in the 9 to 90 kHz, 110 to 490 kHz and above 1000 MHz ranges employ an average detector. Otherwise, a quasi-peak detector is used.

² Extrapolation below 30 MHz is calculated at 40 dB/decade.

Procedure: Test measurements were made in accordance with ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, Section 6.5.

Results: Compliant - The transmitter installed in the unit under test meets the FCC Part 15.209 emissions requirements.

Sample Calculation: Final Result (dB μ V/m) = Measurement Value (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) – Pre-amplifier Gain (dB) Internal or External.


Note: All correction factors are loaded into the measurement instrument prior to testing to determine the final result.

7. Measurement Data (continued)


7.3. Spurious Radiated Emissions, 9 kHz to 1 GHz (15.225, § (d), 15.209) (cont'd)

7.3.1. Spurious Radiated Emissions, 9 kHz to 150 kHz Test Results

7.3.1.1. Parallel Antenna



7.3.1.2. Perpendicular Antenna




Test Number: 197-24
Issue Date: 1/16/2025

7. Measurement Data (continued)

7.3. Spurious Radiated Emissions, 9 kHz to 1 GHz (15.225, § (d), 15.209) (cont'd)


7.3.1. Spurious Radiated Emissions, 9 kHz to 150 kHz Test Results

7.3.1.3. Ground Parallel Antenna



7.3.2. Spurious Radiated Emissions, 150 kHz to 30 MHz Test Results

7.3.2.1. Parallel Antenna




7. Measurement Data (continued)

7.3. Spurious Radiated Emissions, 9 kHz to 1 GHz (15.225, § (d), 15.209) (cont'd)

7.3.2. Spurious Radiated Emissions, 150 kHz to 30 MHz Test Results

7.3.2.2. Perpendicular Antenna




Date: 20.JUN.2024 10:10:18

06/20/2024
10:10:17 AM

7.3.2. Spurious Radiated Emissions, 150 kHz to 30 MHz Test Results

7.3.2.3. Ground Parallel Antenna



Date: 20.JUN.2024 10:10:07


06/20/2024
10:10:06 AM

7. Measurement Data (continued)

7.3. Spurious Radiated Emissions, 9 kHz to 1 GHz (15.225, § (d), 15.209) (cont'd)


7.3.3. Spurious Radiated Emissions, 30 MHz to 1 GHz Test Results

7.3.3.1 Horizontal Polarity



Date: 19.JUN.2024 16:40:27

7.3.3.2 Vertical Polarity



Date: 19.JUN.2024 16:44:45

7. Measurement Data (continued)

7.4. Frequency Stability (§ 15.225 (e))

Requirement: The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Notes: The size of the host device that houses the device under test exceeds the volume of the site environmental chamber. In order to test the RFID transmitter and antenna assembly, it was necessary to remove the assembly from the host device and test it in the environmental chamber. In order to do this, a custom cable capable of carrying all power and signal lines to the DUT was constructed. By doing so, the DUT was subjected to the required temperature variations while maintaining operational communications with the host device.

Result: Compliant - The unit under test complies with the requirements detailed in FCC Part 15.225 (e).

7.4.1. Temperature and Voltage Variation

Temp °C	Supply Voltage	Meas Freq. (MHz)	Limit			Offset (%)	Result
			F _{MIN} (MHz)	F _{MAX} (MHz)	%		
Ambient	120 VAC	13.56198	N/A			N/A	
-20		13.56192	13.560624	13.563336	± 0.01	0.00044241	Compliant
-10		13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant
0		13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant
+10		13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant
+20		13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant
+30		13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant
+40		13.56195	13.560624	13.563336	± 0.01	0.00022121	Compliant
+50		13.56195	13.560624	13.563336	± 0.01	0.00022121	Compliant
Ambient	102 VAC	13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant
	138 VAC	13.56198	13.560624	13.563336	± 0.01	0.00000000	Compliant

7. Measurement Data (continued)

7.5. Occupied Bandwidth (Section 15.215 (c) and ANSI C63.10, Section 6.9)

Requirement: Intentional radiators operating under the alternative provisions to the general emission limits, as contained in Sections 15.217 through 15.255 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW


Frequency Band: $F_{\text{MIN}} = 13.110 \text{ MHz}$

$F_{\text{MAX}} = 14.010 \text{ MHz}$

Result: Compliant.

-20 dB Frequency Measured		Lower & Upper Band Edge		Result	
(F _{LO} & F _{HI})		(F _{MIN} & F _{Max})			
MHz		MHz			
F _{LO}	13.559403	F _{MIN}	13.11	Compliant (F _{LO} > F _{MIN})	
F _{HI}	13.564468	F _{MAX}	14.01	Compliant (F _{HI} < F _{Max})	

7.5.1. Plot of 20 dB Bandwidth vs. Frequency Band



Date: 19 JUN 2024 10:42:24

7. Measurement Data (continued)

7.6. 99% Power Bandwidth (RSS-GEN Section 4.6.1)


Requirement: When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than the actual.

Procedure: This test was performed utilizing the automated 99% bandwidth function of the spectrum analyzer.

Frequency (MHz)	99% Power Bandwidth (kHz)
13.560	11.449

7.6.1. Plot of 99% Power Bandwidth



Date: 19.JUN.2024 10:50:37

7. Measurement Data (continued)

7.7. Power Line Conducted Emissions (FCC Part 15.207)

Requirement: For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-Peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5.0	56	46
5.0 to 30.0	60	50

* Decreases with the logarithm of the frequency.

Procedure: Test measurements were made in accordance with ANSI C63.10-2013, Section 6.2: Standard test method for ac powerline conducted emissions from unlicensed wireless devices.

Results: The device under test meets the FCC Part 15.207 conducted emissions requirements.

Notes: A dummy load was used in place of the EUT antenna for the measurement at the fundamental frequency of 13.56 MHz per FCC KDB 174176 Line Conducted FAQs v01r01 Q5, dated June 3, 2015.

Sample Calculation: Final Result (dB μ V) = Measurement Value (dB μ V) + LISN Insertion Loss (dB) + Cable Loss (dB).

Note: All correction factors are loaded into the measurement instrument prior to testing to determine the final result.


7. Conducted Emissions Test Results

7.7. Power Line Conducted Emissions (15.207)

7.7.1. 120 Volts, 60 Hz Phase

Test No.: 207-24, 120 Volts, 60 Hz Phase

EN55032, Class B



Frequency (MHz)	Pk Amp (dB μ V)	QP Amp (dB μ V)	QP Limit (dB μ V)	QP Margin (dB)	Avg Amp (dB μ V)	Avg Limit (dB μ V)	Avg Margin (dB)	Comments
.1613	49.22	38.99	65.40	-26.41	23.70	55.40	-31.70	
.1995	44.14	30.78	63.63	-32.85	18.88	53.63	-34.75	
.2378	40.08	32.29	62.17	-29.88	18.30	52.17	-33.87	
.2850	42.13	34.91	60.67	-25.76	21.39	50.67	-29.28	
.2963	41.84	34.03	60.35	-26.32	20.68	50.35	-29.67	
.3503	40.69	32.65	58.96	-26.31	17.72	48.96	-31.24	
.3908	40.94	32.68	58.05	-25.37	18.07	48.05	-29.98	
.4493	39.78	32.80	56.89	-24.09	16.31	46.89	-30.58	
.5685	32.45	24.40	56.00	-31.60	9.15	46.00	-36.85	
.6270	34.25	25.18	56.00	-30.82	13.50	46.00	-32.50	
.6990	32.08	22.82	56.00	-33.18	5.42	46.00	-40.58	
.8115	28.64	19.87	56.00	-36.13	6.02	46.00	-39.98	
.9375	28.49	20.31	56.00	-35.69	5.83	46.00	-40.17	
1.0455	25.74	17.71	56.00	-38.29	2.21	46.00	-43.79	
3.0053	22.98	10.74	56.00	-45.26	-3.05	46.00	-49.05	
6.3195	15.92	7.68	60.00	-52.32	4.16	50.00	-45.84	
11.6273	36.85	29.60	60.00	-30.40	22.85	50.00	-27.15	
12.6443	36.68	29.22	60.00	-30.78	22.86	50.00	-27.14	
15.2633	34.64	26.10	60.00	-33.90	16.50	50.00	-33.50	
20.2245	31.69	24.08	60.00	-35.92	14.73	50.00	-35.27	
23.6018	24.27	16.98	60.00	-43.02	10.42	50.00	-39.58	
27.1973	27.67	16.77	60.00	-43.23	2.99	50.00	-47.01	
27.4133	27.50	17.37	60.00	-42.63	7.51	50.00	-42.49	
28.8533	28.44	17.35	60.00	-42.65	3.69	50.00	-46.31	


7. Conducted Emissions Test Results

7.7. Power Line Conducted Emissions (15.207)

7.7.2. 120 Volts, 60 Hz Neutral

Test No.: 207-24, 120 Volts, 60 Hz Neutral

EN55032, Class B



Frequency (MHz)	Pk Amp (dB μ V)	QP Amp (dB μ V)	QP Limit (dB μ V)	QP Margin (dB)	Avg Amp (dB μ V)	Avg Limit (dB μ V)	Avg Margin (dB)	Comments
.1568	46.72	38.84	65.63	-26.79	24.60	55.63	-31.03	
.1973	44.55	25.50	63.72	-38.22	14.18	53.72	-39.54	
.2355	39.35	29.99	62.25	-32.26	14.57	52.25	-37.68	
.2580	33.44	26.92	61.50	-34.58	12.46	51.50	-39.04	
.2760	37.30	29.73	60.94	-31.21	15.47	50.94	-35.47	
.3525	34.60	25.48	58.90	-33.42	11.19	48.90	-37.71	
.4088	34.41	27.68	57.67	-29.99	10.94	47.67	-36.73	
.4515	34.12	27.17	56.85	-29.68	8.93	46.85	-37.92	
.4740	27.00	19.11	56.44	-37.33	6.86	46.44	-39.58	
.5168	24.93	17.80	56.00	-38.20	5.58	46.00	-40.42	
.5865	27.30	19.51	56.00	-36.49	3.43	46.00	-42.57	
.6270	27.32	19.31	56.00	-36.69	5.42	46.00	-40.58	
.7058	24.96	16.54	56.00	-39.46	-.47	46.00	-46.47	
.8025	22.76	11.59	56.00	-44.41	-2.69	46.00	-48.69	
.8925	19.58	11.55	56.00	-44.45	-4.46	46.00	-50.46	
.9465	20.54	12.94	56.00	-43.06	-2.88	46.00	-48.88	
1.1040	18.82	11.45	56.00	-44.55	-5.04	46.00	-51.04	
1.3268	18.13	9.00	56.00	-47.00	-7.40	46.00	-53.40	
2.9288	19.28	8.15	56.00	-47.85	-4.31	46.00	-50.31	
3.7905	13.87	4.28	56.00	-51.72	-2.44	46.00	-48.44	
6.3195	16.49	8.76	60.00	-51.24	4.05	50.00	-45.95	
9.5393	28.73	21.01	60.00	-38.99	13.55	50.00	-36.45	
11.4945	37.01	30.10	60.00	-29.90	23.59	50.00	-26.41	
12.1358	38.06	33.04	60.00	-26.96	26.89	50.00	-23.11	
13.3575	36.56	30.29	60.00	-29.71	24.78	50.00	-25.22	
15.6165	34.78	28.04	60.00	-31.96	21.63	50.00	-28.37	
16.2173	33.16	25.69	60.00	-34.31	14.48	50.00	-35.52	
17.6910	35.80	27.35	60.00	-32.65	19.84	50.00	-30.16	
24.3150	23.59	15.04	60.00	-44.96	8.81	50.00	-41.19	
25.2960	19.23	10.90	60.00	-49.10	3.84	50.00	-46.16	
27.4155	22.29	12.31	60.00	-47.69	6.84	50.00	-43.16	

8. Test Site Description

Compliance Worldwide is located at 357 Main Street in Sandown, New Hampshire. The test sites at Compliance Worldwide are used for conducted and radiated emissions testing in accordance with the Federal Communications Commission (FCC) and Industry Canada standards. Through our American Association for Laboratory Accreditation (A2LA) ISO Guide 17025 Accreditation our test sites are designated with the FCC (designation number **US1091**) and Industry Canada (file number **IC 3023A-1**) and VCCI (Member number 3168) under registration number A-0274.

Compliance Worldwide is also designated as a Phase 1 CAB under APEC-MRA (US0132) for Australia/New Zealand AS/NZS CISPR 11, AS/NZS CISPR 14-1, AS/NZS CISPR 15, AS/NZS CISPR 32, Chinese-Taipei (Taiwan) BSMI CNS 15936 and Korea (RRA) KS C 9811, KS C 9814-1, KS C 9815, KS C 9832, KS C 9610-6-3 & KS C 9610-6-4.

The radiated emissions test site is a 3- and 10-meter enclosed open area test site (OATS). Personnel, support equipment and test equipment are located in the basement beneath the OATS ground plane.

The conducted emissions site is part of a 16' x 20' x 12' ferrite tile chamber and uses one of the walls for the vertical ground plane. A second conducted emissions site is also located in the basement of the OATS site with a 2.3 x 2.5-meter ground plane and a 2.4 x 2.4-meter vertical wall.

The radiated emissions test site for measurements above 1GHz is a 3 Meter open area test site (OATS) with a 3.6 by 3.6-meter anechoic absorber floor patch to achieve a quasi-free space measurement environment per ANSI C63.4/C63.10 and CISPR 16-1-4 standards.

The sites are designed to test products or systems 1.5 meters W x 1.5 meters L x 2.0 meters H, floor standing or tabletop.

9. Test Setup Photographs

9.1. Radiated Emissions Front View Below 30 MHz



9. Test Setup Photographs

9.2. Radiated Emissions Rear View – Fundamental & Spurious Emissions < 30 MHz



9. Test Setup Photographs

9.3. Radiated Emissions Front View Emissions 30 MHz to 1 GHz



9. Test Setup Photographs

9.4. Radiated Emissions Rear View Emissions 30 MHz to 1 GHz



9. Test Setup Photographs

9.5. Power Line Conducted Emissions - Front



9. Test Setup Photographs

9.6. Power Line Conducted Emissions – Back



9. Test Setup Photographs

9.7. Temperature Stability Setup



9. Test Setup Photographs

9.8. Temperature Stability EUT

