

RF Exposure Evaluation

FCC ID: 2APJG-CK01

1. Client Information

Applicant	:	Tronicc Technologies
Address	:	18584 Budge, Pierrefonds, QC, Canada
Manufacturer	:	Tronicc Technologies
Address	:	18584 Budge, Pierrefonds, QC, Canada

2. General Description of EUT

EUT Name	:	CareKii	
Models No.	:	CK01	
Model Difference	:	N/A	
Product Description	Operation Frequency:	Bluetooth 4.2: 2402MHz~2480MHz	
	Modulation Type:	BLE: GFSK	
	Antenna Gain:	0.5dBi PCB Antenna	
Power Rating	:	DC 3.7V 90mAh by Li-ion battery	
Software Version	:	N/A	
Hardware Version	:	N/A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Remark	:	The antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.	

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$$
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2

Calculation:

Test separation: 5mm							
BLE Mode (GFSK)							
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value	
2.402	-0.446	0±1	1	1.259	0.390	3.0	
2.442	-0.196	0±1	1	1.259	0.393	3.0	
2.480	-0.162	0±1	1	1.259	0.397	3.0	

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----