

**FCC Part 15C**  
**Measurement and Test Report**  
**For**  
**JCO Electronic Technology Co.,LTD**

**FCC ID: 2APKX-H265N40F**

|                                      |                                 |
|--------------------------------------|---------------------------------|
| <b>FCC Rule(s):</b>                  | <u>FCC Part 15C</u>             |
| <b>Product Description:</b>          | <u>H.265 WIFI</u>               |
| <b>Tested Model:</b>                 | <u>H265/N40F</u>                |
| <b>Report No.:</b>                   | <u>BSL18041048130003Y-ER-3</u>  |
| <b>Tested Date:</b>                  | <u>2018-04-16 to 2018-04-20</u> |
| <b>Issued Date:</b>                  | <u>2018-04-25</u>               |
| <b>Tested By:</b>                    | <u>Lisa. Li / Engineer</u>      |
| <b>Reviewed By:</b>                  | <u>arno. Liu / EMC Manager</u>  |
| <b>Approved &amp; Authorized By:</b> | <u>Mike mo / PSQ Manager</u>    |
| <b>Prepared By:</b>                  |                                 |

*Lisa. Li*  
*Arno. Liu*  
*Mike mo*

**BSL Testing Co.,LTD.**  
NO. 24, ZH Park, Nantou, Shenzhen, 518000 China  
Tel: 86- 755-26508703 Fax: 86- 755-26508703

**TABLE OF CONTENTS**

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION.....</b>                          | <b>3</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3         |
| 1.2 TEST STANDARDS.....                                     | 4         |
| 1.3 TEST METHODOLOGY.....                                   | 4         |
| 1.4 TEST FACILITY.....                                      | 4         |
| 1.5 EUT SETUP AND TEST MODE.....                            | 5         |
| 1.6 MEASUREMENT UNCERTAINTY.....                            | 5         |
| 1.7 TEST EQUIPMENT LIST AND DETAILS.....                    | 6         |
| <b>2. SUMMARY OF TEST RESULTS.....</b>                      | <b>7</b>  |
| <b>3. RF EXPOSURE.....</b>                                  | <b>8</b>  |
| 3.1 STANDARD APPLICABLE.....                                | 8         |
| 3.2 TEST RESULT.....                                        | 8         |
| <b>4. ANTENNA REQUIREMENT.....</b>                          | <b>9</b>  |
| 4.1 STANDARD APPLICABLE.....                                | 9         |
| 4.2 EVALUATION INFORMATION.....                             | 9         |
| <b>5. POWER SPECTRAL DENSITY.....</b>                       | <b>10</b> |
| 5.1 STANDARD APPLICABLE.....                                | 10        |
| 5.2 TEST PROCEDURE.....                                     | 10        |
| 5.3 ENVIRONMENTAL CONDITIONS.....                           | 10        |
| 5.4 SUMMARY OF TEST RESULTS/PLOTS.....                      | 11        |
| <b>6. GDB BANDWIDTH.....</b>                                | <b>24</b> |
| 6.1 STANDARD APPLICABLE.....                                | 24        |
| 6.2 TEST PROCEDURE.....                                     | 24        |
| 6.3 ENVIRONMENTAL CONDITIONS.....                           | 24        |
| 6.4 SUMMARY OF TEST RESULTS/PLOTS.....                      | 24        |
| <b>7. RF OUTPUT POWER.....</b>                              | <b>38</b> |
| 7.1 STANDARD APPLICABLE.....                                | 38        |
| 7.2 TEST PROCEDURE.....                                     | 38        |
| 7.3 ENVIRONMENTAL CONDITIONS.....                           | 38        |
| 7.4 SUMMARY OF TEST RESULTS/PLOTS.....                      | 39        |
| <b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....</b>         | <b>48</b> |
| 8.1 MEASUREMENT UNCERTAINTY.....                            | 48        |
| 8.2 STANDARD APPLICABLE.....                                | 48        |
| 8.3 TEST PROCEDURE.....                                     | 48        |
| 8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....           | 50        |
| 8.5 ENVIRONMENTAL CONDITIONS.....                           | 50        |
| 8.6 SUMMARY OF TEST RESULTS/PLOTS.....                      | 50        |
| <b>9. OUT OF BAND EMISSIONS.....</b>                        | <b>66</b> |
| 9.1 STANDARD APPLICABLE.....                                | 66        |
| 9.2 TEST PROCEDURE.....                                     | 66        |
| 9.3 ENVIRONMENTAL CONDITIONS.....                           | 67        |
| 9.4 SUMMARY OF TEST RESULTS/PLOTS.....                      | 67        |
| <b>10. CONDUCTED EMISSIONS.....</b>                         | <b>76</b> |
| 10.1 MEASUREMENT UNCERTAINTY.....                           | 76        |
| 10.2 TEST PROCEDURE.....                                    | 76        |
| 10.3 BASIC TEST SETUP BLOCK DIAGRAM.....                    | 76        |
| 10.4 ENVIRONMENTAL CONDITIONS.....                          | 76        |
| 10.5 TEST RECEIVER SETUP.....                               | 77        |
| 10.6 SUMMARY OF TEST RESULTS/PLOTS.....                     | 77        |
| 10.7 CONDUCTED EMISSIONS TEST DATA.....                     | 77        |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: JCO Electronic Technology Co.,LTD  
 Address of applicant: Fulian Industrial Park,Dalang South Rd.,Longhua,Shenzhen,China  
 Manufacturer: JCO Electronic Technology Co.,LTD  
 Address of manufacturer: Fulian Industrial Park,Dalang South Rd.,Longhua,Shenzhen,China

| General Description of EUT                                                                                                                                                                                                                                                                   |                                                                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| Product Name:                                                                                                                                                                                                                                                                                | H.265 WIFI                                                                    |
| Trade Name:                                                                                                                                                                                                                                                                                  | N/A                                                                           |
| Model No.:                                                                                                                                                                                                                                                                                   | H265/N40F                                                                     |
| Adding Model(s):                                                                                                                                                                                                                                                                             | N40FA,N40FC,N40FD,N40FV,N40FS,N80FE,N80FT,N80FR,N80FL,N80FQ                   |
| Rated Voltage:                                                                                                                                                                                                                                                                               | DC 12V from adapter                                                           |
| Adapter information:                                                                                                                                                                                                                                                                         | Model: YGY-120200<br>Input: AC100-240V, 50/60Hz, 0.5A<br>Output: DC 12V, 2.0A |
| <i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model H265/N40F, but the circuit and the electronic construction do not change, declared by the manufacturer.</i> |                                                                               |

| Technical Characteristics of EUT |                                                                      |
|----------------------------------|----------------------------------------------------------------------|
| Support Standards:               | 802.11b, 802.11g, 802.11n                                            |
| Frequency Range:                 | 2412-2462MHz for 802.11b/g/n(HT20)<br>2422-2452MHz for 802.11n(HT40) |
| RF Output Power:                 | 19.00dBm(Conducted)                                                  |
| Type of Modulation:              | CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM                                  |
| Data Rate:                       | 1-11Mbps, 6-54Mbps, up to 150Mbps                                    |
| Quantity of Channels:            | 11 for 802.11b/g/n(HT20);7 for 802.11n(HT40)                         |
| Channel Separation:              | 5MHz                                                                 |
| Type of Antenna:                 | Rubber Duck Antenna                                                  |
| Antenna Gain:                    | Chain 1:0dBi, Chain 2:0dBi                                           |
| Lowest Internal Frequency        | 32.768KHz                                                            |

## 1.2 Test Standards

The following report is prepared on behalf of the JCO Electronic Technology Co.,LTD in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 V04 for digital transmission systems and KDB 662911 D01 Multiple Transmitter Output v02r01 shall be performed also.

## 1.4 Test Facility

BSL Testing Co.,LTD.

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

Designation Number : CN1217

Test Firm Registration Number: 866035

Tel: 86- 755-26508703

Fax: 86- 755-26508703

### 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List                                                                                                                         |              |                           |
|----------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------------------|
| Test Mode                                                                                                                              | Description  | Remark                    |
| TM1                                                                                                                                    | 802.11b      | 2412MHz, 2437MHz, 2462MHz |
| TM2                                                                                                                                    | 802.11g      | 2412MHz, 2437MHz, 2462MHz |
| TM3                                                                                                                                    | 802.11n-HT20 | 2412MHz, 2437MHz, 2462MHz |
| TM4                                                                                                                                    | 802.11n-HT40 | 2422MHz, 2437MHz, 2452MHz |
| Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report. |              |                           |

| EUT Cable List and Details |            |                     |                        |
|----------------------------|------------|---------------------|------------------------|
| Cable Description          | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                          | /          | /                   | /                      |

| Special Cable List and Details |            |                     |                        |
|--------------------------------|------------|---------------------|------------------------|
| Cable Description              | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| /                              | /          | /                   | /                      |

| Auxiliary Equipment List and Details |              |       |               |
|--------------------------------------|--------------|-------|---------------|
| Description                          | Manufacturer | Model | Serial Number |
| /                                    | /            | /     | /             |

### 1.6 Measurement Uncertainty

| Measurement uncertainty        |            |                     |
|--------------------------------|------------|---------------------|
| Parameter                      | Conditions | Uncertainty         |
| RF Output Power                | Conducted  | $\pm 0.42\text{dB}$ |
| Occupied Bandwidth             | Conducted  | $\pm 1.5\%$         |
| Power Spectral Density         | Conducted  | $\pm 1.8\text{dB}$  |
| Conducted Spurious Emission    | Conducted  | $\pm 2.17\text{dB}$ |
| Conducted Emissions            | Conducted  | $\pm 2.88\text{dB}$ |
| Transmitter Spurious Emissions | Radiated   | $\pm 5.1\text{dB}$  |

**1.7 Test Equipment List and Details**

| Description                         | Manufacturer     | Model                 | Serial No. | Cal Date   | Due. Date  |
|-------------------------------------|------------------|-----------------------|------------|------------|------------|
| Communication Tester                | Rohde & Schwarz  | CMW500                | 100358     | 2017-10-21 | 2018-10-20 |
| Spectrum Analyzer                   | R&S              | FSP40                 | 100550     | 2017-10-21 | 2018-10-20 |
| Test Receiver                       | R&S              | ESCI7                 | US47140102 | 2017-10-21 | 2018-10-20 |
| Signal Generator                    | HP               | 83630B                | 3844A01028 | 2017-10-22 | 2018-10-21 |
| Test Receiver                       | R&S              | ESPI-3                | 100180     | 2017-10-21 | 2018-10-20 |
| Amplifier                           | Agilent          | 8449B                 | 4035A00116 | 2017-10-22 | 2018-10-21 |
| Amplifier                           | HP               | 8447E                 | 2945A02770 | 2017-10-22 | 2018-10-21 |
| Signal Generator                    | IFR              | 2023A                 | 202307/242 | 2017-10-22 | 2018-10-21 |
| Broadband Antenna                   | SCHAFFNER        | 2774                  | 2774       | 2017-10-17 | 2018-10-16 |
| Biconical and log periodic antennas | ELECTRO-METRIC   | EM-6917B-1            | 171        | 2017-10-17 | 2018-10-16 |
| Horn Antenna                        | R&S              | HF906                 | 100253     | 2017-10-17 | 2018-10-16 |
| Horn Antenna                        | EM               | EM-6961               | 6462       | 2017-10-17 | 2018-10-16 |
| LISN                                | R&S              | ESH3-Z5               | 100196     | 2017-10-17 | 2018-10-16 |
| LISN                                | COM-POWER        | LI-115                | 02027      | 2017-10-17 | 2018-10-16 |
| 3m Semi-Anechoic Chamber            | Chengyu Electron | 9 (L)*6 (W)*<br>6 (H) | BSL086     | 2017-10-21 | 2018-10-20 |
| Horn Antenna                        | A-INFOMW         | LB-180400KF           | BSL088     | 2017-10-21 | 2018-10-20 |

## 2. SUMMARY OF TEST RESULTS

---

| FCC Rules                   | Description of Test Item          | Result    |
|-----------------------------|-----------------------------------|-----------|
| § 2.1093                    | RF Exposure                       | Compliant |
| § 15.203; § 15.247(b)(4)(i) | Antenna Requirement               | Compliant |
| §15.205                     | Restricted Band of Operation      | Compliant |
| § 15.207(a)                 | Conducted Emission                | Compliant |
| § 15.247(e)                 | Power Spectral Density            | Compliant |
| § 15.247(a)(2)              | 6 dB Bandwidth                    | Compliant |
| § 15.247(b)(3)              | RF Output Power                   | Compliant |
| § 15.209(a)                 | Radiated Emission                 | Compliant |
| § 15.247(d)                 | Band Edge (Out of Band Emissions) | Compliant |

N/A: not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1091, the mobile transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has two Rubber Duck antennas, fulfill the requirement of this section.

## 5. Power Spectral Density

---

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 V04, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = PK
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.3 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 26° C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

**5.4 Summary of Test Results/Plots**

| Test Mode    | Test Channel<br>MHz | Power Spectral Density<br>dBm/3kHz |         |        | Limit<br>dBm/3kHz |
|--------------|---------------------|------------------------------------|---------|--------|-------------------|
|              |                     | Chain 1                            | Chain 2 | Total  |                   |
| 802.11b      | 2412                | -10.55                             | -8.16   | -6.18  | 8                 |
|              | 2437                | -9.24                              | -9.06   | -6.14  | 8                 |
|              | 2462                | -7.96                              | -11.37  | -6.33  | 8                 |
| 802.11g      | 2412                | -10.47                             | -12.56  | -8.38  | 8                 |
|              | 2437                | -10.12                             | -17.19  | -9.34  | 8                 |
|              | 2462                | -11.61                             | -14.99  | -9.97  | 8                 |
| 802.11n HT20 | 2412                | -10.83                             | -17.92  | -10.05 | 8                 |
|              | 2437                | -11.17                             | -16.14  | -9.97  | 8                 |
|              | 2462                | -11.80                             | -15.17  | -10.16 | 8                 |
| 802.11n-HT40 | 2422                | -14.08                             | -16.05  | -11.94 | 8                 |
|              | 2437                | -11.34                             | -17.39  | -10.38 | 8                 |
|              | 2452                | -9.30                              | -12.34  | -7.55  | 8                 |


Note:

$$1. \text{ The Total PSD Level} = 10 * \log\{10^{(\text{chain 1 PSD}/10)} + 10^{(\text{chain 2 PSD}/10)}\}$$


Please refer to the following test plots:

Chain 1:


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel



802.11n-HT20-High Channel




802.11n-HT40-Low Channel






802.11n-HT40-Middle Channel




802.11n-HT40-High Channel




Chain 2


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



## 6. 6dB Bandwidth

---

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25° C     |
| Relative Humidity: | 53%       |
| ATM Pressure:      | 1018 mbar |

### 6.4 Summary of Test Results/Plots



**Chain 1:**


| Test Mode    | Test Channel<br>MHz | 6 dB Bandwidth<br>MHz | Limit<br>kHz |
|--------------|---------------------|-----------------------|--------------|
| 802.11b      | 2412                | 9.560                 | ≥500         |
|              | 2437                | 9.360                 | ≥500         |
|              | 2462                | 9.320                 | ≥500         |
| 802.11g      | 2412                | 16.560                | ≥500         |
|              | 2437                | 16.560                | ≥500         |
|              | 2462                | 16.620                | ≥500         |
| 802.11n-HT20 | 2412                | 17.820                | ≥500         |
|              | 2437                | 17.760                | ≥500         |
|              | 2462                | 17.760                | ≥500         |
| 802.11n-HT40 | 2422                | 36.600                | ≥500         |
|              | 2437                | 36.500                | ≥500         |
|              | 2452                | 35.700                | ≥500         |

**Chain 2:**


| Test Mode    | Test Channel<br>MHz | 6 dB Bandwidth<br>MHz | Limit<br>kHz |
|--------------|---------------------|-----------------------|--------------|
| 802.11b      | 2412                | 9.360                 | ≥500         |
|              | 2437                | 9.320                 | ≥500         |
|              | 2462                | 9.880                 | ≥500         |
| 802.11g      | 2412                | 16.620                | ≥500         |
|              | 2437                | 16.560                | ≥500         |
|              | 2462                | 16.500                | ≥500         |
| 802.11n-HT20 | 2412                | 17.820                | ≥500         |
|              | 2437                | 17.760                | ≥500         |
|              | 2462                | 17.700                | ≥500         |
| 802.11n-HT40 | 2422                | 36.650                | ≥500         |
|              | 2437                | 35.970                | ≥500         |
|              | 2452                | 35.860                | ≥500         |

Please refer to the following test plots:


Chain 1  
802.11b-Low Channel




802.11b-Middle Channel




## 802.11b-High Channel




## 802.11g-Low Channel




## 802.11g-Middle Channel




## 802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel




802.11n-HT40-High Channel






Chain 2

802.11b-Low Channel




802.11b-Middle Channel







802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel




7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



7.3 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 26° C     |
| Relative Humidity: | 57%       |
| ATM Pressure:      | 1011 mbar |

**7.4 Summary of Test Results/Plots**


| Test Mode            | Frequency MHz | Chain 1 Power dBm | Chain 2 Power dBm | Total Power dBm | Output Power mW | Limit mW |
|----------------------|---------------|-------------------|-------------------|-----------------|-----------------|----------|
| 802.11b _ 11Mbps     | 2412          | 15.71             | 16.25             | 19.00           | 79.43           | 1000     |
|                      | 2437          | 15.92             | 15.79             | 18.87           | 77.09           | 1000     |
|                      | 2462          | 14.32             | 16.55             | 18.59           | 72.28           | 1000     |
| 802.11g_54Mbps       | 2412          | 14.46             | 14.78             | 17.63           | 57.94           | 1000     |
|                      | 2437          | 15.37             | 14.97             | 18.18           | 65.77           | 1000     |
|                      | 2462          | 13.54             | 15.16             | 17.44           | 55.46           | 1000     |
| 802.11n<br>HT20_MCS7 | 2412          | 16.42             | 14.49             | 18.57           | 71.94           | 1000     |
|                      | 2437          | 14.52             | 15.15             | 17.86           | 61.09           | 1000     |
|                      | 2462          | 14.19             | 15.17             | 17.72           | 59.16           | 1000     |
| 802.11n<br>HT40_MCS7 | 2422          | 16.37             | 13.96             | 18.34           | 68.23           | 1000     |
|                      | 2437          | 14.00             | 14.12             | 17.07           | 50.93           | 1000     |
|                      | 2452          | 14.72             | 15.11             | 17.93           | 62.09           | 1000     |

Note:


1. The Total Power (dBm) =  $10 \cdot \log \{ 10^{(\text{Chain 1 Power} / 10)} + 10^{(\text{Chain 2 Power} / 10)} \}$ .

**Chain 1**


## 802.11b-Low Channel



## 802.11b-Middle Channel




## 802.11b-High Channel







802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




## 802.11n-HT20-Low Channel




## 802.11n-HT20-Middle Channel




## 802.11n-HT20-High Channel




## 802.11n-HT40-Low Channel



## 802.11n-HT40-Middle Channel




## 802.11n-HT40-High Channel




Chain 2


802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel



802.11g-Middle Channel




802.11g-High Channel







802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



## 8. Field Strength of Spurious Emissions

---

### 8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 8.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.



### 8.3 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

#### 8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

#### 8.5 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

#### 8.6 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note:*

- 1. Worst-case radiated emission below 1GHz is 802.11b (CH Low) of Chain 1 mode.*
- 2. Worst-case radiated emission above 1GHz is 802.11g (CH Low, Middle, High) of Chain2 mode.*


### Plot of Radiated Emissions Test Data (30MHz to 1GHz): 802.11b (CH Low) of Chain 1

Test Specification: Horizontal



| No. | Mk. | Freq.    | Measure-<br>ment | Limit  | Over   | Antenna<br>Height | Table<br>Degree |        |
|-----|-----|----------|------------------|--------|--------|-------------------|-----------------|--------|
|     |     | MHz      | dBuV/m           | dBuV/m | dB     | Detector          | cm              | degree |
| 1   |     | 69.3568  | 14.88            | 40.00  | -25.12 | QP                |                 |        |
| 2   |     | 124.5690 | 22.35            | 43.50  | -21.15 | QP                |                 |        |
| 3   |     | 202.1005 | 27.63            | 43.50  | -15.87 | QP                |                 |        |
| 4   | *   | 331.3546 | 35.75            | 46.00  | -10.25 | QP                |                 |        |
| 5   |     | 401.8385 | 32.73            | 46.00  | -13.27 | QP                |                 |        |
| 6   |     | 677.5797 | 33.22            | 46.00  | -12.78 | QP                |                 |        |

Test Specification: Vertical



| No. | Mk. | Freq.    | Measure-<br>ment | Limit  | Over   | Antenna<br>Height | Table<br>Degree |        |
|-----|-----|----------|------------------|--------|--------|-------------------|-----------------|--------|
|     |     | MHz      | dBuV/m           | dBuV/m | dB     | Detector          | cm              | degree |
| 1   |     | 34.2760  | 20.88            | 40.00  | -19.12 | QP                |                 |        |
| 2   |     | 58.6126  | 25.90            | 40.00  | -14.10 | QP                |                 |        |
| 3   |     | 124.5690 | 22.35            | 43.50  | -21.15 | QP                |                 |        |
| 4   |     | 202.1005 | 22.13            | 43.50  | -21.37 | QP                |                 |        |
| 5   |     | 326.7395 | 28.93            | 46.00  | -17.07 | QP                |                 |        |
| 6   | *   | 677.5797 | 33.22            | 46.00  | -12.78 | QP                |                 |        |

*Spurious Emissions Above 1GHz**Test Mode: 802.11g of Chain 2:*

| Frequency              | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low channel-2412MHz    |          |          |        |       |          |
| 4824.000               | 54.02    | 74       | -19.98 | H     | PK       |
| 4824.000               | 41.76    | 54       | -12.24 | H     | AV       |
| 7236.000               | 52.28    | 74       | -21.72 | H     | PK       |
| 7236.000               | 38.74    | 54       | -15.26 | H     | AV       |
| 4824.000               | 50.41    | 74       | -23.59 | V     | PK       |
| 4824.000               | 41.33    | 54       | -12.67 | V     | AV       |
| 7236.000               | 53.60    | 74       | -20.4  | V     | PK       |
| 7236.000               | 34.74    | 54       | -19.26 | V     | AV       |
| Middle channel-2437MHz |          |          |        |       |          |
| 4874.000               | 56.31    | 74       | -17.69 | H     | PK       |
| 4874.000               | 48.41    | 54       | -5.59  | H     | AV       |
| 7311.000               | 54.60    | 74       | -19.4  | H     | PK       |
| 7311.000               | 32.04    | 54       | -21.96 | H     | AV       |
| 4874.000               | 59.55    | 74       | -14.45 | V     | PK       |
| 4874.000               | 48.62    | 54       | -5.38  | V     | AV       |
| 7311.000               | 54.41    | 74       | -19.59 | V     | PK       |
| 7311.000               | 35.93    | 54       | -18.07 | V     | AV       |
| High channel-2462MHz   |          |          |        |       |          |
| 4924.000               | 50.09    | 74       | -23.91 | H     | PK       |
| 4924.000               | 33.16    | 54       | -20.84 | H     | AV       |
| 7386.000               | 56.43    | 74       | -17.57 | H     | PK       |
| 7386.000               | 37.42    | 54       | -16.58 | H     | AV       |
| 4924.000               | 57.95    | 74       | -16.05 | V     | PK       |
| 4924.000               | 46.74    | 54       | -7.26  | V     | AV       |
| 7386.000               | 51.81    | 74       | -22.19 | V     | PK       |
| 7386.000               | 38.63    | 54       | -15.37 | V     | AV       |

Note:


1. Calculation of result is: Result (dBm) = Reading (dBm) + Correction Factor (dB).
2. Correction Factor (dB)=Ant. Factor + Cable Loss – Ampl. Gain.
3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The worst data of spurious (Conducted)


Chain 1:

802.11b-Lowest


Lowest




Middle




Highest




802.11g-Lowest  
Lowest



Middle




Highest






802.11n-HT20-Lowest


Lowest



Middle




Highest




802.11n-HT40-Lowest


Lowest




Middle




Highest




Chain 2:  
802.11b-Lowest  
Lowest



Middle




Highest




802.11g-Lowest


Lowest




Middle




Highest




802.11n-HT20-Lowest  
Lowest



Middle




Highest




802.11n-HT40-Lowest

Lowest






Middle



Highest



## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074D01 v04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 V04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW  $\geq$  300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

### 9.3 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 23°C      |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

### 9.4 Summary of Test Results/Plots

802.11b- Bandedge (Radiated)

Note: we pre-scan all modes, the worst data is 802.11b mode of Chain 2.


| Channel | Freq.(MHz) | Level(dBuV) | Limit(dBuV) | Margin(dB) | Detector |
|---------|------------|-------------|-------------|------------|----------|
|         | 2400       | 59.42       | 74          | -14.58     | Peak     |
| LOW     | 2400       | 31.61       | 54          | -22.39     | Average  |
|         | 2483.5     | 52.36       | 74          | -21.64     | Peak     |
| HIGH    | 2483.5     | 37.10       | 54          | -16.9      | Average  |

Bandedge (Conducted)


Chain WIFI 1:

802.11b-Lowest


Lowest




Highest




802.11g-Lowest




Highest




802.11n-HT20-Lowest  
Lowest




Highest




802.11n-HT40-Lowest  
Lowest




Highest



Chain 2:  
802.11b-Lowest  
Lowest




Highest






802.11g-Lowest




Highest




802.11n-HT20-Lowest


Lowest




Highest



802.11n-HT40-Lowest  
Lowest



Highest



## 10. Conducted Emissions

### 10.1 Measurement Uncertainty


Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

### 10.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.3 Basic Test Setup Block Diagram



### 10.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

10.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:


|                                   |         |
|-----------------------------------|---------|
| Start Frequency.....              | 150 kHz |
| Stop Frequency.....               | 30 MHz  |
| Sweep Speed.....                  | Auto    |
| IF Bandwidth.....                 | 10 kHz  |
| Quasi-Peak Adapter Bandwidth..... | 9 kHz   |
| Quasi-Peak Adapter Mode.....      | Normal  |

10.6 Summary of Test Results/Plots

According to the data in section 10.7, the EUT complied with the FCC Part 15.207 Conducted margin for this device


10.7 Conducted Emissions Test Data

Note: we are pre-scan all modes, the worst data is 802.11n HT20(Low) mode of WIFI 1.

**Plot of Conducted Emissions Test Data: 802.11n HT20(Low)***Test Specification: Neutral*

| No. | Mk. | Freq.   | Measure-<br>ment | Limit | Over   |          |         |
|-----|-----|---------|------------------|-------|--------|----------|---------|
|     |     | MHz     | dBuV             | dBuV  | dB     | Detector | Comment |
| 1   |     | 0.2268  | 28.62            | 62.56 | -33.94 | QP       |         |
| 2   |     | 0.2268  | 17.24            | 52.56 | -35.32 | AVG      |         |
| 3   |     | 0.3149  | 29.20            | 59.84 | -30.64 | QP       |         |
| 4   |     | 0.3149  | 16.38            | 49.84 | -33.46 | AVG      |         |
| 5   | *   | 1.1656  | 29.70            | 56.00 | -26.30 | QP       |         |
| 6   |     | 1.1656  | 17.36            | 46.00 | -28.64 | AVG      |         |
| 7   |     | 4.8224  | 26.89            | 56.00 | -29.11 | QP       |         |
| 8   |     | 4.8224  | 15.27            | 46.00 | -30.73 | AVG      |         |
| 9   |     | 8.0198  | 28.81            | 60.00 | -31.19 | QP       |         |
| 10  |     | 8.0198  | 15.73            | 50.00 | -34.27 | AVG      |         |
| 11  |     | 14.5170 | 28.65            | 60.00 | -31.35 | QP       |         |
| 12  |     | 14.5170 | 15.88            | 50.00 | -34.12 | AVG      |         |

Test Specification: Live



| No. Mk. | Freq.   | Measure-<br>ment | Limit | Over   | Detector | Comment |
|---------|---------|------------------|-------|--------|----------|---------|
|         |         |                  |       |        |          |         |
|         | MHz     | dBuV             | dBuV  | dB     |          |         |
| 1       | 0.3537  | 31.82            | 58.87 | -27.05 | QP       |         |
| 2       | 0.3537  | 20.85            | 48.87 | -28.02 | AVG      |         |
| 3       | 0.6405  | 37.86            | 56.00 | -18.14 | QP       |         |
| 4       | 0.6405  | 26.27            | 46.00 | -19.73 | AVG      |         |
| 5       | 0.8260  | 34.77            | 56.00 | -21.23 | QP       |         |
| 6       | 0.8260  | 15.86            | 46.00 | -30.14 | AVG      |         |
| 7 *     | 4.5015  | 39.06            | 56.00 | -16.94 | QP       |         |
| 8       | 4.5015  | 20.20            | 46.00 | -25.80 | AVG      |         |
| 9       | 8.4561  | 30.92            | 60.00 | -29.08 | QP       |         |
| 10      | 8.4561  | 17.46            | 50.00 | -32.54 | AVG      |         |
| 11      | 15.1456 | 29.21            | 60.00 | -30.79 | QP       |         |
| 12      | 15.1456 | 16.43            | 50.00 | -33.57 | AVG      |         |

\*\*\*\*\* END OF REPORT \*\*\*\*\*