

Page : 1 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

Maximum Permissible Exposure Report

Product : Essential Spotlight Camera

Model Name : VMC2030

FCC ID : 2APLE18300409

Test Regulation: 47 CFR FCC Part 2.1091

Received Date : Apr. 8, 2020

Issued Date : May. 14, 2020

Applicant: Arlo Technologies Inc

2200 Faraday Avenue, Suite 150, Carlsbad, CA 92008, USA

Issued By: Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,

Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 3.0



Page : 2 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

REVISION HISTORY

Original Test Report No.: 4789445245-US-R1-V0

Rev.	Test report No.	Date	Page revised	Contents
Original	4789445245-US-R1-V0	May. 11, 2020	-	Initial issue
originar	.,0,1.102.10 0.0 111 10	1.14.11, 2020		Modify Note 1. Modify accessory devices.
_	4789445245-US-R1-V0	May. 14, 2020	P.6	Modify accessory
_	4789443243-03-K1-V0	Way. 14, 2020	1.0	devices
				devices.

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 3.0



Doc No: 17-EM-F0864 / 3.0

Page : 3 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

Table Of Contents

1.	. At	testation of Test Results	. 4
2.	. Te	est Methodology and Reference Procedures	. 5
3.	. Fa	cilities and Accreditation	. 5
4.	. Eq	quipment Under Test	. 6
	4.1.	Description of EUT	6
	4.2.	Description Of Available Antennas	. 7
5.	. Re	equirement	. 8
6.	. Ra	adio Frequency Radiation Exposure Evaluation	. 9



Page : 4 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

1. Attestation of Test Results

APPLICANT: Arlo Technologies Inc

2200 Faraday Avenue, Suite 150, Carlsbad, CA 92008, USA

MANUFACTURER Funing Precision Component Co., Ltd.

Lot B, Que Vo Industrial Zone, Van Duong Ward, Bac Ninh City, Bac

Ninh Province, VIETNAM

EUT DESCRIPTION: Essential Spotlight Camera

BRAND: Arlo

MODEL: VMC2030

SAMPLE STAGE: Identical Prototype

APPLICABLE STANDARDS

STANDARD

Test Results

47 CFR FCC PART 2.1091

PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Approved and Authorized By:

Cindy Hsin

Date: May. 14, 2020

Howard Kao

Date: May. 14,

2020

Project Handler Project Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 3.0



Page : 5 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.		
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan		
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398. The full scope of accreditation can be viewed at http://accreditation.taftw.org.tw/taf/public/basic/viewApplyItems.action?unitNo=3398		



Page : 6 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

4. Equipment Under Test

4.1. Description of EUT

Product Name	Essential Spotlight Camera			
Brand Name	Arlo			
Model Name	VMC2030			
Operating Frequency	WLAN 2.4GHz: 2412MHz ~ 2462MHz			
Modulation	WLAN CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM			
Number of Channel	WLAN	2.4GHz: 802.11b, 802.11g, 802.11n (HT20): 11		
Normal Voltage	5Vdc (adapter or host equipment) 3.63Vdc for battery			
Hardware Version	DV2			
SW/FW version	20200324-2_mfg			

Note:

1. The EUT incorporates a SISO diversity function. Physically, the EUT provides one completed transmitter and one receiver.

Modulation Mode	Tx,Rx Function		
802.11b	1TX,1RX		
802.11g	1TX,1RX		
802.11n (HT20)	1TX,1RX		

2. The EUT contains following accessory devices

Product	Brand Model		Description	
USB Cable	Arlo	310-50001-01	Length: 0.3meter, non-shielded cable	
Security Mount	Arlo	300-11092-01	-	
Mount Screw kit	Arlo	422-50002-01	-	

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX):+886-3-583-7948 Doc No: 17-EM-F0864 / 3.0



Page : 7 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

4.2. Description Of Available Antennas

WLAN 2.4GHz

Antenna	Brand Name	Model Name	Antenna Type	Antenna Gain(dBi)	
Ant 0	Masterwave	902P00239S0	Monopole	1.8	
Ant 1	Masterwave	902P00239S0	Monopole	1.4	

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.



Page : 8 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

5. Requirement

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E 2, H 2 or S (minutes)			
0.3-1.34	614	1.63	*100	30			
1.34-30	824/f	2.19/f	*180/f ²	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

 $S=(P*G)/4\pi R^2$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator <math>R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Page : 9 of 9

Issued date : May. 14, 2020 FCC ID : 2APLE18300409

6. Radio Frequency Radiation Exposure Evaluation

WLAN 2.4GHz

Evaluation Frequency	Max. Average Power	Antenna Gain	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)
2412 ~ 2462	24.11	1.8	25.91	389.942	0.078	1

Note:

- 1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
- 2. Max. EIRP (mW) = $10^{(\text{Max. EIRP (dBm)}/10)}$
- 3. Power density (mW/cm²) = Max. EIRP (mW) / [$4 \times \pi \times (calculated \ distance)^2$], the calculated distance is 20 cm.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.