



## FCC RF EXPOSURE REPORT

*For*

**Security Camera**

**MODEL NUMBER: VMC3081, VMC2081**

**REPORT NUMBER: 4791756546-1-RF-4**

**ISSUE DATE: August 1, 2025**

**FCC ID: 2APLE18300433**

*Prepared for*

**Arlo Technologies, Inc.  
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,  
Guangdong, China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

## Revision History

Rev.	Issue Date	Revisions	Revised By
V0	August 1, 2025	Initial Issue	

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY .....	5
3. FACILITIES AND ACCREDITATION.....	5
4. DESCRIPTION OF EUT .....	6
5. REQUIREMENT .....	7

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Arlo Technologies, Inc.  
Address: 5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

### Manufacturer Information


Company Name: Arlo Technologies, Inc.  
Address: 5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

### EUT Information

EUT Name: Security Camera  
Model: VMC3081  
Series Model: VMC2081  
Sample Received Date: March 20, 2025  
Sample Status: Normal  
Sample ID: 8388280  
Date of Tested: March 21, 2025 to August 1, 2025

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
447498 D04 Interim General RF Exposure Guidance v01	PASS

Prepared By:



Fanny Huang

Engineer Project Associate

Checked By:



Kebo Zhang

Senior Project Engineer

Approved By:



Stephen Guo

Operations Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 1 Subpart I, section 1.1307 and KDB 447498 D04 Interim General RF Exposure Guidance v01.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p>
---------------------------	--

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. DESCRIPTION OF EUT

EUT Name:		Security Camera
Model:		VMC3081
Series Model:		VMC2081
Model Difference:		Please refer to the declaration letter.
Product Description (BLE)	Frequency Range:	2402 MHz to 2480 MHz
	Type of Modulation:	GFSK
	Data Rate:	1Mbps
Product Description (2.4G WLAN)	Frequency Range:	2412 MHz to 2462 MHz
	Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
	Radio Technology:	IEEE 802.11b/g/n HT20
Product Description (5G RLAN)	Frequency Range:	5180 MHz to 5240 MHz 5260 MHz to 5320 MHz 5500 MHz to 5720 MHz 5745 MHz to 5825 MHz
	Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	Radio Technology:	IEEE 802.11a/n HT20
Normal Test Voltage:		AC 120 V, 60 Hz

## 5. REQUIREMENT

### LIMIT AND CALCULATION METHOD

According to 447498 D04 Interim General RF Exposure Guidance v01,

#### 2.1.4 MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.<sup>10</sup> For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

#### MPE-based Exemption

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and  $ERP_{20\text{cm}}$  is per Formula (B.1).

## CALCULATED RESULTS

### For Single RF Source

Operating Mode	Max. Tune up Power	Max. Antenna Gain	EIRP	ERP	ERP	Distance	Limit Threshold
	(dBm)	(dBi)	(dBm)	(dBm)	(mW)	(cm)	(mW)
BLE	16.57	2.9	19.47	17.32	53.95106	20	3060
WIFI 2.4G	24.20	2.9	27.1	24.95	312.608	20	3060
WIFI 5G	22.94	1.8	24.74	22.59	181.5516	20	3060

### Note:

1. The calculated distance is 20 cm.
2. The power comes from operation description.
3. The EUT can't transmit simultaneously. (declared by client)

---

## END OF REPORT