

# RADIO TEST REPORT

**Product** : Security Camera  
**Model Name** : VMC5050  
**Series Model** : VMC5052  
**FCC ID** : 2APLE18300435  
**Test Regulation** : FCC 47 CFR Part 15 Subpart C (Section 15.247)  
**Received Date** : 2025/4/16  
**Test Date** : 2025/4/16 ~ 2025/6/26  
**Issued Date** : 2025/7/15

**Applicant** : Arlo Technologies Inc  
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

**Issued By** : Underwriters Laboratories Taiwan Co., Ltd.  
Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd.,  
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

## **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## REVISION HISTORY

## Original Test Report No.: 4791841496-US-R0-V0

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Bundling A, B and E, No. 372-7, Sec. 4  
Telephone :+886-2-7737-3000

Telephone :+886-2-7737-3000  
Facsimile (FAX) :+886-3-583-7948

## Table of Contents

<b>1. Attestation of Test Results .....</b>	<b>4</b>
<b>2. Summary of Test Results .....</b>	<b>5</b>
<b>3. Test Methodology and Reference Procedures.....</b>	<b>6</b>
<b>4. Facilities and Accreditation .....</b>	<b>6</b>
<b>5. Measurement Uncertainty .....</b>	<b>7</b>
<b>6. Equipment under Test.....</b>	<b>8</b>
6.1. Description of EUT .....	8
6.2. Channel List .....	10
6.3. Test Condition.....	11
6.4. Description of Available Antennas .....	12
6.5. Test Mode Applicability and Tested Channel Detail.....	13
6.6. Duty cycle .....	14
<b>7. Test Equipment .....</b>	<b>15</b>
<b>8. Description of Test Setup .....</b>	<b>17</b>
<b>9. Test Results .....</b>	<b>19</b>
9.1. 6dB Bandwidth .....	19
9.2. Conducted Output Power.....	23
9.3. Power Spectral Density.....	25
9.4. Conducted Out of Band Emission.....	29
9.5. Radiated Spurious Emission .....	39
9.6. AC Power Line Conducted Emission .....	61

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX ) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 1. Attestation of Test Results

**APPLICANT:** Arlo Technologies Inc  
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

**MANUFACTURER:** Arlo Technologies Inc  
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

**EUT DESCRIPTION:** Security Camera

**BRAND:** arlo

**MODEL:** VMC5050

**SERIES MODEL:** VMC5052

**SAMPLE STAGE:** Engineering Verification Test Sample

**DATE of TESTED:** 2025/4/16 ~ 2025/6/26

APPLICABLE STANDARDS	
STANDARD	Test Results
FCC 47 CFR PART 15 Subpart C (Section 15.247)	PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:



Sally Lu  
Project Handler

Date : 2025/7/15

Approved and Authorized By:



Eric Lee  
Senior Laboratory Engineer

Date : 2025/7/15

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 2. Summary of Test Results

Summary of Test Results		
FCC Clause	Test Items	Result
15.247(a)(2)	6dB Bandwidth	PASS
15.247(b)	Conducted Output Power	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Antenna Port Emission	PASS
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS
15.207	AC Power Conducted Emission	PASS
15.203	Antenna Requirement	PASS

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

### 3. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2, KDB558074 D01 Meas Guidance v05r02, KDB414788 D01 Radiated Test Site v01r01, ANSI C63.10-2013.

### 4. Facilities and Accreditation

<b>Test Location</b>	Underwriters Laboratories Taiwan Co., Ltd.
<b>Address</b>	Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
<b>Accreditation Certificate</b>	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.

#### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 5. Measurement Uncertainty

For statement of conformity, Simple acceptance (Section 3.1.4 of IEC Guide 115) was applied as decision rule for measurement in this test report.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k=2$ .

Determining compliance based on the results of the compliance measurement, not considering measurement instrumentation uncertainty.

Measurement	Frequency	Uncertainty
Conducted disturbance at mains terminals ports	150kHz ~ 30MHz	3.0 dB
RF Conducted	9 kHz - 40GHz	2.4 dB
Radiated disturbance below 30MHz	9 kHz - 30 MHz	1.9 dB
Radiated disturbance below 1 GHz	30MHz ~ 1GHz	5.6 dB
Radiated disturbance above 1 GHz	1GHz ~ 40GHz	4.6 dB

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 6. Equipment under Test

### 6.1. Description of EUT

<b>Product</b>	Security Camera
<b>Brand Name</b>	arlo
<b>Model Name</b>	VMC5050
<b>Series Model</b>	VMC5052
<b>Normal Voltage</b>	5Vdc from USB Host 3.6Vdc/3.89Vdc from Battery

<b>Operating Frequency</b>	2412MHz ~ 2462MHz
<b>Modulation</b>	CCK, DQPSK, DBPSK for DSSS
	64QAM, 16QAM, QPSK, BPSK for OFDM
<b>Transfer Rate</b>	802.11b: up to 11 Mbps
	802.11g: up to 54 Mbps
	802.11n: up to MCS7
<b>Maximum Output Power</b>	2412MHz ~ 2462MHz: 27.41 dBm
<b>Sample ID</b>	Conducted Test:8586803
	Radiated Test:8586803

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Note:

1. The models difference table as below:

Model	Difference
VMC5050	Regular housing ; 1 cell battery(A-23)
VMC5052	Large housing ; 4 cell battery(A-14)

2. EUT provides a complete 1Tx port and 1Rx port. Please refer to the following working transmission conditions:

Modulation Mode	Tx Function	Rx Function
802.11b	1Tx Diversity	1Rx Diversity
802.11g	1Tx Diversity	1Rx Diversity
802.11n (HT20)	1Tx Diversity	1Rx Diversity

3. The EUT contains following accessory devices:

Product	Brand	Model	Description
Battery	Arlo	A-23	3.89Vdc, 21.41Wh, 5655mAh
Battery	Arlo	A-14	3.6Vdc, 46.8Wh, 13000mAh
Mount	Arlo	Mount	-

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual, the laboratory shall not be held responsible.

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 6.2. Channel List

11 channels are provided for WLAN 20MHz bandwidth system:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	-	-

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX ) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

### 6.3. Test Condition

Test Item	Test Site No.	Environmental	Input Power	Test Date	Tested by
Antenna Port Conducted Measurement	SR4	22~24°C/ 64~69%RH	5Vdc	2025/06/11~ 2025/06/24	WaterNil Guan
Radiated Spurious Emission	966-2	22~26°C/ 62~68%RH	5Vdc	2025/04/16~ 2025/06/16	WaterNil Guan
AC power Line Conducted Emission	SR1	23°C/ 66%RH	120Vac/ 60Hz	2025/06/26	WaterNil Guan

### Sample Calculation:

#### Antenna Port Conducted Measurement:

- Where relevant, the follow sample calculation is provided:  

$$\text{Result Value (dBm)} = \text{Reading Value (dBm)} + \text{Attenuator Factor (dB)} + \text{Cable Loss (dB)}$$

Example: Result Value (10dBm) = Reading Value (-2dBm) + Attenuator Factor (10dB) + Cable Loss(2dB).

\*Test plot only shown the “Result Value”.

#### Radiated Spurious Emission:

- Where relevant, the follow sample calculation is provided:  

$$\text{Result Value (dBuV/m)} = \text{Reading Value (dBuV)} + \text{Correction Factor (dB/m)}$$

$$\text{Correction Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Preamp Factor (dB)}$$

Example: Result Value (34.5dBuV/m) = Reading Value (40.1dBuV) + Antenna Factor (18.7dB/m) + Cable Loss (4.2dB) - Preamp Factor (28.5dB).

#### AC power Line Conducted Emission:

- Where relevant, the follow sample calculation is provided:  

$$\text{Result Value (dBuV)} = \text{Reading Value (dBuV)} + \text{Correction Factor (dB)}$$

$$\text{Correction Factor (dB)} = \text{Insertion loss(dB)} + \text{Cable loss(dB)}$$

Example: Result Value (53.7dBuV) = Reading Value (35.1dBuV) + Insertion loss(18.1dB) + Cable loss(0.5dB).

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

#### 6.4. Description of Available Antennas

Ant. No.	Transmitter Circuit	Frequency Range	Brand Name	Model Name	Maximum Gain (dBi)	Ant. Type	Connector Type
1/2	Chain 1/0	2400 ~ 2483.5MHz 5150 ~ 5875MHz	ARLO	2APLE18300435	2.4GHz: 3.8 5GHz: 4.2	Internal, Metal	None

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual, the laboratory shall not be held responsible.

#### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 6.5. Test Mode Applicability and Tested Channel Detail

Test Item	Mode	Modulation Technology	Available Channel	Test Channel	Data Rate
Radiated Bandedge	802.11b	DSSS	1 to 11	1,6,11	1 Mbps
	802.11g	OFDM	1 to 11	1,6,11	6 Mbps
	802.11n (HT20)	OFDM	1 to 11	1,6,11	MCS0
Radiated Emissions (Above 1GHz)	802.11b	DSSS	1 to 11	1,6,11	1 Mbps
	802.11g	OFDM	1 to 11	1,6,11	6 Mbps
Radiated Emissions (Below 1GHz)	802.11b	DSSS	1 to 11	6	1 Mbps
AC Power Line Conducted Emission	802.11g	OFDM	1 to 11	6	6 Mbps
Antenna Port Conducted Measurement	802.11b	DSSS	1 to 11	1,6,11	1 Mbps
	802.11g	OFDM	1 to 11	1,6,11	6 Mbps
	802.11n (HT20)	OFDM	1 to 11	1,6,11	MCS0

- The EUT supports 802.11b, 802.11g, and 802.11n (HT20) with 1Tx diversity, utilizing transmitter ports Chain 0 (ANT2) and Chain 1 (ANT1). The highest conducted output power was observed on Chain 0 (ANT2); therefore, only the test data from this chain is included in the report.
- The fundamental of the EUT was investigated in three orthogonal axes X-Y/Y-Z/X-Z, it was determined that X-Y plane was worst-case. Therefore, all final radiated testing was performed with the EUT in X-Y plane.
- The EUT has 2 types of Battery: 3.89Vdc-5655mAh(A-23) for VMC5050 and 3.6Vdc-13000mAh(A-14) for VMC5052, above types were pre-tested, the worst case was found in the 3.89Vdc-5655mAh(A-23) for VMC5050, and therefore the AC conduction was performed using this worst-case mode.
- The radiated spurious emission test was performed in all test modes. The worst case were 802.11b and 802.11g. Therefore, only the worst case data is shown in this report to represent all test modes.
- In the transmit mode, 802.11g channel 6 has the highest RF output power. Therefore, the AC conduction was performed using this worst-case mode.
- In the transmit mode, 802.11b channel 6 has the worst case of Tx spurious emission (above 1GHz). Therefore, all final tests for the spurious emission (below 1GHz) were performed using this worst-case mode.
- For Antenna Port Conducted Measurement, this item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- For below 30MHz testing, investigation was done on three antenna orientations (parallel, perpendicular, and ground-parallel), parallel and perpendicular are the worst orientations, therefore testing was performed on these two orientations only.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 6.6. Duty cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle	Duty Factor (dB)	VBW Set (above 1GHz)
802.11b	8.595	8.730	0.9845	N/A	10Hz
802.11g	1.400	1.535	0.9121	0.40	1kHz
802.11n(HT20)	1.325	1.450	0.9138	0.39	1kHz



**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 7. Test Equipment

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
<b>Radiated Spurious Emission</b>					
Spectrum Analyzer	Keysight	N9010A	MY56070818	2025/3/12	2026/3/11
EMI Test Reciever	Rohde & Schwarz	ESR7	101754	2024/12/24	2025/12/23
Loop Antenna	ETS lindgren	6502	00213440	2024/12/11	2025/12/10
Trilog-Broadband Antenna with 5dB Attenuator	Schwarzbeck & EMCI	VULB 9168 & N-6-05	774 & AT-N0538	2024/12/30	2025/12/29
Horn Antenna (1-18 GHz)	Schwarzbeck	BBHA 9120 D	01690	2024/11/27	2025/11/26
Horn Antenna (18-40 GHz)	Schwarzbeck	BBHA 9170	781	2024/12/18	2025/12/17
Preamplifier (30-1000 MHz)	EMCI	EMC330E	980405	2024/5/28	2025/5/27
Preamplifier (1-18 GHz)				2025/5/12	2026/5/11
Preamplifier (18-40GHz)	EMCI	EMC051835BE	980406	2025/1/13	2026/1/12
Cables (9k-18 GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-4 & 170425-2	2024/11/22	2025/11/21
Cables (18-40GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-1 & 170214-2	2024/11/22	2025/11/21

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
<b>Antenna Port Conducted Measurement</b>					
Signal Analyzer	Rohde & Schwarz	FSVA3044	101281	2025/3/5	2026/3/4
Signal Analyzer	Rohde & Schwarz	FSV40	101490	2024/7/1	2025/6/30
Attenuator	EMCI	EMC-40ATK2W10	17002	2024/11/13	2025/11/12
USB Power Sensor	Anritsu	MA24408A	12031	2024/7/13	2025/7/12
Temperature &Humidity Test Chamber	GIANT FORCE	GTH-150- 40-CP-AR	MAA1701-010	2025/2/25	2026/2/24
<b>AC power Line Conducted Emission</b>					
EMI Test Receiver	Rohde & Schwarz	ESR7	101753	2024/10/1	2025/9/30
Two-Line V-Network	Rohde & Schwarz	ENV216	102136	2025/5/27	2026/5/26
Impuls-Begrenzer Pulse Limiter	Rohde & Schwarz	ESH3-Z2	102219-Qt	2024/8/29	2025/8/28
Cables	TITAN	CFD200	T0732ACFD 20020A300-2	2025/4/21	2026/4/20

UL Software		
Description	Name	Version
Radiated measurement	e3	6.191211 (V6)
Conducted measurement	RF-Conducted-FCC 15247	ver 1.0
AC power Line Conducted Emission	EZ_EMU	UL-3A1.2

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 8. Description of Test Setup

### Tx Mode

#### Support Equipment

ID	Equipment	Brand Name	Model Name	S/N	Remark
A	Laptop	DELL	Latitude E5470	3JFKWF2	Provided by Lab
B	Mount	Arlo	Mount	N/A	Provided by Client

#### I/O Cables

ID	Equipment	Brand Name	Model Name	Length (m)	Remark
1	USB Cable	Nienyi	310-50024-01	0.9	Provided by Client

### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## **Test Setup**

Controlled using a bespoke application (Typing RF command by terminal tool(Tera Term version 4.94)) on a test Notebook. The application was used to enable a continuous transmission mode and to select the test channels, data rates, modulation schemes and power setting as required.

## **Setup Diagram for Test**

### **Tx Mode**



## **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 9. Test Results

### 9.1. 6dB Bandwidth


#### Requirements

The minimum 6 dB bandwidth shall be at least 500 kHz.

#### Test procedure

- a. Set resolution bandwidth (RBW) = 100kHz.
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

#### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## Test Data

Mode	CH	Freq (MHz)	6dB BW (MHz)	Limit (MHz)	Result
			Chain 0		
802.11b	1	2412	8.584	0.5	PASS
	6	2437	9.086	0.5	PASS
	11	2462	8.600	0.5	PASS



## **Underwriters Laboratories Taiwan Co., Ltd.**


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	CH	Freq (MHz)	6dB BW (MHz)	Limit (MHz)	Result
			Chain 0		
802.11g	1	2412	16.373	0.5	PASS
	6	2437	16.393	0.5	PASS
	11	2462	16.374	0.5	PASS



### Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	CH	Freq (MHz)	6dB BW	Limit (MHz)	Result
			Chain 0		
802.11n(HT20)	1	2412	17.612	0.5	PASS
	6	2437	17.601	0.5	PASS
	11	2462	17.622	0.5	PASS



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 9.2. Conducted Output Power

### Requirements

For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt.


Note:

1.  $P_{\text{Out}} = \text{maximum conducted output power in dBm}$ ,  $G_{\text{TX}} = \text{the maximum transmitting antenna directional gain in dBi}$ ,  $B$  is the 26 dB emission bandwidth in megahertz
2. If EUT with Multiple Transmitter Output:
  - a. Directional Gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{Gn/20})^2 / \text{Nant}] \text{ dBi}$ .
  - Nant: Number of Transmit Antennas
  - G1, G2, ..., Gn: Gain of Individual Antennas
  - Example: two antenna and gain 5 dBi / 3dBi, so if it was used for TxBF power measurement  
 $\text{Directional Gain} = 10 \log[(105/20 + 103/20)^2 / 2] \text{ dBi} = 7.07 \text{ dBi}$
  - b. Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices, CDD  
 $\text{Array Gain} = 0 \text{ dB}$  (i.e., no array gain) for  $\text{NANT} \leq 4$ ;  
 $\text{Array Gain} = 0 \text{ dB}$  (i.e., no array gain) for channel widths  $\geq 40 \text{ MHz}$  for any  $\text{NANT}$ ;  
 $\text{Array Gain} = 5 \log(\text{NANT}/\text{NSS}) \text{ dB}$  or 3 dB, whichever is less for 20-MHz channel widths with  $\text{NANT} \geq 5$ .  
 $\text{Example: Maximum antenna gain} = 5 \text{ dBi}$  and  $\text{NANT} \leq 4$ , so if it was used for CDD power measurement  
 $\text{Directional Gain} = 5 \text{ dBi} + \text{Array Gain} = 5 \text{ dBi} + 0 \text{ dB} = 5 \text{ dBi}$
  - c. For power measurement of KDB 662911 is used with multiple transmitter output. Total conducted power is the sum of the conducted power levels measured at the various output ports.

### Test Procedure

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

### Test Setup



The loss between RF output port of the EUT and the input port of the Power Meter has been taken into consideration.

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## Test Data

Mode	CH	Freq. (MHz)	Peak Power (dBm) Chain 0	Total PK Power (mW)	Total PK Power (dBm)	AVG Power (dBm) Chain 0	Total Power (mW)	Total Power (dBm)	Limit (dBm)	Result
802.11b	1	2412	25.92	390.841	25.92	23.23	210.378	23.23	30	PASS
	6	2437	26.64	461.318	26.64	24.19	262.422	24.19	30	PASS
	11	2462	25.97	395.367	25.97	23.29	213.304	23.29	30	PASS
802.11g	1	2412	26.81	479.733	26.81	18.73	74.645	18.73	30	PASS
	6	2437	27.41	550.808	27.41	22.54	179.473	22.54	30	PASS
	11	2462	26.56	452.898	26.56	18.26	66.988	18.26	30	PASS
802.11n(HT20)	1	2412	26.61	458.142	26.61	18.31	67.764	18.31	30	PASS
	6	2437	27.38	547.016	27.38	22.53	179.061	22.53	30	PASS
	11	2462	26.13	410.204	26.13	17.73	59.293	17.73	30	PASS

Note: Average Power is for reference Only.

## **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX ) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 9.3. Power Spectral Density

### Requirements

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz (If  $G_{TX} > 6$  dBi, then PSD =  $8 - (G_{TX} - 6)$ ).


Note:

1. PSD = power spectral density that the same method as used to determine the conducted output power shall be used to determine the power spectral density. And power spectral density in dBm/MHz.
2.  $G_{TX}$  = the maximum transmitting antenna directional gain in dBi.
3. If EUT with Multiple Transmitter Output:
  - a. Directional Gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{Gn/20})^2 / N_{ant}]$  dBi.  
 N<sub>ant</sub>: Number of Transmit Antennas  
 G<sub>1</sub>, G<sub>2</sub>, ..., G<sub>n</sub>: Gain of Individual Antennas  
 Example: two antenna and gain 5 dBi / 3dBi, so if it was used for power density measurement  
 Directional Gain =  $10 \log[(10^{5/20} + 10^{3/20})^2 / 2]$  dBi = 7.07 dBi
  - b. "PSD per chain" of the report shown is maximum value for each chain, at the "Total PSD" is summing entire spectra across corresponding frequency bins on the various outputs by computer, refer KDB 662911 Method a) for calculating total power density.
  - c. Method a) of power density measurement of KDB 662911 is used for calculating total power density with multiple transmitter output. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

### Test procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

### Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.


### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan  
 Telephone : +886-2-7737-3000  
 Facsimile (FAX) : +886-3-583-7948

## Test Data

Mode	CH	Freq (MHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Directional Gain (dBi)	Result
802.11b	1	2412	0.46	8	3.8	PASS
	6	2437	0.93	8	3.8	PASS
	11	2462	0.22	8	3.8	PASS

Mode	CH	Freq (MHz)	PSD per Chain (dBm/3kHz)
			Chain 0
802.11b	1	2412	0.46
	6	2437	0.93
	11	2462	0.22



## **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	CH	Freq (MHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Directional Gain (dBi)	Result
802.11g	1	2412	-6.12	8	3.8	PASS
	6	2437	-2.61	8	3.8	PASS
	11	2462	-7.24	8	3.8	PASS

Mode	CH	Freq (MHz)	PSD per Chain (dBm/3kHz)
			Chain 0
802.11g	1	2412	-6.12
	6	2437	-2.61
	11	2462	-7.24



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	CH	Freq (MHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Directional Gain (dBi)	Result
802.11n(HT20)	1	2412	-7.95	8	3.8	PASS
	6	2437	-2.77	8	3.8	PASS
	11	2462	-7.52	8	3.8	PASS

Mode	CH	Freq (MHz)	PSD per Chain (dBm/3kHz)
			Chain 0
802.11n(HT20)	1	2412	-7.95
	6	2437	-2.77
	11	2462	-7.52



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 9.4. Conducted Out of Band Emission

### Requirements

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b) (3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209 (a) is not required.

### Test procedure


#### Measurement Procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### Measurement Procedure OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.


### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

## Test Data




## Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


### 802.11b, CH6, Chain 0, Reference



### 802.11b, CH6, Chain 0, Conducted Emission



### 802.11b, CH6, Chain 0, Band edge



### Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000


Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


### 802.11b, CH11, Chain 0, Reference



### 802.11b, CH11, Chain 0, Conducted Emission



### 802.11b, CH11, Chain 0, Band edge




### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


### 802.11g, CH1, Chain 0, Reference



### 802.11g, CH1, Chain 0, Conducted Emission



### 802.11g, CH1, Chain 0, Band edge



### Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000


Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


### 802.11g, CH6, Chain 0, Reference



### 802.11g, CH6, Chain 0, Conducted Emission



### 802.11g, CH6, Chain 0, Band edge




### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


### 802.11g, CH11, Chain 0, Reference



### 802.11g, CH11, Chain 0, Conducted Emission



### 802.11g, CH11, Chain 0, Band edge



### Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000


Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1


### 802.11n(HT20), CH1, Chain 0, Reference



### 802.11n(HT20), CH1, Chain 0, Conducted Emission



### 802.11n(HT20), CH1, Chain 0, Band edge




### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


### 802.11n(HT20), CH6, Chain 0, Reference



### 802.11n(HT20), CH6, Chain 0, Conducted Emission



### 802.11n(HT20), CH6, Chain 0, Band edge




### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


### 802.11n(HT20), CH11, Chain 0, Reference



### 802.11n(HT20), CH11, Chain 0, Conducted Emission



### 802.11n(HT20), CH11, Chain 0, Band edge



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 9.5. Radiated Spurious Emission

### Requirements

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency(MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## **Test Procedures**

[For 9 kHz ~ 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 30MHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

[For above 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

## **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Note:

- a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- b. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.

Peak

Frequency	RBW	VBW
9 kHz~150 kHz	200 Hz	600 Hz
150 kHz~30 MHz	10 kHz	30 kHz
30 MHz~1 GHz	120 kHz	360 kHz
Above 1GHz	1 MHz	3 MHz

Average for above 1GHz

RBW	VBW
1MHz	Refer to section 6.6 for duty cycle.

- d. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
- e. Test data of Result value (dBuV/m) = Reading value (dBuV/m) + Correction Factor (dB/m).
- f. Test data of Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
- g. Test data of Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB).
- h. Test data of Notation "@" = Fundamental Frequency
- i. Test data of Notation "\*" = The peak result under 20 dB above and complies with AVG limit, AVG result is deemed to comply with AVG limit.

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## Test Setup

<Frequency Range 9 kHz ~ 30 MHz>



<Frequency Range 30 MHz ~ 1 GHz >



**Underwriters Laboratories Taiwan Co., Ltd.**


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX ) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the Setup Configurations.

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## Test Data

### Above 1 GHz

Mode	802.11b	Channel	1
------	---------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2389.8	43.69	19.17	62.86	74	-11.14	PK
		2389.99	34.39	19.17	53.56	54	-0.44	AVG
	@	2412	96.63	19.14	115.77	N/A	N/A	PK
	@	2412	91.54	19.14	110.68	N/A	N/A	AVG
	*	4824	47.95	2.63	50.58	74	-23.42	PK
Vertical		2389.99	41.22	19.17	60.39	74	-13.61	PK
		2389.99	33.27	19.17	52.44	54	-1.56	AVG
	@	2412	91.02	19.14	110.16	N/A	N/A	PK
	@	2412	87.65	19.14	106.79	N/A	N/A	AVG
	*	4824	44.67	2.63	47.3	74	-26.7	PK


### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11b	Channel	6
------	---------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2380.11	42.21	19.23	61.44	74	-12.56	PK
		2389.42	28.18	19.17	47.35	54	-6.65	AVG
	@	2437	97.51	19.18	116.69	N/A	N/A	PK
	@	2437	91.95	19.18	111.13	N/A	N/A	AVG
		2486.7	29.76	19.19	48.95	54	-5.05	AVG
		2498.48	40.77	19.19	59.96	74	-14.04	PK
		4874	51.84	2.66	54.5	74	-19.5	PK
		4874	51.22	2.66	53.88	54	-0.12	AVG
Vertical	*	7311	36.74	10.57	47.31	74	-26.69	PK
		2350.85	40.96	19.39	60.35	74	-13.65	PK
		2389.8	26.92	19.17	46.09	54	-7.91	AVG
	@	2437	92.99	19.18	112.17	N/A	N/A	PK
	@	2437	86.94	19.18	106.12	N/A	N/A	AVG
		2484.99	41.72	19.19	60.91	74	-13.09	PK
		2487.84	27.5	19.19	46.69	54	-7.31	AVG
	*	4874	46.94	2.66	49.6	74	-24.4	PK
	*	7311	39.1	10.57	49.67	74	-24.33	PK


### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11b	Channel	11
------	---------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2462	96.03	19.19	115.22	N/A	N/A	PK
	@	2462	90.93	19.19	110.12	N/A	N/A	AVG
		2483.66	34.44	19.19	53.63	54	-0.37	AVG
		2484.99	43.31	19.19	62.5	74	-11.5	PK
		4924	51.83	2.72	54.55	74	-19.45	PK
		4924	51.15	2.72	53.87	54	-0.13	AVG
	*	7386	35.96	10.71	46.67	74	-27.33	PK
Vertical	@	2462	93.25	19.19	112.44	N/A	N/A	PK
	@	2462	89.31	19.19	108.5	N/A	N/A	AVG
		2483.66	33.39	19.19	52.58	54	-1.42	AVG
		2484.61	43.21	19.19	62.4	74	-11.6	PK
	*	4924	47.54	2.72	50.26	74	-23.74	PK
	*	7386	38.62	10.71	49.33	74	-24.67	PK


### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11g	Channel	1
------	---------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2384.67	54.12	19.2	73.32	74	-0.68	PK
		2389.99	34.33	19.17	53.5	54	-0.5	AVG
	@	2412	93.37	19.14	112.51	N/A	N/A	PK
	@	2412	82.07	19.14	101.21	N/A	N/A	AVG
	*	4824	39.2	2.63	41.83	74	-32.17	PK
Vertical		2380.68	50.09	19.22	69.31	74	-4.69	PK
		2389.99	34.1	19.17	53.27	54	-0.73	AVG
	@	2412	88.17	19.14	107.31	N/A	N/A	PK
	@	2412	78.99	19.14	98.13	N/A	N/A	AVG
	*	4824	37.14	2.63	39.77	74	-34.23	PK


### **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX ) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11g	Channel	6
------	---------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2386.19	53.07	19.19	72.26	74	-1.74	PK
		2389.99	34.72	19.17	53.89	54	-0.11	AVG
	@	2437	97.16	19.18	116.34	N/A	N/A	PK
	@	2437	85.8	19.18	104.98	N/A	N/A	AVG
		2484.99	33.96	19.19	53.15	54	-0.85	AVG
		2488.03	51.63	19.19	70.82	74	-3.18	PK
	*	4874	45.6	2.66	48.26	74	-25.74	PK
Vertical	*	7311	36.5	10.57	47.07	74	-26.93	PK
		2389.42	34.65	19.17	53.82	54	-0.18	AVG
		2389.99	52.16	19.17	71.33	74	-2.67	PK
	@	2437	92.83	19.18	112.01	N/A	N/A	PK
	@	2437	83.57	19.18	102.75	N/A	N/A	AVG
		2484.42	33.55	19.19	52.74	54	-1.26	AVG
		2485.18	50.1	19.19	69.29	74	-4.71	PK
Vertical	*	4874	41.85	2.66	44.51	74	-29.49	PK
	*	7311	38.19	10.57	48.76	74	-25.24	PK


### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11g	Channel	11
------	---------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2462	92.2	19.19	111.39	N/A	N/A	PK
	@	2462	81.17	19.19	100.36	N/A	N/A	AVG
		2483.66	45.43	19.19	64.62	74	-9.38	PK
		2483.66	33.7	19.19	52.89	54	-1.11	AVG
	*	4924	42.85	2.72	45.57	74	-28.43	PK
	*	7386	32.9	10.71	43.61	74	-30.39	PK
Vertical	@	2462	89.52	19.19	108.71	N/A	N/A	PK
	@	2462	80.63	19.19	99.82	N/A	N/A	AVG
		2483.66	33.58	19.19	52.77	54	-1.23	AVG
		2484.04	48.74	19.19	67.93	74	-6.07	PK
	*	4924	38.82	2.72	41.54	74	-32.46	PK
	*	7386	32.79	10.71	43.5	74	-30.5	PK


**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1



**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11n(HT20)	Channel	1
------	---------------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2389.42	54.37	19.17	73.54	74	-0.46	PK
		2389.8	34.01	19.17	53.18	54	-0.82	AVG
	@	2412	91.38	19.14	110.52	N/A	N/A	PK
	@	2412	81.27	19.14	100.41	N/A	N/A	AVG
Vertical		2389.42	49.76	19.17	68.93	74	-5.07	PK
		2389.8	33.64	19.17	52.81	54	-1.19	AVG
	@	2412	86.96	19.14	106.1	N/A	N/A	PK
	@	2412	78.19	19.14	97.33	N/A	N/A	AVG


**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11n(HT20)	Channel	6
------	---------------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		2389.42	52.81	19.17	71.98	74	-2.02	PK
		2389.42	34.27	19.17	53.44	54	-0.56	AVG
	@	2437	98.06	19.18	117.24	N/A	N/A	PK
	@	2437	85.29	19.18	104.47	N/A	N/A	AVG
		2483.66	51.18	19.19	70.37	74	-3.63	PK
		2483.66	34.13	19.19	53.32	54	-0.68	AVG
Vertical		2384.86	51.9	19.2	71.1	74	-2.9	PK
		2389.42	34.08	19.17	53.25	54	-0.75	AVG
	@	2437	91.71	19.18	110.89	N/A	N/A	PK
	@	2437	83.24	19.18	102.42	N/A	N/A	AVG
		2484.04	34.46	19.19	53.65	54	-0.35	AVG
		2487.65	49.17	19.19	68.36	74	-5.64	PK



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	802.11n(HT20)	Channel	11
------	---------------	---------	----

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	@	2462	91.36	19.19	110.55	N/A	N/A	PK
	@	2462	80.48	19.19	99.67	N/A	N/A	AVG
		2484.04	33.95	19.19	53.14	54	-0.86	AVG
		2486.13	46.82	19.19	66.01	74	-7.99	PK
Vertical	@	2462	88.83	19.19	108.02	N/A	N/A	PK
	@	2462	79.77	19.19	98.96	N/A	N/A	AVG
		2483.66	33.69	19.19	52.88	54	-1.12	AVG
		2483.85	44.94	19.19	64.13	74	-9.87	PK



### Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000



Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

**Below 1 GHz**

Mode	802.11b	Channel	6
------	---------	---------	---

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		70.74	40.1	-14.55	25.55	40	-14.45	PK
		150.28	37.53	-11.43	26.1	43.5	-17.4	PK
		195.87	45.7	-14.27	31.43	43.5	-12.07	PK
		236.61	44.79	-12.85	31.94	46	-14.06	PK
		299.66	40.52	-10.28	30.24	46	-15.76	PK
		504.33	35.65	-4.85	30.8	46	-15.2	PK
Vertical		43.58	45.09	-12.28	32.81	40	-7.19	PK
		82.38	47.1	-17.19	29.91	40	-10.09	PK
		154.16	42.16	-11.35	30.81	43.5	-12.69	PK
		176.47	41.54	-12.53	29.01	43.5	-14.49	PK
		247.28	39.27	-12.25	27.02	46	-18.98	PK
		576.11	34.06	-3.12	30.94	46	-15.06	PK

**TX, 802.11b (Ch 6)  
Radiated Spurious Emission, Horizontal**

**TX, 802.11b (Ch 6)  
Radiated Spurious Emission, Vertical**

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

**9 kHz ~ 30 MHz Data:**

For 9 kHz to 30 MHz radiated emission have performed all modes of operation were investigated. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

No non-compliance noted:

**KDB 414788 D01 OATS and Chamber Correlation Justification**

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.
- OATs and chamber correlation testing had been performed and chamber measured test results is the worst case test result.

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX ) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## 9.6. AC Power Line Conducted Emission

### Requirements

Frequency (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.
2. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
3. Test data of Result value (dB $\mu$ V) = Reading value (dB $\mu$ V) + Correction Factor (dB).
4. Test data of Margin(dB) = Result value (dB $\mu$ V) - Limit value (dB $\mu$ V).
5. Test data of Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).

### **Underwriters Laboratories Taiwan Co., Ltd.**


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## Test Setup



**Note: 1. Support units were connected to second LISN.**

For the actual test configuration, please refer to the Setup Configurations.

## **Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

## Test Data

Mode	G_TX2437	Channel	6
------	----------	---------	---



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1601	44.73	9.96	54.69	65.46	-10.77	QP
2	0.1601	17.81	9.96	27.77	55.46	-27.69	AVG
3	0.1732	48.26	9.96	58.22	64.81	-6.59	QP
4	0.1732	29.91	9.96	39.87	54.81	-14.94	AVG
5	0.2511	35.67	9.97	45.64	61.72	-16.08	QP
6	0.2511	15.99	9.97	25.96	51.72	-25.76	AVG
7	0.2785	32.00	9.97	41.97	60.86	-18.89	QP
8	0.2785	10.33	9.97	20.30	50.86	-30.56	AVG
9	10.5623	24.83	10.29	35.12	60.00	-24.88	QP
10	10.5623	17.60	10.29	27.89	50.00	-22.11	AVG
11	24.7598	23.10	10.68	33.78	60.00	-26.22	QP
12	24.7598	16.36	10.68	27.04	50.00	-22.96	AVG

### **Underwriters Laboratories Taiwan Co., Ltd.**


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1

Mode	G_TX2437	Channel	6
------	----------	---------	---



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1518	49.47	9.94	59.41	65.90	-6.49	QP
2	0.1518	28.97	9.94	38.91	55.90	-16.99	AVG
3	0.1714	49.06	9.94	59.00	64.89	-5.89	QP
4	0.1714	32.40	9.94	42.34	54.89	-12.55	AVG
5	0.1928	31.60	9.94	41.54	63.92	-22.38	QP
6	0.1928	5.90	9.94	15.84	53.92	-38.08	AVG
7	0.2292	37.80	9.94	47.74	62.48	-14.74	QP
8	0.2292	13.46	9.94	23.40	52.48	-29.08	AVG
9	3.7883	14.39	10.06	24.45	56.00	-31.55	QP
10	3.7883	4.38	10.06	14.44	46.00	-31.56	AVG
11	10.0946	25.44	10.24	35.68	60.00	-24.32	QP
12	10.0946	18.11	10.24	28.35	50.00	-21.65	AVG

## END OF REPORT

**Underwriters Laboratories Taiwan Co., Ltd.**

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 6.1