


UTi640Q 2.4&5G Antenna

FEATURES



- 2.37 dBi Peak Gain@2.4G
- 4.12 dBi Peak Gain@5G
- Welding RG 1.13 cable, Ipex connector, 3M sticker for easy installation.
- For smart device wireless, Zigbee, Bluetooth terminal

PRODUCTS

Part No.	Weight	Dimensions (L x WxH)	Cables Dimensions	Connector	Color
M01-0200950R0A		FPC:37.4*17.5*0.2 mm	Φ1.13*145mm	IPEX1	Black

SPECIFICATIONS



PARAMETER	SPECIFICATION	
Frequency Bands, MHz	2412-2462	5150 5250 5725-5850
VSWR (Max)	3.0:1	3.0:1
Peak Gain, dBi (Typ)	Up to 2.37 dBi@2.4G/Up to 4.12 dBi@5G	
Nominal Impedance	50 Ω	
Max Power (ambient temp of 25°C)	10 Watts	
Azimuth Beam Width (deg)	60°	
Polarization	Linear	
Color	Black	
Storage Temperature Range (°C)	-40° C to +85° C	
Operational Temperature Range (°C)	-40° C to +85° C	
Material Substance Compliance	REACH/RoHS Compliant	
HSCODE	8517707090	
USHSCODE	8517620010	
UPC		

MyAntenna RF Technology Co., Ltd

ADD: No.RM 405, R3-A Building, Shenzhen High-Tech Park, Nanshan, Shenzhen, P.R. China.


TEL: +86-0755-86503881 FAX: +86-0755-27801677 E-mail: nfc@myantenna.com


ELECTRICAL DATA






Peak Gain (dBi)






RADIATION PATTERNS

2D Radiation Pattern at 2450MHz



2D Radiation Pattern at 5500MHz



HOUSING CONFIGURATIONS

