



MPE REPORT

FCC ID: 2APN7KING-U

Date of issue: Sept. 25, 2019

Report number: MTi19082801-1E2

Sample description: Wi-Fi Smart Switch

Model(s): KING-U, KING-G, KING-K, KING-M, KING-L, KING-Q, KING-X, KING-R, KING-T

Applicant: SHENZHEN KINGART TECHNOLOGY CO., LIMITED

Address: No. 7th Fl, Bao Yi Building, 22-8 Wu Lian Rd, Long Gang District, Shenzhen, 518000 China.

Date of test: Sept. 02, 2019 to Sept. 23, 2019

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.



TEST RESULT CERTIFICATION	
Applicant's name:	SHENZHEN KINGART TECHNOLOGY CO., LIMITED
Address:	No. 7th Fl, Bao Yi Building, 22-8 Wu Lian Rd, Long Gang District, Shenzhen, 518000 China.
Manufacture's name:	SHENZHEN BIAO WANG TECHNOLOGY CO., LIMITED
Address:	No. 7th Fl, Bao Yi Building, 22-8 Wu Lian Rd, Long Gang District, Shenzhen, 518000 China.
Product name:	Wi-Fi Smart Switch
Trademark:	KINGART
Model and/or type reference ..:	KINGART®
Serial model.....:	KING-G, KING-K, KING-M , KING-L, KING-Q, KING-X , KING-R, KING-T
RF exposure procedures.....:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Demi Mu

Sept. 23, 2019

Reviewed by:

Blue Zheng

Sept. 25, 2019

Approved by:

Smith Chen

Sept. 25, 2019



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1415926

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm²

Antenna Type: Wifi Antenna: PCB Antenna;

WIFI antenna gain: 1dBi

R=20cm

mW=10^(dBm/10)

antenna gain Numeric=10^(dBi/10)= 10^(1/10)=1.26

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power	Gain			
		Ant A	Ant A	Ant A	Ant A	Ant A		
2412	802.11b	15.17	16±1	17	50.118723	1.26	0.01256	1
2437		16.83	16±1	17	50.118723	1.26	0.01256	1
2462		16.29	16±1	17	50.118723	1.26	0.01256	1
2412	802.11g	12.93	12±1	13	19.952623	1.26	0.00500	1
2437		13.29	12±1	13	19.952623	1.26	0.00500	1
2462		12.48	12±1	13	19.952623	1.26	0.00500	1
2412	802.11n H20	12.81	13±1	13	19.952623	1.26	0.00500	1
2437		13	13±1	13	19.952623	1.26	0.00500	1
2462		12.4	13±1	13	19.952623	1.26	0.00500	1

Conclusion:

For the max result: 0.01256≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----