

RADIO TEST REPORT

Test Report No. 14834725M

Customer	TAKAZONO Technology Incorporated
Description of EUT	S Cassetter Base
Model Number of EUT	GW-CB-S-002
FCC ID	2APN9GW-CB-S-002
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	July 6, 2023
Remarks	-

Representative test engineer	Approved by
	
Hiromitsu Tanabe Engineer	Kazuhiro Ando Engineer
 	
CERTIFICATE 1266.01	
☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.	
☒ There is no testing item of "Non-accreditation".	

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 22.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Kashima EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where
UL Japan, Inc. has been accredited.
- The information provided from the customer for this report is identified in SECTION 1.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No. 14834725M

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	14834725M	July 6, 2023	-

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information	5
SECTION 2: Equipment Under Test (EUT).....	5
SECTION 3: Test specification, procedures & results	6
SECTION 4: Operation of EUT during testing	9
SECTION 5: Conducted Emission.....	12
SECTION 6: Radiated Emission (Fundamental, Spurious Emission and Spectrum Mask)	13
SECTION 7: Other tests.....	15
APPENDIX 1: Test data	16
Conducted Emission	16
Fundamental Emission and Spectrum Mask	22
Spurious Emission	24
20 dB Bandwidth and 99% Occupied Bandwidth.....	28
Frequency Tolerance	29
APPENDIX 2: Test instruments	30
APPENDIX 3: Photographs of test setup.....	32
Conducted Emission	32
Radiated Emission	33
Frequency Tolerance	36

SECTION 1: Customer Information

Company Name	TAKAZONO Technology Incorporated
Address	2-8-1 Tsudayamate, Hirakata-shi, Osaka, 573-0128 Japan
Telephone Number	+81-72-808-0200
Contact Person	Keiichi Noda

*Remarks:

TAKAZONO Technology Incorporated designates Yoshikawa RF Semicon Co., Ltd. as manufacturer of the product (S Cassetter Base).

The information provided from the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	S Cassetter Base
Model Number	GW-CB-S-002
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	August 26, 2022
Test Date	August 26 to September 27, 2022

2.2 Product Description

General Specification

Rating	DC 5 V (-10 % to +5 %, Radio Part) DC 12 V (-10 % to +5 %, Motor Part)
Operating Temperature	-2 deg. C to +40 deg. C

Radio Specification

Equipment Type	Transceiver
Frequency of Operation	13.56 MHz
Type of Modulation	ASK

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.225 Operation within the band 13.110-14.010 MHz.

* The customer has declared that the EUT has complies with FCC Part 15 Subpart B as SDoC.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 8.8	<FCC> Section 15.207 ----- <ISED> RSS-Gen 8.8	19.6 dB, 29.49130 MHz, AV, L 19.6 dB, 29.49134 MHz, AV, L	Complied	-
Electric Field Strength of Fundamental Emission	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 6.4, 6.12	<FCC> Section 15.225(a) ----- <ISED> RSS-210 B.6	74.7 dB, 13.56000 MHz, QP, 180 deg.	Complied	Radiated
Spectrum Mask	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 6.4, 6.13	<FCC> Section 15.225(b)(c) ----- <ISED> RSS-210 B.6	44.5 dB, 13.11000 MHz, QP, 180 deg	Complied	Radiated
20 dB Bandwidth	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> -	<FCC> Section15.215(c) ----- <ISED> -	See data	Complied	Radiated
Electric Field Strength of Spurious Emission	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 6.4, 6.13	<FCC> Section 15.209, Section 15.225 (d) ----- <ISED> RSS-210 B.6 RSS-Gen 8.9	3.8 dB 908.520 MHz, Horizontal, QP	Complied	Radiated
Frequency Tolerance	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 6.11, 8.11	<FCC> Section 15.225(e) ----- <ISED> RSS-210 B.6	See data	Complied	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

FCC Part 15.31 (e)

The test was carried out with minimum and maximum rating of the product specification according to ANSI C63.10-2013, 5.13 b) because the rating range of the EUT is -10 % to +5 %.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.

Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% emission bandwidth	<ISED>RSS-Gen 6.7	-	N/A	-	Radiated
Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.					

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.

Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor $k = 2$.

Conducted emission

Frequency range	Calculate Uncertainty (+/-)
0.15 MHz to 30 MHz	3.2 dB

Radiated emission

Measurement distance	Frequency range	Calculate Uncertainty (+/-)
3 m	9 kHz to 30 MHz	2.9 dB
	30 MHz to 200 MHz	6.2 dB
	200 MHz to 1000 MHz	6.3 dB
	1 GHz to 6 GHz	5.0 dB
	6 GHz to 18 GHz	5.4 dB
	18 GHz to 40 GHz	5.5 dB
1 m	1 GHz to 18 GHz	5.4 dB
	18 GHz to 40 GHz	5.6 dB
0.5m	26.5 GHz to 40 GHz	5.9 dB

Antenna Terminal test

Test Item	Calculate Uncertainty (+/-)
Frequency Tolerance	7.9×10^{-8}
20 dB Bandwidth / 99 % Occupied Bandwidth	1.6 %

3.5 Test Location

UL Japan, Inc. Kashima EMC Lab.

1614 Mushihata, Katori-shi, Chiba-ken, 289-0341 Japan

Telephone: +81-478-88-6500

A2LA Certificate Number: 1266.01 / FCC Test Firm Registration Number: 910230

ISED Lab Company Number: 4659A / CAB identifier: JP0006

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
No.1 Open site	6.0 x 5.5 x 2.5	20 x 40	10 m
No.5 Open site	8.6 x 7.1 x 2.4	18 x 23	10 m
No.1 Shielded room	5.4 x 4.5 x 2.3	-	-
No.5 Shielded Room	4.2 x 3.1 x 2.5	-	-
No.9 Shielded Room	6.1 x 3.6 x 2.8	-	-
No.6 Semi-anechoic Chamber	8.5 x 5.5 x 5.2	-	3 m
No.10 Semi-anechoic Chamber	18.4 x 9.9 x 7.7	-	10 m
No.11 Semi-anechoic Chamber	9.0 x 6.5 x 5.2	-	3 m
No.1 Measurement room	5.0 x 3.7 x 2.6	-	-
No.2 Measurement room	4.3 x 4.4 x 2.7	-	-

3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)

The mode is used:


Test mode	Remarks
1) Transmitting mode (Tx) - with Tag - without Tag	The EUT Transmits and Receives at the same time and there is no receiving mode.
The EUT was operated in a manner similar to typical use during the tests.	
*Power of the EUT was set by the software as follows; Power Setting: Fixed Software: YRCZ931_EMI-JIG_NXP2022 (Date: 2022/08/24, Storage location: embedded CPU_Memory in DUT) *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product. Justification: The system was configured in typical fashion (as a user would normally use it) for testing.	

Test Item	Operating mode*
Conducted Emission	Tx Mod on, with Tag / without Tag
Electric Field Strength of Fundamental Emission	Tx Mod on, with Tag / without Tag
Spectrum Mask	Tx Mod on, with Tag / without Tag
20 dB Bandwidth and 99 % Occupied Bandwidth	Tx Mod on, with Tag / without Tag
Electric Field Strength of Spurious Emission	Tx Mod on, with Tag / without Tag
Frequency Tolerance	Tx Mod off


Frequency Tolerance:	
Temperature	-20 deg. C to +50 deg. C Step 10 deg. C
Voltage	Normal Voltage DC 5 V Maximum Voltage DC 5.25 V (DC 5 V +5 % *1)) Minimum Voltage DC 4.5 V (DC 5 V -10 % *1))
*1) The specification of this EUT is DC 5 V -10 % to +5 %.	

4.2 Configuration and peripherals

Conducted emission test



Other tests



* Cabling and setup were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remark
A	S Cassetter Base	GW-CB-S-002	170516001001	Yoshikawakogyo RF Semicon Co., Ltd.	EUT
B	Tag	Icode-SLIX2	15	Yoshikawakogyo RF Semicon Co., Ltd.	-
C	DC Power Supply	PMX18-2A	YB000247	KIKUSUI ELECTRONICS CORP.	*1)
D	DC Power Supply	PMX35-3A	AV000507	KIKUSUI ELECTRONICS CORP.	*1)
E	DC Power Supply	GSV3000	1708192899	DAIMOND ANTENNA	*2)
F	DC Power Supply	GSV3000	1708192900	DAIMOND ANTENNA	*2)

List of Cables Used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	DC Cable	0.35	Unshielded	Unshielded	-
		0.35 + 0.9	Unshielded	Unshielded	*3)
2	DC Cable	0.35	Unshielded	Unshielded	
		0.35 + 1.2	Unshielded	Unshielded	*3)
3	Signal Cable	0.1	Unshielded	Unshielded	
4	AC Cable	2.0	Unshielded	Unshielded	*1)
5	AC Cable	2.0	Unshielded	Unshielded	*1)
6	AC Cable	1.7	Unshielded	Unshielded	*2)
7	AC Cable	1.7	Unshielded	Unshielded	*2)

*1) Used for Conducted emission test

*2) Used for Other tests

*3) Frequency Tolerance test only

SECTION 5: Conducted Emission

Test Procedure and conditions

EUT was placed on a wooden table of nominal size, 1.0 m by 2.0 m, raised 0.8 m above the conducting ground plane.

The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80 cm from any other grounded conducting surface. EUT was located 80 cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.


Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN / (AMN) to the input power source. All unused 50 ohm connectors of the LISN (AMN) were resistivity terminated in 50 ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Shielded room.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

Figure 1: Test Setup



The test results and limit are rounded off to one decimal place, so some differences might be observed.

Detector	: QP and CISPR AV
Measurement range	: 0.15 MHz to 30 MHz
Test data	: APPENDIX
Test result	: Pass

SECTION 6: Radiated Emission (Fundamental, Spurious Emission and Spectrum Mask)

Test Procedure

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[Limit conversion]

The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

[Frequency: From 9 kHz to 30 MHz]

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0 deg., 45 deg., 90 deg., and 135 deg.) and horizontal polarization.

*Refer to Figure 3 about Direction of the Loop Antenna.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

These tests were performed in semi anechoic chamber. Therefore the measured level of emissions may be higher than if measurements were made without a ground plane. However test results were confirmed to pass against standard limit.

[Frequency: From 30 MHz to 1 GHz]

The measuring antenna height varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

[Test instruments and test settings]

Frequency	Below 30 MHz	30 MHz to 1 GHz
Antenna Type	Loop	Hybrid

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.


Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz
Instrument used	Test Receiver				
Detector	PK / AV	QP	PK / AV	QP	QP
IF Bandwidth	200 Hz	200 Hz	9 kHz	9 kHz	120 kHz
Test Distance	3 m *1)	3 m *1)	3 m *1)	3 m *2)	3 m

*1) Distance Factor: $40 \times \log (3 \text{ m} / 300 \text{ m}) = -80 \text{ dB}$

*2) Distance Factor: $40 \times \log (3 \text{ m} / 30 \text{ m}) = -40 \text{ dB}$

Figure 2: Test Setup


Below 1 GHz




Test Distance: 3 m

Figure 3: Direction of the Loop Antenna

Side View (Vertical)




Top View (Horizontal)



Antenna was not rotated.

Top View (Vertical)



The test was made on EUT at the normal use position.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 9 kHz to 1 GHz
Test data : APPENDIX
Test result : Pass

SECTION 7: Other tests

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
20 dB Bandwidth	300 kHz	3 kHz	10 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99 % Occupied Bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer
Frequency Tolerance *2)	-	-	-	-	-	-	Frequency counter

*1) The measurement was performed with Max Hold since the duty cycle was not 100 %.

Peak hold was applied as Worst-case measurement.

*2) The temperature test was started after the temperature stabilization time of 30 minutes.

The test was begun from 50 deg.C and the temperature was lowered each 10 deg.C.

Test data : APPENDIX
Test result : Pass

APPENDIX 1: Test data

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Kashima EMC Lab. No.5 Shielded Room
Date : 2022/09/13

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : Without Tag

Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V (AC120V/60Hz)
Temp./Humi. : 21 deg.C / 45 %RH

Limit : FCC_Part 15 Subpart C(15.207)

Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		LISN [dB]	LOSS [dB]	Results		Limit		Margin		Phase	Comment
		<QP> [dBuV]	<AV> [dBuV]			<QP> [dBuV]	<AV> [dBuV]	<QP> [dBuV]	<AV> [dBuV]	<QP> [dB]	<AV> [dB]		
1	0.15000	29.20	3.50	10.04	0.07	39.31	13.61	66.00	56.00	26.6	42.3	N	Carrier
2	0.20915	23.60	15.70	10.04	0.08	33.72	25.82	63.24	53.24	29.5	27.4	N	
3	7.03750	4.90	0.10	10.25	0.45	15.60	10.80	60.00	50.00	44.4	39.2	N	
4	13.56000	48.60	44.50	10.44	0.64	59.68	55.58	60.00	50.00	0.3	-5.6	N	
5	14.74575	10.90	8.00	10.49	0.67	22.06	19.16	60.00	50.00	37.9	30.8	N	
6	24.75850	7.30	5.40	10.71	0.90	18.91	17.01	60.00	50.00	41.0	32.9	N	
7	27.12000	2.00	0.10	10.69	0.95	13.64	11.74	60.00	50.00	46.3	38.2	N	
8	29.49145	21.60	18.10	10.63	0.99	33.22	29.72	60.00	50.00	26.7	20.2	N	
9	0.15000	29.40	3.40	10.02	0.07	39.49	13.49	66.00	56.00	26.5	42.5	L	
10	0.20984	23.70	15.70	10.02	0.08	33.80	25.80	63.21	53.21	29.4	27.4	L	
11	7.05500	4.60	0.10	10.27	0.45	15.32	10.82	60.00	50.00	44.6	39.1	L	Carrier
12	13.56000	48.60	44.60	10.57	0.64	59.81	55.81	60.00	50.00	0.1	-5.9	L	
13	14.74540	10.90	8.00	10.64	0.67	22.21	19.31	60.00	50.00	37.7	30.6	L	
14	24.76050	7.60	5.60	10.97	0.90	19.47	17.47	60.00	50.00	40.5	32.5	L	
15	27.12000	2.00	0.10	10.97	0.95	13.92	12.02	60.00	50.00	46.0	37.9	L	
16	29.49130	21.90	18.40	10.92	0.99	33.81	30.31	60.00	50.00	26.1	19.6	L	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN):CLS-11


Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.5 Shielded Room
Date : 2022/09/13

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : With Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V (AC120V/60Hz)
Temp./Humi. : 21 deg.C / 45 %RH

Limit : FCC_Part 15 Subpart C(15.207)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		LISN	LOSS	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>			<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
		[dBuV]	[dBuV]			[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	0.15000	29.40	3.50	10.04	0.07	39.51	13.61	66.00	56.00	26.4	42.3	N	Carrier
2	0.20944	23.70	15.80	10.04	0.08	33.82	25.92	63.23	53.23	29.4	27.3	N	
3	7.28251	3.90	0.10	10.25	0.46	14.61	10.81	60.00	50.00	45.3	39.1	N	
4	13.13607	19.70	7.10	10.42	0.63	30.75	18.15	60.00	50.00	29.2	31.8	N	
5	13.56000	48.60	41.90	10.44	0.64	59.68	52.98	60.00	50.00	0.3	-3.0	N	
6	24.75935	8.10	5.30	10.71	0.90	19.71	16.91	60.00	50.00	40.2	33.0	N	
7	27.12000	3.60	0.10	10.69	0.95	15.24	11.74	60.00	50.00	44.7	38.2	N	
8	29.49132	21.60	18.10	10.63	0.99	33.22	29.72	60.00	50.00	26.7	20.2	N	
9	0.15000	29.30	3.50	10.02	0.07	39.39	13.59	66.00	56.00	26.6	42.4	L	Carrier
10	0.20949	23.90	15.80	10.02	0.08	34.00	25.90	63.23	53.23	29.2	27.3	L	
11	7.24050	4.10	0.10	10.27	0.46	14.83	10.83	60.00	50.00	45.1	39.1	L	
12	13.13592	19.60	7.00	10.55	0.63	30.78	18.18	60.00	50.00	29.2	31.8	L	
13	13.56000	48.50	41.80	10.57	0.64	59.71	53.01	60.00	50.00	0.2	-3.1	L	
14	24.75860	7.60	5.70	10.97	0.90	19.47	17.57	60.00	50.00	40.5	32.4	L	
15	27.12000	2.60	0.10	10.97	0.95	14.52	12.02	60.00	50.00	45.4	37.9	L	
16	29.49134	22.00	18.40	10.92	0.99	33.91	30.31	60.00	50.00	26.0	19.6	L	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN):CLS-11

Conducted Emission


DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.5 Shielded Room
Date : 2022/09/13

Company	: TAKAZONO Technology Incorporated	Mode	: Transmitting and Receiving mode
Kind of EUT	: S Cassetter Base	Order No.	: 14834725
Model No.	: GW-CB-S-002	Power	: DC 5.25 V (AC120V/60Hz)
Serial No.	: 170516001001	Temp./Humi.	: 21 deg.C / 45 %RH
Remarks	: Antenna Terminated		

Limit : FCC_Part 15 Subpart C(15.207)

Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		LISN	LOSS	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>			<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
		[dBuV]	[dBuV]			[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	13.56000	6.40	1.90	10.44	0.64	17.48	12.98	60.00	50.00	42.5	37.0	N	
2	13.56000	6.40	1.90	10.57	0.64	17.61	13.11	60.00	50.00	42.3	36.8	L	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN):CLS-11


Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.5 Shielded Room
Date : 2022/09/13

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : Without Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 12.6 V (AC120V/60Hz)
Temp./Humi. : 21 deg.C / 45 %RH

Limit : FCC_Part 15 Subpart C(15.207)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		LISN	LOSS	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>			<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
		[dBuV]	[dBuV]			[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	0.15000	22.00	0.50	10.04	0.07	32.11	10.61	66.00	56.00	33.8	45.3	N	Carrier
2	0.20974	17.30	15.80	10.04	0.08	27.42	25.92	63.22	53.22	35.8	27.3	N	
3	7.06050	5.00	0.10	10.25	0.45	15.70	10.80	60.00	50.00	44.3	39.2	N	
4	13.56000	49.40	45.40	10.44	0.64	60.48	56.48	60.00	50.00	-0.5	-6.5	N	
5	14.74571	10.20	6.30	10.49	0.67	21.36	17.46	60.00	50.00	38.6	32.5	N	
6	24.83212	4.40	1.20	10.70	0.90	16.00	12.80	60.00	50.00	44.0	37.2	N	
7	27.12000	9.90	2.50	10.69	0.95	21.54	14.14	60.00	50.00	38.4	35.8	N	
8	29.49141	19.80	16.20	10.63	0.99	31.42	27.82	60.00	50.00	28.5	22.1	N	
9	0.15000	22.20	0.60	10.02	0.07	32.29	10.69	66.00	56.00	33.7	45.3	L	
10	0.20975	17.30	15.60	10.02	0.08	27.40	25.70	63.22	53.22	35.8	27.5	L	
11	7.05320	4.70	0.10	10.27	0.45	15.42	10.82	60.00	50.00	44.5	39.1	L	
12	13.56000	49.40	45.30	10.57	0.64	60.61	56.51	60.00	50.00	-0.7	-6.6	L	Carrier
13	14.74541	10.00	6.30	10.64	0.67	21.31	17.61	60.00	50.00	38.6	32.3	L	
14	24.83460	7.50	2.10	10.97	0.90	19.37	13.97	60.00	50.00	40.6	36.0	L	
15	27.12000	11.40	2.90	10.97	0.95	23.32	14.82	60.00	50.00	36.6	35.1	L	
16	29.49147	20.20	16.60	10.92	0.99	32.11	28.51	60.00	50.00	27.8	21.4	L	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN):CLS-11


Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.5 Shielded Room
Date : 2022/09/13

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : With Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 12.6 V (AC120V/60Hz)
Temp./Humi. : 21 deg.C / 45 %RH

Limit : FCC_Part 15 Subpart C(15.207)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		LISN	LOSS	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>			<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
		[dBuV]	[dBuV]			[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	0.15000	21.90	0.70	10.04	0.07	32.01	10.81	66.00	56.00	33.9	45.1	N	Carrier
2	0.20972	17.50	15.90	10.04	0.08	27.62	26.02	63.22	53.22	35.6	27.2	N	
3	7.28725	4.10	0.10	10.25	0.46	14.81	10.81	60.00	50.00	45.1	39.1	N	
4	13.13562	19.80	7.20	10.42	0.63	30.85	18.25	60.00	50.00	29.1	31.7	N	
5	13.56000	49.30	42.60	10.44	0.64	60.38	53.68	60.00	50.00	-0.4	-3.7	N	
6	24.83425	7.40	1.70	10.70	0.90	19.00	13.30	60.00	50.00	41.0	36.7	N	
7	27.12000	9.60	2.50	10.69	0.95	21.24	14.14	60.00	50.00	38.7	35.8	N	
8	29.49137	19.90	16.30	10.63	0.99	31.52	27.92	60.00	50.00	28.4	22.0	N	
9	0.15000	22.10	0.70	10.02	0.07	32.19	10.79	66.00	56.00	33.8	45.2	L	
10	0.20977	17.50	15.80	10.02	0.08	27.60	25.90	63.21	53.21	35.6	27.3	L	
11	7.30175	4.00	0.10	10.27	0.46	14.73	10.83	60.00	50.00	45.2	39.1	L	Carrier
12	13.13595	19.80	7.20	10.55	0.63	30.98	18.38	60.00	50.00	29.0	31.6	L	
13	13.56000	49.20	42.50	10.57	0.64	60.41	53.71	60.00	50.00	-0.5	-3.8	L	
14	24.83287	7.30	2.10	10.97	0.90	19.17	13.97	60.00	50.00	40.8	36.0	L	
15	27.12000	9.90	2.70	10.97	0.95	21.82	14.62	60.00	50.00	38.1	35.3	L	
16	29.49132	20.30	16.70	10.92	0.99	32.21	28.61	60.00	50.00	27.7	21.3	L	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN):CLS-11


Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.5 Shielded Room
Date : 2022/09/13

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : Antenna Terminated
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 12.6 V (AC120V/60Hz)
Temp./Humi. : 21 deg.C / 45 %RH

Limit : FCC_Part 15 Subpart C(15.207)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		LISN	LOSS	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>			<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
		[dBuV]	[dBuV]			[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	13.56000	10.00	6.20	10.44	0.64	21.08	17.28	60.00	50.00	38.9	32.7	N	
2	13.56000	9.30	6.20	10.57	0.64	20.51	17.41	60.00	50.00	39.4	32.5	L	

Calculation: Result[dBuV]=Reading[dBuV]+C.Fac(LISN(AMN)+Cable+ATT)[dB]
LISN(AMN):CLS-11

Fundamental Emission and Spectrum Mask


DATA OF RADIATED EMISSION(below 30MHz) TEST

UL Japan, Inc. Kashima EMC Lab. No.10 Semi-Anechoic Chamber
Date : 2022/08/26

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : Without Tag

Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V, DC 12.6 V
Temp./Humi. : 23 deg.C / 53 %RH

Limit : FCC15.225,PK/AV/QP,9-90 kHz:PK/AV,110-490 kHz:PK/AV,other:QP(<490 kHz:300 m,>490 kHz:30 m)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Antenna	Table	Comment
		[QP] [dBuV]	[PK] [dBuV]				[QP] [dBuV/m]	[PK] [dBuV/m]	[QP] [dBuV/m]	[PK] [dBuV/m]	[QP] [dB]	[PK] [dB]			
1	13.11000	22.70	---	19.39	-33.05	24.21	-15.17	---	29.50	---	44.6	---	180deg	0	
2	13.41000	22.70	---	19.39	-33.03	24.22	-15.16	---	40.50	---	55.6	---	180deg	0	
3	13.55300	33.10	---	19.39	-33.03	24.23	-4.77	---	50.40	---	55.1	---	180deg	0	
4	13.56000	46.60	---	19.39	-33.03	24.23	8.73	---	83.90	---	75.1	---	180deg	0	
5	13.56000	46.30	---	19.39	-33.03	24.23	8.43	---	83.90	---	75.4	---	180deg	0	DC 4.5 V
6	13.56000	46.50	---	19.39	-33.03	24.23	8.63	---	83.90	---	75.2	---	180deg	0	DC 5 V
7	13.56700	32.80	---	19.39	-33.03	24.23	-5.07	---	50.40	---	55.4	---	180deg	0	
8	13.71000	22.60	---	19.40	-33.02	24.23	-15.25	---	40.50	---	55.7	---	180deg	0	
9	14.01000	22.60	---	19.40	-33.01	24.25	-15.26	---	29.50	---	44.7	---	180deg	0	
10	13.56000	33.20	---	19.39	-33.03	24.23	-4.67	---	83.90	---	88.5	---	90deg	260	

Calculation: Result[dBuV/m]=Reading[dBuV]+Ant.Fac[dB/m]+Loss(Cable+ATT+D.Fac)[dB]-Gain(AMP)[dB]
Ant.Type=LOOP: Loop Antenna

Result of the fundamental Emission at 3 m without Distance factor

QP											
Ant Deg [deg]	Frequency	Detector	Reading	Ant Factor	Loss	Gain	Duty Factor	Result	Limit	Margin	Remark
	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
180	13.56000	QP	46.60	19.39	6.97	24.23	-	48.73	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)


Fundamental Emission and Spectrum Mask

DATA OF RADIATED EMISSION(below 30MHz) TEST

UL Japan, Inc. Kashima EMC Lab. No.10 Semi-Anechoic Chamber
Date : 2022/08/26

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : With Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V, DC 12.6 V
Temp./Humi. : 23 deg.C / 53 %RH

Limit : FCC15.225,PK/AV/QP,9-90 kHz:PK/AV,110-490 kHz:PK/AV,other:QP(<490 kHz:300 m,>490 kHz:30 m)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Antenna	Table [deg]	Comment
		[QP] [dBuV]	[PK] [dBuV]				[QP] [dBuV/m]	[PK] [dBuV/m]	[QP] [dBuV/m]	[PK] [dBuV/m]	[QP] [dB]	[PK] [dB]			
1	13.11000	22.80	---	19.39	-33.05	24.21	-15.07	---	29.50	---	44.5	---	180deg	0	
2	13.41000	22.70	---	19.39	-33.03	24.22	-15.16	---	40.50	---	55.6	---	180deg	0	
3	13.55300	33.20	---	19.39	-33.03	24.23	-4.67	---	50.40	---	55.0	---	180deg	0	
4	13.56000	47.00	---	19.39	-33.03	24.23	9.13	---	83.90	---	74.7	---	180deg	0	
5	13.56700	32.90	---	19.39	-33.03	24.23	-4.97	---	50.40	---	55.3	---	180deg	0	
6	13.71000	22.70	---	19.40	-33.02	24.23	-15.15	---	40.50	---	55.6	---	180deg	0	
7	14.01000	22.70	---	19.40	-33.01	24.25	-15.16	---	29.50	---	44.6	---	180deg	0	
8	13.56000	33.30	---	19.39	-33.03	24.23	-4.57	---	83.90	---	88.4	---	90deg	243	

Calculation:Result[dBuV/m]=Reading[dBuV]+Ant.Fac[dB/m]+Loss(Cable+ATT+D.Fac)[dB]-Gain(AMP)[dB]
Ant.Type=LOOP:Loop Antenna

Result of the fundamental Emission at 3 m without Distance factor

QP											
Ant Deg [deg]	Frequency	Detector	Reading	Ant Factor	Loss	Gain	Duty Factor	Result	Limit	Margin	Remark
	[MHz]		[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
180	13.56000	QP	47.00	19.39	6.97	24.23	-	49.13	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)


Spurious Emission

DATA OF RADIATED EMISSION(below 30MHz) TEST

UL Japan, Inc. Kashima EMC Lab. No.10 Semi-Anechoic Chamber
Date : 2022/08/26

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : Without Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V, DC 12.6 V
Temp./Humi. : 23 deg.C / 53 %RH

Limit : FCC15.225,PK/AV/QP,9-90 kHz:PK/AV,110-490 kHz:PK/AV,other:QP(<490 kHz:300 m,>490 kHz:30 m)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Antenna [deg]	Table	Comment
		<QP> [dBuV]	<PK> [dBuV]				<QP> [dBuV/m]	<PK> [dBuV/m]	<QP> [dBuV/m]	<PK> [dBuV/m]	<QP> [dB]	<PK> [dB]			
1	27.12000	22.30	---	19.88	-32.57	24.42	-14.81	---	29.50	---	44.3	---	180deg	0	
2	27.12000	22.20	---	19.88	-32.57	24.42	-14.91	---	29.50	---	44.4	---	90deg	0	

Calculation: Result[dBuV/m]=Reading[dBuV]+Ant.Fac[dB/m]+Loss(Cable+ATT+D.Fac)[dB]-Gain(AMP)[dB]
Ant.Type=LOOP:Loop Antenna


Spurious Emission

DATA OF RADIATED EMISSION(below 30MHz) TEST

UL Japan, Inc. Kashima EMC Lab. No.10 Semi-Anechoic Chamber
Date : 2022/08/26

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : With Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V, DC 12.6 V
Temp./Humi. : 23 deg.C / 53 %RH

Limit : FCC15.225,PK/AV/QP,9-90 kHz:PK/AV,110-490 kHz:PK/AV,other:QP(<490 kHz:300 m,>490 kHz:30 m)
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Antenna	Table	Comment
		<QP> [dBuV]	<PK> [dBuV]				<QP> [dBuV/m]	<PK> [dBuV/m]	<QP> [dBuV/m]	<PK> [dBuV/m]	<QP> [dB]	<PK> [dB]			
1	27.12000	22.10	---	19.88	-32.57	24.42	-15.01	---	29.50	---	44.5	---	180deg	0	
2	27.12000	22.00	---	19.88	-32.57	24.42	-15.11	---	29.50	---	44.6	---	90deg	0	

Calculation: Result[dBuV/m]=Reading[dBuV]+Ant.Fac[dB/m]+Loss(Cable+ATT+D.Fac)[dB]-Gain(AMP)[dB]
Ant.Type=LOOP:Loop Antenna


Spurious Emission

DATA OF RADIATED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.10 Semi-Anechoic Chamber
Date : 2022/08/26

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : Without Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V, DC 12.6 V
Temp./Humi. : 23 deg.C / 53 %RH

Limit : FCC15.209 3 m, below 1 GHz:QP, above 1 GHz:AV/PK
Tested by : Hiromitsu Tanabe



No.	Freq. [MHz]	Reading (QP)	Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result (QP)	Limit (QP)	Margin (QP)	Pola [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		[dBuV]				[dBuV/m]	[dBuV/m]						
1	108.480	47.90	10.22	6.95	31.48	33.59	43.50	9.9	Hori.	293	267	HB	
2	122.040	46.00	11.56	7.10	31.46	33.20	43.50	10.3	Hori.	265	265	HB	
3	135.600	46.50	12.72	7.24	31.43	35.03	43.50	8.4	Hori.	229	263	HB	
4	623.760	31.00	20.20	10.77	31.09	30.88	46.00	15.1	Hori.	131	0	HB	
5	881.400	36.60	22.98	11.94	30.87	40.65	46.00	5.3	Hori.	100	298	HB	
6	908.520	37.20	23.44	12.06	30.84	41.86	46.00	4.1	Hori.	100	295	HB	
7	935.640	36.10	23.86	12.19	30.81	41.34	46.00	4.6	Hori.	100	295	HB	
8	81.360	40.30	8.71	6.65	31.54	24.12	40.00	15.8	Vert.	100	192	HB	
9	108.480	44.20	10.22	6.95	31.48	29.89	43.50	13.6	Vert.	100	192	HB	
10	122.040	43.30	11.56	7.10	31.46	30.50	43.50	13.0	Vert.	100	44	HB	
11	135.600	44.70	12.72	7.24	31.43	33.23	43.50	10.2	Vert.	100	71	HB	
12	433.920	32.60	16.65	9.80	31.21	27.84	46.00	18.1	Vert.	117	111	HB	
13	908.520	33.90	23.44	12.06	30.84	38.56	46.00	7.4	Vert.	105	0	HB	
14	935.640	34.60	23.86	12.19	30.81	39.84	46.00	6.1	Vert.	100	150	HB	

Calculation: Result[dBuV/m]=Reading[dBuV]+Ant.Fac[dB/m]+Loss(Cable+ATT)[dB]-Gain(AMP)[dB]
Ant.Type=HB: Hybrid Antenna


Spurious Emission

DATA OF RADIATED EMISSION TEST

UL Japan, Inc. Kashima EMC Lab. No.10 Semi-Anechoic Chamber
Date : 2022/08/26

Company : TAKAZONO Technology Incorporated
Kind of EUT : S Cassetter Base
Model No. : GW-CB-S-002
Serial No. : 170516001001
Remarks : With Tag
Mode : Transmitting and Receiving mode
Order No. : 14834725
Power : DC 5.25 V, DC 12.6 V
Temp./Humi. : 23 deg.C / 53 %RH

Limit : FCC15.209 3 m, below 1 GHz:QP, above 1 GHz:AV/PK
Tested by : Hiromitsu Tanabe




No.	Freq. [MHz]	Reading (QP)	Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result (QP)	Limit (QP)	Margin (QP)	Pola [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		[dBuV]				[dBuV/m]	[dBuV/m]						
1	108.480	47.90	10.22	6.95	31.48	33.59	43.50	9.9	Hori.	291	277	HB	
2	122.040	47.60	11.56	7.10	31.46	34.80	43.50	8.7	Hori.	270	111	HB	
3	135.600	46.40	12.72	7.24	31.43	34.93	43.50	8.5	Hori.	221	286	HB	
4	637.320	31.60	20.33	10.85	31.08	31.70	46.00	14.3	Hori.	147	17	HB	
5	881.400	36.90	22.98	11.94	30.87	40.95	46.00	5.0	Hori.	100	311	HB	
6	908.520	37.50	23.44	12.06	30.84	42.16	46.00	3.8	Hori.	100	300	HB	
7	935.640	36.10	23.86	12.19	30.81	41.34	46.00	4.6	Hori.	100	305	HB	
8	81.360	40.20	8.71	6.65	31.54	24.02	40.00	15.9	Vert.	100	122	HB	
9	108.480	44.30	10.22	6.95	31.48	29.99	43.50	13.5	Vert.	100	206	HB	
10	122.040	44.70	11.56	7.10	31.46	31.90	43.50	11.6	Vert.	100	44	HB	
11	135.600	44.50	12.72	7.24	31.43	33.03	43.50	10.4	Vert.	100	73	HB	
12	433.920	34.00	16.65	9.80	31.21	29.24	46.00	16.7	Vert.	184	0	HB	
13	908.520	34.40	23.44	12.06	30.84	39.06	46.00	6.9	Vert.	105	0	HB	
14	935.640	34.60	23.86	12.19	30.81	39.84	46.00	6.1	Vert.	100	150	HB	

Calculation: Result[dBuV/m]=Reading[dBuV]+Ant.Fac[dB/m]+Loss(Cable+ATT)[dB]-Gain(AMP)[dB]
Ant.Type=HB: Hybrid Antenna

20 dB Bandwidth and 99% Occupied Bandwidth

Test place Kashima EMC Lab. No.2 Measurement room
Date September 27, 2022
Temperature / Humidity 23 deg. C / 55 % RH
Engineer Hiromitsu Tanabe
Mode Tx Mod on

FREQ [MHz]	Mode	20dB Bandwidth [kHz]	99% Occupied Bandwidth [kHz]
13.56	With Tag	54.76	148.89
	Without Tag	76.18	154.19



* Since the transmitter signal is CW-like it is impractical to use a RBW setting of 1 - 5% of the emission bandwidth since the emission bandwidth will be proportional to the RBW.

Frequency Tolerance

Test place Kashima EMC Lab. No.2 Measurement room
Date September 27, 2022
Temperature / Humidity 23 deg. C / 55 % RH
Engineer Hiromitsu Tanabe
Mode Tx Mod off

Test condition		Tested timing	Measured frequency [MHz]	Frequency error [MHz]	Result		Limit
Temp. [deg. C]	Voltage [V]				[%]	[ppm]	
50	5	Power on	13.559919	-0.000081	-0.00060	-6.0	0.01
		+ 2 min.	13.559905	-0.000095	-0.00070	-7.0	0.01
		+ 5 min.	13.559905	-0.000095	-0.00070	-7.0	0.01
		+ 10 min.	13.559905	-0.000095	-0.00070	-7.0	0.01
40	5	Power on	13.559941	-0.000059	-0.00044	-4.4	0.01
		+ 2 min.	13.559915	-0.000085	-0.00063	-6.3	0.01
		+ 5 min.	13.559910	-0.000090	-0.00066	-6.6	0.01
		+ 10 min.	13.559908	-0.000092	-0.00068	-6.8	0.01
30	5	Power on	13.559974	-0.000026	-0.00019	-1.9	0.01
		+ 2 min.	13.559940	-0.000060	-0.00044	-4.4	0.01
		+ 5 min.	13.559930	-0.000070	-0.00052	-5.2	0.01
		+ 10 min.	13.559927	-0.000073	-0.00054	-5.4	0.01
20	5	Power on	13.560007	0.000007	0.00005	0.5	0.01
		+ 2 min.	13.559971	-0.000029	-0.00021	-2.1	0.01
		+ 5 min.	13.559959	-0.000041	-0.00030	-3.0	0.01
		+ 10 min.	13.559955	-0.000045	-0.00033	-3.3	0.01
20	4.5 (5V -10%)	Power on	13.559993	-0.000007	-0.00005	-0.5	0.01
		+ 2 min.	13.559965	-0.000035	-0.00026	-2.6	0.01
		+ 5 min.	13.559955	-0.000045	-0.00033	-3.3	0.01
		+ 10 min.	13.559952	-0.000048	-0.00035	-3.5	0.01
20	5.25 (5V +5%)	Power on	13.560012	0.000012	0.00009	0.9	0.01
		+ 2 min.	13.559973	-0.000027	-0.00020	-2.0	0.01
		+ 5 min.	13.559961	-0.000039	-0.00029	-2.9	0.01
		+ 10 min.	13.559957	-0.000043	-0.00032	-3.2	0.01
10	5	Power on	13.560032	0.000032	0.00024	2.4	0.01
		+ 2 min.	13.560003	0.000003	0.00002	0.2	0.01
		+ 5 min.	13.559992	-0.000008	-0.00006	-0.6	0.01
		+ 10 min.	13.559988	-0.000012	-0.00009	-0.9	0.01
0	5	Power on	13.560041	0.000041	0.00030	3.0	0.01
		+ 2 min.	13.560028	0.000028	0.00021	2.1	0.01
		+ 5 min.	13.560020	0.000020	0.00015	1.5	0.01
		+ 10 min.	13.560017	0.000017	0.00013	1.3	0.01
-10	5	Power on	13.560026	0.000026	0.00019	1.9	0.01
		+ 2 min.	13.560041	0.000041	0.00030	3.0	0.01
		+ 5 min.	13.560038	0.000038	0.00028	2.8	0.01
		+ 10 min.	13.560036	0.000036	0.00027	2.7	0.01
-20	5	Power on	13.559978	-0.000022	-0.00016	-1.6	0.01
		+ 2 min.	13.560031	0.000031	0.00023	2.3	0.01
		+ 5 min.	13.560039	0.000039	0.00029	2.9	0.01
		+ 10 min.	13.560040	0.000040	0.00029	2.9	0.01

Calculation formula: Frequency error = Measured frequency - Tested frequency
Result [%] = Frequency error / Tested frequency * 100

Tested frequency: 13.56 MHz
Limit (+/-): 0.01 % (+/- 100ppm)

* The specification of this EUT is DC 5 V -10 % to +5 %.

APPENDIX 2: Test instruments

Test Equipment

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	CBL-08	143121	LOGBICON	Schwarzbeck Mess-Elektronik OHG	VULB 9168	343	2022/04/18	12
RE	CAT5-03	178806	5dB Fixed Atten.	Pasternack Enterprises	PE7047-5	none	2022/04/01	12
RE	CCC-S10-R3	143165	10 Site RE 3m System	UL Japan	none	none	2021/08/10	12
RE	CAF-28	183880	Pre-Amplifier	UL Japan	ZKL-2	001	2022/04/06	12
RE	CTR-09	144199	Test Receiver	Keysight Technologies Inc	N9038A	MY53290016	2022/07/21	12
RE	CAEC-10(NSA)	144632	Semi Anechoic Chamber	TDK	NSA (No.10)	10	2022/05/15	12
RE	KLP-01	143833	Loop Antenna	Rohde & Schwarz	HFH2-Z2	827779/008	2021/10/06	12
RE	CCC-M01	143161	Coaxial Cable	Fujikura,HP,Mini-Circuits,Fujikura	3D2W	none	2022/05/16	12
RE	CAT6-17	144245	6dB Fixed Atten.	Suhner	6906.01.A	none	2022/07/20	12
RE	CAF-24	171927	Pre Amplifier	UL Japan	GALI-84+	001	2022/07/06	12
RE	CCC-S10-C	143157	10 Site CE System	UL Japan	none	none	2021/08/10	12
RE	CSCL-26	222745	Measure	SHINWA RULES	80862	none	-	-
RE	COS-10	143542	Temperature & Humidity Indicator	HIOKI E.E. CORPORATION	3641/9680-50	090999895/090905406	2022/06/20	12
RE	CTS-14	144216	Digital Multimeter	Fluke Corporation	115	994460954	2021/10/20	12
RE, CE	COTS-CEMI-03	178804	EMI Software	TSJ (Techno Science Japan)	TEPTO-DV3(RE,CE,ME, PE)	-	-	-
CE	CLS-08	143502	A.M.N.	Rohde & Schwarz	ESH3-Z5	847265/011	2022/07/20	12
CE	CLS-11	143505	A.M.N.	Rohde & Schwarz	ESH3-Z5	835239/022	2022/07/20	12
CE	CTM-28	143705	Terminator	Suhner	65_BNC-50-0-2/133_NE	none	2021/11/17	12
CE	CCC-S5-C(SR)	143167	5 Site CE (SR) System	N/A	none(No.5 CE SR)	-	2022/07/01	12
CE	CTR-05	144196	Test Receiver	Rohde & Schwarz	ESCI	100608	2021/10/22	12
CE	CSCL-21	222614	Measure	SHINWA RULES	80862	none	-	-
CE	COS-03	143535	Temperature & Humidity Indicator	A&D Company	AD-5681	6877292	2022/07/20	12
CE	CTS-09	144211	Digital Multimeter	Fluke Corporation	112	89790194	2021/10/20	12
FT	CCH-04	143181	Temperature and Humidity Chamber	Espec	PL-1J	15004059	2021/10/14	12
FT	CFC-02	143423	Frequency Counter	Keysight Technologies Inc	53151A	US40511823	2022/04/13	12
BW	CSA-07	143643	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY52490024	2022/06/23	12
FT, BW	CMS-07	143942	Near Field Probe	Langer	LF-R400	02-0815	-	-
FT, BW	CTS-08	144210	Digital Multimeter	Fluke Corporation	112	89790193	2021/10/11	12
FT, BW	COS-27	200034	Temperature & Humidity Logger	HIOKI E.E. CORPORATION	LR5001/LR9504	200636456/200699552	2022/07/22	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

CE: Conducted Emission
RE: Radiated Emission
FT: Frequency Tolerance
BW: Bandwidth