



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904
Rev.: 01
Page: 1 of 7

TEST REPORT

Application No.: SUCR2503000209TL
Applicant: Gosuncn Technology Group Co., Ltd.
Address of Applicant: 6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China.
Manufacturer: Gosuncn Technology Group Co., Ltd.
Address of Manufacturer: 6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China.
EUT Description: Tracker
Model No.: GT117U
Trade Mark: Gosuncn
Contain FCC ID: 2APNR-GT117U
Standards: 47 CFR Part 2.1091
FCC KDB 447498 D01 v06
Date of Receipt: April 19, 2025
Date of Issue: April 19, 2025

Test Result:	PASS*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.
Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Wireless Laboratory

South of No. 6 Plant, No. 1, RunSheng Road, Suzhou Industrial Park,
Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

t (86-512) 6229 2980
www.sgsgroup.com.cn




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904
Rev.: 01
Page: 2 of 7

Version

Revision Record			
Version	Description	Date	Remark
00	Original	April 19, 2025	/

Authorized for issue by:				
Tested By				
		Nature Shen / Project Manager		
Approved By				
		Cloud Peng/Technical Manager		



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904
Rev.: 01
Page: 3 of 7

Contents

1 General Information 4

1.1 General Description of EUT 4

1.2 Test Facility 5

2 RF Exposure Evaluation 6

2.1 RF Exposure Compliance Requirement..... 6



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904

Rev.: 01

Page: 4 of 7

1 General Information

1.1 General Description of EUT

Hardware Version:	GT117_HW_V1.0			
Software Version:	BG95M1LAR02A04			
Antenna Type:	☐ External, ☒ Integrated			
Antenna Gain:	LTE Cat-M1 Band 2:	1.88dBi	LTE Cat-M1 Band 4:	1.83dBi
	LTE Cat-M1 Band 5:	2.47dBi	LTE Cat-M1 Band 12:	0.79dBi
	LTE Cat-M1 Band 13:	0.79dBi	LTE Cat-M1 Band 25:	1.88dBi
	LTE Cat-M1 Band 26:	2.47dBi	LTE Cat-M1 Band 66:	1.83dBi
	BLE:	2.63dBi		
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.			
Note: *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.				
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.				



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904

Rev.: 01

Page: 5 of 7

1.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

- **FCC –Designation Number: CN1312**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904

Rev.: 01

Page: 6 of 7

2 RF Exposure Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250300020904

Rev.: 01

Page: 7 of 7

2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

2.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Band	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Distance R (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
LTE Cat-M1 Band 2	1880	25	1.88	26.88	20.00	0.097	1.00
LTE Cat-M1 Band 4	1732.5	25	1.83	26.83	20.00	0.096	1.00
LTE Cat-M1 Band 5	836.5	25	2.47	27.47	20.00	0.111	0.56
LTE Cat-M1 Band 12	707.5	25	0.79	25.79	20.00	0.075	0.47
LTE Cat-M1 Band 13	782	25	0.79	25.79	20.00	0.075	0.52
LTE Cat-M1 Band 25	1882.5	25	1.88	26.88	20.00	0.097	1.00
LTE Cat-M1 Band 26 (814 to 824 MHz)	819	25	2.47	27.47	20.00	0.111	0.55
LTE Cat-M1 Band 26 (824 to 849 MHz)	836.5	25	2.47	27.47	20.00	0.111	0.56
LTE Cat-M1 Band 66	1745	25	1.83	26.83	20.00	0.096	1.00
BLE	2440	0	2.73	2.73	20.00	0.000	1.00

---End of Report---