

Appendix 5

RF Exposure Information

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power(mW)	Separation Distance (mm)
2402	6.63	4.603	5
2441	7.21	5.260	5
2480	6.30	4.266	5

According to KDB 447498 D01:

These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(4.603/5) * \sqrt{2.402} = 1.427 < 3.0$$

$$(5.260/5) * \sqrt{2.441} = 1.644 < 3.0$$

$$(4.266/5) * \sqrt{2.480} = 1.344 < 3.0$$

Conclusion:

No SAR is required.