

源创星电子（深圳）有限公司

Yuanchuangxing electronics (Shenzhen) CO., LTD.

Customer Name: Junneng

Customer Moder:

Customer P/N: 01E1EW0500051

Customer Describe:

YCX P/N: YCX09N-B622-400G

Customer Describe: 5G antenna (FPC L31.2*W13) Gray Cable1.13 length L=400mm With IPEX

PRODUCT SPECIFICATION

Signature and seal of confirmation					
YCX Approved			Customer Approved		
Sample	audit	approved	validation	audit	approved
Zouyc					
YCX Approved By			Customer Approved By		
Date	2022-10-22		Date	2022-10-22	

源创星电子（深圳）有限公司

Yuanchuangxing electronics (Shenzhen) CO., LTD

File for amendment/revocation/resume

[illegible]


3、Directory

1、directory.....	1
2、File for amendment/revocation/resume.....	2
3、directory.....	3
4、Product drawings.....	4
5、Passive performance test paramete.....	5
6、2D、3D Performance figure.....	6
7、Electrical performance test report.....	7

源创星电子（深圳）有限公司

Yuanchuangxing electronics (Shenzhen)CO.,LTD.

4、Product drawings




源创星电子（深圳）有限公司

Yuanchuangxing electronics (Shenzhen) CO., LTD.

5、Passive performance test parameters

Frequency(GHz)	5.15	5.55	5.85
VSWR	1.40	1.70	1.15



源创星电子（深圳）有限公司


Yuanchuangxing electronics (Shenzhen) CO., LTD.

6、2D、3D Performance figure


Passive Test

Freq (MHz)	Effi (%)	Gain (dBi)		
5150	61	4.28		
5550	60	4.5		
5850	62	4.35		


5150.000MHz H




5150.000MHz E1




5150.000MHz E2




5500.000MHz H




5500.000MHz E1




5500.000MHz E2




5850.000MHz H



5850.000MHz E1



5850.000MHz E2



源创星电子（深圳）有限公司

Yuanchuangxing electronics (Shenzhen) CO., LTD.

7、Electrical performance test report

Electrical parameters	
Frequency range	5150-5850Mhz
input impedance	50Ω
VSWR	<2.0
Gain	4.5dBi MAX
Polarization mode	Vertical polarization
Radiation direction	omnidirectional
connection method	IPEX
Mechanical parameters	
Cable	
Salt spray test	
Environmental parameters	
Working temperature	-40~85℃